

ATTIC AND CAVITY WALL CARD

Jet Stream® ULTRA Blowing Insulation



HOMEOWNERS NAME: _____ JOB SITE ADDRESS: 14784 SW Tustanuggee Ave
CITY: Fort White STATE: FL ZIP: 32036

BUILDER'S INSULATION STATEMENT

Jet Stream ULTRA has been installed in conformance with the included recommendations to provide a thermal resistance of:

LOCATION	R-VALUE	NO. OF BAGS	MINIMUM THICKNESS		TO COVER	
Attic Area	R- <u>38</u>		at <u>13</u>	inches	<u>1772</u>	sq. ft
Sloped Ceilings	R-		at	inches		sq. ft
Walls	R-		at	inches		sq. ft
Floors (over an unheated crawl space)	R-		at	inches		sq. ft
Crawl Space Perimeter	R-		at	inches		sq. ft

THERMAL PERFORMANCE

The stated thermal resistance (R-value) is provided by installing the required number of bags per 1,000 square feet of net area, at not less than the labeled minimum thickness (per the manufacturer's instructions). Failure to install both the required number of bags and at least the minimum thickness will result in lower insulation R-values.

Field blending of this product with other loose fill insulation or application of this product in conjunction with adhesive or binder systems may affect its thermal performance and is not recommended by the manufacturer.

EQUIPMENT REQUIRED

To achieve labeled R-value, this product must be applied with a pneumatic blowing machine and a corrugated hose with a minimum 0.25" internal corrugation, a minimum length of 150' and a diameter of at least 3". Coils in the hose should not be less than 36" in diameter. The recommended feed rate is 15-25 lbs./min. For closed cavity applications, fabric or netting must be applied.

CONTRACTOR'S SIGNATURE: Yahir P DATE: 1-9-26
COMPANY: SunShine Insulation LLC
ADDRESS: _____ PHONE: _____