



TESTING & TESTING LABORATORY
P.O. Box 1625, Lake City, FL 32056-1625
2907 Spring Glen Road • Jacksonville, FL 32207

Lake City • (386) 755-3633
Fax • (386) 752-5456

Jacksonville • (904) 381-8901
Fax • (904) 381-8902

JOB NO.: 26-541
DATE TESTED: ~~8/12/26~~
8/12/26

ASTM METHOD:

✓ (D-2922) Nuclear

(D-2937) Drive Cylinder

Other

PROJECT: 4461 SW Flim church road

CLIENT: Hunter Faulkner

GENERAL CONTRACTOR: SAL

EARTHWORK CONTRACTOR: SAC

SOIL USE (SEE NOTE): 7

SPECIFICATION REQUIREMENTS: 45%

TECHNICIAN: S. D. / 900

MODIFIED (ASTM D-1557):

STANDARD (ASTM D-698):

REMARKS:

PROCTOR
NO.

SOIL DESCRIPTION

PROCTOR VALUE

OPT. MOIST.

NOTE: 1. Building Fill 2. Trench Backfill 3. Base Course 4. Subbase/Stabilized Subgrade 5. Embankment 6. Subgrade/Natural Soil 7. Other

The test results presented in this report are specific only to the samples tested at the time of testing. The tests were performed in accordance with generally accepted methods and standards. Since material conditions can vary between test location and change with time, sound judgement should be exercised with regard to the use and interpretation of the data.