







116

116

116

116





































JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

FELT  
SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

FELT  
OVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

FELT  
OVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

FELT  
OVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

FELT  
OVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION

JIN MAXFELT  
MAXIMUM TRACTION PROVEN SATISFACTION







PROFILE CU  
FI  
DIRECT LAR  
R









UNFINISHED SURFACE  
RATED SHEATHING  
2 1/2" x 8"  
SIZED FOR SPACING  
16" O.C.

THICKNESS 0.418 in  
CLASSIFICATION  
HUD-UM-90

ED1 STRENGTH ANALYSIS  
LIFE PERIODS 10, 20, 30, 40, 50

THIS SIDE DOWN  
ADD CLIPS  
HERE TO  
SPACE

U20  
RhinoRoof

U20  
RhinoRoof

U20  
RhinoRoof

U20  
RhinoRoof

U20  
RhinoRoof

U20  
RhinoRoof











THICKNESS 1/2" (12.5mm)  
STRENGTH CLASS  
OSB-2

OSB-2  
1250 x 2500 mm  
18 mm