

# **LOT # 39 ROLLING MEADOWS ELECTRICAL INFO**

**ALL SMOKE DEDECTORS MUST BE HOT-WIRED  
AND WITH BATTERY BACKUP**

**ALL WETROOMS HAVE GFCI-PROTECTION**

**ALL SLEEPING ROOMS WILL BE ON A.F.C.I.  
ARCE FAULT CIRCUIT INTERRUPTER**

**ALL BATHROOMS HAVE EXHAUST FANS  
INSTALLED IN CEILING, VENT OVER ROOF  
OR SOFIT**

**ALL BATHROOMS AND STAIR WAYS ARE  
HANDICAPPED ACCESSABLE**

**POWER SUPPLY BY CLAY ELECTRIC COOP**

**BATH ROOMS SHALL HAVE**

**NOTE: A DISCONNECT WILL BE INSTALLED AT THE  
EXTERIOR OF THE STRUCTUR BY THE METER CAN,  
DESIGNED AS AN OVERCURRENT PROTECTION DEVICE.  
CONDUCTORS USED FROM THIS DEVISE TO A PANEL  
OR SUB PANEL SHALL HAVE FOUR-WIRE CONDUCTORS,  
OF WHICH ONE IS USED AS AN EQUIPMENT GROUND.**



# LOT # 39 ROLLING MEDOWS

## WINDOW & DOOR SCHEDULE & OTHER REQUIREMENTS

1. ENTRANCE DOOR 36"/96" IN STEEL
2. GARAGE DOOR 7' x 16' , W/SQUARE TOPLITES... CLOPAY, MODEL#75
3. WINDOWS INSULATED, COLONIAL, WHITE SIVER LINE SERIES 2900
  - 6 x 30/50
  - 2 x 30/30 Tempered
  - 1 x 30/30
  - 3 x 20/36
  - 1 x 20/36 Tempered
  - 1 x 40/50 Arch Top
  - 1 x 20/30 Obscure
  - 1 x 10/46 Old English/Tempered
  - 1 x 40/40 Glass Block
4. PATIO FRENCH DOOR, STEEL, PBDDIO RH INSWING 60"/96", COLONIAL WHITE
5. ATTIC ACCESS PULL DOWN LADDER IN GARAGE CEILING MEETING REQUIREMENTS OF FRC-2004 C: R309.2
6. DOOR TO GARAGE FROM FOYER IS A MIN 20-MIN FIRE RATED STEEL DOOR W/ HONEYCOMBS MIN 13/8 THICKNES, MEETING REQUIREMENTS OF SECTION R309.1
7. THE DRYWALL ON GARAGE CEILING AND WALLS IS 1/2" GYPSUM BOARD

### AREA SUMMARY

LIVING AREA	1771	S . F
GARAGE AREA	507	S . F
REAR PORCH AREA	115	S . F
ENTRY AREA	20	S . F
<b>TOTAL AREA</b>	<b>2413</b>	<b>S . F</b>

