

- KNOTNOTES**
1. FINISH FACE SHALL PAINTED WITH BLENDED WHITE ALUMINUM FLAKE GEL ENAMEL. ALL SURFACES SHALL BE REINFORCED WITH WIRE @ 5/8" C TYP. SUBWALL 2" SPCC. BRONZ BEAMS TO HAVE 1/2" X 1/2" X 1/2" FLASHING ONLY BETWEEN GROUTED CELLS. PAN FLASHING IS AN ACCEPTABLE COURSE TO BE SMOOTH, GROUT CELL @ ANCHOR BOLT LOCATIONS. WIRE AT BASE OF CMU TO CONFINE GROUT. SEE STRUCTURAL DRAWINGS.
  2. 1/2" DIA. X 8' LONG STAINLESS STEEL EYE BOLTS (CLOSED WITH TYPICAL OPENINGS, DUBIL AND EXACTLY TO BLOCK WALL) (6) BOLTS TO BE LOCATED AS SHOWN IN SECTION 101 AND 102.
  3. SIGN FURNISHED AND SUPPLIED BY TENANT WITH GROUT AS NOTED ON ELECTRICAL PLAN. CONTRACTOR TO PROVIDE BLOCKING AS REQUIRED BY SIGN MANUFACTURER TO SUPPORT SIGN WEIGHT OF THE SIGN. CONTRACTOR TO PROVIDE THE PROPER SPOUNGE TO BE USED WITH TENANT.
  4. PRE-FINISHED METAL WALL PANEL IS FOR THE FASCIA AND PARAPET OVER THE ENTRANCE RECESS AND PROTECT THE SIGN MANUFACTURER'S GALVALUME SIGN.
  5. BURNISHED COTTON WHITE AND DOWNSPOUT REMOVE LEAF GUARDS IF LOCATED WITHIN 25'-0" OF A TREE, WHERE NO SIDEWALK EXIST. MIN. 5" PERFORATED LUNDSOFAPE PIPE STRAPPED TO A 12X24" CONCRETE SPLASHLOCK. SEE EXTERIOR FINISH.
  6. PRE-FINISHED METAL COINGS.
  7. CONCRETE SLAB AND FOUNDATION WITH STRUCTURAL TIE BARS 4" DIA. W/ 6" WIRE MESH OVER POLYETHYLENE VAPOR BARRIER. MIN. 10" MIN THICK OVER CRUSHED STONE BASE. TYPICAL ON EQUIVALENT PROVIDE CONTROL JOINTS AT 14'-0" ON CENTER.
  8. REINFORCED METAL WALL PANELS FOR THE SIDES AND REAR. PROVIDE RAFTER RESISTANT FASTENERS FOR BOTTOM 8'-0".
  9. REINFORCED METAL WALL PANELS FOR THE SIDES AND REAR. PROVIDE RAFTER RESISTANT FASTENERS FOR BOTTOM 8'-0".
  10. REINFORCED METAL WALL PANELS FOR THE SIDES AND REAR. PROVIDE RAFTER RESISTANT FASTENERS FOR BOTTOM 8'-0".
  11. REINFORCED METAL WALL PANELS FOR THE SIDES AND REAR. PROVIDE RAFTER RESISTANT FASTENERS FOR BOTTOM 8'-0".
  12. REINFORCED METAL WALL PANELS FOR THE SIDES AND REAR. PROVIDE RAFTER RESISTANT FASTENERS FOR BOTTOM 8'-0".
  13. REINFORCED METAL WALL PANELS FOR THE SIDES AND REAR. PROVIDE RAFTER RESISTANT FASTENERS FOR BOTTOM 8'-0".
  14. REINFORCED METAL WALL PANELS FOR THE SIDES AND REAR. PROVIDE RAFTER RESISTANT FASTENERS FOR BOTTOM 8'-0".
  15. LEAD WALL PANE AT THE POINTS OF PENETRATION THROUGH THE WALLS. TYP. SEE ELECTRICAL DRAWINGS.
  16. DOOR AND WINDOW SENSORS MOUNTED ABOVE RECESSING DOORS.
  17. RECESSING DOOR BUZZER. SEE ELECTRICAL DRAWINGS.
  18. 2" FLOOR SCOPE.


EXTERIOR FINISHES	PRE-FINISHED METAL BUILDING VENDOR	UP BUILDING DAVIS BRUSH	STAR BUILDING SYSTEMS	INDOOR BUILDING SYSTEMS	INDUSTRIAL BUILDING SYSTEMS	PRE-FINISHED METAL BUILDING VENDOR	UP BUILDING DAVIS BRUSH	STAR BUILDING SYSTEMS	INDOOR BUILDING SYSTEMS	INDUSTRIAL BUILDING SYSTEMS
COOL EGYPTIAN WHITE						BURNISHED SLATE				
COOL DARK BRONZE						BRONZE				
COOL COTTON WHITE						POLAR WHITE				
GALVALUME						GALVALUME				
LIGHTSTONE						PARCHEMENT				
MEDIUM BRONZE KYMAR EGG						ANTIQUE BRONZE				
BRONZE						BRONZE				
POLAR WHITE						POLAR WHITE				
GALVALUME						GALVALUME				
LIGHTSTONE						SHERWIN WILLIAMS #707 "MILK CHOCOLATE BEIGE"				
MEDIUM BRONZE KYMAR EGG						SHERWIN WILLIAMS #701 "VAN DYKE" BROWN				
BRONZE						BRONZE				
POLAR WHITE						WRITE BY PRMS MANUFACTURER				
GALVALUME						GALVALUME				

NOTE: REFER TO SHEET 1-A FOR ADDITIONAL INFORMATION ON RECOMMENDED MATERIAL ACCOUNT NUMBERS. NATIONAL ACCOUNT AND CONTRACT INFORMATION SUBJECT TO CHANGE.

# DOLLAR GENERAL

4824 HWY 421  
LAKE CITY, FL 32055

STORE # 30549  
2019 PROTOTYPE PLAN DGB-B 10,840 SQ. FT.



**REVISIONS**

NO.	DATE	DESCRIPTION
1		
2		
3		
4		
5		

DATE: 08/28/2019  
DRAWN BY: JRS  
CHECKED BY: JRS  
DESIGNED BY: JRS  
PROJECT TITLE: DOLLAR GENERAL EXTERIOR ELEVATION

SHEET NO. **A2.0**  
DATE: 08/28/2019  
DRAWN BY: JRS



