



ASTM E108 CLASS A
TDI Listed
CCR #1045

GULFEAGLE SUPPLY

ASTM E108 CLASS A
TDI Listed
CCR #1045

GULFEAGLE SUPPLY

GULFEAGLE SUPPLY

GULFEAGLE SUPPLY

GULFEAGLE SUPPLY

GULFEAGLE SUPPLY

GULFEAGLE SUPPLY

GULFEAGLE SUPPLY

GULFEAGLE SUPPLY

GULFEAGLE SUPPLY

GULFEAGLE SUPPLY

GULFEAGLE SUPPLY

GULFEAGLE SUPPLY





THE WOOD ASSOCIATION

RATED SHEATHING
2 1/2" x 7/16" INCH
SIZED FOR SPACING
EXPOSURE 1

500

PS-2-03 SHEATHING
PIP-108 HUD-MAN-04

FOR STEEL-SHEATHING
STRUCTURE APPLICATIONS
SPACE STUDS 1-FLOOR
PANELS 1/2" AT ALL JOINTS
ADVERSE MOISTURE EXPOSURE
DIRTY SLAT CASE PANEL FINISH
SPECKLING-SAND JOINTS
FINISH
APPLYING CERAMIC
GLAZE, VINYL AND OTHER THIN
NON-TEXTILE FINISHING.

THIS SIDE

DOWN

6 B



Georgia-Pacific
BLUE RIBBON
OSB

APPA

THE ENGINEERED
WOOD ASSOCIATION

RATED SHEATHING
24/16 7/16 INCH
SIZED 1/8" SPACING
EXPOSURE 1

RESIST SHEATHING
FOR USE WITH 1/4" - 1/2"

FOR SITE-BUILT JOIST
SPACING APPLICATIONS
SPACE STUDS 1-1/2" TO 2"
APART. ALL JOISTS
MAY EXPOSE MOISTURE EXPOSURE
RATED SHEATHING TO
SWELLING - SAND JOINTS
BEFORE APPLYING FINISH
FINISH FLOORING. INSTALL
SEPARATE UNDERLAYMENT
BEFORE APPLYING CERAMIC
TILE, VINYL AND OTHER
NON-TEXTILE FLOORING.

THIS SIDE

DOWN