

FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

<p>Project Name: Thomas Residence Street: City, State, Zip: , FL, <i>5335W Duval Ave. Lake City, FL 32024</i> Owner: Design Location: FL, Gainesville</p>	<p>Builder Name: Permit Office: Permit Number: Jurisdiction: County: Columbia(Florida Climate Zone 2)</p>
---	---

<p>1. New construction or existing New (From Plans) 2. Single family or multiple family Detached 3. Number of units, if multiple family 1 4. Number of Bedrooms 5 5. Is this a worst case? No 6. Conditioned floor area above grade (ft²) 3371 Conditioned floor area below grade (ft²) 0 7. Windows(529.0 sqft.) Description Area a. U-Factor: Dbl, U=0.26 529.00 ft² SHGC: SHGC=0.20 b. U-Factor: N/A ft² SHGC: c. U-Factor: N/A ft² SHGC: Area Weighted Average Overhang Depth: 7.216 ft Area Weighted Average SHGC: 0.200 8. Skylights Description Area U-Factor:(AVG) N/A N/A ft² SHGC(AVG): N/A 9. Floor Types Insulation Area a. Slab-On-Grade Edge Insulation R= 0.0 2320.00 ft² b. Floor Over Other Space R= 0.0 1051.00 ft² c. N/A R= ft²</p>	<p>10. Wall Types(3801.3 sqft.) Insulation Area a. Frame - Wood, Exterior R=13.0 3245.50 ft² b. Interior Frame - Wood, Interior R=13.0 312.75 ft² c. Frame - Wood, Adjacent R=13.0 243.00 ft² d. N/A 11. Ceiling Types(3371.0 sqft.) Insulation Area a. Single assembly, no ai (Unvented) R=0.0 2487.00 ft² b. Single assembly, no ai (Unvented) R=30.0 884.00 ft² c. N/A 12. Roof(Metal, Unvent) Deck R=38.0 2788 ft² 13. Ducts, location & insulation level R ft² a. Sup: 1st Floor, Ret: 1st Floor, AH: 1st Floor 6 225 b. Sup: Master Be, Ret: Master Be, AH: Master Be 6 225 c. 1 additional duct system(s) (see details) 14. Cooling Systems kBtu/hr Efficiency a. Central Unit 36.0 SEER2:15.00 b. Central Unit 18.0 SEER2:15.00 c. Central Unit 30.0 SEER2:15.00 15. Heating Systems kBtu/hr Efficiency a. Electric Heat Pump 36.0 HSPF2:7.50 b. Electric Heat Pump 18.0 HSPF2:7.50 c. Electric Heat Pump 30.0 HSPF2:7.50 16. Hot Water Systems a. PropaneTankless Cap: 1 gallons EF: 0.590 b. Conservation features None 17. Credits CF, Pstat</p>
--	---

Glass/Floor Area: 0.157

Total Proposed Modified Loads: 79.50
 Total Baseline Loads: 93.47

PASS

NOTE: Proposed residence must have annual total normalized Modified Loads that are less than or equal to 95 percent of the annual total loads of the standard reference design in order to comply.

I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.

PREPARED BY: *[Signature]*

DATE: 9-8-25

I hereby certify that this building, as designed, is in compliance with the Florida Energy Code.

OWNER/AGENT: *[Signature]*

DATE: 2-10-26

Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.



BUILDING OFFICIAL: _____

DATE: _____

- Compliance requires certification by the air handler unit manufacturer that the air handler enclosure qualifies as certified factory-sealed in accordance with R403.3.2.1.
- Compliance with a proposed duct leakage Qn requires a PERFORMANCE Duct Leakage Test Report confirming duct leakage to outdoors, tested in accordance with ANSI/RESNET/ICC 380, is not greater than 0.030 Qn for whole house.
- Compliance requires an Air Barrier and Insulation Inspection Checklist in accordance with R402.4.1.1 and this project requires a PERFORMANCE envelope leakage test report with envelope leakage no greater than 7.00 ACH50 (R402.4.1.2).

INPUT SUMMARY CHECKLIST REPORT

PROJECT

Title:	Thomas Residence	Bedrooms:	5	Address type:	Street Address
Building Type:	User	Conditioned Area:	3371	Lot #:	---
Owner:		Total Stories:	2	Block/SubDivision:	---
Builder Home ID:		Worst Case:	No	PlatBook:	---
Builder Name:		Rotate Angle:	0	Street:	
Permit Office:		Cross Ventilation:		County:	Columbia
Jurisdiction:		Whole House Fan:		City, State, Zip:	, FL,
Family Type:	Detached	Terrain:	Rural		
New/Existing:	New (From Plans)	Shielding:	Moderate/Rural		
Year Construct:	2025				
Comment:					

CLIMATE

✓ Design Location	Tmy Site	Design Temp		Int Design Temp		Heating Degree Days	Design Moisture	Daily temp Range
		97.5%	2.5%	Winter	Summer			
___ FL, Gainesville	FL_GAINESVILLE_REGIONA	32	92	70	75	1305.5	51	Medium

BLOCKS

✓ Number	Name	Area	Volume
___ 1	Block1	1436	12924 cu ft
___ 2	Block2	884	7956 cu ft
___ 3	Block3	1051	9459 cu ft

SPACES

✓ Number	Name	Area	Volume	Kitchen	Occupants	Bedrooms	Finished	Cooled	Heated
___ 1	1st Floor	1436	12924	Yes	10	1	Yes	Yes	Yes
___ 2	2nd Floor	1051	9459	No	6	3	Yes	Yes	Yes
___ 3	Master Bedroom	884	7956	No	2	1	Yes	Yes	Yes

FLOORS

(Total Exposed Area = 2320 sq.ft.)

✓ #	Floor Type	Space	Exposed Perim(ft)	Area	R-Value Perim.	U-Factor Joist	Slab Insul. Vert/Horiz	Tile	Wood	Carpet	
___ 1	Slab-On-Grade Edge Ins	1st Floor	101	1436 sqft	0.0	---	0.563	0 (ft)/0 (ft)	0.20	0.60	0.20
___ 2	Floor Over Other Space	2nd Floor	---	1051 sqft	---	0.0	0.219	---	0.10	0.25	0.65
___ 3	Slab-On-Grade Edge Ins	Master Bedroom	136	884 sqft	0.0	---	0.547	0 (ft)/0 (ft)	0.25	0.00	0.75

ROOF

✓ #	Type	Materials	Roof Area	Gable Area	Framing. Fract.	Roof Color	Rad Barr	Solar Absor.	SA Tested	Emitt	Emitt Tested	Deck Insul.	Pitch (deg)
___ 1	Gable or shed	Metal	2788 ft²	774 ft²	0.11	Unf, Gal.	N	0.7	No	0.7	No	38	33.69

ATTIC

✓ #	Type	Ventilation	Vent Ratio (1 in)	Area	RBS	IRCC
___ 1	No attic	Unvented	0	2320 ft²	N	N

INPUT SUMMARY CHECKLIST REPORT

CEILING (Total Exposed Area = 3371 sq.ft.)

✓ #	Ceiling Type	Space	R-Value	Ins. Type	Area	U-Factor	Framing Frac.	Truss Type
___ 1	Single assembly, no airspace(Unvented)	1st Floor	0.0	Blown	1436.0ft ²	0.025	0.11	Wood
___ 2	Single assembly, no airspace(Unvented)	2nd Floor	0.0	Blown	1051.0ft ²	0.025	0.11	Wood
___ 3	Single assembly, no airspace(Unvented)	Master Bedroom	30.0	Blown	884.0ft ²	0.015	0.11	Wood

WALLS (Total Exposed Area = 3489 sq.ft.)

✓ #	Ornt	Adjacent To	Wall Type	Space	Cavity R-Value	Width Ft In	Height Ft In	Area sq.ft.	U-Factor	Sheath R-Value	Frm. Frac.	Solar Absor.	Below Grade
___ 1	N	Exterior	Frame - Wood	1st Floor	13.0	26.0 0	9.0 0	234.0	0.084		0.23	0.75	0 %
___ 2	E	Exterior	Frame - Wood	1st Floor	13.0	3.0 0	9.0 0	27.0	0.084		0.23	0.75	0 %
___ 3	N	Exterior	Frame - Wood	1st Floor	13.0	19.0 8	19.0 6	383.5	0.084		0.23	0.75	0 %
___ 4	W	Exterior	Frame - Wood	Master Bedroom	13.0	11.0 0	9.0 0	99.0	0.084		0.23	0.75	0 %
___ 5	N	Exterior	Frame - Wood	Master Bedroom	13.0	20.0 8	9.0 0	186.0	0.084		0.23	0.75	0 %
___ 6	E	Exterior	Frame - Wood	Master Bedroom	13.0	35.0 0	9.0 0	315.0	0.084		0.23	0.75	0 %
___ 7	S	Exterior	Frame - Wood	Master Bedroom	13.0	8.0 0	9.0 0	72.0	0.084		0.23	0.75	0 %
___ 8	W	Exterior	Frame - Wood	Master Bedroom	13.0	12.0 8	9.0 0	114.0	0.084		0.23	0.75	0 %
___ 9	S	Exterior	Frame - Wood	Master Bedroom	13.0	12.0 8	9.0 0	114.0	0.084		0.23	0.75	0 %
___ 10	W	Exterior	Frame - Wood	Master Bedroom	13.0	2.0 0	9.0 0	18.0	0.084		0.23	0.75	0 %
___ 11	S	Exterior	Frame - Wood	1st Floor	13.0	10.0 8	9.0 0	96.0	0.084		0.23	0.75	0 %
___ 12	E	Exterior	Frame - Wood	1st Floor	13.0	2.0 0	9.0 0	18.0	0.084		0.23	0.75	0 %
___ 13	S	Exterior	Frame - Wood	1st Floor	13.0	12.0 8	9.0 0	114.0	0.084		0.23	0.75	0 %
___ 14	W	Exterior	Frame - Wood	1st Floor	13.0	12.0 8	9.0 0	114.0	0.084		0.23	0.75	0 %
___ 15	S	Exterior	Frame - Wood	1st Floor	13.0	22.0 0	9.0 0	198.0	0.084		0.23	0.75	0 %
___ 16	W	Garage	Frame - Wood	1st Floor	13.0	27.0 0	9.0 0	243.0	0.084		0.23	0.75	0 %
___ 17	N	1st Floor	Interior Fr. Wood	2nd Floor	13.0	12.0 0	9.0 0	108.0	0.085		0.23	0.75	0 %
___ 18	W	Exterior	Frame - Wood	2nd Floor	13.0	5.0 4	9.0 0	48.0	0.084		0.23	0.75	0 %
___ 19	E	Exterior	Frame - Wood	2nd Floor	13.0	3.0 0	9.0 0	27.0	0.084		0.23	0.75	0 %
___ 20	N	1st Floor	Interior Fr. Wood	2nd Floor	13.0	22.0 9	9.0 0	204.8	0.085		0.23	0.75	0 %
___ 21	E	Exterior	Frame - Wood	2nd Floor	13.0	18.0 8	9.0 0	168.0	0.084		0.23	0.75	0 %
___ 22	S	Exterior	Frame - Wood	2nd Floor	13.0	8.0 0	9.0 0	72.0	0.084		0.23	0.75	0 %
___ 23	W	Exterior	Frame - Wood	2nd Floor	13.0	12.0 8	9.0 0	114.0	0.084		0.23	0.75	0 %
___ 24	S	Exterior	Frame - Wood	2nd Floor	13.0	12.0 8	9.0 0	114.0	0.084		0.23	0.75	0 %
___ 25	W	Exterior	Frame - Wood	2nd Floor	13.0	2.0 0	9.0 0	18.0	0.084		0.23	0.75	0 %
___ 26	S	Exterior	Frame - Wood	2nd Floor	13.0	10.0 8	9.0 0	96.0	0.084		0.23	0.75	0 %
___ 27	W	Exterior	Frame - Wood	2nd Floor	13.0	2.0 0	9.0 0	18.0	0.084		0.23	0.75	0 %
___ 28	S	Exterior	Frame - Wood	2nd Floor	13.0	12.0 8	9.0 0	114.0	0.084		0.23	0.75	0 %
___ 29	W	Exterior	Frame - Wood	2nd Floor	13.0	12.0 8	9.0 0	114.0	0.084		0.23	0.75	0 %
___ 30	S	Exterior	Frame - Wood	2nd Floor	13.0	8.0 0	9.0 0	72.0	0.084		0.23	0.75	0 %
___ 31	W	Exterior	Frame - Wood	2nd Floor	13.0	18.0 8	9.0 0	168.0	0.084		0.23	0.75	0 %

DOORS (Total Exposed Area = 135 sq.ft.)

✓ #	Ornt	Adjacent To	Door Type	Space	Storms	U-Value	Width Ft In	Height Ft In	Area
___ 1	N	Exterior	Insulated	1st Floor	None	0.46	3.00 0	6.00 8	20.0ft ²
___ 2	N	Exterior	Insulated	1st Floor	None	0.46	6.00 0	8.00 0	48.0ft ²
___ 3	W	Exterior	Insulated	Master Bedroom	None	0.46	3.00 0	6.00 8	20.0ft ²
___ 4	S	Exterior	Insulated	1st Floor	None	0.46	4.00 0	6.00 8	26.7ft ²
___ 5	W	Garage	Insulated	1st Floor	None	0.46	3.00 0	6.00 8	20.0ft ²

INPUT SUMMARY CHECKLIST REPORT

WINDOWS

(Total Exposed Area = 529 sq.ft.)

✓ #	Omt	Wall ID	Frame	Panes	NFRC U-Factor	SHGC	Imp	Storm	Total Area (ft²)	Same Units	Width (ft)	Height (ft)	--Overhang-- Depth (ft) Sep. (ft)		Interior Shade	Screen
___ 1	N	1	Vinyl	Low-E Double	Y 0.26	0.20	N	N	54.0	3	3.00	6.00	9.5	1.3	None	None
___ 2	N	3	Vinyl	Low-E Double	Y 0.26	0.20	N	N	54.0	3	3.00	6.00	14.5	1.3	None	None
___ 3	N	3	Vinyl	Low-E Double	Y 0.26	0.20	N	N	90.0	3	5.00	6.00	14.5	1.3	None	None
___ 4	N	5	Vinyl	Low-E Double	Y 0.26	0.20	N	N	54.0	3	3.00	6.00	1.5	1.3	None	None
___ 5	E	6	Vinyl	Low-E Double	Y 0.26	0.20	N	N	20.0	2	2.00	5.00	1.5	1.3	None	None
___ 6	S	7	Vinyl	Low-E Double	Y 0.26	0.20	N	N	20.0	1	4.00	5.00	1.5	1.3	None	None
___ 7	S	9	Vinyl	Low-E Double	Y 0.26	0.20	N	N	30.0	2	3.00	5.00	9.5	1.3	None	None
___ 8	S	13	Vinyl	Low-E Double	Y 0.26	0.20	N	N	30.0	2	3.00	5.00	9.5	1.3	None	None
___ 9	W	14	Vinyl	Low-E Double	Y 0.26	0.20	N	N	30.0	2	3.00	5.00	9.5	1.3	None	None
___ 10	S	15	Vinyl	Low-E Double	Y 0.26	0.20	N	N	12.0	1	4.00	3.00	1.5	1.3	None	None
___ 11	S	15	Vinyl	Low-E Double	Y 0.26	0.20	N	N	30.0	2	3.00	5.00	1.5	1.3	None	None
___ 12	S	22	Vinyl	Low-E Double	Y 0.26	0.20	N	N	15.0	1	3.00	5.00	1.5	1.3	None	None
___ 13	S	24	Vinyl	Low-E Double	Y 0.26	0.20	N	N	30.0	2	3.00	5.00	1.5	1.3	None	None
___ 14	S	26	Vinyl	Low-E Double	Y 0.26	0.20	N	N	15.0	1	3.00	5.00	1.5	1.3	None	None
___ 15	S	28	Vinyl	Low-E Double	Y 0.26	0.20	N	N	30.0	2	3.00	5.00	1.5	1.3	None	None
___ 16	S	30	Vinyl	Low-E Double	Y 0.26	0.20	N	N	15.0	1	3.00	5.00	1.5	1.3	None	None

INFILTRATION

✓ #	Scope	Method	SLA	CFM50	ELA	EqLA	ACH	ACH50	Space(s)	Infiltration Test Volume
___ 1	Wholehouse	Proposed ACH(50)	0.00040	3540	194.19	364.57	0.1897	7.0	All	30339 cu ft

GARAGE

✓ #	Floor Area	Length	Width	Roof Area	Exposed Perimeter	Area Under Uncond.	Avg. Wall Height	Exposed Wall Insulation
___ 1	648 ft²	24.0 ft²	27.0 ft²	648 ft²	75 ft	648 ft	9 ft	1

MASS

✓ #	Mass Type	Area	Thickness	Furniture Fraction	Space
___ 1	Default(8 lbs/sq.ft.)	0 ft²	0 ft	0.30	1st Floor
___ 2	Default(8 lbs/sq.ft.)	0 ft²	0 ft	0.30	2nd Floor
___ 3	Default(8 lbs/sq.ft.)	0 ft²	0 ft	0.30	Master Bedroom

HEATING SYSTEM

✓ #	System Type	Subtype/Speed	AHRI #	Efficiency	Capacity kBtu/hr	---Geothermal HeatPump---			Ducts	Block	
						Entry	Power	Volt	Current		
___ 1	Electric Heat Pump	None/Single		HSPF2: 7.50	36.0		0.00	0.00	0.00	sys#1	1
___ 2	Electric Heat Pump	None/Single		HSPF2: 7.50	18.0		0.00	0.00	0.00	sys#2	2
___ 3	Electric Heat Pump	None/Single		HSPF2: 7.50	30.0		0.00	0.00	0.00	sys#3	3

COOLING SYSTEM

✓ #	System Type	Subtype/Speed	AHRI #	Efficiency	Capacity kBtu/hr	Air Flow cfm	SHR	Duct	Block
___ 1	Central Unit	None/Single		SEER2:15.0	36.0	1080	0.75	sys#1	1
___ 2	Central Unit	None/Single		SEER2:15.0	18.0	540	0.75	sys#2	2
___ 3	Central Unit	None/Single		SEER2:15.0	30.0	900	0.75	sys#3	3

INPUT SUMMARY CHECKLIST REPORT

HOT WATER SYSTEM												
✓ #	System Type	Subtype	Location	EF(UEF)	Cap	Use	SetPnt	Fixt. Flow	Trap	Pipe Ins.	Pipe length	
___ 1	Propane	Tankless	Exterior	0.59 (0.59)	1.0 gal	80 gal	120 deg	Standard	Yes	None	99	
	Recirculation System	Recirc Control Type	Loop length	Branch length	Pump power	DWHR	Facilities Connected	Equal Flow	DWHR Eff	Other Credits		
___ 1	No		NA	NA	NA	No	NA	NA	NA	None		

DUCTS													
✓ Duct #	Supply Location	Supply R-Value	Supply Area	Return Location	Return R-Value	Return Area	Leakage Type	AHU Location	CFM 25 TOT OUT	QN OUT	AHU SEALED	RLF	HVAC # Heat Cool
___ 1	1st Floor	6.0	225 ft²	1st Floor	6.0	56 ft²	Prop. Leak Free	1st Floor	---	0.030	Yes	0.50	1 1
___ 2	Master Bedroo	6.0	225 ft²	Master Bedroo	6.0	56 ft²	Prop. Leak Free	Master Bed	---	0.030	Yes	0.50	2 2
___ 3	2nd Floor	6.0	225 ft²	2nd Floor	6.0	56 ft²	Prop. Leak Free	2nd Floor	---	0.030	Yes	0.50	3 3

TEMPERATURES													
Programable Thermostat: Y						Ceiling Fans: N							
Cooling	<input type="checkbox"/> Jan	<input type="checkbox"/> Feb	<input type="checkbox"/> Mar	<input type="checkbox"/> Apr	<input type="checkbox"/> May	<input checked="" type="checkbox"/> Jun	<input checked="" type="checkbox"/> Jul	<input checked="" type="checkbox"/> Aug	<input checked="" type="checkbox"/> Sep	<input type="checkbox"/> Oct	<input type="checkbox"/> Nov	<input type="checkbox"/> Dec	
Heating	<input checked="" type="checkbox"/> Jan	<input checked="" type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar	<input type="checkbox"/> Apr	<input type="checkbox"/> May	<input type="checkbox"/> Jun	<input type="checkbox"/> Jul	<input type="checkbox"/> Aug	<input type="checkbox"/> Sep	<input type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov	<input checked="" type="checkbox"/> Dec	
Venting	<input type="checkbox"/> Jan	<input type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar	<input checked="" type="checkbox"/> Apr	<input type="checkbox"/> May	<input type="checkbox"/> Jun	<input type="checkbox"/> Jul	<input type="checkbox"/> Aug	<input type="checkbox"/> Sep	<input checked="" type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov	<input type="checkbox"/> Dec	
✓ Thermostat Schedule: HERS 2006 Reference	Schedule Type	1	2	3	4	5	6	7	8	9	10	11	12
___ Cooling (WD)	AM PM	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	80 78	80 78	80 78	80 78
___ Cooling (WEH)	AM PM	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	80 78	80 78	80 78	80 78
___ Heating (WD)	AM PM	65 68	65 68	65 68	65 68	65 68	65 68	65 68	65 68	68 68	68 68	68 68	68 68
___ Heating (WEH)	AM PM	65 68	65 68	65 68	65 68	65 68	65 68	65 68	65 68	68 68	68 68	68 68	68 68

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE INDEX* = 85

The lower the EnergyPerformance Index, the more efficient the home.

,,FL,

<p>1. New construction or existing New (From Plans)</p> <p>2. Single family or multiple family Detached</p> <p>3. Number of units, if multiple family 1</p> <p>4. Number of Bedrooms 5</p> <p>5. Is this a worst case? No</p> <p>6. Conditioned floor area above grade (ft²) 3371 Conditioned floor area below grade (ft²) 0</p> <p>7. Windows**</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 20%;">a. U-Factor:</td> <td style="width: 20%;">Description</td> <td style="width: 20%;">Area</td> <td style="width: 40%;"></td> </tr> <tr> <td></td> <td>DbI, U=0.26</td> <td>529.00 ft²</td> <td></td> </tr> <tr> <td>SHGC:</td> <td>SHGC=0.20</td> <td></td> <td></td> </tr> <tr> <td>b. U-Factor:</td> <td>N/A</td> <td>ft²</td> <td></td> </tr> <tr> <td>SHGC:</td> <td></td> <td></td> <td></td> </tr> <tr> <td>c. U-Factor:</td> <td>N/A</td> <td>ft²</td> <td></td> </tr> <tr> <td>SHGC:</td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="2">Area Weighted Average Overhang Depth:</td> <td>7.216 ft</td> <td></td> </tr> <tr> <td colspan="2">Area Weighted Average SHGC:</td> <td>0.200</td> <td></td> </tr> </table> <p>8. Skylights</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 20%;">U-Factor:(AVG)</td> <td style="width: 20%;">Description</td> <td style="width: 20%;">Area</td> <td style="width: 40%;"></td> </tr> <tr> <td></td> <td>N/A</td> <td>N/A ft²</td> <td></td> </tr> <tr> <td>SHGC(AVG):</td> <td>N/A</td> <td></td> <td></td> </tr> </table> <p>9. Floor Types</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 30%;"></td> <td style="width: 10%;">Insulation</td> <td style="width: 10%;">Area</td> <td style="width: 50%;"></td> </tr> <tr> <td>a. Slab-On-Grade Edge</td> <td>R= 0.0</td> <td>2320.00 ft²</td> <td></td> </tr> <tr> <td>b. Floor Over Other Space</td> <td>R= 0.0</td> <td>1051.00 ft²</td> <td></td> </tr> <tr> <td>c. N/A</td> <td>R=</td> <td>ft²</td> <td></td> </tr> </table>	a. U-Factor:	Description	Area			DbI, U=0.26	529.00 ft ²		SHGC:	SHGC=0.20			b. U-Factor:	N/A	ft ²		SHGC:				c. U-Factor:	N/A	ft ²		SHGC:				Area Weighted Average Overhang Depth:		7.216 ft		Area Weighted Average SHGC:		0.200		U-Factor:(AVG)	Description	Area			N/A	N/A ft ²		SHGC(AVG):	N/A				Insulation	Area		a. Slab-On-Grade Edge	R= 0.0	2320.00 ft ²		b. Floor Over Other Space	R= 0.0	1051.00 ft ²		c. N/A	R=	ft ²		<p>10. Wall Types(3801.3 sqft.)</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 60%;">a. Frame - Wood, Exterior</td> <td style="width: 10%;">Insulation</td> <td style="width: 30%;">Area</td> </tr> <tr> <td></td> <td>R=13.0</td> <td>3245.50 ft²</td> </tr> <tr> <td>b. Interior Frame - Wood, Interior</td> <td>R=13.0</td> <td>312.75 ft²</td> </tr> <tr> <td>c. Frame - Wood, Adjacent</td> <td>R=13.0</td> <td>243.00 ft²</td> </tr> <tr> <td>d. N/A</td> <td></td> <td></td> </tr> </table> <p>11. Ceiling Types(3371.0 sqft.)</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 60%;">a. Single assembly, no ai (Unvented)</td> <td style="width: 10%;">Insulation</td> <td style="width: 30%;">Area</td> </tr> <tr> <td></td> <td>R=0.0</td> <td>2487.00 ft²</td> </tr> <tr> <td>b. Single assembly, no ai (Unvented)</td> <td>R=30.0</td> <td>884.00 ft²</td> </tr> <tr> <td>c. N/A</td> <td></td> <td></td> </tr> </table> <p>12. Roof(Metal, Unvent) Deck R=38.0 2788 ft²</p> <p>13. Ducts, location & insulation level R ft²</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 60%;">a. Sup: 1st Floor, Ret: 1st Floor, AH: 1st Floor</td> <td style="width: 10%;">R</td> <td style="width: 30%;">6 225</td> </tr> <tr> <td>b. Sup: Master Be, Ret: Master Be, AH: Master Be</td> <td></td> <td>6 225</td> </tr> <tr> <td colspan="3">c. 1 additional duct system(s) (see details)</td> </tr> </table> <p>14. Cooling Systems</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 60%;">a. Central Unit</td> <td style="width: 10%;">kBTu/hr</td> <td style="width: 30%;">Efficiency</td> </tr> <tr> <td></td> <td>36.0</td> <td>SEER2:15.00</td> </tr> <tr> <td>b. Central Unit</td> <td>18.0</td> <td>SEER2:15.00</td> </tr> <tr> <td>c. Central Unit</td> <td>30.0</td> <td>SEER2:15.00</td> </tr> </table> <p>15. Heating Systems</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 60%;">a. Electric Heat Pump</td> <td style="width: 10%;">kBTu/hr</td> <td style="width: 30%;">Efficiency</td> </tr> <tr> <td></td> <td>36.0</td> <td>HSPF2:7.50</td> </tr> <tr> <td>b. Electric Heat Pump</td> <td>18.0</td> <td>HSPF2:7.50</td> </tr> <tr> <td>c. Electric Heat Pump</td> <td>30.0</td> <td>HSPF2:7.50</td> </tr> </table> <p>16. Hot Water Systems</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 60%;">a. PropaneTankless</td> <td style="width: 10%;">Cap:</td> <td style="width: 30%;">1 gallons</td> </tr> <tr> <td></td> <td>EF:</td> <td>0.590</td> </tr> <tr> <td colspan="3">b. Conservation features</td> </tr> <tr> <td></td> <td></td> <td>None</td> </tr> </table> <p>17. Credits</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 60%;"></td> <td style="width: 10%;"></td> <td style="width: 30%;">CF, Pstat</td> </tr> </table>	a. Frame - Wood, Exterior	Insulation	Area		R=13.0	3245.50 ft ²	b. Interior Frame - Wood, Interior	R=13.0	312.75 ft ²	c. Frame - Wood, Adjacent	R=13.0	243.00 ft ²	d. N/A			a. Single assembly, no ai (Unvented)	Insulation	Area		R=0.0	2487.00 ft ²	b. Single assembly, no ai (Unvented)	R=30.0	884.00 ft ²	c. N/A			a. Sup: 1st Floor, Ret: 1st Floor, AH: 1st Floor	R	6 225	b. Sup: Master Be, Ret: Master Be, AH: Master Be		6 225	c. 1 additional duct system(s) (see details)			a. Central Unit	kBTu/hr	Efficiency		36.0	SEER2:15.00	b. Central Unit	18.0	SEER2:15.00	c. Central Unit	30.0	SEER2:15.00	a. Electric Heat Pump	kBTu/hr	Efficiency		36.0	HSPF2:7.50	b. Electric Heat Pump	18.0	HSPF2:7.50	c. Electric Heat Pump	30.0	HSPF2:7.50	a. PropaneTankless	Cap:	1 gallons		EF:	0.590	b. Conservation features					None			CF, Pstat
a. U-Factor:	Description	Area																																																																																																																																										
	DbI, U=0.26	529.00 ft ²																																																																																																																																										
SHGC:	SHGC=0.20																																																																																																																																											
b. U-Factor:	N/A	ft ²																																																																																																																																										
SHGC:																																																																																																																																												
c. U-Factor:	N/A	ft ²																																																																																																																																										
SHGC:																																																																																																																																												
Area Weighted Average Overhang Depth:		7.216 ft																																																																																																																																										
Area Weighted Average SHGC:		0.200																																																																																																																																										
U-Factor:(AVG)	Description	Area																																																																																																																																										
	N/A	N/A ft ²																																																																																																																																										
SHGC(AVG):	N/A																																																																																																																																											
	Insulation	Area																																																																																																																																										
a. Slab-On-Grade Edge	R= 0.0	2320.00 ft ²																																																																																																																																										
b. Floor Over Other Space	R= 0.0	1051.00 ft ²																																																																																																																																										
c. N/A	R=	ft ²																																																																																																																																										
a. Frame - Wood, Exterior	Insulation	Area																																																																																																																																										
	R=13.0	3245.50 ft ²																																																																																																																																										
b. Interior Frame - Wood, Interior	R=13.0	312.75 ft ²																																																																																																																																										
c. Frame - Wood, Adjacent	R=13.0	243.00 ft ²																																																																																																																																										
d. N/A																																																																																																																																												
a. Single assembly, no ai (Unvented)	Insulation	Area																																																																																																																																										
	R=0.0	2487.00 ft ²																																																																																																																																										
b. Single assembly, no ai (Unvented)	R=30.0	884.00 ft ²																																																																																																																																										
c. N/A																																																																																																																																												
a. Sup: 1st Floor, Ret: 1st Floor, AH: 1st Floor	R	6 225																																																																																																																																										
b. Sup: Master Be, Ret: Master Be, AH: Master Be		6 225																																																																																																																																										
c. 1 additional duct system(s) (see details)																																																																																																																																												
a. Central Unit	kBTu/hr	Efficiency																																																																																																																																										
	36.0	SEER2:15.00																																																																																																																																										
b. Central Unit	18.0	SEER2:15.00																																																																																																																																										
c. Central Unit	30.0	SEER2:15.00																																																																																																																																										
a. Electric Heat Pump	kBTu/hr	Efficiency																																																																																																																																										
	36.0	HSPF2:7.50																																																																																																																																										
b. Electric Heat Pump	18.0	HSPF2:7.50																																																																																																																																										
c. Electric Heat Pump	30.0	HSPF2:7.50																																																																																																																																										
a. PropaneTankless	Cap:	1 gallons																																																																																																																																										
	EF:	0.590																																																																																																																																										
b. Conservation features																																																																																																																																												
		None																																																																																																																																										
		CF, Pstat																																																																																																																																										

I certify that this home has complied with the Florida Energy Efficiency Code for Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature: *KOSP* Date: 2-10-24

Address of New Home: 533 SW Dyal Ave City/FL Zip: LAKE CITY, FL 32054



*Note: This is not a Building Energy Rating. If your Index is below 70, your home may qualify for energy efficient mortgage (EEM) incentives if you obtain a Florida Energy Rating. For information about the Florida Building Code, Energy Conservation, contact the Florida Building Commission's support staff.

**Label required by Section R303.1.3 of the Florida Building Code, Energy Conservation, if not DEFAULT.