FORM R405-2020

FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name:	Bullard Residence	Builder Name:	
Street:		Permit Office:	
City, State, Zip:	, FL,	Permit Number:	
Owner:		Jurisdiction:	
Design Location:	FL, Gainesville	County:	Columbia(Florida Climate Zone 2)

1. New construction or existing	New (From Plans)
2. Single family or multiple family	Detached
3. Number of units, if multiple family	1
4. Number of Bedrooms	3
5. Is this a worst case?	No
6. Conditioned floor area above grade (ft²)	698
Conditioned floor area below grade (ft²)	0

7. Windows(84.0 sqft.)	Description	Area
a. U-Factor:	Dbl, U=0.26	84.00 ft²
SHGC:	SHGC=0.20	
b. U-Factor:	N/A	ft²
SHGC:		
c. U-Factor:	N/A	ft²
SHGC:		
Area Weighted Average Overhang Depth:		1.500 ft
Area Weighted Average SHGC:		0.200

8. Skylights	Description	Area
U-Factor:(AVG)	N/A	N/A ft²
SHGC(AVG):	N/A	

9. Floor Types	Insulation	Area
a. Slab-On-Grade Edge Insulation	R= 0.0	698.00 ft²
b. N/A	R=	ft²
c. N/A	R=	ft²

10. Wall Types(954.0 sqft.)	Insulation	Area
a. Frame - Wood, Exterior	R=13.0	954.00 ft²
b. N/A		
c. N/A		
d. N/A		

11. Ceiling Types(698.0 sqft.)	Insulation	Area
a. Flat ceiling under att (Vented)	R=30.0	698.00 ft²
b. N/A		
c. N/A		

12. Roof(Comp. Shingles, Vented)	Deck R=0.0	780 ft²

13. Ducts, location & insulation level	R	ft²
a. Sup: Attic, Ret: Attic, AH: Main	6	140
b.		
c.		

14. Cooling Systems	kBtu/hr	Efficiency
a. Central Unit	24.0	SEER:15.00

15. Heating Systems	kBtu/hr	Efficiency
a. Electric Heat Pump	24.0	HSPF:8.50

16. Hot Water Systems	
a. Electric	Cap: 50 gallons
	EF: 0.920
b. Conservation features	
	None
17. Credits	CF, Pstat

Glass/Floor Area: 0.120

Total Proposed Modified Loads: 32.65

Total Baseline Loads: 33.03

PASS

I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.

PREPARED BY: _____

DATE: 12-13-22

I hereby certify that this building, as designed, is in compliance with the Florida Energy Code.

OWNER/AGENT: _____

DATE: _____

Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.

BUILDING OFFICIAL: _____

DATE: _____

- Compliance requires certification by the air handler unit manufacturer that the air handler enclosure qualifies as certified factory-sealed in accordance with R403.3.2.1.

- Default duct leakage does not require a Duct Leakage Test Report.

- Compliance requires an Air Barrier and Insulation Inspection Checklist in accordance with R402.4.1.1 and this project requires a PERFORMANCE envelope leakage test report with envelope leakage no greater than 5.00 ACH50 (R402.4.1.2).

FORM R405-2020

INPUT SUMMARY CHECKLIST REPORT

PROJECT

Title:	Bullard Residence			Address type:	Street Address
Building Type:	User	Bedrooms:	3	Lot #:	---
Owner:		Conditioned Area:	698	Block/SubDivision:	---
		Total Stories:	1	PlatBook:	---
Builder Name:		Worst Case:	No	Street:	
Permit Office:		Rotate Angle:	0	County:	Columbia
Jurisdiction:		Cross Ventilation:		City, State, Zip:	,
Family Type:	Detached	Whole House Fan:			FL,
New/Existing:	New (From Plans)	Terrain:	Rural		
Year Construct:	2022	Shielding:	Moderate/Rural		
Comment:					

CLIMATE

√	Design Location	Tmy Site	Design Temp 97.5%	Design Temp 2.5%	Int Design Temp Winter	Int Design Temp Summer	Heating Degree Days	Design Moisture	Daily temp Range
___	FL, Gainesville	FL_GAINESVILLE_REGIONA	32	92	70	75	1305.5	51	Medium

BLOCKS

√	Number	Name	Area	Volume
___	1	Block1	698	6282 cu ft

SPACES

√	Number	Name	Area	Volume	Kitchen	Occupants	Bedrooms	Finished	Cooled	Heated
___	1	Main	698	6282	Yes	4	3	Yes	Yes	Yes

FLOORS (Total Exposed Area = 698 sq.ft.)

√	#	Floor Type	Space	Exposed Perim	Perimeter R-Value	Area	U-Factor	Joist R-Value	Tile	Wood	Carpet
___	1	Slab-On-Grade Edge Ins	Main	106	0	698 ft	0.563	---	0.20	0.60	0.20

ROOF

√	#	Type	Materials	Roof Area	Gable Area	Roof Color	Rad Barr	Solar Absor.	SA Tested	Emitt	Emitt Tested	Deck Insul.	Pitch (deg)
___	1	Hip	Composition shingles	780 ft²	0 ft²	Medium	N	0.85	No	0.9	No	0	26.57

ATTIC

√	#	Type	Ventilation	Vent Ratio (1 in)	Area	RBS	IRCC
___	1	Full attic	Vented	300	698 ft²	N	N

CEILING (Total Exposed Area = 698 sq.ft.)

√	#	Ceiling Type	Space	R-Value	Ins. Type	Area	U-Factor	Framing Frac.	Truss Type
___	1	Flat ceiling under attic(Vented)	Main	30.0	Blown	698.0ft²	0.053	0.11	Wood

FORM R405-2020

INPUT SUMMARY CHECKLIST REPORT

WALLS (Total Exposed Area = 954 sq.ft.)

√ #	Ornt	Adjacent To	Wall Type	Space	Cavity R-Value	Width Ft	Width In	Height Ft	Height In	Area sq.ft.	U-Factor	Sheath R-Value	Frm. Frac.	Solar Absor.	Below Grade
___ 1	N	Exterior	Frame - Wood	Main	13.0	24.0	4	9.0	0	219.0	0.094		0.23	0.75	0 %
___ 2	E	Exterior	Frame - Wood	Main	13.0	28.0	8	9.0	0	258.0	0.094		0.23	0.75	0 %
___ 3	S	Exterior	Frame - Wood	Main	13.0	24.0	4	9.0	0	219.0	0.094		0.23	0.75	0 %
___ 4	W	Exterior	Frame - Wood	Main	13.0	28.0	8	9.0	0	258.0	0.094		0.23	0.75	0 %

DOORS (Total Exposed Area = 40 sq.ft.)

√ #	Ornt	Adjacent To	Door Type	Space	Storms	U-Value	Width Ft	Width In	Height Ft	Height In	Area
___ 1	N	Exterior	Insulated	Main	None	0.40	3.00	0	6.00	8	20.0ft²
___ 2	E	Exterior	Insulated	Main	None	0.40	3.00	0	6.00	8	20.0ft²

WINDOWS (Total Exposed Area = 84 sq.ft.)

√ #	Ornt	Wall ID	Frame	Panes	NFRC	U-Factor	SHGC	Imp	Storm	Total Area (ft²)	Same Units	Width (ft)	Height (ft)	--Overhang-- Depth (ft)	Sep. (ft)	Interior Shade	Screen
___ 1	N	1	Vinyl	Low-E Double	Y	0.26	0.20	N	N	10.0	1	2.00	5.00	1.5	2.3	None	None
___ 2	E	2	Vinyl	Low-E Double	Y	0.26	0.20	N	N	25.0	2	2.50	5.00	1.5	2.3	None	None
___ 3	E	2	Vinyl	Low-E Double	Y	0.26	0.20	N	N	12.0	1	6.00	2.00	1.5	2.3	None	None
___ 4	S	3	Vinyl	Low-E Double	Y	0.26	0.20	N	N	9.0	1	3.00	3.00	1.5	2.3	None	None
___ 5	W	4	Vinyl	Low-E Double	Y	0.26	0.20	N	N	25.0	2	2.50	5.00	1.5	2.3	None	None
___ 6	W	4	Vinyl	Low-E Double	Y	0.26	0.20	N	N	3.0	1	3.00	1.00	1.5	2.3	None	None

INFILTRATION

√ #	Scope	Method	SLA	CFM50	ELA	EqLA	ACH	ACH50	Space(s)	Infiltration Test Volume
___ 1	Wholehouse	Proposed ACH(50)	0.00029	524	28.72	53.92	0.1027	5.0	All	6282 cu ft

MASS

√ #	Mass Type	Area	Thickness	Furniture Fraction	Space
___ 1	Default(8 lbs/sq.ft.)	0 ft²	0 ft	0.30	Main

HEATING SYSTEM

√ #	System Type	Subtype/Speed	AHRI #	Efficiency	Capacity kBtu/hr	----Geothermal HeatPump---- Entry	Power	Volt	Current	Ducts	Block
___ 1	Electric Heat Pump	None/Single		HSPF: 8.50	24.0		0.00	0.00	0.00	sys#1	1

COOLING SYSTEM

√ #	System Type	Subtype/Speed	AHRI #	Efficiency	Capacity kBtu/hr	Air Flow cfm	SHR	Duct	Block
___ 1	Central Unit	None/Single		SEER:15.0	24.0	720	0.85	sys#1	1

FORM R405-2020

INPUT SUMMARY CHECKLIST REPORT

HOT WATER SYSTEM

√ #	System Type	Subtype	Location	EF(UEF)	Cap	Use	SetPnt	Fixture Flow	Pipe Ins.	Pipe length
___ 1	Electric	None	Main	0.92 (0.92)	50.00 gal	60 gal	120 deg	Standard	None	99

	Recirculation System	Recirc Control Type	Loop length	Branch length	Pump power	DWHR	Facilities Connected	Equal Flow	DWHR Eff	Other Credits
___ 1	No		NA	NA	NA	No	NA	NA	NA	None

DUCTS

√ Duct #	---------Supply--------- Location	R-Value	Area	---------Return--------- Location	R-Value	Area	Leakage Type	Air Handler	CFM 25 TOT	CFM 25 OUT	QN	RLF	HVAC # Heat	Cool
___ 1	Attic	6.0	140 ft²	Attic	6.0	35 ft²	Default Leakage	Main	(Default)	(Default)			1	1

TEMPERATURES

Programable Thermostat: Y Ceiling Fans: N

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Cooling	[ ]	[ ]	[ ]	[ ]	[ ]	[X]	[X]	[X]	[X]	[ ]	[ ]	[ ]
Heating	[X]	[X]	[X]	[ ]	[ ]	[ ]	[ ]	[ ]	[ ]	[ ]	[X]	[X]
Venting	[ ]	[ ]	[X]	[X]	[ ]	[ ]	[ ]	[ ]	[ ]	[X]	[X]	[ ]

√ Thermostat Schedule: HERS 2006 Reference Schedule Type		Hours 1	2	3	4	5	6	7	8	9	10	11	12
___ Cooling (WD)	AM	78	78	78	78	78	78	78	78	80	80	80	80
	PM	80	80	80	80	78	78	78	78	78	78	78	78
___ Cooling (WEH)	AM	78	78	78	78	78	78	78	78	80	80	80	80
	PM	80	80	80	80	78	78	78	78	78	78	78	78
___ Heating (WD)	AM	65	65	65	65	65	65	65	68	68	68	68	68
	PM	68	68	68	68	68	68	68	68	68	68	68	68
___ Heating (WEH)	AM	65	65	65	65	65	65	65	68	68	68	68	68
	PM	68	68	68	68	68	68	68	68	68	68	68	68