


FLORIDA DEPARTMENT OF
Business & Professional Regulation



[BCIS Home](#) | [Log In](#) | [User Registration](#) | [Hot Topics](#) | [Submit Surcharge](#) | [Stats & Facts](#) | [Publications](#) | [Contact Us](#) | [BCIS Site Map](#) | [Links](#) | [Search](#)



Product Approval
USER: Public User

[Product Approval Menu](#) > [Product or Application Search](#) > [Application List](#) > **Application Detail**

OFFICE OF THE
SECRETARY

FL #

FL11479-R6

Application Type

Revision

Code Version

2023

Application Status

Approved

*Approved by DBPR. Approvals by DBPR shall be reviewed and ratified by the POC and/or the Commission if necessary.

Comments

Archived



Product Manufacturer

Regency Plus Inc

Address/Phone/Email

2000 Locust Gap Highway
Mount Carmel, PA 17851
(570) 339-3374
tony@cwbyrpi.com

Authorized Signature

Tony Procopio
tony@cwbyrpi.com

Technical Representative

Tony Procopio

Address/Phone/Email

2000 Locust Gap Hwy
Mount Carmel, PA 17851
(570) 339-3374
tony@cwbyrpi.com

Quality Assurance Representative

Joe Korzeniecki

Address/Phone/Email

2000 Locust Gap Hwy.
Mount Carmel, PA 17851
(570) 339-3374
joek@window-pros.info

Category

Windows

Subcategory

Mullions

Compliance Method

Certification Mark or Listing

Certification Agency

National Accreditation & Management Institute

Validated By

National Accreditation & Management Institute

Referenced Standard and Year (of Standard)

Standard

Year

AAMA 450

2010

AAMA/WDMA/CSA 101/I.S.2/A440

2008

ASTM E1886

13a

ASTM E1996

14a

TAS 201

1994

TAS 202

1994

TAS 203

1994

Equivalence of Product Standards

Certified By

Florida Licensed Professional Engineer or Architect

[FL11479_R6_Equiv_EERNo2522_Rev2_FL11479_Mullions_ss.pdf](#)

Product Approval Method

Method 1 Option A

Date Submitted

09/04/2023

Date Validated

09/05/2023

Date Pending FBC Approval

Date Approved

09/10/2023

Summary of Products

FL #	Model, Number or Name	Description
X 11479.1	TECH 5000 IMPACT MULLION	TECH 5000 IMPACT MULLION
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: Yes Design Pressure: +70/-70 Other:		Certification Agency Certificate FL11479 R6 C CAC NI007051-R6.pdf Quality Assurance Contract Expiration Date 12/31/2027 Installation Instructions FL11479 R6 II RPLS0057 RevA SERIES-5000-MULLIONS ss.pdf Verified By: Robert J. Amoruso, P.E. FL PE No. 49752 Created by Independent Third Party: Yes Evaluation Reports FL11479 R6 AE PERNo2522 Rev2 FL11479 Mullions ss.pdf Created by Independent Third Party: Yes
11479.2	TECH 5000 T IMPACT MULLION	TECH 5000 T IMPACT MULLION
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: Yes Design Pressure: +70/-70 Other:		Certification Agency Certificate FL11479 R6 C CAC NI007050-R5.pdf Quality Assurance Contract Expiration Date 02/28/2027 Installation Instructions FL11479 R6 II RPLS0058 RevA SERIES-5000-T-MULLIONS ss.pdf Verified By: Robert J. Amoruso, P.E. FL PE No. 49752 Created by Independent Third Party: Yes Evaluation Reports FL11479 R6 AE PERNo2522 Rev2 FL11479 Mullions ss.pdf Created by Independent Third Party: Yes

[Back](#)[Next](#)

[Contact Us](#) :: [2601 Blair Stone Road, Tallahassee FL 32399](#) Phone: 850-487-1824

The State of Florida is an AA/EEO employer. [Copyright 2007-2013 State of Florida](#). :: [Privacy Statement](#) :: [Accessibility Statement](#) :: [Refund Statement](#)

Under Florida law, email addresses are public records. If you do not want your e-mail address released in response to a public-records request, do not send electronic mail to this entity. Instead, contact the office by phone or by traditional mail. If you have any questions, please contact 850.487.1395. *Pursuant to Section 455.275(1), Florida Statutes, effective October 1, 2012, licensees licensed under Chapter 455, F.S. must provide the Department with an email address if they have one. The emails provided may be used for official communication with the licensee. However email addresses are public record. If you do not wish to supply a personal address, please provide the Department with an email address which can be made available to the public. To determine if you are a licensee under Chapter 455, F.S., please click [here](#).

Product Approval Accepts:



Credit Card
Safe

securityMETRICS

REV	DESCRIPTION	DATE	BY
A	REVISED ISSUE	1/4/18	RJA

PROJECT # 47-0906

1. THE PRODUCT SHOWN HAS BEEN TESTED, EVALUATED AND DESIGNED TO COMPLY WITH REQUIREMENTS OF THE CURRENT EDITION OF THE FLORIDA BUILDING CODE INCLUDING THE HIGH VELOCITY HURRICANE ZONE (HVHZ).
2. THE PRODUCT DETAILS CONTAINED HEREIN ARE BASED UPON THE FOLLOWING SIGNED AND SEALED TEST REPORTS AND ASSOCIATED LABORATORY DRAWINGS BY NATIONAL CERTIFIED TESTING LABORATORIES, YORK, PA.
 - 2.1. NCTL-110-10616-1, AAMA/WDMA/CSA 101/I.S.2/A440
 - 2.2. NCTL-110-10616-2, TAS 201, TAS 202 and TAS 203
 - 2.3. NCTL-110-10616-3, ASTM E1886 & ASTM E1996
3. WOOD FRAMING AND MASONRY OPENING TO BE DESIGNED AND ANCHORED TO PROPERLY TRANSFER ALL LOADS TO STRUCTURE. FRAMING AND MASONRY OPENING IS THE RESPONSIBILITY OF THE ARCHITECT OR ENGINEER OF RECORD.
4. INSTALLER/CONTRACTOR IS RESPONSIBLE FOR MAINTAINING STRUCTURAL INTEGRITY OF WINDOW OPENING AND ALL WOOD FRAMING AROUND WINDOW.
5. RESPONSIBILITY OF SELECTING FENESTRATION PRODUCTS TO MEET ANY APPLICABLE LOCAL LAWS, BUILDING CODES, ORDINANCES OR OTHER SAFETY REQUIREMENTS REST SOLELY WITH THE ARCHITECT, ENGINEER OF RECORD, BUILDING OWNER OR CONTRACTOR. APPROVED IMPACT PROTECTIVE SYSTEM IS NOT REQUIRED FOR THIS PRODUCT IN WIND BORNE DEBRIS REGIONS INCLUDING THE HIGH VELOCITY HURRICANE ZONE.
6. DESIGN PRESSURE AND INSTALLATION DETAILS SHOWN IN THIS DOCUMENT APPLY ONLY TO THE MULLION. WINDOWS MUST BE APPROVED UNDER SEPARATE PRODUCT APPROVAL.
7. SINGLE UNITS TO BE MULLED ARE NOT LIMITED TO THOSE SHOWN IN THIS DRAWING. SINGLE UNITS TO BE MULLED TOGETHER MUST BE MANUFACTURED BY REGENCY PLUS, INC. AND MUST BE MADE OF VINYL PVC. FIXED WINDOW SHOWN; OTHER WINDOW TYPES APPROVED.
8. DESIGN PRESSURE OF MULLED UNIT SHALL BE CONTROLLED BY THE LESSER DESIGN PRESSURE OF THE MULLION OR THE INDIVIDUAL WINDOW UNIT.
9. TWIN CONFIGURATION SHOWN. UNITS MAY BE MULLED TOGETHER INDEFINITELY IF THE SINGLE UNIT WIDTH AND THE SINGLE UNIT HEIGHT ARE NOT EXCEEDED, AND MULLION IS ANCHORED AS SHOWN IN THIS INSTALLATION DRAWING.
10. MULLION VERTICAL INSTALLATION SHOWN. MULLION MAY BE USED IN HORIZONTAL APPLICATIONS IF DIMENSIONS SHOWN ARE NOT EXCEEDED AND MULLION IS ANCHORED ACCORDING TO THIS INSTALLATION INSTRUCTION.




TABLE OF CONTENTS	
SHEET	SHEET DESCRIPTION
1	ELEVATION AND GENERAL NOTES
2	CROSS SECTIONS, BOM AND INSTALLATION DETAILS
3	COMPONENTS

Digitally signed by
Robert J Amoruso
Date: 2018.01.09
10:17:48 -05'00'

[illegible]

Robert J. Amoruso, P.E.
Florida P.E. No. 49752



Digitally signed by
Robert J Amoruso
Date: 2018.01.09
10:18:17 -05'00'