


RESIDENTIAL ENERGY CONSERVATION CODE DOCUMENTATION CHECKLIST

Florida Department of Business and Professional Regulation Simulated Performance Alternative (Performance) Method

Applications for compliance with the 2017 Florida Building Code, Energy Conservation via the residential Simulated Performance Method shall include:

- This checklist
- A Form R405 report that documents that the Proposed Design complies with Section R405.3 of the Florida Energy Code. This form shall include a summary page indicating home address, e-ratio and the pass or fail status along with summary areas and types of components, whether the home was simulated as a worst-case orientation, name and version of the compliance software tool, name of individual completing the compliance report (one page) and an input summary checklist that can be used for field verification (usually four pages/may be greater).
- Energy Performance Level (EPL) Display Card (one page)
- HVAC system sizing and selection based on ACCA Manual S or per exceptions provided in Section R403.7
- Mandatory Requirements (five pages)




Required prior to CO for the Performance Method:

- Air Barrier and Insulation Inspection Component Criteria checklist (Table R402.4.1.1 - one page)
- A completed Envelope Leakage Test Report (usually one page)
- If Form R405 duct leakage type indicates anything other than "default leakage", then a completed Form R405 Duct Leakage Test Report (usually one page)

FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

<p>Project Name: Lot 1 Cannon Creek Place Street: City, State, Zip: Lake City, FL, 32025 Owner: Trent Giebeig Design Location: FL, Gainesville</p>	<p>Builder Name: Trent Giebeig Permit Office: Columbia County Permit Number: Jurisdiction: County: Columbia (Florida Climate Zone 2)</p>																																																																																																																											
<table style="width:100%; border-collapse: collapse;"> <tr> <td style="width:30%;">1. New construction or existing</td> <td style="width:30%;">New (From Plans)</td> <td style="width:40%;"></td> </tr> <tr> <td>2. Single family or multiple family</td> <td>Single-family</td> <td></td> </tr> <tr> <td>3. Number of units, if multiple family</td> <td>1</td> <td></td> </tr> <tr> <td>4. Number of Bedrooms</td> <td>3</td> <td></td> </tr> <tr> <td>5. Is this a worst case?</td> <td>No</td> <td></td> </tr> <tr> <td>6. Conditioned floor area above grade (ft²)</td> <td>1600</td> <td></td> </tr> <tr> <td> Conditioned floor area below grade (ft²)</td> <td>0</td> <td></td> </tr> <tr> <td>7. Windows (158.0 sqft.)</td> <td>Description</td> <td>Area</td> </tr> <tr> <td> a. U-Factor:</td> <td>Dbl, U=0.40</td> <td>158.00 ft²</td> </tr> <tr> <td> SHGC:</td> <td>SHGC=0.25</td> <td></td> </tr> <tr> <td> b. U-Factor:</td> <td>N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> <td></td> </tr> <tr> <td> c. U-Factor:</td> <td>N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> <td></td> </tr> <tr> <td> d. U-Factor:</td> <td>N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> <td></td> </tr> <tr> <td>Area Weighted Average Overhang Depth:</td> <td>4.032 ft.</td> <td></td> </tr> <tr> <td>Area Weighted Average SHGC:</td> <td>0.250</td> <td></td> </tr> <tr> <td>8. Floor Types (1600.0 sqft.)</td> <td>Insulation</td> <td>Area</td> </tr> <tr> <td> a. Slab-On-Grade Edge Insulation</td> <td>R=0.0</td> <td>1600.00 ft²</td> </tr> <tr> <td> b. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td> c. N/A</td> <td>R=</td> <td>ft²</td> </tr> </table>	1. New construction or existing	New (From Plans)		2. Single family or multiple family	Single-family		3. Number of units, if multiple family	1		4. Number of Bedrooms	3		5. Is this a worst case?	No		6. Conditioned floor area above grade (ft²)	1600		Conditioned floor area below grade (ft²)	0		7. Windows (158.0 sqft.)	Description	Area	a. U-Factor:	Dbl, U=0.40	158.00 ft²	SHGC:	SHGC=0.25		b. U-Factor:	N/A	ft²	SHGC:			c. U-Factor:	N/A	ft²	SHGC:			d. U-Factor:	N/A	ft²	SHGC:			Area Weighted Average Overhang Depth:	4.032 ft.		Area Weighted Average SHGC:	0.250		8. Floor Types (1600.0 sqft.)	Insulation	Area	a. Slab-On-Grade Edge Insulation	R=0.0	1600.00 ft²	b. N/A	R=	ft²	c. N/A	R=	ft²	<table style="width:100%; border-collapse: collapse;"> <tr> <td style="width:50%;">9. Wall Types (1417.2 sqft.)</td> <td style="width:25%;">Insulation</td> <td style="width:25%;">Area</td> </tr> <tr> <td> a. Face Brick - Wood, Exterior</td> <td>R=13.0</td> <td>835.89 ft²</td> </tr> <tr> <td> b. Frame - Wood, Exterior</td> <td>R=13.0</td> <td>421.33 ft²</td> </tr> <tr> <td> c. Frame - Wood, Adjacent</td> <td>R=13.0</td> <td>160.00 ft²</td> </tr> <tr> <td> d. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>10. Ceiling Types (1600.0 sqft.)</td> <td>Insulation</td> <td>Area</td> </tr> <tr> <td> a. Under Attic (Vented)</td> <td>R=30.0</td> <td>1600.00 ft²</td> </tr> <tr> <td> b. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td> c. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>11. Ducts</td> <td></td> <td>R ft²</td> </tr> <tr> <td> a. Sup: Attic, Ret: Attic, AH: Main</td> <td></td> <td>6 320</td> </tr> <tr> <td>12. Cooling systems</td> <td>kBtu/hr</td> <td>Efficiency</td> </tr> <tr> <td> a. Central Unit</td> <td>20.9</td> <td>SEER:16.00</td> </tr> <tr> <td>13. Heating systems</td> <td>kBtu/hr</td> <td>Efficiency</td> </tr> <tr> <td> a. Electric Heat Pump</td> <td>24.9</td> <td>HSPF:8.90</td> </tr> <tr> <td>14. Hot water systems</td> <td></td> <td>Cap: 50 gallons</td> </tr> <tr> <td> a. Electric</td> <td></td> <td>EF: 0.920</td> </tr> <tr> <td> b. Conservation features</td> <td></td> <td>None</td> </tr> <tr> <td>15. Credits</td> <td></td> <td>Pstat</td> </tr> </table>	9. Wall Types (1417.2 sqft.)	Insulation	Area	a. Face Brick - Wood, Exterior	R=13.0	835.89 ft²	b. Frame - Wood, Exterior	R=13.0	421.33 ft²	c. Frame - Wood, Adjacent	R=13.0	160.00 ft²	d. N/A	R=	ft²	10. Ceiling Types (1600.0 sqft.)	Insulation	Area	a. Under Attic (Vented)	R=30.0	1600.00 ft²	b. N/A	R=	ft²	c. N/A	R=	ft²	11. Ducts		R ft²	a. Sup: Attic, Ret: Attic, AH: Main		6 320	12. Cooling systems	kBtu/hr	Efficiency	a. Central Unit	20.9	SEER:16.00	13. Heating systems	kBtu/hr	Efficiency	a. Electric Heat Pump	24.9	HSPF:8.90	14. Hot water systems		Cap: 50 gallons	a. Electric		EF: 0.920	b. Conservation features		None	15. Credits		Pstat
1. New construction or existing	New (From Plans)																																																																																																																											
2. Single family or multiple family	Single-family																																																																																																																											
3. Number of units, if multiple family	1																																																																																																																											
4. Number of Bedrooms	3																																																																																																																											
5. Is this a worst case?	No																																																																																																																											
6. Conditioned floor area above grade (ft²)	1600																																																																																																																											
Conditioned floor area below grade (ft²)	0																																																																																																																											
7. Windows (158.0 sqft.)	Description	Area																																																																																																																										
a. U-Factor:	Dbl, U=0.40	158.00 ft²																																																																																																																										
SHGC:	SHGC=0.25																																																																																																																											
b. U-Factor:	N/A	ft²																																																																																																																										
SHGC:																																																																																																																												
c. U-Factor:	N/A	ft²																																																																																																																										
SHGC:																																																																																																																												
d. U-Factor:	N/A	ft²																																																																																																																										
SHGC:																																																																																																																												
Area Weighted Average Overhang Depth:	4.032 ft.																																																																																																																											
Area Weighted Average SHGC:	0.250																																																																																																																											
8. Floor Types (1600.0 sqft.)	Insulation	Area																																																																																																																										
a. Slab-On-Grade Edge Insulation	R=0.0	1600.00 ft²																																																																																																																										
b. N/A	R=	ft²																																																																																																																										
c. N/A	R=	ft²																																																																																																																										
9. Wall Types (1417.2 sqft.)	Insulation	Area																																																																																																																										
a. Face Brick - Wood, Exterior	R=13.0	835.89 ft²																																																																																																																										
b. Frame - Wood, Exterior	R=13.0	421.33 ft²																																																																																																																										
c. Frame - Wood, Adjacent	R=13.0	160.00 ft²																																																																																																																										
d. N/A	R=	ft²																																																																																																																										
10. Ceiling Types (1600.0 sqft.)	Insulation	Area																																																																																																																										
a. Under Attic (Vented)	R=30.0	1600.00 ft²																																																																																																																										
b. N/A	R=	ft²																																																																																																																										
c. N/A	R=	ft²																																																																																																																										
11. Ducts		R ft²																																																																																																																										
a. Sup: Attic, Ret: Attic, AH: Main		6 320																																																																																																																										
12. Cooling systems	kBtu/hr	Efficiency																																																																																																																										
a. Central Unit	20.9	SEER:16.00																																																																																																																										
13. Heating systems	kBtu/hr	Efficiency																																																																																																																										
a. Electric Heat Pump	24.9	HSPF:8.90																																																																																																																										
14. Hot water systems		Cap: 50 gallons																																																																																																																										
a. Electric		EF: 0.920																																																																																																																										
b. Conservation features		None																																																																																																																										
15. Credits		Pstat																																																																																																																										
<p>Glass/Floor Area: 0.099</p>	<p>Total Proposed Modified Loads: 43.37 Total Baseline Loads: 43.37</p>	PASS																																																																																																																										
<p>I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.</p> <p>PREPARED BY: <u>Walter H. Lucia</u> DATE: <u>7/13/20</u></p> <p>I hereby certify that this building, as designed, is in compliance with the Florida Energy Code.</p> <p>OWNER/AGENT: _____ DATE: _____</p>	<p>Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.</p> <div style="text-align: center;">  </div> <p>BUILDING OFFICIAL: _____ DATE: _____</p>																																																																																																																											

- Compliance requires certification by the air handler unit manufacturer that the air handler enclosure qualifies as certified factory-sealed in accordance with R403.3.2.1.
- Compliance requires an Air Barrier and Insulation Inspection Checklist in accordance with R402.4.1.1 and this project requires an envelope leakage test report with envelope leakage no greater than 7.00 ACH50 (R402.4.1.2).

INPUT SUMMARY CHECKLIST REPORT

PROJECT												
Title:	Lot 1 Cannon Creek Place	Bedrooms:	3	Address Type:	Lot Information							
Building Type:	User	Conditioned Area:	1600	Lot #:	10							
Owner Name:	Trent Giebeig	Total Stories:	1	Block/Subdivision:	Cannon Creek PI							
# of Units:	1	Worst Case:	No	PlatBook:								
Builder Name:	Trent Giebeig	Rotate Angle:	90	Street:								
Permit Office:	Columbia County	Cross Ventilation:		County:	Columbia							
Jurisdiction:		Whole House Fan:		City, State, Zip:	Lake City , FL , 32025							
Family Type:	Single-family											
New/Existing:	New (From Plans)											
Comment:												
CLIMATE												
<input checked="" type="checkbox"/>	Design Location	TMY Site	Design Temp	Int Design Temp	Heating	Design	Daily Temp					
	FL, Gainesville	FL_GAINESVILLE_REGI	97.5 % 2.5 %	Winter Summer	Degree Days	Moisture	Range					
			32 92	70 75	1305.5	51	Medium					
BLOCKS												
Number	Name	Area	Volume									
1	Block1	1600	12800									
SPACES												
Number	Name	Area	Volume	Kitchen	Occupants	Bedrooms	Infil ID	Finished	Cooled	Heated		
1	Main	1600	12800	Yes	3	3	1	Yes	Yes	Yes		
FLOORS												
<input checked="" type="checkbox"/>	#	Floor Type	Space	Perimeter	R-Value	Area	Tile	Wood	Carpet			
	1	Slab-On-Grade Edge Insulatio	Main	165.5 ft	0	1600 ft²	---	0.25	0.25	0.5		
ROOF												
<input checked="" type="checkbox"/>	#	Type	Materials	Roof Area	Gable Area	Roof Color	Solar Absor.	SA Tested	Emitt Tested	Emitt Tested	Deck Insul.	Pitch (deg)
	1	Hip	Composition shingles	1789 ft²	0 ft²	Light	0.96	No	0.9	No	0	26.6
ATTIC												
<input checked="" type="checkbox"/>	#	Type	Ventilation	Vent Ratio (1 in)	Area	RBS	IRCC					
	1	Full attic	Vented	300	1600 ft²	N	N					
CEILING												
<input checked="" type="checkbox"/>	#	Ceiling Type	Space	R-Value	Ins Type	Area	Framing Frac	Truss Type				
	1	Under Attic (Vented)	Main	30	Blown	1600 ft²	0.11	Wood				

INPUT SUMMARY CHECKLIST REPORT

WALLS														
✓ #	Ornt	Adjacent To	Wall Type	Space	Cavity R-Value	Width Ft	In	Height Ft	In	Area	Sheathing R-Value	Framing Fraction	Solar Absor.	Below Grade%
___ 1	N=>E	Exterior	Frame - Wood	Main	13	14		8		112.0 ft²		0.23	0.75	0
___ 2	N=>E	Exterior	Frame - Wood	Main	13	14		8		112.0 ft²		0.23	0.75	0
___ 3	N=>E	Exterior	Frame - Wood	Main	13	24	8	8		197.3 ft²		0.23	0.75	0
___ 4	E=>S	Exterior	Face Brick - Wood	Main	13	30	1	8		240.7 ft²		0.23	0.75	0
___ 5	S=>W	Garage	Frame - Wood	Main	13	20		8		160.0 ft²		0.23	0.75	0
___ 6	S=>W	Exterior	Face Brick - Wood	Main	13	11	8	9	4	108.9 ft²		0.23	0.75	0
___ 7	W=>N	Exterior	Face Brick - Wood	Main	13	4		9	4	37.3 ft²		0.23	0.75	0
___ 8	S=>W	Exterior	Face Brick - Wood	Main	13	7	9	9	4	72.3 ft²		0.23	0.75	0
___ 9	E=>S	Exterior	Face Brick - Wood	Main	13	4		8		32.0 ft²		0.23	0.75	0
___ 10	S=>W	Exterior	Face Brick - Wood	Main	13	13		8		104.0 ft²		0.23	0.75	0
___ 11	W=>N	Exterior	Face Brick - Wood	Main	13	30	1	8		240.7 ft²	0	0.23	0.75	0

DOORS											
✓ #	Ornt	Door Type	Space	Storms	U-Value	Width Ft	In	Height Ft	In	Area	
___ 1	S=>W	Insulated	Main	None	.4	3		6	8	20 ft²	
___ 2	S=>W	Insulated	Main	None	.4	2	8	6	8	17.8 ft²	

WINDOWS														
Orientation shown is the entered orientation (=>) changed to As Built (rotated 90 degrees).														
✓ #	Ornt	Wall ID	Frame	Panes	NFRC	U-Factor	SHGC	Imp	Area	Overhang Depth	Separation	Int Shade	Screening	
___ 1	N=>E	1	Vinyl	Double (Tinted)	Yes	0.4	0.25	N	15.0 ft²	1 ft 6 in	1 ft 0 in	Roller shade	Exterior 1	
___ 2	N=>E	2	Vinyl	Double (Tinted)	Yes	0.4	0.25	N	40.0 ft²	11 ft 6 in	1 ft 0 in	Roller shade	Exterior 1	
___ 3	N=>E	3	Vinyl	Double (Tinted)	Yes	0.4	0.25	N	20.0 ft²	1 ft 6 in	1 ft 0 in	Roller shade	Exterior 1	
___ 4	N=>E	3	Vinyl	Double (Tinted)	Yes	0.4	0.25	N	30.0 ft²	1 ft 6 in	1 ft 0 in	Roller shade	Exterior 1	
___ 5	E=>S	4	Vinyl	Double (Tinted)	Yes	0.4	0.25	N	8.0 ft²	1 ft 6 in	1 ft 0 in	Roller shade	Exterior 1	
___ 6	S=>W	6	Vinyl	Double (Tinted)	Yes	0.4	0.25	N	30.0 ft²	1 ft 6 in	1 ft 0 in	Roller shade	Exterior 1	
___ 7	S=>W	6	Vinyl	Double (Tinted)	Yes	0.4	0.25	N	15.0 ft²	1 ft 6 in	1 ft 0 in	Roller shade	Exterior 1	

GARAGE						
✓ #	Floor Area	Ceiling Area	Exposed Wall Perimeter	Avg. Wall Height	Exposed Wall Insulation	
___ 1	400 ft²	400 ft²	60 ft	8 ft	1	

INFILTRATION								
#	Scope	Method	SLA	CFM 50	ELA	EqLA	ACH	ACH 50
1	Wholehouse	Proposed ACH(50)	.000356	1493.3	81.98	154.18	.2719	7

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE INDEX* = 100

The lower the Energy Performance Index, the more efficient the home.

<p>1. New home or, addition</p> <p>2. Single-family or multiple-family</p> <p>3. No. of units (if multiple-family)</p> <p>4. Number of bedrooms</p> <p>5. Is this a worst case? (yes/no)</p> <p>6. Conditioned floor area (sq. ft.)</p> <p>7. Windows, type and area a) U-factor:(weighted average) b) Solar Heat Gain Coefficient (SHGC) c) Area</p> <p>8. Skylights a) U-factor:(weighted average) b) Solar Heat Gain Coefficient (SHGC)</p> <p>9. Floor type, insulation level: a) Slab-on-grade (R-value) b) Wood, raised (R-value) c) Concrete, raised (R-value)</p> <p>10. Wall type and insulation: A. Exterior: 1. Wood frame (Insulation R-value) 2. Masonry (Insulation R-value) B. Adjacent: 1. Wood frame (Insulation R-value) 2. Masonry (Insulation R-value)</p> <p>11. Ceiling type and insulation level a) Under attic b) Single assembly c) Knee walls/skylight walls d) Radiant barrier installed</p>	<p>1. <u>New (From Plans)</u></p> <p>2. <u>Single-family</u></p> <p>3. <u>1</u></p> <p>4. <u>3</u></p> <p>5. <u>No</u></p> <p>6. <u>1600</u></p> <p>7a. <u>0.400</u> 7b. <u>0.250</u> 7c. <u>158.0</u></p> <p>8a. <u>NA</u> 8b. <u>NA</u></p> <p>9a. <u>0.0</u> 9b. _____ 9c. _____</p> <p>10A1. <u>13.0</u> 10A2. _____ 10B1. <u>13.0</u> 10B2. _____</p> <p>11a. <u>30.0</u> 11b. _____ 11c. _____ 11d. <u>No</u></p>	<p>12. Ducts, location & insulation level a) Supply ducts R <u>6.0</u> b) Return ducts R <u>6.0</u> c) AHU location <u>Attic/Attic</u></p> <p>13. Cooling system: Capacity <u>20.9</u> a) Split system SEER <u>16.0</u> b) Single package SEER _____ c) Ground/water source SEER/COP _____ d) Room unit/PTAC EER _____ e) Other _____</p> <p>14. Heating system: Capacity <u>24.9</u> a) Split system heat pump HSPF <u>8.9</u> b) Single package heat pump HSPF _____ c) Electric resistance COP _____ d) Gas furnace, natural gas AFUE _____ e) Gas furnace, LPG AFUE _____ f) Other _____</p> <p>15. Water heating system a) Electric resistance EF <u>0.92</u> b) Gas fired, natural gas EF _____ c) Gas fired, LPG EF _____ d) Solar system with tank EF _____ e) Dedicated heat pump with tank EF _____ f) Heat recovery unit HeatRec% _____ g) Other _____</p> <p>16. HVAC credits claimed (Performance Method) a) Ceiling fans _____ b) Cross ventilation <u>No</u> c) Whole house fan <u>No</u> d) Multizone cooling credit _____ e) Multizone heating credit _____ f) Programmable thermostat <u>Yes</u></p>
---	--	---

*Label required by Section R303.1.3 of the Florida Building Code, Energy Conservation, if not DEFAULT.

I certify that this home has complied with the Florida Building Code, Energy Conservation, through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL display card will be completed based on installed code compliant features.

Builder Signature: _____ Date: _____

Address of New Home: _____ City/FL Zip: Lake City, FL 32025

INPUT SUMMARY CHECKLIST REPORT

HEATING SYSTEM																								
✓	#	System Type	Subtype		Efficiency	Capacity	Block	Ducts																
	1	Electric Heat Pump/	Split		HSPF:8.9	24.87 kBtu/hr	1	sys#1																
COOLING SYSTEM																								
✓	#	System Type	Subtype		Efficiency	Capacity	Air Flow	SHR	Block	Ducts														
	1	Central Unit/	Split		SEER: 16 20.91	kBtu/hr	630 cfm	0.75	1	sys#1														
HOT WATER SYSTEM																								
✓	#	System Type	SubType	Location	EF	Cap	Use	SetPnt	Conservation															
	1	Electric	None	Garage	0.92	50 gal	60 gal	120 deg	None															
SOLAR HOT WATER SYSTEM																								
✓	FSEC Cert #	Company Name		System Model #		Collector Model #		Collector Area	Storage Volume	FEF														
	None	None						ft²																
DUCTS																								
✓	#	--- Supply ---			--- Return ---		Leakage Type	Air Handler	CFM 25 TOT	CFM25 OUT	QN	RLF	HVAC #											
	1	Attic	6	320 ft²	Attic	80 ft²	Default Leakage	Main	(Default)	(Default)			1	1										
TEMPERATURES																								
Programable Thermostat: Y					Ceiling Fans:																			
Cooling	<input type="checkbox"/>	Jan	<input type="checkbox"/>	Feb	<input type="checkbox"/>	Mar	<input type="checkbox"/>	Apr	<input type="checkbox"/>	May	<input checked="" type="checkbox"/>	Jun	<input checked="" type="checkbox"/>	Jul	<input checked="" type="checkbox"/>	Aug	<input checked="" type="checkbox"/>	Sep	<input type="checkbox"/>	Oct	<input type="checkbox"/>	Nov	<input type="checkbox"/>	Dec
Heating	<input checked="" type="checkbox"/>	Jan	<input checked="" type="checkbox"/>	Feb	<input checked="" type="checkbox"/>	Mar	<input type="checkbox"/>	Apr	<input type="checkbox"/>	May	<input type="checkbox"/>	Jun	<input type="checkbox"/>	Jul	<input type="checkbox"/>	Aug	<input type="checkbox"/>	Sep	<input type="checkbox"/>	Oct	<input checked="" type="checkbox"/>	Nov	<input checked="" type="checkbox"/>	Dec
Venting	<input type="checkbox"/>	Jan	<input type="checkbox"/>	Feb	<input type="checkbox"/>	Mar	<input type="checkbox"/>	Apr	<input type="checkbox"/>	May	<input type="checkbox"/>	Jun	<input type="checkbox"/>	Jul	<input type="checkbox"/>	Aug	<input type="checkbox"/>	Sep	<input type="checkbox"/>	Oct	<input type="checkbox"/>	Nov	<input type="checkbox"/>	Dec
Thermostat Schedule:		HERS 2006 Reference																						
Schedule Type		Hours																						
		1	2	3	4	5	6	7	8	9	10	11	12											
Cooling (WD)	AM	78	78	78	78	78	78	78	78	78	80	80	80											
	PM	80	80	78	78	78	78	78	78	78	78	78	78											
Cooling (WEH)	AM	78	78	78	78	78	78	78	78	78	78	78	78											
	PM	78	78	78	78	78	78	78	78	78	78	78	78											
Heating (WD)	AM	66	66	66	66	66	68	68	68	68	68	68	68											
	PM	68	68	68	68	68	68	68	68	68	68	68	66											
Heating (WEH)	AM	66	66	66	66	66	68	68	68	68	68	68	68											
	PM	68	68	68	68	68	68	68	68	68	68	68	66											
MASS																								
Mass Type		Area		Thickness		Furniture Fraction		Space																
Default(8 lbs/sq.ft.		0 ft²		0 ft		0.3		Main																

Name: William H. Freeman

Signature: William H. Freeman

Rating Compant: William H. Freema

Date: 7/13/20