

RE: TEEL - TEELE RES AND GARAGE

TRENCO

818 Soundside Road
Edenton, NC 27932
Telephone 252/482-7000
Fax 252/482-7115

Site Information:

Project Customer: Project Name:
Lot/Block:
Address: 6129 SW CR18
City: FORT WHITE

Subdivision:

State: FLORIDA

No.	Seal#	Truss Name	Date
35	E4483150	J07B	10/26/07
36	E4483151	J07L	10/26/07

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483116
TEEL	A1	HIP	1	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc. Fri Oct 26 14 54 01 2007 Page 1





Plate Offsets (X,Y): [2.0-2.5,Edge], [4.0-3.0,0-2-9], [12.0-3.0,0-2-9], [14.0-2.5,Edge]

LOADING (psf)	SPACING	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.44	Vert(LL)	-0.19	17	>999	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.64	Vert(TL)	-0.50	17-19	>675	MT20H	187/143
BCLL 0.0	Rep Stress Incr NO	WB 0.99	Horz(TL)	0.10	14	n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)						Weight: 269 lb


LUMBER
 TOP CHORD 2 X 6 SYP 2400F 2.0E *Except*
 1-4 2 X 4 SYP No.2D, 12-15 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP 2400F 2.0E
 WEBS 2 X 4 SYP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied or 3-0-9 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
 WEBS 1 Row at midpt 5-22, 8-22, 10-19

REACTIONS (lb/size) 2=369/0-3-0, 22=4009/0-3-8, 14=1931/0-3-8
 Max Horz 2=56(LC 5)
 Max Uplift 2=-36(LC 5), 22=-909(LC 3), 14=-471(LC 6)
 Max Grav 2=378(LC 7), 22=4009(LC 1), 14=1937(LC 8)

FORCES (lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/33, 2-3=-315/116, 3-4=-232/200, 4-5=-203/186, 5-6=-737/3316, 6-26=-737/3316, 7-26=-737/3316, 7-8=-737/3316, 8-27=-2660/767, 27-28=-2660/767, 9-28=-2660/767, 9-29=-2660/767, 29-30=-2660/767, 30-31=-2660/767, 10-31=-2660/767, 10-32=-3553/922, 32-33=-3553/922, 11-33=-3553/922, 11-34=-3553/923, 12-34=-3550/922, 12-13=-3800/972, 13-14=-3900/943, 14-15=0/33
 BOT CHORD 2-25=-87/268, 24-25=-1192/517, 23-24=-1192/517, 22-23=-1192/517, 21-22=-70/104, 21-35=-70/104, 35-36=-70/104, 20-36=-70/104, 20-37=-70/104, 37-38=-70/104, 19-38=-70/104, 19-39=-1109/4332, 39-40=-1109/4332, 18-40=-1109/4332, 18-41=-1109/4332, 17-41=-1109/4332, 17-42=-1109/4332, 42-43=-1109/4332, 43-44=-1109/4332, 16-44=-1109/4332, 16-45=-820/3535, 45-46=-820/3535, 46-47=-820/3535, 14-47=-820/3535
 WEBS 3-25=-248/100, 4-25=-282/150, 5-25=-262/1249, 5-24=0/229, 5-22=-2389/427, 6-22=-565/200, 8-22=-4057/1044, 8-20=0/313, 8-19=-766/3095, 9-19=-704/290, 10-19=-1852/465, 10-17=0/539, 10-16=-919/300, 12-16=-46/875, 13-16=-39/132

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCDL=5.0psf; BCDL=5.0psf; Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) All plates are MT20 plates unless otherwise indicated.
 - 6) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - 7) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 2.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 36 lb uplift at joint 2, 909 lb uplift at joint 22 and 471 lb uplift at joint 14.



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

Continued on page 2

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.
 Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D58-89 and BC511 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483116
TEEL	A1	HIP	1	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc Fri Oct 26 14 54 01 2007 Page 2

NOTES

9) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 130 lb down and 75 lb up at 21-0-12, 130 lb down and 75 lb up at 23-0-12, 130 lb down and 75 lb up at 25-0-12, 130 lb down and 75 lb up at 27-0-12, 130 lb down and 75 lb up at 29-0-12, 130 lb down and 75 lb up at 31-0-12, 130 lb down and 75 lb up at 33-0-12, 130 lb down and 75 lb up at 35-0-12, 141 lb down and 84 lb up at 37-0-12, and 141 lb down and 84 lb up at 39-0-12, and 295 lb down and 155 lb up at 41-0-0 on top chord, and 96 lb down at 21-0-12, 96 lb down at 23-0-12, 96 lb down at 25-0-12, 96 lb down at 27-0-12, 96 lb down at 29-0-12, 96 lb down at 31-0-12, 96 lb down at 33-0-12, 96 lb down at 35-0-12, 96 lb down at 37-0-12, 96 lb down at 39-0-12, 96 lb down at 40-11-4, 98 lb down at 42-11-4, and 114 lb down at 44-11-4, and 98 lb down at 46-11-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

10) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-4=-60, 4-12=-60, 12-15=-60, 2-14=-20

Concentrated Loads (lb)

Vert: 7=-130(F) 12=-255(F) 16=-48(F) 26=-130(F) 27=-130(F) 28=-130(F) 29=-130(F) 30=-130(F) 31=-130(F) 32=-130(F) 33=-141(F) 34=-141(F) 35=-48(F) 36=-48(F) 37=-48(F) 38=-48(F) 39=-48(F) 40=-48(F) 41=-48(F) 42=-48(F) 43=-48(F) 44=-48(F) 45=-49(F) 46=-88(F) 47=-49(F)

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult **ANSI/TPI1 Quality Criteria, DSB-89 and BCS11 Building Component Safety Information** available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483117
TEEL	A1A	HIP	1	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL.

6 500 s Apr 2 2007 MiTek Industries, Inc Fri Oct 26 14 54 03 2007 Page 1



Hanger nails that extend 1/2" or more beyond back of girder shall be clinched.




Plate Offsets (X,Y):	[3:0-11-0,0-5-8],	[5:0-3-8,0-3-0],	[6:0-3-8,0-2-0],	[12:0-3-0,0-2-9],	[13:0-0-6,0-0-2],	[17:0-3-12,0-3-0],	[18:0-3-8,0-2-0],	[19:0-3-8,0-3-0],	[20:0-4-0,0-1-0]
----------------------	-------------------	------------------	------------------	-------------------	-------------------	--------------------	-------------------	-------------------	------------------

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plates Increase	1.25	TC 0.98	Vert(LL)	-0.28	16-17	>999	240	MT20	244/190
TCDL 10.0	Lumber Increase	1.25	BC 0.73	Vert(TL)	-0.73	16-17	>528	180	MT20H	187/143
BCLL 0.0	Rep Stress Incr	NO	WB 0.95	Horz(TL)	0.08	13	n/a	n/a		
BCDL 10.0	Code FBC2004/TPI2002		(Matrix)							Weight: 262 lb

LUMBER
 TOP CHORD 2 X 6 SYP 2400F 2.0E *Except*
 1-3 2 X 4 SYP No.2D, 12-14 2 X 4 SYP No 2D
 BOT CHORD 2 X 4 SYP 2400F 2.0E
 WEBS 2 X 4 SYP No.3 *Except*
 5-19 2 X 4 SYP 2400F 2.0E, 6-18 2 X 4 SYP 2400F 2.0E
 8-17 2 X 4 SYP 2400F 2.0E


BRACING
 TOP CHORD Structural wood sheathing directly applied or 2-5-12 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 3-7-8 oc bracing.

REACTIONS (lb/size) 2=-96/0-3-8, 20=4677/0-3-8, 13=2239/0-3-0
 Max Horz 2=56(LC 5)
 Max Uplift 2=-370(LC 8), 20=-971(LC 3), 13=-518(LC 6)
 Max Grav 2=141(LC 6), 20=4677(LC 1), 13=2244(LC 8)

FORCES (lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/33, 2-3=-383/1347, 3-4=-603/2597, 4-5=-603/2596, 5-6=-1321/340, 6-23=-4615/1169, 7-23=-4615/1169,
 7-24=-4615/1169, 8-24=-4615/1169, 8-25=-5857/1482, 9-25=-5857/1482, 9-26=-5857/1482, 10-26=-5857/1482,
 10-27=-5857/1482, 27-28=-5857/1482, 11-28=-5857/1482, 11-29=-4383/1074, 29-30=-4382/1074, 12-30=-4380/1074,
 12-13=-4767/1133, 13-14=0/33
 BOT CHORD 2-22=-1209/434, 21-22=-1202/436, 20-21=-4318/1006, 17-31=-1342/5584, 31-32=-1342/5584, 16-32=-1342/5584,
 16-33=-1342/5584, 33-34=-1342/5584, 15-34=-1342/5584, 15-35=-986/4325, 35-36=-986/4325, 36-37=-986/4325,
 13-37=-986/4325, 19-20=-4318/1006, 19-38=-254/1321, 38-39=-254/1321, 39-40=-254/1321, 18-40=-254/1321,
 18-41=-1088/4615, 41-42=-1088/4615, 17-42=-1088/4615
 WEBS 3-22=0/274, 3-21=-1875/363, 4-21=-129/61, 5-21=-386/2096, 5-20=-4578/1014, 5-19=-1425/6332, 6-19=-2242/673,
 6-18=-943/3740, 8-18=-1408/487, 8-17=-357/1415, 10-17=-632/261, 11-17=-76/340, 11-16=0/301, 11-15=-1571/432,
 12-15=-176/1167

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-02; 110mph (3-second gust); h=18ft, TC DL=5.0psf, BCDL=5.0psf, Category II, Exp B, enclosed; MWFRS; cantilevered left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - All plates are MT20 plates unless otherwise indicated.
 - This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - Bearing at joint(s) 20 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 370 lb uplift at joint 2, 971 lb uplift at joint 20 and 518 lb uplift at joint 13.

Continued on page 2



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.
 Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, DSB-89 and BCSI1 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483117
TEEL	A1A	HIP	1	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industnes, Inc Fri Oct 26 14 54 03 2007 Page 2

- NOTES**
- 9) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 142 lb down and 82 lb up at 22-0-12, 130 lb down and 75 lb up at 22-11-4, 130 lb down and 75 lb up at 24-11-4, 130 lb down and 75 lb up at 26-11-4, 130 lb down and 75 lb up at 28-11-4, 130 lb down and 75 lb up at 30-11-4, 130 lb down and 75 lb up at 32-11-4, 130 lb down and 75 lb up at 34-11-4, 130 lb down and 75 lb up at 36-11-4, and 130 lb down and 75 lb up at 38-11-4, and 284 lb down and 146 lb up at 41-0-0 on top chord, and 623 lb down and 59 lb up at 22-0-12, 96 lb down at 22-11-4, 96 lb down at 24-11-4, 96 lb down at 26-11-4, 96 lb down at 28-11-4, 96 lb down at 30-11-4, 96 lb down at 32-11-4, 96 lb down at 34-11-4, 96 lb down at 36-11-4, 96 lb down at 38-11-4, 96 lb down at 40-11-4, 96 lb down at 42-11-4, and 96 lb down at 44-11-4, and 98 lb down at 46-11-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 10) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-3=-60, 3-12=-60, 12-14=-60, 2-17=-20, 13-17=-20

Concentrated Loads (lb)

Vert: 7=-130(B) 12=-244(B) 18=-48(B) 8=-130(B) 15=-48(B) 23=-142(B) 24=-130(B) 25=-130(B) 26=-130(B) 27=-130(B) 28=-130(B) 29=-130(B) 30=-130(B) 31=-48(B) 32=-48(B) 33=-48(B) 34=-48(B) 35=-48(B) 36=-48(B) 37=-49(B) 38=-623(B) 39=-48(B) 40=-48(B) 41=-48(B) 42=-48(B)

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult **ANSI/TPI1 Quality Criteria, D58-89 and BC511 Building Component Safety Information** available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483118
TEEL	A2	HIP	1	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc Fri Oct 26 14 54 05 2007 Page 1



LOADING (psf)	SPACING	CSI	DEFL	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.47	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plates Increase 1.25	BC 0.63	Vert(LL) -0.21 15-17 >999 240		
BCLL 0.0	Lumber Increase 1.25	WB 0.97	Vert(TL) -0.56 15-17 >599 180		
BCDL 10.0	Rep Stress Incr YES	(Matrix)	Horz(TL) 0.05 13 n/a n/a		
	Code FBC2004/TPI2002			Weight 238 lb	

LUMBER
TOP CHORD 2 X 4 SYP No.2D
BOT CHORD 2 X 4 SYP No.2D
WEBS 2 X 4 SYP No.3


BRACING
TOP CHORD Structural wood sheathing directly applied or 4-7-8 oc purtins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 1 Row at midpt 5-18

REACTIONS (lb/size) 2=582/0-3-0, 18=2417/0-3-8, 13=1015/0-3-8
Max Horz 2=-67(LC 6)
Max Uplift 2=-142(LC 5), 18=-316(LC 3), 13=-159(LC 6)
Max Grav 2=606(LC 7), 18=2417(LC 1), 13=1029(LC 8)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/33, 2-3=-824/142, 3-4=-490/66, 4-5=-402/80, 5-6=-142/1485, 6-7=-142/1485, 7-8=-805/153, 8-9=-805/153,
9-10=-805/153, 10-11=-1406/187, 11-12=-1559/186, 12-13=-1874/222, 13-14=0/33
BOT CHORD 2-20=-122/723, 19-20=-360/85, 18-19=-360/85, 17-18=-248/78, 16-17=-154/1341, 15-16=-154/1341, 13-15=-158/1671
WEBS 3-20=-347/136, 4-20=-141/84, 5-20=-9/832, 5-18=-1418/222, 6-18=-306/110, 7-18=-1656/260, 7-17=-131/1311,
9-17=-293/108, 10-17=-681/128, 10-15=-29/205, 11-15=0/356, 12-15=-303/134

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-02, 110mph (3-second gust); h=18ft, TCDFL=5.0psf; BCDL=5.0psf; Category II, Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - Provide mechanical connection (by others) of truss to bearing plate at joint(s) 2.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 142 lb uplift at joint 2, 316 lb uplift at joint 18 and 159 lb uplift at joint 13.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
Truss Engineering Co.
818 Soundside Road
Edenton, NC 27932
FL COA #7239

October 26, 2007



WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.
Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult **ANSI/TPI1 Quality Criteria, DSB-89 and BCS11 Building Component Safety Information** available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

ENGINEERING BY
TRENCO
A MiTek Affiliate
818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483119
TEEL	A2A	HIP	1	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc. Fri Oct 26 14 54 06 2007 Page 1



9-0-0	15-10-4	24-0-0	32-1-12	39-0-0	47-10-0	48-0-0
9-0-0	6-10-4	8-1-12	8-1-12	6-10-4	8-10-0	0-2-0

Plate Offsets (X,Y): [4:0-3-0,0-2-4], [10:0-3-0,0-2-4], [15:0-2-8,0-3-0], [17:0-2-8,0-3-0]									
LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.65	Vert(LL)	-0.15	12-14	>999	240	MT20
TCDL 10.0	Lumber Increase	1.25	BC 0.62	Vert(TL)	-0.42	12-14	>913	180	244/190
BCLL 0.0	Rep Stress Incr	YES	WB 0.53	Horz(TL)	0.05	12	n/a	n/a	
BCDL 10.0	Code FBC2004/TPI2002		(Matrix)						Weight 239 lb


LUMBER	BRACING
TOP CHORD 2 X 4 SYP No 2D	TOP CHORD Structural wood sheathing directly applied or 4-2-4 oc purlins.
BOT CHORD 2 X 4 SYP No 2D	BOT CHORD Rigid ceiling directly applied or 4-11-6 oc bracing.
WEBS 2 X 4 SYP No.3	WEBS 1 Row at midpt 6-17

REACTIONS (lb/size) 2=316/0-3-8, 17=2522/0-3-8, 12=1176/0-3-0
 Max Horz 2=-67(LC 6)
 Max Uplift 2=-138(LC 5), 17=-327(LC 3), 12=-161(LC 6)
 Max Grav 2=346(LC 7), 17=2522(LC 1), 12=1186(LC 8)

FORCES (lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/33, 2-3=-157/355, 3-4=-53/470, 4-5=-21/426, 5-6=-147/1631, 6-7=-824/159, 7-8=-824/159, 8-9=-1953/317,
 9-10=-1783/255, 10-11=-1956/257, 11-12=-2241/281, 12-13=0/33
 BOT CHORD 2-18=-300/114, 17-18=-1631/250, 16-17=-8/175, 15-16=-163/1352, 14-15=-216/1953, 12-14=-210/2019
 WEBS 3-18=-353/126, 4-18=-455/133, 5-18=-148/1534, 5-17=-1159/217, 6-17=-2123/311, 6-16=-80/1126, 8-16=-918/188,
 8-15=-65/750, 9-15=-292/106, 9-14=-313/78, 10-14=0/442, 11-14=-274/125

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCCL=5.0psf; BCDL=5.0psf; Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 138 lb uplift at joint 2, 327 lb uplift at joint 17 and 161 lb uplift at joint 12.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.
 Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, DSB-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483120
TEEL	A3	HIP	2	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6.500 s Apr 2 2007 MiTek Industries, Inc. Fri Oct 26 14 54 07 2007 Page 1




Plate Offsets (X,Y): [2.0-2.5,Edge], [11.0-2.5,Edge], [14.0-3.0,0-3-0], [16.0-3.0,0-3-0]

LOADING (psf)	SPACING	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.91	Vert(LL)	-0.44	15	>999	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.63	Vert(TL)	-1.14	15-16	>503		
BCLL 0.0	Rep Stress Incr YES	WB 1.00	Horz(TL)	0.28	11	n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)						Weight: 245 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP 2400F 2.0E
 WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(lb/size) 2=2007/0-3-8, 11=2007/0-3-8
 Max Horz 2=76(LC 5)
 Max Uplift 2=-248(LC 3), 11=-248(LC 4)


FORCES

(lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/33, 2-3=-4233/523, 3-4=-3851/477, 4-5=-3531/462, 5-6=-4997/696, 6-7=-4997/696, 7-8=-4997/696,
 8-9=-3531/462, 9-10=-3851/477, 10-11=-4233/523, 11-12=0/33
 BOT CHORD 2-17=-414/3846, 16-17=-490/4402, 15-16=-490/4402, 14-15=-495/4402, 13-14=-495/4402, 11-13=-426/3846
 WEBS 3-17=-387/171, 4-17=-94/1174, 5-17=-1294/219, 5-16=0/186, 5-15=-99/780, 6-15=-510/188, 8-15=-98/780, 8-14=0/186,
 8-13=-1294/219, 9-13=-94/1174, 10-13=-387/171

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCCL=5.0psf; BCCL=5.0psf; Category II; Exp B; enclosed, MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 248 lb uplift at joint 2 and 248 lb uplift at joint 11.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MI-7473 BEFORE USE.
 Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D58-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483121
TEEL	A4	HIP	2	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc. Fri Oct 26 14 54 08 2007 Page 1




Plate Offsets (X,Y): [2,0-2-5,Edge], [4,0-2-8,0-3-12], [22,0-3-0,0-2-9], [24,0-2-5,Edge]

LOADING (psf)	SPACING	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.53	Vert(LL)	-0.31	29-30	>999	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.80	Vert(TL)	-0.83	29-30	>693	MT20H	187/143
BCLL 0.0	Rep Stress Incr YES	WB 0.51	Horz(TL)	0.30	24	n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)						Weight: 325 lb

LUMBER
 TOP CHORD 2 X 4 SYP No.2D *Except*
 4-15 2 X 6 SYP 2400F 2.0E, 15-22 2 X 6 SYP 2400F 2.0E
 BOT CHORD 2 X 4 SYP No.2D
 WEBS 2 X 4 SYP No.3


BRACING
 TOP CHORD Structural wood sheathing directly applied or 2-8-11 oc purlins.
 Except:
 5-7-0 oc bracing: 10-13, 13-18
 5-8-0 oc bracing: 5-6, 6-10
 6-0-0 oc bracing: 18-20, 20-21
 BOT CHORD Rigid ceiling directly applied or 9-9-2 oc bracing
 WEBS 1 Row at midpt 18-30, 18-27
 JOINTS 1 Brace at Jt(s): 10, 18, 6, 13, 20

REACTIONS (lb/size) 2=2007/0-3-8, 24=2007/0-3-8
 Max Horz 2=-137(LC 6)
 Max Uplift 2=-274(LC 5), 24=-274(LC 6)

FORCES (lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/33, 2-3=-4277/432, 3-4=-3686/393, 4-5=-3736/389, 5-6=-3056/426, 6-8=-3056/426, 8-10=-3056/426,
 10-12=-3056/426, 12-13=-3056/426, 13-15=-3056/426, 15-17=-3056/426, 17-18=-3056/426, 18-20=-2666/431,
 20-21=-2666/431, 21-22=-3346/389, 22-23=-3689/393, 23-24=-4275/432, 24-25=0/33, 5-7=-826/42, 7-9=-782/66,
 9-11=-775/84, 11-14=-772/104, 14-16=-778/110, 16-19=-796/86, 19-21=-822/49
 BOT CHORD 2-33=-444/3857, 32-33=-444/3857, 31-32=-326/3360, 30-31=-326/3360, 29-30=-226/3746, 28-29=-226/3746,
 27-28=-226/3746, 26-27=-308/3855, 24-26=-308/3855
 WEBS 3-33=0/268, 3-32=-581/129, 4-32=0/447, 4-30=-110/498, 10-30=-213/148, 18-30=-125/384, 18-29=0/289,
 18-27=-501/104, 22-27=-5/659, 23-27=-612/130, 23-26=0/267, 6-7=-161/78, 8-9=-107/55, 11-12=-105/55,
 13-14=-51/399, 16-17=-168/97, 19-20=-215/110

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCCL=5.0psf; BCDL=5.0psf; Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - All plates are MT20 plates unless otherwise indicated.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 274 lb uplift at joint 2 and 274 lb uplift at joint 24.
 - Design requires purlins at oc spacing indicated.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII 7473 BEFORE USE.
 Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D58-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483122
TEEL	A5	COMMON	12	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc. Fri Oct 26 14 54 09 2007 Page 1




Plate Offsets (X,Y): [2:0-2-5,Edge], [10:0-2-5,Edge]

LOADING (psf)	SPACING	CSI	DEFL	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.93	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plates Increase 1.25	BC 0.91	Vert(LL) -0.29 14-15 >999 240		
BCLL 0.0	Lumber Increase 1.25	WB 0.79	Vert(TL) -0.86 14-15 >664 180		
BCDL 10.0	Rep Stress Incr YES	(Matrix)	Horz(TL) 0.25 10 n/a n/a		
	Code FBC2004/TPI2002			Weight: 245 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP No.2D
 WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied or 9-8-7 oc bracing.

REACTIONS

(lb/size) 2=2007/0-3-8, 10=2007/0-3-8
 Max Horz 2=-140(LC 6)
 Max Uplift 2=-274(LC 5), 10=-274(LC 6)


FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/33, 2-3=-4183/437, 3-4=-3975/433, 4-5=-3882/461, 5-6=-3008/375, 6-7=-3008/375, 7-8=-3882/461,
 8-9=-3975/434, 9-10=-4183/437, 10-11=0/33
 BOT CHORD 2-17=-440/3766, 16-17=-277/3018, 15-16=-277/3018, 14-15=-106/2284, 13-14=-138/3018, 12-13=-138/3018,
 10-12=-300/3766
 WEBS 3-17=-441/201, 5-17=-118/841, 5-15=-794/254, 6-15=-153/995, 6-14=-153/995, 7-14=-794/254, 7-12=-118/841,
 9-12=-441/201

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust), h=18ft; TCDL=5.0psf, BCDL=5.0psf, Category II, Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 274 lb uplift at joint 2 and 274 lb uplift at joint 10.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D58-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483123
TEEL	B1	HIP	1	1	Job Reference (optional)	
SANTA FE TRUSS, HIGH SPRINGS, FL					6 500 s Apr 2 2007 MiTek Industries, Inc. Fri Oct 26 14 54 11 2007 Page 1	





Plate Offsets (X,Y): [2:0-1-6,0-0-2], [4:0-3-0,0-2-9], [5:0-1-6,0-0-2], [8:0-5-15,0-0-5]

LOADING (psf)	SPACING	CSI	DEFL	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.57	Vert(LL) -0.16 7-9 >999 240	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.69	Vert(TL) -0.48 7-9 >539 180	MT20H	187/143
BCLL 0.0	Rep Stress Incr NO	WB 0.23	Horz(TL) 0.10 5 n/a n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)			Weight: 99 lb

LUMBER	BRACING
TOP CHORD 2 X 4 SYP 2400F 2.0E *Except* 3-4 2 X 6 SYP 2400F 2.0E	TOP CHORD Structural wood sheathing directly applied or 4-1-7 oc purlins.
BOT CHORD 2 X 4 SYP 2400F 2.0E	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2 X 4 SYP No.3	WEBS 1 Row at midpt 4-9


REACTIONS (lb/size) 2=1671/0-3-0, 5=1674/0-3-0
 Max Horz 2=-56(LC 6)
 Max Uplift 2=-395(LC 5), 5=-388(LC 6)

FORCES (lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/33, 2-3=-3360/755, 3-10=-3034/737, 10-11=-3034/737, 11-12=-3034/737, 4-12=-3034/737, 4-5=-3364/752, 5-6=0/33
 BOT CHORD 2-13=-665/3052, 13-14=-665/3052, 14-15=-665/3052, 9-15=-665/3052, 9-16=-644/3036, 8-16=-644/3036, 8-17=-644/3036, 17-18=-644/3036, 7-18=-644/3036, 7-19=-640/3054, 19-20=-640/3054, 20-21=-640/3054, 5-21=-640/3054
 WEBS 3-9=0/714, 4-9=-185/143, 4-7=0/717

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCCL=5.0psf; BCDL=5.0psf; Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - All plates are MT20 plates unless otherwise indicated.
 - This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 395 lb uplift at joint 2 and 388 lb uplift at joint 5.
 - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 244 lb down and 146 lb up at 7-0-0, 130 lb down and 75 lb up at 9-0-12, 130 lb down and 75 lb up at 11-0-12, and 130 lb down and 75 lb up at 13-0-12, and 284 lb down and 146 lb up at 15-0-0 on top chord, and 98 lb down at 1-0-12, 96 lb down at 3-0-12, 96 lb down at 5-0-12, 96 lb down at 7-0-12, 96 lb down at 9-0-12, 96 lb down at 11-0-12, 96 lb down at 13-0-12, 96 lb down at 14-11-4, 96 lb down at 16-11-4, and 96 lb down at 18-11-4, and 98 lb down at 20-11-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
 - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

Continued on page 2



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.
 Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D58-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483123
TEEL	B1	HIP	1	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc Fri Oct 26 14 54 11 2007 Page 2

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-3=-60, 3-4=-60, 4-6=-60, 2-5=-20

Concentrated Loads (lb)

Vert: 3=-244(B) 4=-244(B) 9=-48(B) 7=-48(B) 10=-130(B) 11=-130(B) 12=-130(B) 13=-49(B) 14=-48(B) 15=-48(B) 16=-48(B) 17=-48(B) 18=-48(B) 19=-48(B) 20=-48(B) 21=-49(B)

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult **ANSI/TPI1 Quality Criteria, DSB-89 and BCS11 Building Component Safety Information** available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

ENGINEERING BY
TRENCO
 A MiTek Affiliate

818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483124
TEEL	B2	HIP	1	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc. Fri Oct 26 14:54:11 2007 Page 1




Plate Offsets (X,Y): [2 0-3-0,0-1-8], [5 0-5-4,0-2-0], [7 0-3-0,0-1-8]

LOADING (psf)	SPACING	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.29	Vert(LL)	-0.15	7-9	>999	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.49	Vert(TL)	-0.40	7-9	>654		
BCLL 0.0	Rep Stress Incr YES	WB 0.15	Horz(TL)	0.05	7	n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)						
							Weight: 104 lb	

LUMBER
 TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP No.2D
 WEBS 2 X 4 SYP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied or 4-8-12 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=968/0-3-0, 7=968/0-3-0
 Max Horz 2=-67(LC 6)
 Max Uplift 2=-151(LC 5), 7=-151(LC 6)

FORCES (lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/33, 2-3=-1710/171, 3-4=-1379/123, 4-5=-1234/127, 5-6=-1378/123, 6-7=-1710/172, 7-8=0/33
 BOT CHORD 2-11=-147/1536, 10-11=-27/1233, 9-10=-27/1233, 7-9=-101/1536
 WEBS 3-11=-343/131, 4-11=0/323, 5-11=-114/116, 5-9=0/323, 6-9=-344/131

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=18ft, TCCL=5.0psf, BCDL=5.0psf, Category II, Exp B; enclosed, MWFRS, cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 151 lb uplift at joint 2 and 151 lb uplift at joint 7.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII 7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSITPI1 Quality Criteria, DSB-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483125
TEEL	B3	COMMON	4	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc Fri Oct 26 14 54 12 2007 Page 1




Plate Offsets (X,Y): [2.0-3.0,0-1.8], [6.0-3.0,0-1.8]

LOADING (psf)	SPACING	CSI	DEFL	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.28	Vert(LL) -0.07 6-8 >999 240	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.39	Vert(TL) -0.21 6-8 >999 180		
BCLL 0.0	Rep Stress Incr YES	WB 0.17	Horz(TL) 0.05 6 n/a n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)			Weight: 98 lb

LUMBER

TOP CHORD 2 X 4 SYP No 2D
 BOT CHORD 2 X 4 SYP No 2D
 WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-9-5 oc purlins
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing

REACTIONS

(lb/size) 2=968/0-3-0, 6=968/0-3-0
 Max Horz 2=76(LC 5)
 Max Uplift 2=-162(LC 5), 6=-162(LC 6)

FORCES

(lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/33, 2-3=-1707/175, 3-4=-1500/161, 4-5=-1500/162, 5-6=-1707/175, 6-7=0/33
 BOT CHORD 2-10=-156/1512, 9-10=-44/1029, 8-9=-44/1029, 6-8=-80/1512
 WEBS 3-10=-324/139, 4-10=-46/515, 4-8=-46/515, 5-8=-324/139

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCDL=5.0psf, BCDL=5.0psf, Category II, Exp B; enclosed, MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 162 lb uplift at joint 2 and 162 lb uplift at joint 6.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MI-7473 BEFORE USE.
 Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANS/TP11 Quality Criteria, D58-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483126
TEEL	B4	COMMON	2	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc. Fri Oct 26 14 54 13 2007 Page 1



LOADING (psf)	SPACING	CSI	DEFL	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.29	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plates Increase 1.25	BC 0.43	Vert(LL) -0.07 6-7 >999 240		
BCLL 0.0	Lumber Increase 1.25	WB 0.18	Vert(TL) -0.23 6-7 >999 180		
BCDL 10.0	Rep Stress Incr YES	(Matrix)	Horz(TL) 0.05 6 n/a n/a		
	Code FBC2004/TPI2002			Weight: 96 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP No.2D
 WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-8-3 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(lb/size) 6=869/Mechanical, 2=974/0-3-0
 Max Horz 2=84(LC 5)
 Max Uplift 6=-94(LC 6), 2=-163(LC 5)


FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/33, 2-3=-1722/176, 3-4=-1515/162, 4-5=-1538/182, 5-6=-1737/198
 BOT CHORD 2-9=-165/1525, 8-9=-53/1044, 7-8=-53/1044, 6-7=-134/1558
 WEBS 3-9=-324/139, 4-9=-46/514, 4-7=-64/546, 5-7=-344/150

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02, 110mph (3-second gust); h=18ft; TCDL=5.0psf, BCDL=5.0psf, Category II, Exp B; enclosed, MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 94 lb uplift at joint 6 and 163 lb uplift at joint 2.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, DSB-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483127
TEEL	B5	COMMON	1	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc Fri Oct 26 14 54 14 2007 Page 1




Plate Offsets (X,Y): [6:0-1-6,0-0-2]

LOADING (psf)	SPACING	CSI	DEFL	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.25	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plates Increase 1.25	BC 0.39	Vert(LL) -0.08 7-9 >999 240		
BCLL 0.0	Lumber Increase 1.25	WB 0.60	Vert(TL) -0.20 7-9 >984 180		
BCDL 10.0	Rep Stress Incr YES	(Matrix)	Horz(TL) 0.02 7 n/a n/a		
	Code FBC2004/TPI2002			Weight: 96 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP No.2D
 WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS (lb/size) 6=121/Mechanical, 2=706/0-3-8, 7=1016/0-3-8
 Max Horz 2=84(LC 5)
 Max Uplift 6=-23(LC 6), 2=-147(LC 5), 7=-96(LC 6)
 Max Grav 6=146(LC 8), 2=706(LC 1), 7=1016(LC 1)


FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/33, 2-3=-1055/130, 3-4=-845/116, 4-5=0/193, 5-6=-35/215
 BOT CHORD 2-9=-123/912, 8-9=-19/401, 7-8=-19/401, 6-7=-129/51
 WEBS 3-9=-330/142, 4-9=-32/550, 4-7=-708/87, 5-7=-374/165

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCDL=5.0psf; BCDL=5.0psf, Category II; Exp B; enclosed, MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 23 lb uplift at joint 6, 147 lb uplift at joint 2 and 96 lb uplift at joint 7.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MI-7473 BEFORE USE.
 Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, DSB-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483128
TEEL	C1	COMMON	3	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc. Fri Oct 26 14 54:14 2007 Page 1




Plate Offsets (X,Y): [2,0-3-0,0-1-8], [6,0-3-0,0-1-8], [7,0-4-0,0-3-0]

LOADING (psf)	SPACING	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.29	Vert(LL) -0.14	2-7	>999	240	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.61	Vert(TL) -0.40	6-7	>592	180		
BCLL 0.0	Rep Stress Incr YES	WB 0.20	Horz(TL) 0.04	6	n/a	n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)						Weight: 85 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP No.2D
 WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-11-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(lb/size) 6=780/0-3-8, 2=886/0-3-0
 Max Horz 2=79(LC 5)
 Max Uplift 6=-84(LC 6), 2=-154(LC 5)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/33, 2-3=-1489/173, 3-4=-1124/109, 4-5=-1125/101, 5-6=-1501/193
 BOT CHORD 2-7=-159/1331, 6-7=-131/1346
 WEBS 3-7=-404/150, 4-7=0/582, 5-7=-420/165

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02, 110mph (3-second gust); h=18ft; TCCL=5.0psf, BCDL=5.0psf, Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 84 lb uplift at joint 6 and 154 lb uplift at joint 2.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MI-7473 BEFORE USE.
 Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D58-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483129
TEEL	CET	GABLE	1	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc. Fri Oct 26 14:54:15 2007 Page 1




Plate Offsets (X,Y) [2 0-2-13,0-0-8], [2 0-0-4,Edge], [8 0-2-13,0-0-8], [8 0-0-4,Edge], [10 0-6-0,Edge]

LOADING (psf)	SPACING	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.86	Vert(LL) -0.28	8-9	>833	240	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.79	Vert(TL) -0.62	8-9	>379	180		
BCLL 0.0	Rep Stress Incr YES	WB 0.23	Horz(TL) 0.03	8	n/a	n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)						Weight: 95 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP 2400F 2.0E
 WEBS 2 X 4 SYP No.3
 OTHERS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(lb/size) 2=886/0-3-0, 8=780/0-3-8
 Max Horz 2=75(LC 5)
 Max Uplift 2=-154(LC 5), 8=-85(LC 6)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-0/33, 2-3=-1404/106, 3-4=-1343/132, 4-5=-1321/173, 5-6=-1321/166, 6-7=-1343/121, 7-8=-1402/95
 BOT CHORD 2-11=-70/1240, 10-11=-70/1240, 9-10=-70/1240, 8-9=-70/1240
 WEBS 5-10=-123/703, 4-11=-227/137, 6-9=-232/142

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCDL=5.0psf; BCDL=5.0psf; Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1-2002.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- All plates are 2x4 MT20 unless otherwise indicated.
- This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- Gable studs spaced at 2-0-0 oc.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 154 lb uplift at joint 2 and 85 lb uplift at joint 8.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MI-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D38-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483130
TEEL	CJ01	MONO TRUSS	4	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc. Fri Oct 26 14 54 16 2007 Page 1



LOADING (psf)	SPACING	CSI	DEFL	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.47	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.02	Vert(LL) -0.00 2 >999 240		
BCLL 0.0	Rep Stress Incr NO	WB 0.00	Vert(TL) -0.00 2 >999 180		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)	Horz(TL) -0.00 4 n/a n/a		
				Weight: 21 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP No.2D

BRACING

TOP CHORD Structural wood sheathing directly applied or 1-5-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 4=174/Mechanical, 5=23/0-3-8, 2=265/0-5-0, 3=416/0-3-8
 Max Horz 2=125(LC 3)
 Max Uplift 4=-81(LC 3), 2=-87(LC 3), 3=-163(LC 4)
 Max Grav 4=174(LC 1), 5=46(LC 2), 2=265(LC 1), 3=416(LC 1)


FORCES (lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/35, 2-6=-88/0, 6-7=-72/38, 3-7=-64/44, 3-8=-75/1, 4-8=-31/40
 BOT CHORD 2-5=0/0

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft, TCDL=5.0psf, BCDL=5.0psf, Category II; Exp B; enclosed, MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 81 lb uplift at joint 4, 87 lb uplift at joint 2 and 163 lb uplift at joint 3.
- 6) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 3.
- 7) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1 lb down and 18 lb up at 4-3-4, 1 lb down and 11 lb up at 4-3-4, 61 lb down and 46 lb up at 7-1-3, 66 lb down and 44 lb up at 7-1-3, and 22 lb down at 1-5-4, and 22 lb down at 1-5-4 on top chord, and 19 lb down at 1-4-10 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Regular: Lumber Increase=1.25, Plate Increase=1.25
 Uniform Loads (plf)
 Vert: 1-4=-60, 2-5=-20
 Concentrated Loads (lb)
 Vert: 5=-10(F) 7=5(F=-1, B=6) 8=-127(F=-61, B=-66)



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.
 Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D58-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483131
TEEL	CJ02	MONO TRUSS	4	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MITek Industries, Inc. Fri Oct 26 14 54 17 2007 Page 1



LOADING (psf)	SPACING	CSI	DEFL	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.31	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.06	Vert(LL) -0.00 2-5 >999 240		
BCLL 0.0	Rep Stress Incr NO	WB 0.00	Vert(TL) -0.00 2-5 >999 180		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)	Horz(TL) -0.00 4 n/a n/a		
				Weight: 21 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP No.2D

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-9-15 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 4=52/Mechanical, 2=306/0-5-0, 5=44/0-3-8, 3=479/0-3-8
 Max Horz 2=111(LC 3)
 Max Uplift 4=-24(LC 3), 2=-134(LC 3), 3=-177(LC 4)
 Max Grav 4=52(LC 1), 2=306(LC 1), 5=89(LC 2), 3=479(LC 1)


FORCES (lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/35, 2-6=-62/0, 3-6=-43/33, 3-4=-29/10
 BOT CHORD 2-5=0/0

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCCL=5.0psf; BCCL=5.0psf, Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 24 lb uplift at joint 4, 134 lb uplift at joint 2 and 177 lb uplift at joint 3.
- 6) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 3.
- 7) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 10 lb down and 36 lb up at 2-10-4, 12 lb down and 52 lb up at 2-10-4, and 1 lb down and 18 lb up at 5-8-3, and 264 lb down and 86 lb up at 5-8-3 on top chord, and 39 lb down at 2-8-3 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Regular: Lumber Increase=1.25, Plate Increase=1.25
 Uniform Loads (plf)
 Vert: 1-4=-60, 2-5=-20
 Concentrated Loads (lb)
 Vert: 5=-20(F) 3=-265(F=-1, B=-264) 6=88(F=36, B=52)



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239


October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.
 Design valid for use only with MITek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D5B-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483132
TEEL	DET	GABLE	1	1	Job Reference (optional)	
SANTA FE TRUSS, HIGH SPRINGS, FL					6 500 s Apr 2 2007 MiTek Industries, Inc. Fri Oct 26 14:54:18 2007 Page 1	



LOADING (psf)	SPACING	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.12	Vert(LL) -0.00	7	n/r	120	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.11	Vert(TL) 0.00	6	n/r	120		
BCLL 0.0	Rep Stress Incr YES	WB 0.00	Horz(TL) 0.00	6	n/a	n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)						Weight: 32 lb

LUMBER
TOP CHORD 2 X 4 SYP No.2D
BOT CHORD 2 X 4 SYP No.2D
OTHERS 2 X 4 SYP No.3


BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=315/6-8-0, 6=315/6-8-0, 8=83/6-8-0
Max Horz 2=35(LC 5)
Max Uplift 2=-118(LC 5), 6=-118(LC 6)
Max Grav 2=315(LC 1), 6=315(LC 1), 8=167(LC 2)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/33, 2-3=-287/60, 3-4=-247/63, 4-5=-247/63, 5-6=-287/60, 6-7=0/33
BOT CHORD 2-8=-38/240, 6-8=-38/240

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCCL=5.0psf; BCCL=5.0psf; Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1-2002.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 118 lb uplift at joint 2 and 118 lb uplift at joint 6.
 - Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 6.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
Truss Engineering Co.
818 Soundside Road
Edenton, NC 27932
FL COA #7239

October 26, 2007


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII 7473 BEFORE USE.
Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D58-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

ENGINEERING BY
TRENCO
A MiTek Affiliate
818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483133
TEEL	DGT	COMMON	1	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc Fri Oct 26 14 54:18 2007 Page 1



LOADING (psf)	SPACING	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.15	Vert(LL) -0.02	1-4	>999	240	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.46	Vert(TL) -0.04	1-4	>999	180		
BCLL 0.0	Rep Stress Incr NO	WB 0.17	Horz(TL) 0.01	3	n/a	n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)						Weight: 23 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP No.2D
 WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(lb/size) 1=656/0-3-8, 3=546/0-3-8
 Max Horz 1=17(LC 5)
 Max Uplift 1=-74(LC 5), 3=-56(LC 6)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-930/87, 2-3=-930/87
 BOT CHORD 1-5=-60/821, 5-6=-60/821, 4-6=-60/821, 4-7=-60/821, 3-7=-60/821
 WEBS 2-4=-11/543

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=18ft, TCCL=5.0psf, BCDL=5.0psf, Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 74 lb uplift at joint 1 and 56 lb uplift at joint 3.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 249 lb down and 30 lb up at 1-0-12, and 249 lb down and 30 lb up at 2-11-4, and 194 lb down and 15 lb up at 4-11-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- Regular: Lumber Increase=1.25, Plate Increase=1.25
 Uniform Loads (plf)
 Vert: 1-2=-60, 2-3=-60, 1-3=-20
 Concentrated Loads (lb)
 Vert: 5=-249(B) 6=-249(B) 7=-194(B)



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MI-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D5B-89 and BCS11 Building Component Safety information available from Truss Plate Institute, 583 D Onofrio Drive, Madison, WI 53719.



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483134
TEEL	EJ6	JACK	16	1	Job Reference (optional)	
SANTA FE TRUSS, HIGH SPRINGS, FL			6 500 s Mar 8 2007 MiTek Industries, Inc. Fri Oct 26 16 24 37 2007 Page 1			



LOADING (psf)	SPACING 2-0-0	CSI	DEFL in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.33	Vert(LL) -0.06 2-4 >999 240	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.28	Vert(TL) -0.14 2-4 >495 180		
BCLL 0.0	Rep Stress Incr YES	WB 0.00	Horz(TL) -0.00 3 n/a n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)			Weight: 21 lb


LUMBER	BRACING
TOP CHORD 2 X 4 SYP No.2D	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2 X 4 SYP No.2D	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=158/Mechanical, 2=341/0-3-0, 4=58/Mechanical
 Max Horz 2=109(LC 5)
 Max Uplift 3=-70(LC 5), 2=-94(LC 5)
 Max Grav 3=158(LC 1), 2=341(LC 1), 4=116(LC 2)

FORCES (lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/33, 2-3=-74/49
 BOT CHORD 2-4=0/0


- NOTES**
- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft, TCDL=5.0psf, BCDL=5.0psf, Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 70 lb uplift at joint 3 and 94 lb uplift at joint 2.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007



LOADING (psf)	SPACING 2-0-0	CSI	DEFL in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.48	Vert(LL) -0.11 2-4 >768 240	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.39	Vert(TL) -0.27 2-4 >307 180		
BCLL 0.0	Rep Stress Incr YES	WB 0.00	Horz(TL) -0.00 3 n/a n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)			Weight: 24 lb

LUMBER
TOP CHORD 2 X 4 SYP No.2D
BOT CHORD 2 X 4 SYP No.2D

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=190/Mechanical, 4=68/Mechanical, 2=379/0-3-0
Max Horz 2=123(LC 5)
Max Uplift 3=-85(LC 5), 2=-96(LC 5)
Max Grav 3=190(LC 1), 4=136(LC 2), 2=379(LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/33, 2-3=-84/59
BOT CHORD 2-4=0/0

- NOTES**
- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TC DL=5.0psf; BCDL=5.0psf; Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 85 lb uplift at joint 3 and 96 lb uplift at joint 2.

LOAD CASE(S) Standard




Marvin A. Strzyzewski, FL Lic. #43144
Truss Engineering Co.
818 Soundside Road
Edenton, NC 27932
FL COA #7239

October 26, 2007

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483136
TEEL	EJ7A	JACK	3	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Mar 8 2007 MiTek Industries, Inc. Fri Oct 26 16 25 46 2007 Page 1



LOADING (psf)	SPACING 2-0-0	CSI	DEFL in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.54	Vert(LL) -0.11 1-3 >776 240	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.39	Vert(TL) -0.26 1-3 >310 180		
BCLL 0.0	Rep Stress Incr YES	WB 0.00	Horz(TL) -0.00 2 n/a n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)			Weight: 22 lb

LUMBER
TOP CHORD 2 X 4 SYP No.2D
BOT CHORD 2 X 4 SYP No.2D


BRACING
TOP CHORD Structural wood sheathing directly applied or 7-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 1=269/Mechanical, 2=201/Mechanical, 3=68/Mechanical
Max Horz 1=93(LC 5)
Max Uplift 1=-20(LC 5), 2=-94(LC 5)
Max Grav 1=269(LC 1), 2=201(LC 1), 3=136(LC 2)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=-64/64
BOT CHORD 1-3=0/0

- NOTES**
- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCDL=5.0psf; BCDL=5.0psf; Category II, Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Refer to girder(s) for truss to truss connections.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 20 lb uplift at joint 1 and 94 lb uplift at joint 2.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
Truss Engineering Co.
818 Soundside Road
Edenton, NC 27932
FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII 7473 BEFORE USE.
Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not Truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D5B-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

ENGINEERING BY
TRENCO
A MiTek Affiliate
818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483137
TEEL	EJGT	MONO TRUSS	1	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Mar 8 2007 MiTek Industries, Inc. Fri Oct 26 16 27 13 2007 Page 1




Plate Offsets (X,Y): [1:0-1-8,0-2-0]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.63	Vert(LL)	-0.08	1-3	>999	240	MT20	244/190
TCDL 10.0	Lumber Increase	1.25	BC 0.64	Vert(TL)	-0.20	1-3	>404	180		
BCLL 0.0	Rep Stress Incr	NO	WB 0.00	Horz(TL)	-0.00	2	n/a	n/a		
BCDL 10.0	Code	FBC2004/TPI2002	(Matrix)						Weight	33 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 8 SYP 2400F 2.0E

BRACING

TOP CHORD Structural wood sheathing directly applied or 7-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 8-3-6 oc bracing.

REACTIONS (lb/size) 2=202/Mechanical, 3=643/Mechanical, 1=1520/0-3-0
 Max Horz 1=88(LC 5)
 Max Uplift 2=-92(LC 5), 3=-49(LC 3), 1=-180(LC 5)

FORCES (lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-2=-61/61
 BOT CHORD 1-4=0/0, 4-5=0/0, 5-6=0/0, 3-6=0/0

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft, TCDL=5.0psf, BCDL=5.0psf; Category II, Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 92 lb uplift at joint 2, 49 lb uplift at joint 3 and 180 lb uplift at joint 1.
- 6) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 849 lb down and 104 lb up at 1-0-12, and 849 lb down and 104 lb up at 3-0-12, and 126 lb down and 33 lb up at 5-0-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 7) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Regular: Lumber Increase=1.25, Plate Increase=1.25
 Uniform Loads (plf)
 Vert: 1-2=-60, 1-3=-20
 Concentrated Loads (lb)
 Vert: 4=-849(F) 5=-849(F) 6=-126(F)



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D5B-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D Onofrio Drive, Madison, WI 53719.



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483138
TEEL	G1	HIP	2	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc. Fri Oct 26 14 54 22 2007 Page 1




Plate Offsets (X,Y): [2:0-10-2,0-0-6], [3:0-3-0,0-2-9], [12:0-3-0,0-2-9], [13:0-10-2,0-0-6]

LOADING (psf)	SPACING	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 2-0-0	TC 0.44	Vert(LL)	-0.15	16	>999	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.95	Vert(TL)	-0.45	15-16	>682		
BCLL 0.0	Rep Stress Incr NO	WB 0.29	Horz(TL)	0.15	13	n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)						Weight: 155 lb

LUMBER	BRACING
TOP CHORD 2 X 4 SYP No.2D *Except* 3-12 2 X 6 SYP 2400F 2.0E	TOP CHORD Structural wood sheathing directly applied or 3-1-1 oc purlins. Except: 6-0-0 oc bracing: 4-5, 5-7, 7-9, 9-11
BOT CHORD 2 X 4 SYP No.2D	BOT CHORD Rigid ceiling directly applied or 7-11-8 oc bracing
WEBS 2 X 4 SYP No.3	JOINTS 1 Brace at Jt(s): 7, 9, 5

REACTIONS (lb/size) 2=1807/0-3-0, 13=1811/0-3-0
Max Horz 2=-83(LC 6)
Max Uplift 2=-383(LC 5), 13=-384(LC 6)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/33, 2-3=-3800/716, 3-4=-3647/777, 4-19=-2325/515, 19-20=-2325/515, 5-20=-2325/515, 5-21=-2325/515, 7-21=-2325/515, 7-22=-2325/515, 9-22=-2325/515, 9-23=-2325/515, 23-24=-2325/515, 11-24=-2325/515, 11-12=-3647/777, 12-13=-3810/721, 13-14=0/33, 4-34=-1520/313, 34-35=-1482/316, 6-35=-1452/323, 6-36=-1470/335, 8-36=-1433/339, 8-37=-1433/338, 10-37=-1469/334, 10-38=-1455/322, 38-39=-1482/315, 11-39=-1520/312
BOT CHORD 2-25=-663/3460, 25-26=-663/3460, 18-26=-663/3460, 18-27=-666/3442, 27-28=-666/3442, 17-28=-666/3442, 16-17=-666/3442, 16-29=-615/3451, 29-30=-615/3451, 30-31=-615/3451, 15-31=-615/3451, 15-32=-611/3469, 32-33=-611/3469, 13-33=-611/3469
WEBS 3-18=0/542, 3-16=-123/300, 7-16=0/487, 12-16=-120/357, 12-15=0/546, 7-8=-187/898, 9-10=-113/61, 5-6=-115/61

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCDL=5.0psf; Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 383 lb uplift at joint 2 and 384 lb uplift at joint 13.
- Design requires purlins at oc spacing indicated.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 170 lb down and 73 lb up at 6-0-0, 138 lb down and 59 lb up at 8-0-12, 138 lb down and 59 lb up at 10-0-12, 138 lb down and 59 lb up at 12-0-12, 138 lb down and 59 lb up at 14-0-12, 138 lb down and 59 lb up at 16-0-12, and 138 lb down and 59 lb up at 18-0-12, and 170 lb down and 73 lb up at 20-0-0 on top chord, and 76 lb down at 2-0-12, 107 lb down and 10 lb up at 4-0-12, 76 lb down at 6-0-12, 76 lb down at 8-0-12, 76 lb down at 10-0-12, 76 lb down at 12-0-12, 76 lb down at 14-0-12, 76 lb down at 16-0-12, 76 lb down at 18-0-12, 76 lb down at 19-11-4, and 107 lb down and 10 lb up at 21-11-4, and 76 lb down at 23-11-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

Continued on page 2
LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
Truss Engineering Co.
818 Soundside Road
Edenton, NC 27932
FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MI-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANS/IPI Quality Criteria, D58-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483138
TEEL	G1	HIP	2	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc Fri Oct 26 14:54:22 2007 Page 2

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-3=-60, 3-4=-60, 11-12=-60, 12-14=-60, 2-13=-20, 4-8=-60, 8-11=-60

Concentrated Loads (lb)

Vert: 3=-90(B) 12=-90(B) 17=-38(B) 18=-38(B) 15=-38(B) 19=-98(B) 20=-98(B) 21=-98(B) 22=-98(B) 23=-98(B) 24=-98(B) 25=-38(B) 26=-107(B) 27=-38(B) 28=-38(B) 29=-38(B) 30=-38(B) 31=-38(B) 32=-107(B) 33=-38(B)

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult **ANSI/TPI1 Quality Criteria, DSB-89 and BCS11 Building Component Safety Information** available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

ENGINEERING BY
TRENCO
 A MiTek Affiliate

818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483139
TEEL	G2	COMMON	8	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc Fri Oct 26 14 54 23 2007 Page 1




Plate Offsets (X,Y): [2-0-3-0,0-1-8], [6-0-3-0,0-1-8]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plates Increase	1.25	TC 0.29	Vert(LL)	-0.13	2-10	>999	240	MT20	244/190
TCDL 10.0	Lumber Increase	1.25	BC 0.52	Vert(TL)	-0.38	2-10	>812	180		
BCLL 0.0	Rep Stress Incr	YES	WB 0.20	Horz(TL)	0.07	6	n/a	n/a		
BCDL 10.0	Code FBC2004/TPI2002		(Matrix)							Weight: 115 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP No.2D
 WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-2-7 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(lb/size) 2=1128/0-3-0, 6=1128/0-3-0
 Max Horz 2=86(LC 5)
 Max Uplift 2=-179(LC 5), 6=-179(LC 6)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/33, 2-3=-2049/216, 3-4=-1801/198, 4-5=-1801/199, 5-6=-2049/216, 6-7=0/33
 BOT CHORD 2-10=-196/1820, 9-10=-57/1228, 8-9=-57/1228, 6-8=-110/1820
 WEBS 3-10=-394/169, 4-10=-61/625, 4-8=-61/625, 5-8=-394/169

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCCL=5.0psf; BCDL=5.0psf, Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 179 lb uplift at joint 2 and 179 lb uplift at joint 6.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MI-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D58-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483140
TEEL	J01	JACK	4	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Mar 8 2007 MiTek Industries, Inc Fri Oct 26 16 27 56 2007 Page 1



LOADING (psf)	SPACING 2-0-0	CSI	DEFL in (loc)	L/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.20	Vert(LL) -0.00 2	>999	240	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.01	Vert(TL) -0.00 2	>999	180		
BCLL 0.0	Rep Stress Incr YES	WB 0.00	Horz(TL) -0.00 4	n/a	n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)					Weight: 12 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP No.2D

BRACING

TOP CHORD Structural wood sheathing directly applied or 1-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 4=121/Mechanical, 5=9/0-3-8, 2=210/0-3-0, 3=62/0-3-8
 Max Horz 2=96(LC 5)
 Max Uplift 4=-56(LC 5), 2=-106(LC 5), 3=-33(LC 4)
 Max Grav 4=121(LC 1), 5=19(LC 2), 2=210(LC 1), 3=62(LC 1)


FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/33, 2-3=-46/0, 3-4=-37/37
 BOT CHORD 2-5=0/0

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCDL=5.0psf; BCDL=5.0psf; Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 56 lb uplift at joint 4, 106 lb uplift at joint 2 and 33 lb uplift at joint 3.
- 6) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 3.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, DSB-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483141
TEEL	J01A	JACK	4	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Mar 8 2007 MiTek Industries, Inc Fri Oct 26 16 28 17 2007 Page 1



Scale = 1:9.9

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.12	Vert(LL)	-0.00	2	>999	240	MT20	244/190
TCDL 10.0	Lumber Increase	1.25	BC 0.01	Vert(TL)	-0.00	2	>999	180		
BCLL 0.0	Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	4	n/a	n/a		
BCDL 10.0	Code	FBC2004/TPI2002	(Matrix)							Weight: 9 lb

LUMBER
TOP CHORD 2 X 4 SYP No.2D
BOT CHORD 2 X 4 SYP No.2D


BRACING
TOP CHORD Structural wood sheathing directly applied or 1-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 4=61/Mechanical, 5=9/0-3-8, 2=210/0-3-0, 3=2/0-3-8
Max Horz 2=70(LC 5)
Max Uplift 4=-28(LC 5), 2=-118(LC 5), 3=-14(LC 4)
Max Grav 4=61(LC 1), 5=19(LC 2), 2=210(LC 1), 3=27(LC 3)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/33, 2-3=-46/0, 3-4=-19/19
BOT CHORD 2-5=0/0

- NOTES**
- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCDL=5.0psf, BCDL=5.0psf, Category II, Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 28 lb uplift at joint 4, 118 lb uplift at joint 2 and 14 lb uplift at joint 3.
 - 6) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 3.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
Truss Engineering Co
818 Soundside Road
Edenton, NC 27932
FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII 7473 BEFORE USE.
Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult **ANSI/TPI1 Quality Criteria, DSB-89 and BCS11 Building Component Safety Information** available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483142
TEEL	J01B	JACK	4	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Mar 8 2007 MiTek Industries, Inc Fri Oct 26 16 28 41 2007 Page 1



Scale = 1:6.2

LOADING (psf)	SPACING	CSI	DEFL	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.12	in (loc) l/def L/d	MT20	244/190
TCDL 10.0	Plates Increase 1.25	BC 0.01	Vert(LL) -0.00 2 >999 240		
BCLL 0.0	Lumber Increase 1.25	WB 0.00	Vert(TL) -0.00 2 >999 180		
BCDL 10.0	Rep Stress Incr YES	(Matrix)	Horz(TL) -0.00 3 n/a n/a		
	Code FBC2004/TPI2002			Weight: 6 lb	

LUMBER
TOP CHORD 2 X 4 SYP No.2D
BOT CHORD 2 X 4 SYP No.2D


BRACING
TOP CHORD Structural wood sheathing directly applied or 1-0-0 oc purtins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 4=10/Mechanical, 2=202/0-3-0, 3=-42/Mechanical
Max Horz 2=44(LC 5)
Max Uplift 2=-121(LC 5), 3=-42(LC 1)
Max Grav 4=19(LC 2), 2=202(LC 1), 3=43(LC 5)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/33, 2-3=-42/17
BOT CHORD 2-4=0/0

- NOTES**
- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCDL=5.0psf; BCDL=5.0psf; Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 121 lb uplift at joint 2 and 42 lb uplift at joint 3.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
Truss Engineering Co.
818 Soundside Road
Edenton, NC 27932
FL COA #7239

October 26, 2007


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MU-7473 BEFORE USE.
Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult **ANSI/TPI1 Quality Criteria, DSB-89 and BCS11 Building Component Safety Information** available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

ENGINEERING BY
TRENCO
A MiTek Affiliate
818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483143
TEEL	J02	JACK	4	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Mar 8 2007 MiTek Industries, Inc. Fri Oct 26 16 29 03 2007 Page 1



LOADING (psf)	SPACING	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 2-0-0	TC 0.12	Vert(LL) -0.00	2	>999	240		MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.03	Vert(TL) -0.00	2-5	>999	180			
BCLL 0.0	Rep Stress Incr YES	WB 0.00	Horz(TL) -0.00	4	n/a	n/a			
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)							Weight: 12 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP No.2D

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 4=61/Mechanical, 2=204/0-3-0, 5=19/0-3-8, 3=78/0-3-8
 Max Horz 2=83(LC 5)
 Max Uplift 4=-28(LC 5), 2=-85(LC 5), 3=-29(LC 4)
 Max Grav 4=61(LC 1), 2=204(LC 1), 5=39(LC 2), 3=78(LC 1)


FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/33, 2-3=-37/2, 3-4=-19/19
 BOT CHORD 2-5=0/0

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft, TCDL=5.0psf; BCDL=5.0psf; Category II, Exp B; enclosed, MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 28 lb uplift at joint 4, 85 lb uplift at joint 2 and 29 lb uplift at joint 3.
- 6) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 3.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D5B-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483144
TEEL	J02A	JACK	4	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Mar 8 2007 MiTek Industries, Inc. Fri Oct 26 16 29 27 2007 Page 1



Scale: 1.5"=1'

LOADING (psf)	SPACING	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 2-0-0 1.25	TC 0.12	Vert(LL) -0.00	2	>999	240		MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.03	Vert(TL) -0.00	2-4	>999	180			
BCLL 0.0	Rep Stress Incr YES	WB 0.00	Horz(TL) -0.00	3	n/a	n/a			
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)							Weight: 9 lb

LUMBER
 TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP No.2D

BRACING
 TOP CHORD Structural wood sheathing directly applied or 2-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS (lb/size) 2=206/0-3-0, 4=20/Mechanical, 3=24/Mechanical
 Max Horz 2=58(LC 5)
 Max Uplift 2=-96(LC 5), 3=-13(LC 4)
 Max Grav 2=206(LC 1), 4=39(LC 2), 3=24(LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/33, 2-3=-38/5
 BOT CHORD 2-4=0/0

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCDL=5.0psf; BCDL=5.0psf; Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 96 lb uplift at joint 2 and 13 lb uplift at joint 3.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, DSB-89 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

ENGINEERING BY
TRENCO
 A MiTek Affiliate

818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483145
TEEL	J06	JACK	4	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Apr 2 2007 MiTek Industries, Inc Fri Oct 26 14 54 26 2007 Page 1




Plate Offsets (X,Y): [6:0-0-5,0-1-8]

LOADING (psf)	SPACING	CSI	DEFL	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.13	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plates Increase 1.25	BC 0.28	Vert(LL) -0.05 2-6 >999 240		
BCLL 0.0	Lumber Increase 1.25	WB 0.03	Vert(TL) -0.13 2-6 >512 180		
BCDL 10.0	Rep Stress Incr YES	(Matrix)	Horz(TL) 0.00 6 n/a n/a		
	Code FBC2004/TPI2002			Weight: 22 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP No.2D
 WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-0-7 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=324/0-3-0, 6=127/Mechanical

Max Horz 2=83(LC 5)
 Max Uplift 2=-96(LC 5)
 Max Grav 2=324(LC 1), 6=144(LC 2)


FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/33, 2-3=-169/32, 3-4=-14/0
 BOT CHORD 2-6=-51/110, 5-6=0/0
 WEBS 3-6=-128/60

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TC DL=5.0psf; BCDL=5.0psf; Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 96 lb uplift at joint 2.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITTEK REFERENCE PAGE MII-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D58-B9 and BCS11 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483146
TEEL	J06A	JACK	4	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Mar 8 2007 MiTek Industries, Inc. Fri Oct 26 16 29 55 2007 Page 1



LOADING (psf)	SPACING	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0 Plates Increase 1.25	TC 0.13	Vert(LL) -0.06	2-4	>999	240	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.28	Vert(TL) -0.14	2-4	>495	180		
BCLL 0.0	Rep Stress Incr YES	WB 0.00	Horz(TL) -0.00	3	n/a	n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)						Weight 15 lb


LUMBER	BRACING
TOP CHORD 2 X 4 SYP No.2D	TOP CHORD Structural wood sheathing directly applied or 2-0-7 oc purlins.
BOT CHORD 2 X 4 SYP No.2D	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=8/Mechanical, 2=253/0-3-0, 4=58/Mechanical
 Max Horz 2=56(LC 5)
 Max Uplift 3=-10(LC 4), 2=-86(LC 5)
 Max Grav 3=12(LC 3), 2=253(LC 1), 4=116(LC 2)

FORCES (lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/33, 2-3=-41/4
 BOT CHORD 2-4=0/0

- NOTES**
- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft, TCDL=5.0psf, BCDL=5.0psf, Category II, Exp B, enclosed, MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 10 lb uplift at joint 3 and 86 lb uplift at joint 2.

LOAD CASE(S) Standard




Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483147
TEEL	J07	JACK	3	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Mar 8 2007 MiTek Industries, Inc Fri Oct 26 16:30 20 2007 Page 1



LOADING (psf)	SPACING	CSI	DEFL	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.21	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plates Increase 1.25	BC 0.39	Vert(LL) -0.11 2-4 >768 240		
BCLL 0.0	Lumber Increase 1.25	WB 0.00	Vert(TL) -0.27 2-4 >307 180		
BCDL 10.0	Rep Stress Incr YES	(Matrix)	Horz(TL) -0.00 3 n/a n/a		
	Code FBC2004/TPI2002			Weight: 21 lb	

LUMBER
TOP CHORD 2 X 4 SYP No.2D
BOT CHORD 2 X 4 SYP No.2D


BRACING
TOP CHORD Structural wood sheathing directly applied or 5-0-7 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=126/Mechanical, 4=68/Mechanical, 2=325/0-3-0
Max Horz 2=96(LC 5)
Max Uplift 3=-54(LC 5), 2=-83(LC 5)
Max Grav 3=126(LC 1), 4=136(LC 2), 2=325(LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/33, 2-3=-64/39
BOT CHORD 2-4=0/0

- NOTES**
- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCDL=5.0psf; BCDL=5.0psf; Category II, Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 54 lb uplift at joint 3 and 83 lb uplift at joint 2.

LOAD CASE(S) Standard




Marvin A. Strzyzewski, FL Lic. #43144
Truss Engineering Co.
818 Soundside Road
Edenton, NC 27932
FL COA #7239

October 26, 2007

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483148
TEEL	J07A	JACK	3	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Mar 8 2007 MiTek Industries, Inc. Fri Oct 26 16:30:39 2007 Page 1



LOADING (psf)	SPACING	CSI	DEFL	PLATES	GRIP
TCLL 20.0	Plates Increase 2-0-0 1.25	TC 0.14	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.39	Vert(LL) -0.11 2-4 >768 240		
BCLL 0.0	Rep Stress Incr YES	WB 0.00	Vert(TL) -0.27 2-4 >307 180		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)	Horz(TL) -0.00 3 n/a n/a		
				Weight: 18 lb	

LUMBER
 TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP No.2D


BRACING
 TOP CHORD Structural wood sheathing directly applied or 3-0-7 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=54/Mechanical, 4=68/Mechanical, 2=277/0-3-0
 Max Horz 2=70(LC 5)
 Max Uplift 3=-21(LC 4), 2=-76(LC 5)
 Max Grav 3=54(LC 1), 4=136(LC 2), 2=277(LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/33, 2-3=-46/15
 BOT CHORD 2-4=0/0

- NOTES**
- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCDL=5.0psf, BCDL=5.0psf; Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 21 lb uplift at joint 3 and 76 lb uplift at joint 2.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, D5B-89 and BCSI1 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483149
TEEL	J07AL	JACK	1	1	Job Reference (optional)	
SANTA FE TRUSS, HIGH SPRINGS, FL					6 500 s Apr 2 2007 MiTek Industries, Inc Fri Oct 26 14 54 28 2007 Page 1	



LOADING (psf)	SPACING 2-0-0	CSI	DEFL in (loc) l/defl L/d	PLATES GRIP
TCLL 20.0	Plates Increase 1.25	TC 0.06	Vert(LL) -0.10 1-5 >799 240	MT20 244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.39	Vert(TL) -0.25 1-5 >319 180	
BCLL 0.0	Rep Stress Incr YES	WB 0.07	Horz(TL) 0.00 5 n/a n/a	Weight: 22 lb
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)		

LUMBER	BRACING
TOP CHORD 2 X 4 SYP No.2D	TOP CHORD Structural wood sheathing directly applied or 3-0-7 oc purlins.
BOT CHORD 2 X 4 SYP No.2D	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2 X 4 SYP No.3	

REACTIONS (lb/size) 1=203/0-3-8, 5=108/Mechanical
 Max Horz 1=40(LC 5)
 Max Uplift 1=-10(LC 5)
 Max Grav 1=203(LC 1), 5=154(LC 2)

FORCES (lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=-194/56, 2-3=-14/0
 BOT CHORD 1-5=-70/158, 4-5=0/0
 WEBS 2-5=-162/72

- NOTES**
- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TCCL=5.0psf, BCDL=5.0psf; Category II; Exp B; enclosed, MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 10 lb uplift at joint 1.

LOAD CASE(S) Standard




Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483150
TEEL	J07B	JACK	4	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Mar 8 2007 MiTek Industries, Inc Fri Oct 26 16 31 04 2007 Page 1



LOADING (psf)	SPACING	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase 2-0-0 1.25	TC 0.12	Vert(LL) -0.11	2-4	>736	240	MT20	244/190
TCDL 10.0	Lumber Increase 1.25	BC 0.40	Vert(TL) -0.28	2-4	>294	180		
BCLL 0.0	Rep Stress Incr YES	WB 0.00	Horz(TL) -0.00	3	n/a	n/a		
BCDL 10.0	Code FBC2004/TPI2002	(Matrix)						Weight: 15 lb

LUMBER
TOP CHORD 2 X 4 SYP No.2D
BOT CHORD 2 X 4 SYP No.2D


BRACING
TOP CHORD Structural wood sheathing directly applied or 1-0-7 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 4=69/Mechanical, 2=261/0-3-0, 3=-42/Mechanical
Max Horz 2=44(LC 5)
Max Uplift 2=-92(LC 5), 3=-42(LC 1)
Max Grav 4=138(LC 2), 2=261(LC 1), 3=43(LC 5)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/33, 2-3=-42/17
BOT CHORD 2-4=0/0

- NOTES**
- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TC DL=5.0psf; BC DL=5.0psf; Category II; Exp B; enclosed; MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 92 lb uplift at joint 2 and 42 lb uplift at joint 3.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
Truss Engineering Co.
818 Soundside Road
Edenton, NC 27932
FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MH-7473 BEFORE USE.
Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI1 Quality Criteria, DSB-89 and BCSI1 Building Component Safety Information available from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	TEELE RES AND GARAGE	E4483151
TEEL	J07L	JACK	1	1	Job Reference (optional)	

SANTA FE TRUSS, HIGH SPRINGS, FL

6 500 s Mar 8 2007 MiTek Industries, Inc. Fri Oct 26 16 31 29 2007 Page 1




Plate Offsets (X,Y): [1:0-1-8,0-1-0]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.28	Vert(LL)	-0.11	1-3	>748	240	MT20	244/190
TCDL 10.0	Lumber Increase	1.25	BC 0.40	Vert(TL)	-0.28	1-3	>299	180		
BCLL 0.0	Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	2	n/a	n/a		
BCDL 10.0	Code	FBC2004/TPI2002	(Matrix)							Weight: 19 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2D
 BOT CHORD 2 X 4 SYP No.2D

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-0-7 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 1=214/Mechanical, 2=145/Mechanical, 3=69/Mechanical
 Max Horz 1=66(LC 5)
 Max Uplift 1=-5(LC 5), 2=-68(LC 5)
 Max Grav 1=214(LC 1), 2=145(LC 1), 3=138(LC 2)


FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-46/46
 BOT CHORD 1-3=0/0

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=18ft; TC DL=5.0psf, BCDL=5.0psf, Category II, Exp B; enclosed, MWFRS; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33.
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) This truss requires plate inspection per the Tooth Count Method when this truss is chosen for quality assurance inspection.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 5 lb uplift at joint 1 and 68 lb uplift at joint 2.

LOAD CASE(S) Standard



Marvin A. Strzyzewski, FL Lic. #43144
 Truss Engineering Co.
 818 Soundside Road
 Edenton, NC 27932
 FL COA #7239

October 26, 2007

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to insure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult **ANSI/TPI1 Quality Criteria, DSB-89 and BCS11 Building Component Safety Information** available from Truss Plate Institute, 583 D Onofrio Drive, Madison, WI 53719.



818 Soundside Road
 Edenton, NC 27932