

# ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE INDEX\* = 75

The lower the EnergyPerformance Index, the more efficient the home

514 SW Pinehurst Drive, Lake City, FL, 32024-

1 New construction or existing New (From Plans)  
2 Single family or multiple family Single-family  
3 Number of units, if multiple family 1  
4 Number of Bedrooms 3  
5 Is this a worst case? No  
6 Conditioned floor area (ft<sup>2</sup>) 2005

7 Windows**	Description	Area
a U-Factor	Dbl, U=0.55	216.00 ft <sup>2</sup>
	SHGC	SHGC=0.50
b U-Factor	N/A	ft <sup>2</sup>
	SHGC	
c U-Factor	N/A	ft <sup>2</sup>
	SHGC	
d U-Factor	N/A	ft <sup>2</sup>
	SHGC	
Area Weighted Average Overhang Depth		0.667 ft
Area Weighted Average SHGC		0.500

8 Floor Types	Insulation	Area
a Slab-On-Grade Edge Insulation	R=0.0	2005.00 ft <sup>2</sup>
b N/A	R=	ft <sup>2</sup>
c N/A	R=	ft <sup>2</sup>

9 Wall Types	Insulation	Area
a Frame - Wood, Exterior	R=19.0	1713.30 ft <sup>2</sup>
b Frame - Wood, Adjacent	R=19.0	503.33 ft <sup>2</sup>
c N/A	R=	ft <sup>2</sup>
d N/A	R=	ft <sup>2</sup>

10 Ceiling Types	Insulation	Area
a Under Attic (Vented)	R=30.0	2005.00 ft <sup>2</sup>
b N/A	R=	ft <sup>2</sup>
c N/A	R=	ft <sup>2</sup>


11 Ducts	R	ft <sup>2</sup>
a Sup Attic, Ret Attic, AH 1st Floor	6	401

12 Cooling systems	kBtu/hr	Efficiency
a Central Unit	35.0	SEER 14.00

13 Heating systems	kBtu/hr	Efficiency
a Electric Heat Pump	35.0	HSPF 7.70

14 Hot water systems	Cap	50 gallons
a Electric		EF 1
b Conservation features		
None		

15 Credits Pstat



I certify that this home has complied with the Florida Energy Efficiency Code for Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature [Signature]

Date 4/9/13

Address of New Home 514 SW Pinehurst Drive

City/FL Zip Lake City, FL 32024

\*Note This is not a Building Energy Rating. If your Index is below 70, your home may qualify for energy efficient mortgage (EEM) incentives if you obtain a Florida EnergyGauge Rating. Contact the EnergyGauge Hotline at (321) 638-1492 or see the EnergyGauge web site at [energygauge.com](http://energygauge.com) for information and a list of certified Raters. For information about the Florida Building Code, Energy Conservation, contact the Florida Building Commission's support staff.

\*\*Label required by Section 303.1.3 of the Florida Building Code, Energy Conservation, if not DEFAULT.

**FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION**

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name McDuffie Energy Calc  
 Street 514 SW Pinehurst Drive  
 City, State, Zip Lake City, FL, 32024-  
 Owner Lee McDuffie  
 Design Location FL, Gainesville

Builder Name Trademark Construction Group,  
 Permit Office Columbia County  
 Permit Number  
 Jurisdiction

1 New construction or existing New (From Plans)  
 2 Single family or multiple family Single-family  
 3 Number of units, if multiple family 1  
 4 Number of Bedrooms 3  
 5 Is this a worst case? No  
 6 Conditioned floor area above grade (ft<sup>2</sup>) 2005  
 Conditioned floor area below grade (ft<sup>2</sup>) 0  
 7 Windows (216 0 sqft) Description Area  
 a U-Factor Dbl, U=0 55 216 00 ft<sup>2</sup>  
 SHGC SHGC=0 50  
 b U-Factor N/A ft<sup>2</sup>  
 SHGC  
 c U-Factor N/A ft<sup>2</sup>  
 SHGC  
 d U-Factor N/A ft<sup>2</sup>  
 SHGC  
 Area Weighted Average Overhang Depth 0 667 ft  
 Area Weighted Average SHGC 0 500  
 8 Floor Types (2005 0 sqft) Insulation Area  
 a Slab-On-Grade Edge Insulation R=0 0 2005 00 ft<sup>2</sup>  
 b N/A R= ft<sup>2</sup>  
 c N/A R= ft<sup>2</sup>

9 Wall Types (2216 7 sqft) Insulation Area  
 a Frame - Wood, Exterior R=19 0 1713 30 ft<sup>2</sup>  
 b Frame - Wood, Adjacent R=19 0 503 33 ft<sup>2</sup>  
 c N/A R= ft<sup>2</sup>  
 d N/A R= ft<sup>2</sup>  
 10 Ceiling Types (2005 0 sqft) Insulation Area  
 a Under Attic (Vented) R=30 0 2005 00 ft<sup>2</sup>  
 b N/A R= ft<sup>2</sup>  
 c N/A R= ft<sup>2</sup>  
 11 Ducts R ft<sup>2</sup>  
 a Sup Attic, Ret Attic, AH 1st Floor 6 401  
 12 Cooling systems kBtu/hr Efficiency  
 a Central Unit 35 0 SEER 14 00  
 13 Heating systems kBtu/hr Efficiency  
 a Electric Heat Pump 35 0 HSPF 7 70  
 14 Hot water systems Cap 50 gallons  
 a Electric EF 1 000  
 b Conservation features  
 None  
 15 Credits Pstat

Glass/Floor Area 0 108

Total Proposed Modified Loads 32 80  
 Total Standard Reference Loads 43 58

**PASS**

I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code

PREPARED BY                       
 DATE 8/9/13

I hereby certify that this building, as designed, is in compliance with the Florida Energy Code

OWNER/AGENT                       
 DATE 8/9/13

Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes



BUILDING OFFICIAL                       
 DATE                     

- Compliance requires completion of a Florida Air Barrier and Insulation Inspection Checklist

PROJECT											
Title	McDuffie Energy Calc	Bedrooms	3	Address Type	Street Address						
Building Type	User	Conditioned Area	2005	Lot #							
Owner	Lee McDuffie	Total Stories	1	Block/SubDivision							
# of Units	1	Worst Case	No	PlatBook							
Builder Name	Trademark Construction Grou	Rotate Angle	0	Street	514 SW Pinehurst Drive						
Permit Office	Columbia County	Cross Ventilation		County	Columbia						
Jurisdiction		Whole House Fan		City, State, Zip	Lake City , FL , 32024-						
Family Type	Single-family										
New/Existing	New (From Plans)										
Comment											
CLIMATE											
✓	Design Location	TMY Site	IECC Zone	Design Temp 97 5 %	2 5 %	Int Design Temp Winter	Summer	Heating Degree Days	Design Moisture	Daily Temp Range	
_____	FL, Gainesville	FL_GAINESVILLE_REGI	2	32	92	70	75	1305 5	51	Medium	
BLOCKS											
	Number	Name	Area	Volume							
	1	Block	2005	20050							
SPACES											
	Number	Name	Area	Volume	Kitchen	Occupants	Bedrooms	Infil ID	Finished	Cooled	Heated
	1	1st Floor	2005	20050	Yes	4	3	1	Yes	Yes	Yes
FLOORS											
✓	#	Floor Type	Space	Perimeter	R-Value	Area			Tile	Wood	Carpet
_____	1	Slab-On-Grade Edge Insulatio	1st Floor	228 ft	0	2005 ft²	----		0 25	0 5	0 25
ROOF											
✓	#	Type	Materials	Roof Area	Gable Area	Roof Color	Solar Absor	SA Tested	Emitt	Emitt Tested	Deck Insul Pitch (deg)
_____	1	Hip	Composition shingles	2322 ft²	0 ft²	Medium	0 96	No	0 9	No	0 30 3
ATTIC											
✓	#	Type	Ventilation	Vent Ratio (1 in)	Area	RBS	IRCC				
_____	1	Full attic	Vented	300	2005 ft²	N	N				
CEILING											
✓	#	Ceiling Type	Space	R-Value	Area	Framing Frac	Truss Type				
_____	1	Under Attic (Vented)	1st Floor	30	2005 ft²	0 11	Wood				

WALLS														
✓ #	Ornt	Adjacent To	Wall Type	Space	Cavity R-Value	Width Ft	In	Height Ft	In	Area	Sheathing R-Value	Framing Fraction	Solar Absor.	Below Grade%
1	W	Exterior	Frame - Wood	1st Floor	19	60	6	10		605 ft²		0.23	0.75	0
2	N	Exterior	Frame - Wood	1st Floor	19	50	4	10		503.3333		0.23	0.75	0
3	E	Exterior	Frame - Wood	1st Floor	19	60	6	10		605 ft²	0	0.23	0.75	0
4	S	Garage	Frame - Wood	1st Floor	19	50	4	10		503.3333		0.23	0.75	0

DOORS										
✓ #	Ornt	Door Type	Space	Storms	U-Value	Width Ft	In	Height Ft	In	Area
1	W	Insulated	1st Floor	None	0.460000	6		8		48 ft²
2	E	Insulated	1st Floor	None	0.460000	6		8		48 ft²
3	S	Insulated	1st Floor	None	0.460000	6		8		24 ft²
4	S	Insulated	1st Floor	None	0.460000	6		8		24 ft²

WINDOWS													
Orientation shown is the entered, Proposed orientation													
✓ #	Ornt	Wall ID	Frame	Panes	NFRC	U-Factor	SHGC	Area	Overhang Depth	Separation	Int Shade	Screening	
1	W	1	Vinyl	Low-E Double	Yes	0.55	0.5	96 ft²	1 ft 6 in	0 ft 0 in	Drapes/blinds	None	
2	N	2	Vinyl	Low-E Double	Yes	0.55	0.5	18 ft²	0 ft 0 in	0 ft 0 in	Drapes/blinds	None	
3	E	3	Vinyl	Low-E Double	Yes	0.55	0.5	96 ft²	0 ft 0 in	0 ft 0 in	Drapes/blinds	None	
4	E	3	Vinyl	Low-E Double	Yes	0.55	0.5	6 ft²	0 ft 0 in	0 ft 0 in	Drapes/blinds	None	

GARAGE						
✓ #	Floor Area	Ceiling Area	Exposed Wall Perimeter	Avg Wall Height	Exposed Wall Insulation	
1	519.84 ft²	519.84 ft²	40 ft	10 ft	13	

INFILTRATION								
#	Scope	Method	SLA	CFM 50	ELA	EqLA	ACH	ACH 50
1	Wholehouse	Best Guess	0.000300	1577.7	86.616	162.89	0.2310	4.7214

HEATING SYSTEM							
✓ #	System Type	Subtype	Efficiency	Capacity	Block	Ducts	
1	Electric Heat Pump	None	HSPF 7.7	35 kBtu/hr	1	sys#1	

COOLING SYSTEM								
✓ #	System Type	Subtype	Efficiency	Capacity	Air Flow	SHR	Block	Ducts
1	Central Unit	Single	SEER 14	35 kBtu/hr	1050 cfm	0.75	1	sys#1

HOT WATER SYSTEM														
✓	#	System Type	SubType	Location	EF	Cap	Use	SetPnt	Conservation					
✓	1	Electric	Heat Pump	Garage	1	50 gal	60 gal	120 deg	None					

SOLAR HOT WATER SYSTEM									
✓	FSEC	Company Name	System Model #	Collector Model #	Collector Area	Storage Volume	FEF		
✓	None	None					ft²		

DUCTS														
✓	#	---- Supply ----			---- Return ----		Leakage Type	Air Handler	CFM 25	Percent Leakage	QN	RLF	HVAC #	
		Location	R-Value	Area	Location	Area							Heat	Cool
✓	1	Attic	6	401 ft²	Attic	100 25	Default Leakage	1st Floor	(Default)	(Default) %			1	1

TEMPERATURES														
Programable Thermostat Y					Ceiling Fans									
Cooling	[ ] Jan	[ ] Feb	[ ] Mar	[ ] Apr	[ ] May	[X] Jun	[X] Jul	[X] Aug	[X] Sep	[ ] Oct	[ ] Nov	[ ] Dec		
Heating	[X] Jan	[X] Feb	[X] Mar	[ ] Apr	[ ] May	[ ] Jun	[ ] Jul	[ ] Aug	[ ] Sep	[X] Oct	[X] Nov	[X] Dec		
Venting	[ ] Jan	[ ] Feb	[X] Mar	[X] Apr	[ ] May	[ ] Jun	[ ] Jul	[ ] Aug	[ ] Sep	[X] Oct	[X] Nov	[X] Dec		
Thermostat Schedule		HERS 2006 Reference												
Schedule Type		Hours												
		1	2	3	4	5	6	7	8	9	10	11	12	
Cooling (WD)	AM	78	78	78	78	78	78	78	78	80	80	80	80	
	PM	80	80	78	78	78	78	78	78	78	78	78	78	
Cooling (WEH)	AM	78	78	78	78	78	78	78	78	78	78	78	78	
	PM	78	78	78	78	78	78	78	78	78	78	78	78	
Heating (WD)	AM	66	66	66	66	66	68	68	68	68	68	68	68	
	PM	68	68	68	68	68	68	68	68	68	68	66	66	
Heating (WEH)	AM	66	66	66	66	66	68	68	68	68	68	68	68	
	PM	68	68	68	68	68	68	68	68	68	68	66	66	



# Florida Code Compliance Checklist

Florida Department of Business and Professional Regulations  
Residential Whole Building Performance Method

ADDRESS 514 SW Pinehurst Drive  
Lake City, FL 32024-

PERMIT #

## MANDATORY REQUIREMENTS SUMMARY - See individual code sections for full details.

COMPONENT	SECTION	SUMMARY OF REQUIREMENT(S)	CHECK
Air leakage	402 4	To be caulked, gasketed, weatherstripped or otherwise sealed Recessed lighting IC-rated as meeting ASTM E 283 Windows and doors = 0.30 cfm/sq ft Testing or visual inspection required Fireplaces gasketed doors & outdoor combustion air Must complete envelope leakage report or visually verify Table 402 4 2	
Thermostat & controls	403 1	At least one thermostat shall be provided for each separate heating and cooling system Where forced-air furnace is primary system, programmable thermostat is required Heat pumps with supplemental electric heat must prevent supplemental heat when compressor can meet the load	
Ducts	403 2 2	All ducts, air handlers, filter boxes and building cavities which form the primary air containment passageways for air distribution systems shall be considered ducts or plenum chambers, shall be constructed and sealed in accordance with Section 503 2 7 2 of this code	
	403 3 3	Building framing cavities shall not be used as supply ducts	
Water heaters	403 4	Heat trap required for vertical pipe risers Comply with efficiencies in Table 403 4 3 2 Provide switch or clearly marked circuit breaker (electric) or shutoff (gas) Circulating system pipes insulated to = R-2 + accessible manual OFF switch	
Mechanical ventilation	403 5	Homes designed to operate at positive pressure or with mechanical ventilation systems shall not exceed the minimum ASHRAE 62 level No make-up air from attics, crawlspaces, garages or outdoors adjacent to pools or spas	
Swimming Pools & Spas	403 9	Pool pumps and pool pump motors with a total horsepower (HP) of = 1 HP shall have the capability of operating at two or more speeds Spas and heated pools must have vapor-retardant covers or a liquid cover or other means proven to reduce heat loss except if 70% of heat from site-recovered energy Off/timer switch required Gas heaters minimum thermal efficiency=78% (82% after 4/16/13) Heat pump pool heaters minimum COP= 4.0	
Cooling/heating equipment	403 6	Sizing calculation performed & attached Minimum efficiencies per Tables 503 2 3 Equipment efficiency verification required Special occasion cooling or heating capacity requires separate system or variable capacity system Electric heat >10kW must be divided into two or more stages	
Ceilings/knee walls	405 2 1	R-19 space permitting	