

RESIDENTIAL ENERGY CONSERVATION CODE DOCUMENTATION CHECKLIST**Florida Department of Business and Professional Regulation
Simulated Performance Alternative (Performance) Method**

Applications for compliance with the 2017 Florida Building Code, Energy Conservation via the residential Simulated Performance Method shall include:

- ☐ This checklist
- ☐ A Form R405 report that documents that the Proposed Design complies with Section R405.3 of the Florida Energy Code. This form shall include a summary page indicating home address, e-ratio and the pass or fail status along with summary areas and types of components, whether the home was simulated as a worst-case orientation, name and version of the compliance software tool, name of individual completing the compliance report (one page) and an input summary checklist that can be used for field verification (usually four pages/may be greater).
- ☐ Energy Performance Level (EPL) Display Card (one page)
- ☐ HVAC system sizing and selection based on ACCA Manual S or per exceptions provided in Section R403.7
- ☐ Mandatory Requirements (five pages)

**Required prior to CO for the Performance Method:**

- ☐ Air Barrier and Insulation Inspection Component Criteria checklist (Table R402.4.1.1 - one page)
- ☐ A completed Envelope Leakage Test Report (usually one page)
- ☐ If Form R405 duct leakage type indicates anything other than "default leakage", then a completed Form R405 Duct Leakage Test Report (usually one page)


FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name: Jewett Residence Street: City, State, Zip: Lake City , FL , 32055 Owner: Design Location: FL, Gainesville	Builder Name: Permit Office: Permit Number: Jurisdiction: County: Columbia (Florida Climate Zone 2)
--	---

<table style="width: 100%;"> <tr> <td style="width: 30%;">1. New construction or existing</td> <td style="width: 70%;">New (From Plans)</td> </tr> <tr> <td>2. Single family or multiple family</td> <td>Single-family</td> </tr> <tr> <td>3. Number of units, if multiple family</td> <td>1</td> </tr> <tr> <td>4. Number of Bedrooms</td> <td>3</td> </tr> <tr> <td>5. Is this a worst case?</td> <td>No</td> </tr> <tr> <td>6. Conditioned floor area above grade (ft²)</td> <td>2320</td> </tr> <tr> <td> Conditioned floor area below grade (ft²)</td> <td>0</td> </tr> <tr> <td>7. Windows(330.0 sqft.)</td> <td> <table style="width: 100%;"> <tr> <th style="width: 30%;">Description</th> <th style="width: 70%;">Area</th> </tr> <tr> <td>a. U-Factor: Sgl, U=0.55</td> <td>285.00 ft²</td> </tr> <tr> <td> SHGC: SHGC=0.50</td> <td></td> </tr> <tr> <td>b. U-Factor: Dbl, U=0.55</td> <td>45.00 ft²</td> </tr> <tr> <td> SHGC: SHGC=0.50</td> <td></td> </tr> <tr> <td>c. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> </tr> <tr> <td>d. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> </tr> <tr> <td>Area Weighted Average Overhang Depth:</td> <td>0.000 ft.</td> </tr> <tr> <td>Area Weighted Average SHGC:</td> <td>0.500</td> </tr> </table> </td> </tr> <tr> <td>8. Floor Types (2320.0 sqft.)</td> <td> <table style="width: 100%;"> <tr> <th style="width: 30%;">Insulation</th> <th style="width: 70%;">Area</th> </tr> <tr> <td>a. Slab-On-Grade Edge Insulation</td> <td>R=0.7 2320.00 ft²</td> </tr> <tr> <td>b. N/A</td> <td>R= ft²</td> </tr> <tr> <td>c. N/A</td> <td>R= ft²</td> </tr> </table> </td> </tr> </table>	1. New construction or existing	New (From Plans)	2. Single family or multiple family	Single-family	3. Number of units, if multiple family	1	4. Number of Bedrooms	3	5. Is this a worst case?	No	6. Conditioned floor area above grade (ft²)	2320	Conditioned floor area below grade (ft²)	0	7. Windows(330.0 sqft.)	<table style="width: 100%;"> <tr> <th style="width: 30%;">Description</th> <th style="width: 70%;">Area</th> </tr> <tr> <td>a. U-Factor: Sgl, U=0.55</td> <td>285.00 ft²</td> </tr> <tr> <td> SHGC: SHGC=0.50</td> <td></td> </tr> <tr> <td>b. U-Factor: Dbl, U=0.55</td> <td>45.00 ft²</td> </tr> <tr> <td> SHGC: SHGC=0.50</td> <td></td> </tr> <tr> <td>c. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> </tr> <tr> <td>d. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> </tr> <tr> <td>Area Weighted Average Overhang Depth:</td> <td>0.000 ft.</td> </tr> <tr> <td>Area Weighted Average SHGC:</td> <td>0.500</td> </tr> </table>	Description	Area	a. U-Factor: Sgl, U=0.55	285.00 ft²	SHGC: SHGC=0.50		b. U-Factor: Dbl, U=0.55	45.00 ft²	SHGC: SHGC=0.50		c. U-Factor: N/A	ft²	SHGC:		d. U-Factor: N/A	ft²	SHGC:		Area Weighted Average Overhang Depth:	0.000 ft.	Area Weighted Average SHGC:	0.500	8. Floor Types (2320.0 sqft.)	<table style="width: 100%;"> <tr> <th style="width: 30%;">Insulation</th> <th style="width: 70%;">Area</th> </tr> <tr> <td>a. Slab-On-Grade Edge Insulation</td> <td>R=0.7 2320.00 ft²</td> </tr> <tr> <td>b. N/A</td> <td>R= ft²</td> </tr> <tr> <td>c. N/A</td> <td>R= ft²</td> </tr> </table>	Insulation	Area	a. Slab-On-Grade Edge Insulation	R=0.7 2320.00 ft²	b. N/A	R= ft²	c. N/A	R= ft²	<table style="width: 100%;"> <tr> <td style="width: 30%;">9. Wall Types(1872.0 sqft.)</td> <td style="width: 30%;">Insulation</td> <td style="width: 40%;">Area</td> </tr> <tr> <td>a. Frame - Wood, Exterior</td> <td>R=19.0</td> <td>1872.00 ft²</td> </tr> <tr> <td>b. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>c. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>d. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>10. Ceiling Types (2320.0 sqft.)</td> <td>Insulation</td> <td>Area</td> </tr> <tr> <td>a. Cathedral/Single Assembly (Unvented)</td> <td>R=0.0</td> <td>2320.00 ft²</td> </tr> <tr> <td>b. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>c. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>11. Ducts</td> <td></td> <td>R ft²</td> </tr> <tr> <td>a. Sup: Attic, Ret: Attic, AH: Main</td> <td></td> <td>6 534</td> </tr> <tr> <td>12. Cooling systems</td> <td>kBtu/hr</td> <td>Efficiency</td> </tr> <tr> <td>a. Central Unit</td> <td>28.3</td> <td>SEER:16.00</td> </tr> <tr> <td>13. Heating systems</td> <td>kBtu/hr</td> <td>Efficiency</td> </tr> <tr> <td>a. Electric Heat Pump</td> <td>36.5</td> <td>HSPF:8.70</td> </tr> <tr> <td>14. Hot water systems</td> <td></td> <td></td> </tr> <tr> <td>a. Electric</td> <td></td> <td>Cap: 50 gallons</td> </tr> <tr> <td></td> <td></td> <td>EF: 0.980</td> </tr> <tr> <td>b. Conservation features</td> <td></td> <td></td> </tr> <tr> <td> Heat Recovery Unit</td> <td></td> <td></td> </tr> <tr> <td>15. Credits</td> <td></td> <td>CF, Pstat</td> </tr> </table>	9. Wall Types(1872.0 sqft.)	Insulation	Area	a. Frame - Wood, Exterior	R=19.0	1872.00 ft²	b. N/A	R=	ft²	c. N/A	R=	ft²	d. N/A	R=	ft²	10. Ceiling Types (2320.0 sqft.)	Insulation	Area	a. Cathedral/Single Assembly (Unvented)	R=0.0	2320.00 ft²	b. N/A	R=	ft²	c. N/A	R=	ft²	11. Ducts		R ft²	a. Sup: Attic, Ret: Attic, AH: Main		6 534	12. Cooling systems	kBtu/hr	Efficiency	a. Central Unit	28.3	SEER:16.00	13. Heating systems	kBtu/hr	Efficiency	a. Electric Heat Pump	36.5	HSPF:8.70	14. Hot water systems			a. Electric		Cap: 50 gallons			EF: 0.980	b. Conservation features			Heat Recovery Unit			15. Credits		CF, Pstat
1. New construction or existing	New (From Plans)																																																																																																															
2. Single family or multiple family	Single-family																																																																																																															
3. Number of units, if multiple family	1																																																																																																															
4. Number of Bedrooms	3																																																																																																															
5. Is this a worst case?	No																																																																																																															
6. Conditioned floor area above grade (ft²)	2320																																																																																																															
Conditioned floor area below grade (ft²)	0																																																																																																															
7. Windows(330.0 sqft.)	<table style="width: 100%;"> <tr> <th style="width: 30%;">Description</th> <th style="width: 70%;">Area</th> </tr> <tr> <td>a. U-Factor: Sgl, U=0.55</td> <td>285.00 ft²</td> </tr> <tr> <td> SHGC: SHGC=0.50</td> <td></td> </tr> <tr> <td>b. U-Factor: Dbl, U=0.55</td> <td>45.00 ft²</td> </tr> <tr> <td> SHGC: SHGC=0.50</td> <td></td> </tr> <tr> <td>c. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> </tr> <tr> <td>d. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> </tr> <tr> <td>Area Weighted Average Overhang Depth:</td> <td>0.000 ft.</td> </tr> <tr> <td>Area Weighted Average SHGC:</td> <td>0.500</td> </tr> </table>	Description	Area	a. U-Factor: Sgl, U=0.55	285.00 ft²	SHGC: SHGC=0.50		b. U-Factor: Dbl, U=0.55	45.00 ft²	SHGC: SHGC=0.50		c. U-Factor: N/A	ft²	SHGC:		d. U-Factor: N/A	ft²	SHGC:		Area Weighted Average Overhang Depth:	0.000 ft.	Area Weighted Average SHGC:	0.500																																																																																									
Description	Area																																																																																																															
a. U-Factor: Sgl, U=0.55	285.00 ft²																																																																																																															
SHGC: SHGC=0.50																																																																																																																
b. U-Factor: Dbl, U=0.55	45.00 ft²																																																																																																															
SHGC: SHGC=0.50																																																																																																																
c. U-Factor: N/A	ft²																																																																																																															
SHGC:																																																																																																																
d. U-Factor: N/A	ft²																																																																																																															
SHGC:																																																																																																																
Area Weighted Average Overhang Depth:	0.000 ft.																																																																																																															
Area Weighted Average SHGC:	0.500																																																																																																															
8. Floor Types (2320.0 sqft.)	<table style="width: 100%;"> <tr> <th style="width: 30%;">Insulation</th> <th style="width: 70%;">Area</th> </tr> <tr> <td>a. Slab-On-Grade Edge Insulation</td> <td>R=0.7 2320.00 ft²</td> </tr> <tr> <td>b. N/A</td> <td>R= ft²</td> </tr> <tr> <td>c. N/A</td> <td>R= ft²</td> </tr> </table>	Insulation	Area	a. Slab-On-Grade Edge Insulation	R=0.7 2320.00 ft²	b. N/A	R= ft²	c. N/A	R= ft²																																																																																																							
Insulation	Area																																																																																																															
a. Slab-On-Grade Edge Insulation	R=0.7 2320.00 ft²																																																																																																															
b. N/A	R= ft²																																																																																																															
c. N/A	R= ft²																																																																																																															
9. Wall Types(1872.0 sqft.)	Insulation	Area																																																																																																														
a. Frame - Wood, Exterior	R=19.0	1872.00 ft²																																																																																																														
b. N/A	R=	ft²																																																																																																														
c. N/A	R=	ft²																																																																																																														
d. N/A	R=	ft²																																																																																																														
10. Ceiling Types (2320.0 sqft.)	Insulation	Area																																																																																																														
a. Cathedral/Single Assembly (Unvented)	R=0.0	2320.00 ft²																																																																																																														
b. N/A	R=	ft²																																																																																																														
c. N/A	R=	ft²																																																																																																														
11. Ducts		R ft²																																																																																																														
a. Sup: Attic, Ret: Attic, AH: Main		6 534																																																																																																														
12. Cooling systems	kBtu/hr	Efficiency																																																																																																														
a. Central Unit	28.3	SEER:16.00																																																																																																														
13. Heating systems	kBtu/hr	Efficiency																																																																																																														
a. Electric Heat Pump	36.5	HSPF:8.70																																																																																																														
14. Hot water systems																																																																																																																
a. Electric		Cap: 50 gallons																																																																																																														
		EF: 0.980																																																																																																														
b. Conservation features																																																																																																																
Heat Recovery Unit																																																																																																																
15. Credits		CF, Pstat																																																																																																														

Glass/Floor Area: 0.142	Total Proposed Modified Loads: 59.13	PASS
	Total Baseline Loads: 62.22	

<p>I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.</p> <p>PREPARED BY: _____</p> <p>DATE: _____</p> <p>I hereby certify that this building, as designed, is in compliance with the Florida Energy Code.</p> <p>OWNER/AGENT: _____</p> <p>DATE: _____</p>	<p>Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.</p> <div style="text-align: center;">  </div> <p>BUILDING OFFICIAL: _____</p> <p>DATE: _____</p>
---	---

- Compliance requires certification by the air handler unit manufacturer that the air handler enclosure qualifies as certified factory-sealed in accordance with R403.3.2.1.
- Compliance requires an Air Barrier and Insulation Inspection Checklist in accordance with R402.4.1.1 and this project requires an envelope leakage test report with envelope leakage no greater than 5.00 ACH50 (R402.4.1.2).

INPUT SUMMARY CHECKLIST REPORT

PROJECT

Title:	Jewett Residence	Bedrooms:	3	Address Type:	Street Address
Building Type:	User	Conditioned Area:	2320	Lot #	
Owner Name:		Total Stories:	1	Block/Subdivision:	
# of Units:	1	Worst Case:	No	PlatBook:	
Builder Name:		Rotate Angle:	0	Street:	
Permit Office:		Cross Ventilation:		County:	Columbia
Jurisdiction:		Whole House Fan:		City, State, Zip:	Lake City , FL , 32055
Family Type:	Single-family				
New/Existing:	New (From Plans)				
Comment:					

CLIMATE

✓	Design Location	TMY Site	Design Temp 97.5 %	2.5 %	Int Design Temp Winter	Summer	Heating Degree Days	Design Moisture	Daily Temp Range
_____	FL, Gainesville	FL_GAINESVILLE_REGI	32	92	70	75	1305.5	51	Medium

BLOCKS

Number	Name	Area	Volume
1	Block1	2320	22040

SPACES

Number	Name	Area	Volume	Kitchen	Occupants	Bedrooms	Infil ID	Finished	Cooled	Heated
1	Main	2320	22040	Yes	4	3	1	Yes	Yes	Yes

FLOORS

✓	#	Floor Type	Space	Perimeter	R-Value	Area		Tile	Wood	Carpet
_____	1	Slab-On-Grade Edge Insulatio	Main	252 ft	0.7	2320 ft²	---	0.2	0.8	0

ROOF

✓	#	Type	Materials	Roof Area	Gable Area	Roof Color	Rad Barr	Solar Absor.	SA Tested	Emitt	Emitt Tested	Deck Insul.	Pitch (deg)
_____	1	Gable or shed	Composition shingles	2595 ft²	580 ft²	Medium	N	0.96	No	0.9	No	30	26.6

ATTIC

✓	#	Type	Ventilation	Vent Ratio (1 in)	Area	RBS	IRCC
_____	1	Full attic	Unvented	0	2320 ft²	N	N

CEILING

✓	#	Ceiling Type	Space	R-Value	Ins Type	Area	Framing Frac	Truss Type
_____	1	Cathedral/Single Assembly	(Unvented Main	0	Blown	2320 ft²	0.11	Wood

INPUT SUMMARY CHECKLIST REPORT

WALLS

✓ #	Ornt	Adjacent To	Wall Type	Space	Cavity R-Value	Width Ft	In	Height Ft	In	Area	Sheathing R-Value	Framing Fraction	Solar Absor.	Below Grade%
1	N	Exterior	Frame - Wood	Main	19	63	6	9		571.5 ft²		0.23	0.75	0
2	E	Exterior	Frame - Wood	Main	19	43	0	9		387.0 ft²		0.23	0.75	0
3	S	Exterior	Frame - Wood	Main	19	63	6	9		571.5 ft²		0.23	0.75	0
4	S	Exterior	Frame - Wood	Main	19	38		9		342.0 ft²		0.23	0.75	0

DOORS

✓ #	Ornt	Door Type	Space	Storms	U-Value	Width Ft	In	Height Ft	In	Area
1	N	Insulated	Main	None	.46	9		8		72 ft²
2	E	Insulated	Main	None	.46	3		8		24 ft²
3	S	Insulated	Main	None	.46	3		8		24 ft²

WINDOWS

Orientation shown is the entered, Proposed orientation.

✓ #	Ornt	Wall ID	Frame	Panels	NFRC	U-Factor	SHGC	Imp	Area	Overhang Depth	Separation	Int Shade	Screening
1	N	1	Vinyl	Low-E Single	Yes	0.55	0.5	N	60.0 ft²	0 ft 0 in	0 ft 0 in	Drapes/blinds	None
2	E	2	Vinyl	Low-E Single	Yes	0.55	0.5	N	45.0 ft²	0 ft 0 in	0 ft 0 in	Drapes/blinds	None
3	S	3	Vinyl	Low-E Single	Yes	0.55	0.5	N	180.0 ft²	0 ft 0 in	0 ft 0 in	Drapes/blinds	None
4	S	4	Metal	Double (Tinted)	Yes	0.55	0.5	N	45.0 ft²	0 ft 0 in	0 ft 0 in	Drapes/blinds	None

INFILTRATION

#	Scope	Method	SLA	CFM 50	ELA	EqLA	ACH	ACH 50
1	Wholehouse	Proposed ACH(50)	.000302	1836.7	100.83	189.63	.1216	5

HEATING SYSTEM

✓ #	System Type	Subtype	Speed	Efficiency	Capacity	Block	Ducts
1	Electric Heat Pump/	Split	Singl	HSPF:8.7	36.47 kBtu/hr	1	sys#1

COOLING SYSTEM

✓ #	System Type	Subtype	Subtype	Efficiency	Capacity	Air Flow	SHR	Block	Ducts
1	Central Unit/	None	Singl	SEER: 16	28.26 kBtu/hr	840 cfm	0.85	1	sys#1

HOT WATER SYSTEM

✓ #	System Type	SubType	Location	EF	Cap	Use	SetPnt	Conservation
1	Electric	None	Main	0.98	50 gal	70 gal	120 deg	Heat Recovery Unit

SOLAR HOT WATER SYSTEM															
✓	FSEC Cert #	Company Name	System Model #		Collector Model #		Collector Area	Storage Volume	FEF						
_____	None	None						ft²							
DUCTS															
✓	#	Location	Supply R-Value	Supply Area	Location	Return Area	Leakage Type		Air Handler	CFM 25 TOT	CFM25 OUT	QN	RLF	HVAC # Heat Cool	
_____	1	Attic	6	534 ft²	Attic	133.5 ft	Default Leakage		Main	(Default)	(Default)			1 1	
TEMPERATURES															
Programable Thermostat: Y					Ceiling Fans:										
Cooling Heating Venting	<input checked="" type="checkbox"/> Jan <input type="checkbox"/> Jan <input type="checkbox"/> Jan	<input checked="" type="checkbox"/> Feb <input type="checkbox"/> Feb <input type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar <input type="checkbox"/> Mar <input type="checkbox"/> Mar	<input type="checkbox"/> Apr <input type="checkbox"/> Apr <input checked="" type="checkbox"/> Apr	<input type="checkbox"/> May <input type="checkbox"/> May <input type="checkbox"/> May	<input checked="" type="checkbox"/> Jun <input type="checkbox"/> Jun <input type="checkbox"/> Jun	<input checked="" type="checkbox"/> Jul <input type="checkbox"/> Jul <input type="checkbox"/> Jul	<input checked="" type="checkbox"/> Aug <input type="checkbox"/> Aug <input type="checkbox"/> Aug	<input checked="" type="checkbox"/> Sep <input type="checkbox"/> Sep <input type="checkbox"/> Sep	<input type="checkbox"/> Oct <input type="checkbox"/> Oct <input checked="" type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov <input type="checkbox"/> Nov <input type="checkbox"/> Nov	<input checked="" type="checkbox"/> Dec <input type="checkbox"/> Dec <input type="checkbox"/> Dec			
Thermostat Schedule: HERS 2006 Reference															
Schedule Type	Hours														
	1	2	3	4	5	6	7	8	9	10	11	12			
Cooling (WD)	AM PM	78 80	78 80	78 78	78 78	78 78	78 78	78 78	78 78	80 78	80 78	80 78	80 78		
Cooling (WEH)	AM PM	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78		
Heating (WD)	AM PM	66 68	66 68	66 68	66 68	66 68	68 68	68 68	68 68	68 68	68 68	68 68	68 66	68 66	
Heating (WEH)	AM PM	66 68	66 68	66 68	66 68	66 68	68 68	68 68	68 68	68 68	68 68	68 66	68 66	68 66	
MASS															
Mass Type	Area		Thickness		Furniture Fraction		Space								
Default(8 lbs/sq.ft.	0 ft²		0 ft		0.3		Main								

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE INDEX* = 95

The lower the Energy Performance Index, the more efficient the home.

1. New home or, addition	1. <u>New (From Plans)</u>	12. Ducts, location & insulation level
2. Single-family or multiple-family	2. <u>Single-family</u>	a) Supply ducts R <u>6.0</u>
3. No. of units (if multiple-family)	3. <u>1</u>	b) Return ducts R <u>6.0</u>
4. Number of bedrooms	4. <u>3</u>	c) AHU location <u>Main</u>
5. Is this a worst case? (yes/no)	5. <u>No</u>	13. Cooling system: Capacity <u>28.3</u>
6. Conditioned floor area (sq. ft.)	6. <u>2320</u>	a) Split system SEER <u> </u>
7. Windows, type and area		b) Single package SEER <u> </u>
a) U-factor:(weighted average)	7a. <u>0.550</u>	c) Ground/water source SEER/COP <u> </u>
b) Solar Heat Gain Coefficient (SHGC)	7b. <u>0.500</u>	d) Room unit/PTAC EER <u> </u>
c) Area	7c. <u>330.0</u>	e) Other <u>16.0</u>
8. Skylights		14. Heating system: Capacity <u>36.5</u>
a) U-factor:(weighted average)	8a. <u>NA</u>	a) Split system heat pump HSPF <u>8.7</u>
b) Solar Heat Gain Coefficient (SHGC)	8b. <u>NA</u>	b) Single package heat pump HSPF <u> </u>
9. Floor type, insulation level:		c) Electric resistance COP <u> </u>
a) Slab-on-grade (R-value)	9a. <u>0.7</u>	d) Gas furnace, natural gas AFUE <u> </u>
b) Wood, raised (R-value)	9b. <u> </u>	e) Gas furnace, LPG AFUE <u> </u>
c) Concrete, raised (R-value)	9c. <u> </u>	f) Other <u> </u>
10. Wall type and insulation:		15. Water heating system
A. Exterior:		a) Electric resistance EF <u>0.98</u>
1. Wood frame (Insulation R-value)	10A1. <u>19.0</u>	b) Gas fired, natural gas EF <u> </u>
2. Masonry (Insulation R-value)	10A2. <u> </u>	c) Gas fired, LPG EF <u> </u>
B. Adjacent:		d) Solar system with tank EF <u> </u>
1. Wood frame (Insulation R-value)	10B1. <u> </u>	e) Dedicated heat pump with tank EF <u> </u>
2. Masonry (Insulation R-value)	10B2. <u> </u>	f) Heat recovery unit HeatRec% <u>1.00</u>
11. Ceiling type and insulation level		g) Other <u> </u>
a) Under attic	11a. <u> </u>	16. HVAC credits claimed (Performance Method)
b) Single assembly	11b. <u>0.0</u>	a) Ceiling fans <u>Yes</u>
c) Knee walls/skylight walls	11c. <u> </u>	b) Cross ventilation <u>No</u>
d) Radiant barrier installed	11d. <u>No</u>	c) Whole house fan <u>No</u>
		d) Multizone cooling credit <u> </u>
		e) Multizone heating credit <u> </u>
		f) Programmable thermostat <u>Yes</u>

*Label required by Section R303.1.3 of the Florida Building Code, Energy Conservation, if not DEFAULT.

I certify that this home has complied with the Florida Building Code, Energy Conservation, through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL display card will be completed based on installed code compliant features.

Builder Signature: _____ Date: _____

Address of New Home: _____ City/FL Zip: Lake City, FL 32055