

Roof Replacement or Repair Application #72833

Thursday, August 21, 2025 2:05 PM



Checklist:

___ Address	___ Application Submitted	
___ Drive/ROW	___ Zoning Review	___ Legal Lot of Record
___ Septic	___ Plans Reviewed	___ Flood Zone
___ Site Use Approved	___ Required Inspections Assigned	___ FDEP Needed
___ Docs Reviewed/Accepted	___ Invoiced	

APPLICANT: Marc Boutilier

PHONE: (407) 216-2782

ADDRESS: 10245 E Colonial dr Orlando, FL 32817

OWNER: ANDERSON WAYNE HAROLD, ANDERSON MARIA GERTRUDE

PHONE: (386) 697-5871

ADDRESS: 130 SW TREY WAY LAKE CITY, FL 32024

PARCEL ID: 03-4S-16-02732-546

SUBDIVISION: DEER CREEK PHASE 3

LOT: 46 BLOCK: PHASE: UNIT: ACRES: 0.50

CONTRACTOR	TYPE	LIC#	BUSINESS NAME
MARC BOUTILIER	General		FLORIDA PREMIER ROOFING

ROOFING JOB DETAILS

Type Roofing Job Replacement - Tear off Existing and Replace

Further Job Details (Explain if decking is being replaced and or Repairs are being done.)

Type of structure House

Further Structure Details (if needed)

Total Estimated Cost 20000

Commercial or Residential Residential

Roof Area (for this job) Sq Ft 23

No. of Stories 1

Ventilation: Ridge Vent

Flashing: Replace All

Drip Edge: Replace All

Valley Treatment: New Metal

Roof Pitch 4:12 or Greater

Second Roof Pitch (if applicable)

Any cable and/or race-way wiring located on or within the roof assembly?

Is the existing roof being removed? Yes

Explain if not removing the existing roofing material?

Type of New Roofing Product Asphalt Shingles

Florida Product Approval Number FL18355-R5

Product Manufacturer Tamko

Product Description Asphalt Shingles

Other Roofing Product Type Not Listed

Sealed roof decking options: (Must select an option.)

a self-adhering polymer-modified bitumen underlayment complying with ASTM D1970 applied over the entire roof.;a minimum 4-inch wide strip of selfadhering polymer-modified bitumen complying with ASTM D1970 or a minimum 3 ¼ - inch wide strip of selfadhering flexible flashing tape complying with AAMA 711, applied over all joints in the roof decking. A felt underlayment complying with ASTM D226 Type II, ASTM D4869 Type III or IV, or ASTM D6757, or a synthetic underlayment meeting the performance requirements specified, is required to be applied over the strips/tape over the entire roof.;two layers of felt underlayment comply ASTM 0226 Type II or ASTM D4869 Type III or IV, or two layers of a synthetic underlayment meeting the performance requirements specified, lapped and fastened as specified.;Other (explain)

Sealed roof decking explanation for other option.

Review Notes: