



POOL WILL SERVE 114 TRANSIENT CAMPSITES

INSTALL A 15 MIN. PATRON OPERATED TIMER ON THE THERAPY PUMP CIRCUIT

SHOWER, MAX. 20' FROM POOL/SPA

INSTALLATION OF DECK PAVER SYSTEM

1. A STABLE FOUNDATION IS CAREFULLY PREPARED PRIOR TO INSTALLATION OF THE PAVER DECK SYSTEM.

2. THE PAVERS ARE CONSTRUCTED OF A SMOOTH AND SLIP-RESISTANT MASONRY TYPE MATERIAL.

3. VOIDS BETWEEN THE PAVER DECK SYSTEM AND STRUCTURES SUCH AS COPING STONES, LADDERS, HAND RAILS AND OTHER DECK EQUIPMENT ARE FILLED WITH EPOXY OR MORTAR TYPE MATERIAL.

4. VOIDS BETWEEN PAVERS ARE NOT GREATER THAN 1/8" AND PAVERS ARE INSTALLED IN ACCORDANCE WITH MANUFACTURER SPECIFICATIONS.

5. EDGE RESTRAINS ARE INSTALLED AROUND ALL EDGES OF THE PAVER DECK SYSTEM.

6. NO SHARP EDGES ARE PROTRUDING.

7. MIN. SLOPE REQUIREMENTS ARE MET.

SPA NOTE

A CLEARLY LABELED EMERGENCY SHUT-OFF OR CONTROL SWITCH FOR THE SPA MOTORES THAT CONTROL THE RECIRCULATION PUMP AND THE JET PUMP SHALL BE INSTALLED READILY ACCESSIBLE TO THE USERS AND AT LEAST 5 FEET AWAY, ADJACENT TO, AND WITHIN SIGHT OF THE SPA PER NEC 680-41.

PROVISIONS SHALL BE MADE TO INSTALL A MIN. 80 DECIBEL AUDIBLE ALARM NEAR THE SPA TO SOUND CONTINUOUSLY UNTIL DEACTIVATED. THIS IS TO ALERT POOL PATRONS THAT THE SPA FILTRATION AND TREATMENT SYSTEM MAY BE OFF. THE FOLLOWING ADDITIONAL RULE SIGN SHALL BE VISIBLE BY THE SPA WHICH READS: "ALARM INDICATES SPA PUMPS OFF. DO NOT USE SPA WHEN ALARM SOUNDS UNTIL ADVISED OTHERWISE."

SURFACE MATERIALS:

*POOL DECKS: PAVERS ON SAND

*WALKWAY TO THE POOL RESTROOMS (FIRST 15') CONCRETE

*POOL RESTROOM FLOORS: UNGLAZED TILE (SLIP-RESISTANT AND IMPERVIOUS)

NOTES:

1. REFER TO THE NOTES ON SHEET NO. 4 & 5

2. POOL EQUIPMENT ROOM FLOOR SHALL BE SLIP-RESISTANT AND IMPERVIOUS AND SHALL SLOPE UNIFORMLY AND POSITIVELY TO FLOOR DRAIN OR DOOR.

3. TOILET FACILITIES FLOORS SHALL SLOPE UNIFORMLY AND POSITIVELY TO FLOOR DRAIN AND SHALL BE SLIP-RESISTANT AND IMPERVIOUS. THE INTERSECTION BETWEEN WALLS AND FLOORS MUST BE COVERED.

4. PROVISIONS SHALL BE MADE FOR THE SAFE STORAGE OF CHEMICALS.

5. FOOD AND FACILITIES SHALL BE NO CLOSER THAN 12 FEET FROM WATER'S EDGE.

6. THE FIRST 15 FEET OF THE WALKWAY TO THE TOILETS SHALL BE IMPERVIOUS AND SLIP RESISTANT AND POSITIVELY SLOPED FOR DRAINAGE.

7. TILE ON THE DECK INCLUDING COPING, OPEN GUTTERS, POOL, TOILET FLOORS AND ANY OTHER HORIZONTAL SURFACE SHALL BE SLIP RESISTANT AND UNGLAZED.

8. ALL PIPING SHALL BE PVC SCH. 40 MINIMUM UNLESS OTHERWISE SPECIFIED.

9. POST A SIGN WITH 1" MIN. LETTERS VISIBLE FROM ALL PARTS OF THE POOL DECK WITH DIRECTIONS TO THE POOL TOILETS.

10. THIS DRAWING IS FOR THE PURPOSE OF OBTAINING A POOL/SPA BUILDING PERMIT AND FOR OBTAINING AN OPERATING PERMIT FROM THE LOCAL HEALTH DEPARTMENT. DECKS, FENCES AND OTHER STRUCTURES, ETC. ARE NOT A PART OF THIS DESIGN BUT MUST MEET ALL THE REQUIREMENTS AS SET FORTH IN THE PUBLIC HEALTH ADMINISTRATIVE CODE AND ALL OTHER LOCAL BUILDING CODES.

11. DO NOT SCALE THIS DRAWING FOR DIMENSIONS NOT SHOWN. FOR EXACT DIMENSIONS RELATIVE TO DECKS, BUILDINGS, PROPERTY LINES, EASEMENTS, ETC., SEE THE SURVEY, ARCHITECT'S PLANS AND OTHER PERTINENT DOCUMENTS.

12. IF HIGH FENCE IS REQUIRED SEE NOTES ON SHEET #6.

POOL RULES SIGN

THE FOLLOWING RULES WILL BE POSTED AT OR NEAR POOLSIDE AND WILL BE LEGIBLE FROM THE POOL DECK. THE LETTERS SHALL BE A MIN. OF 1".

NO FOOD OR BEVERAGES IN POOL OR ON POOL WET DECK.

NO GLASS OR ANIMALS IN THE FENCED POOL AREA.

DO NOT SWALLOW THE POOL WATER.

DAYLIGHT USE ONLY.

BATHING LOAD **30** PERSONS.

POOL HOURS a.m. to p.m.

SHOWER BEFORE ENTERING POOL.

(MINIMUM 4" LETTERS)

NO DIVING

SPA RULES SIGN

THE FOLLOWING RULES WILL BE POSTED AT OR NEAR SPA SIDE AND WILL BE LEGIBLE FROM THE DECK. THE LETTERS SHALL BE A MIN. OF 1". PROVIDE CLOCK VISIBLE FROM SPA.

NO FOOD, DRINK OR GLASS IN SPA OR ON DECK.

SHOWER BEFORE ENTERING SPA.

BATHING LOAD **12** PERSONS.

MAXIMUM TEMPERATURE 104 DEG. F.

MAXIMUM TIME USE 15 MIN.

CHILDREN UNDER 12 MUST HAVE ADULT SUPERVISION.

PREGNANT WOMEN, SMALL CHILDREN, PEOPLE WITH HEALTH PROBLEMS AND PEOPLE USING ALCOHOL, NARCOTICS OR OTHER DRUGS THAT CAUSE DROWSINESS SHOULD NOT USE SPA WITHOUT FIRST CONSULTING A DOCTOR.

(MINIMUM 4" LETTERS)

POOL WET DECK LIGHTING PROVIDES FOR USE DURING DAYLIGHT HOURS ONLY. FOR NIGHT TIME USE, PLANS MUST BE SUBMITTED TO THE COUNTY HEALTH DEPARTMENT WITH REQUIREMENTS PER CHAPTER 64E-9, FAC AND F.B.C. FOR NIGHT SWIMMING.

A MIN. OF 7'-0" VERTICAL CLEARANCE MUST BE MAINTAINED ABOVE THE POOL/SPA/WP COPING, DECK AND WATER SURFACE.

POOLDESIGN.NET
1000 EAST ATLANTIC BLVD.
SUITE 100
POMPANO BEACH FLA 33060
(954) 941-1124
info@swimmingpoolplan.com
CERTIFICATE OF AUTHORIZATION N. 9871

REVISIONS

SUWANNEE VALLEY RESORT

AQUATAN POOLS OF FLORIDA INC.

CRAIG PERKINS
561 248 0299

TITLE

SUWANNEE VALLEY RESORT

DESCRIPTION

786 NW STEVEN FOSTER DRIVE
WHITE SPRINGS, FL. 32096

Scale: 1/8" = 1'-0"

PAGE 2 OF 6

DATE 2/4/2012