



FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name 140207 Street 3643 SW Pinemount City, State, Zip Lake City , FL , Owner Carpenter Design Location FL, Gainesville		Builder Name Affinity Conctruction Permit Office Permit Number Jurisdiction					
1 New construction or existing 2 Single family or multiple family 3 Number of units, if multiple family 4 Number of Bedrooms(Bedrms In Addition) 5 Is this a worst case? 6 Conditioned floor area above grade (ft ²) Conditioned floor area below grade (ft ²) 7 Windows(30 0 sqft) a U-Factor Dbl, U=0 35 SHGC SHGC=0 35 b U-Factor N/A SHGC c U-Factor N/A SHGC d U-Factor N/A SHGC Area Weighted Average Overhang Depth Area Weighted Average SHGC 8 Floor Types (432 0 sqft) a Raised Floor b N/A c N/A		Addition Single-family 1 0(0) No 432 0 Description Area 30 00 ft ² ft ² ft ² ft ² 1 000 ft 0 350 Insulation Area R=0 0 432 00 ft ² ft ² ft ²		9 Wall Types (472 0 sqft) a Frame - Wood, Exterior b N/A c N/A d N/A 10 Ceiling Types (432 0 sqft) a Under Attic (Vented) b N/A c N/A 11 Ducts 12 Cooling systems a Central Unit 13 Heating systems a Electric Heat Pump 14 Hot water systems - None required a b Conservation features 15 Credits		Insulation	Area
				R=13 0	472 00 ft ²		
				R=	ft ²		
				R=	ft ²		
				R=	ft ²		
				R=30 0	432 00 ft ²		
				R=	ft ²		
				R=	ft ²		
				R	ft ²		
				kBtu/hr	Efficiency		
				6 0	SEER 13 00		
				kBtu/hr	Efficiency		
				9 7	HSPF 7 70		
				Cap N/A			
				EF 0 000			
				None			
Glass/Floor Area 0 069		Total Proposed Modified Loads. 9.42 Total Standard Reference Loads 12 67		PASS			
I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.		Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.					
PREPARED BY <u>BLA2 Breamsby</u> DATE: <u>2014-05-19</u>		BUILDING OFFICIAL: _____ DATE: _____					
I hereby certify that this building, as designed, is in compliance with the Florida Energy Code							
OWNER/AGENT: _____ DATE: _____							

- Compliance requires completion of a Florida Air Barrier and Insulation Inspection Checklist



PROJECT

Title	140207	Bedrooms	0	Address Type	Street Address
Building Type	User	Conditioned Area	432	Lot #	
Owner	Carpenter	Total Stories	1	Block/SubDivision	
# of Units	1	Worst Case	No	PlatBook	
Builder Name	Affinity Construction	Rotate Angle	0	Street	3643 SW Pinemount
Permit Office		Cross Ventilation		County	Columbia
Jurisdiction		Whole House Fan.		City, State, Zip	Lake City, FL,
Family Type	Single-family				
New/Existing	Addition				
Comment					

CLIMATE

✓	Design Location	TMY Site	IECC Zone	Design Temp		Int Design Temp		Heating Degree Days	Design Moisture	Daily Temp Range
				97.5 %	2.5 %	Winter	Summer			
	FL, Gainesville	FL_GAINESVILLE_REGI	2	32	92	70	75	1305.5	51	Medium

BLOCKS

Number	Name	Area	Volume
1	Block1	432	3456

SPACES

Number	Name	Area	Volume	Kitchen	Occupants	Bedrooms	Infill ID	Finished	Cooled	Heated
1	Main	432	3456	No	2	0	1	Yes	Yes	Yes

FLOORS

✓	#	Floor Type	Space	R-Value		Area	0	0	1	1
				Main	---					
	1	Raised Floor		---	---	432 ft ²				

ROOF

✓	#	Type	Materials	Roof Area	Gable Area	Roof Color	Solar Absor	SA Tested	Emiss		Deck Insul	Pitch (deg)
									Tested	Tested		
	1	Gable or shed	Composition shingles	445 ft ²	54 ft ²	Dark	0.96	No	0.9	No	0	14

ATTIC

✓	#	Type	Ventilation	Vent Ratio (1 in)		Area	RBS	IRCC
				Main	Ventilated			
	1	Full attic	Ventilated	300		432 ft ²	N	N

CEILING

✓	#	Ceiling Type	Space	R-Value		Area	Framing Frac	Truss Type
				Main	30			
	1	Under Attic (Vented)				432 ft ²	0.11	Wood

WALLS

✓ #	Ornt	Adjacent To	Wall Type	Space	Cavity R-Value	Width Ft	Width In	Height Ft	Height In	Area	Sheathing R-Value	Framing Fraction	Solar Absor.	Below Grade%
1	E	Exterior	Frame - Wood	Main	13	16	8	128	0 ft ²		0 23	0 75	0 75	0
2	S	Exterior	Frame - Wood	Main	13	27	8	216	0 ft ²		0 23	0 75	0 75	0
3	W	Exterior	Frame - Wood	Main	13	16	8	128	0 ft ²		0 23	0 75	0 75	0

DOORS

✓ #	Ornt	Door Type	Space	Storms	U-Value	Width Ft	Width In	Height Ft	Height In	Area
1	E	Insulated	Main	None	46	3		6	8	20 ft ²

WINDOWS

Orientation shown is the entered, Proposed orientation

✓ #	Ornt	Wall ID	Frame	Panes	NFRC	U-Factor	SHGC	Area	Overhang Depth	Separation	Int Shade	Screening
1	S	2	Metal	Low-E Double	Yes	0 35	0 35	30 0 ft ²	1 ft 0 in	4 ft 0 in	None	None

INFILTRATION

#	Scope	Method	SLA	CFM 50	ELA	EqLA	ACH	ACH 50
1	Wholehouse	Best Guess	0003	339 9	18 66	35 1	231	5 9018

HEATING SYSTEM

✓ #	System Type	Subtype	Efficiency	Capacity	Block	Ducts
1	Electric Heat Pump	None	HSPF 7 7	9 7 kBtu/hr	1	Ductless

COOLING SYSTEM

✓ #	System Type	Subtype	Efficiency	Capacity	Air Flow	SHR	Block	Ducts
1	Central Unit	None	SEER. 13 6 04	kBtu/hr	180 cfm	0 75	1	Ductless

SOLAR HOT WATER SYSTEM

✓ FSEC	Cert #	Company Name	System Model #	Collector Model #	Collector Area	Storage Volume	FEF
					ft ²		

TEMPERATURES																								
Programable Thermostat			None		Ceiling Fans																			
Cooling	<input type="checkbox"/>	Jan	<input type="checkbox"/>	Feb	<input type="checkbox"/>	Mar	<input type="checkbox"/>	Apr	<input type="checkbox"/>	May	<input checked="" type="checkbox"/>	Jun	<input type="checkbox"/>	Jul	<input type="checkbox"/>	Aug	<input type="checkbox"/>	Sep	<input type="checkbox"/>	Oct	<input type="checkbox"/>	Nov	<input type="checkbox"/>	Dec
Heating	<input checked="" type="checkbox"/>	Jan	<input checked="" type="checkbox"/>	Feb	<input checked="" type="checkbox"/>	Mar	<input checked="" type="checkbox"/>	Apr	<input checked="" type="checkbox"/>	May	<input checked="" type="checkbox"/>	Jun	<input checked="" type="checkbox"/>	Jul	<input checked="" type="checkbox"/>	Aug	<input checked="" type="checkbox"/>	Sep	<input checked="" type="checkbox"/>	Oct	<input checked="" type="checkbox"/>	Nov	<input checked="" type="checkbox"/>	Dec
Venting	<input type="checkbox"/>	Jan	<input type="checkbox"/>	Feb	<input type="checkbox"/>	Mar	<input type="checkbox"/>	Apr	<input type="checkbox"/>	May	<input type="checkbox"/>	Jun	<input type="checkbox"/>	Jul	<input type="checkbox"/>	Aug	<input type="checkbox"/>	Sep	<input type="checkbox"/>	Oct	<input type="checkbox"/>	Nov	<input type="checkbox"/>	Dec
Thermostat Schedule	HERS 2006 Reference												Hours											
Schedule Type	1	2	3	4	5	6	7	8	9	10	11	12	1	2	3	4	5	6	7	8	9	10	11	12
Cooling (WD)	AM PM	78 78	78 78																					
Cooling (WEH)	AM PM	78 78	78 78																					
Heating (WD)	AM PM	68 68	68 68																					
Heating (WEH)	AM PM	68 68	68 68																					

Florida Code Compliance Checklist

Florida Department of Business and Professional Regulations
Residential Whole Building Performance Method

ADDRESS: 3643 SW Pinemount
Lake City, FL,

PERMIT #:

MANDATORY REQUIREMENTS SUMMARY - See individual code sections for full details.

COMPONENT	SECTION	SUMMARY OF REQUIREMENT(S)	CHECK
Air leakage	402 4	To be caulked, gasketed, weatherstripped or otherwise sealed. Recessed lighting IC-rated as meeting ASTM E 283. Windows and doors = 0 30 cfm/sq ft. Testing or visual inspection required. Fireplaces: gasketed doors & outdoor combustion air. Must complete envelope leakage report or visually verify Table 402.4.2.	
Thermostat & controls	403 1	At least one thermostat shall be provided for each separate heating and cooling system. Where forced-air furnace is primary system, programmable thermostat is required. Heat pumps with supplemental electric heat must prevent supplemental heat when compressor can meet the load.	
Ducts	403 2 2	All ducts, air handlers, filter boxes and building cavities which form the primary air containment passageways for air distribution systems shall be considered ducts or plenum chambers, shall be constructed and sealed in accordance with Section 503.2 7 2 of this code	
	403 3 3	Building framing cavities shall not be used as supply ducts.	
Water heaters	403 4	Heat trap required for vertical pipe risers. Comply with efficiencies in Table 403 4 3 2. Provide switch or clearly marked circuit breaker (electric) or shutoff (gas). Circulating system pipes insulated to = R-2 + accessible manual OFF switch	
Mechanical ventilation	403 5	Homes designed to operate at positive pressure or with mechanical ventilation systems shall not exceed the minimum ASHRAE 62 level. No make-up air from attics, crawlspaces, garages or outdoors adjacent to pools or spas.	
Swimming Pools & Spas	403 9	Pool pumps and pool pump motors with a total horsepower (HP) of = 1 HP shall have the capability of operating at two or more speeds. Spas and heated pools must have vapor-retardant covers or a liquid cover or other means proven to reduce heat loss except if 70% of heat from site-recovered energy. Off/timer switch required. Gas heaters minimum thermal efficiency=78% (82% after 4/16/13). Heat pump pool heaters minimum COP= 4 0	
Cooling/heating equipment	403 6	Sizing calculation performed & attached. Minimum efficiencies per Tables 503 2 3. Equipment efficiency verification required. Special occasion cooling or heating capacity requires separate system or variable capacity system. Electric heat >10kW must be divided into two or more stages.	
Ceilings/knee walls	405 2 1	R-19 space permitting	

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE INDEX* = 74

The lower the Energy Performance Index, the more efficient the home


3643 SW Pinemount, Lake City, FL,

1 New construction or existing	Addition		9 Wall Types	Insulation	Area
2 Single family or multiple family	Single-family		a Frame - Wood, Exterior	R=13 0	472 00 ft ²
3 Number of units, if multiple family	1		b N/A	R=	ft ²
4 Number of Bedrooms	0(0)		c N/A	R=	ft ²
5 Is this a worst case?	No		d N/A	R=	ft ²
6 Conditioned floor area (ft ²)	432		10 Ceiling Types	Insulation	Area
7 Windows**	Description	Area	a Under Attic (Vented)	R=30 0	432 00 ft ²
a U-Factor	Dbl, U=0 35	30 00 ft ²	b N/A	R=	ft ²
SHGC	SHGC=0 35		c N/A	R=	ft ²
b U-Factor	N/A	ft ²	11 Ducts	R	ft ²
SHGC			12 Cooling systems	kBtu/hr	Efficiency
c U-Factor	N/A	ft ²	a Central Unit	6 0	SEER 13 00
SHGC			13 Heating systems	kBtu/hr	Efficiency
d U-Factor	N/A	ft ²	a Electric Heat Pump	9 7	HSPF 7 70
Area Weighted Average Overhang Depth		1 000 ft	14 Hot water systems - None required		
Area Weighted Average SHGC		0 350	a		
8 Floor Types	Insulation	Area	b Conservation features		
a Raised Floor	R=0 0	432 00 ft ²			
b N/A	R=	ft ²			
c N/A	R=	ft ²	15 Credits		None

I certify that this home has complied with the Florida Energy Efficiency Code for Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature: _____ Date: _____

Address of New Home: _____ City/FL Zip: _____



*Note This is not a Building Energy Rating. If your Index is below 70, your home may qualify for energy efficient mortgage (EEM) incentives if you obtain a Florida EnergyGauge Rating. Contact the EnergyGauge Hotline at (321) 638-1492 or see the EnergyGauge web site at energygauge.com for information and a list of certified Raters. For information about the Florida Building Code, Energy Conservation, contact the Florida Building Commission's support staff

**Label required by Section 303 1 3 of the Florida Building Code, Energy Conservation, if not DEFAULT.

Residential System Sizing Calculation

Summary

Carpenter
3643 SW Pinemount
Lake City, FL

Project Title:
140207


5/19/2014

Location for weather data Gainesville, FL - Defaults: Latitude(29 7) Altitude(152 ft) Temp Range(M)			
Humidity data Interior RH (50%) Outdoor wet bulb (77F) Humidity difference(54gr)			
Winter design temperature(MJ8 99%)	33 F	Summer design temperature(MJ8 99%)	92 F
Winter setpoint	70 F	Summer setpoint	75 F
Winter temperature difference	37 F	Summer temperature difference	17 F
Total heating load calculation	9634 Btuh	Total cooling load calculation	6123 Btuh
Submitted heating capacity	% of calc Btuh	Submitted cooling capacity	% of calc Btuh
Total (Electric Heat Pump)	100 7 9700	Sensible (SHR = 0.75)	88.2 4531
Heat Pump + Auxiliary(0.0kW)	100 7 9700	Latent	153.6 1510
		Total (Electric Heat Pump)	98 7 6042

WINTER CALCULATIONS

Winter Heating Load (for 432 sqft)


Load component	Load		
Window total	30	sqft	389 Btuh
Wall total	422	sqft	1386 Btuh
Door total	20	sqft	340 Btuh
Ceiling total	432	sqft	509 Btuh
Floor total	432	sqft	6148 Btuh
Infiltration	21	cfm	862 Btuh
Duct loss			0 Btuh
Subtotal			9634 Btuh
Ventilation	0	cfm	0 Btuh
TOTAL HEAT LOSS			9634 Btuh



SUMMER CALCULATIONS

Summer Cooling Load (for 432 sqft)

Load component	Load		
Window total	30	sqft	536 Btuh
Wall total	422	sqft	880 Btuh
Door total	20	sqft	258 Btuh
Ceiling total	432	sqft	715 Btuh
Floor total			1994 Btuh
Infiltration	16	cfm	297 Btuh
Internal gain			460 Btuh
Duct gain			0 Btuh
Sens Ventilation	0	cfm	0 Btuh
Blower Load			0 Btuh
Total sensible gain			5140 Btuh
Latent gain(ducts)			0 Btuh
Latent gain(infiltration)			584 Btuh
Latent gain(ventilation)			0 Btuh
Latent gain(internal/occupants/other)			400 Btuh
Total latent gain			984 Btuh
TOTAL HEAT GAIN			6123 Btuh



8th Edition

EnergyGauge® System Sizing
PREPARED BY EVAN B. SMITH
DATE 2014-05-19