Parcel:

13-7S-16-04207-000

Owner & Property Info

Result: 1 of 2

HUSCUSSON WANDA G

Owner

POBOX27

FORT WHITE, FL 320380027

Site

129 MAJESTIC LN, FORT WHITE

Description* SW1/4 OF SW1/4 OF SE1/4. 734-975, 756-868, 774-345, 802-963, 814-953, LE 1403-492,

Area

10.04 AC

S/T/R

13-7S-16

Use Code** SINGLE FAM (000100)

Tax District 3

MOBILE HOME INSTALLATION SUBCONTRACTOR VERIFICATION FORM

APPIRATIONING	MBER	CONTRA	ACTOR _Richard Ray	DOLU SHOWE	352-257-1282
		THIS FORM MUST BE SUBMITTE	ED PRIOR TO THE ISSUANCE		cusson
records of the Ordinance 89-	subcontractor 6, a contractor	mit will cover all trades doing is who actually did the trade is shall require all subcontrac insurance and a valid Certific	specific work under to tors to provide evider	he permit. Per Florida Str ice of workers' compens	atute 440 and ation or
(a) (a) (b) (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c		contractor is responsible fo			
(a) (a) (b) (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c		contractor is responsible fo beginning any work. Violatio			
start of that su	Print Name	peginning any work. Violatio	ons will result in stop	work orders and for fing	
start of that su	Print Name	Melvin Lopez	SignaturePhone #:	work orders and for fing	
start of that su	Print Name	Melvin Lopez EC 13005725	SignaturePhone #:	work orders and for fing	
start of that su	Print Name License #: Print Name	Melvin Lopez EC 13005725 Qualifier Form	Signature Phone #:	352-414-7599	

Qualifier Forms cannot be submitted for any Specialty License.

Specialty License	License Number	Sub-Contractors Printed Name	Sub-Contractors Signature
MASON			
CONCRETE FINISHER			

F. S. 440.103 Building permits; identification of minimum premium policy.--Every employer shall, as a condition to applying for and receiving a building permit, show proof and certify to the permit issuer that it has secured compensation for its employees under this chapter as provided in ss. 440.10 and 440.38, and shall be presented each time the employer applies for a building permit.

Revised 10/30/2015

DERNIT NIMBIR

		arrange wall piets within 2' of end of home polytals 15C	Southern Sex blocking		Typical pier spacing - Lateral Show locations of Longitudinal and Lateral Systems (use dark lines to show these locations)	I understand Lateral Arm Systems cannot be used on any home (new or used) where the sidewall ties exceed 5 ft 4 in. Installer's initials	Manufacturer) 2 () 5 () Length x width 2 () X (129 SU 129 SU	
within 2' of and of home spaced at 5' 4" oc spaced at 5' 4" oc Longitudinal Stabilizing Device (LSD) Manufacturer Manufacturer	Pier pad size	20 × 20 1/16 × 25 1/12 × 25 24 × 24 26 × 26	Perimeter pier pad size 16 × 16 286 16 × 18 288 288 288 288 286 288 288 288 288 28	8' 8' 8' 8' 8' 8' 8' 8' 8' 8' 8' 8' 8'	256) 1/2" (342) (400) (484)" (576)" 3' 4' 5' 6' 7' 5' 8' 8' 8' 8' 8' 8'	Load Fcoter 15" 18 12" x 18 20" x 20" 22" x 20" 24" x 24" 25" x 26"	Installation De Serial #	ed to the Manufacturer's installation accordance with Rule Wind Zone II	

Site Preparation

Note: A state approved lateral arm system is being used and 4 ft anchors are allowed at the sidewall locations. I understand 5 ft anchors are required at all centerly the points where the torque test reading is 275 or less and where the mobile home manufacturer may require anchors with 4000 lbh olding capacity. ALL TESTS MUST BE PERFORMED BY A LICENSED INSTALLER Installer Name Solution State All Services and	TORQUE PROBE TEST The results of the torque probe test is Langued in the pounds or check here if you are declaring 5' anchors without testing Language A test showing 275 inch pounds or less will require 5 foot anchors.	3. Using 500 lb. increments, take the lowest reading and round down to that increment × (SC) × (SC) × (SC)	POCKET PENETROMETER TESTING METHOD 1. Test the perimeter of the home at 6 locations. 2. Take the reading at the depth of the footer.	3/x	The packet penetrometer tests are rounded down to $\sqrt{S^{C^3}}$ psf or check here to declare 1000 lb. soil without testing
Weatherproofing The bottomboard will be repaired and/or taped. Yes. Siding on units is installed to manufacturer's specifications. Yes. Fireplace chimney installed so as not to allow intrusion of rain water. Yes. Miscellaneous Skirting to be installed. Yes. Oryer vent installed outside of skirting. Yes. NA Range downflow vant installed outside of skirting. Yes. Drain lines supported at 4 foot intervals. Yes. Electrical crossovers protected. Yes	Type gasket Installed Installed Between Floors Yes Between Walls Yes Bottom of ridgeteam Yes	I understand a properly installed gasket is a requirement of all new and used homes and that condensation, mold, meldew and buckled marriage walls are a result of a poorly installed or no gasket being-installed. I understand a strip of tape will not serve as a gasket.	Type Fastener Type Fastener Type Fastener For used homes will be centered of roofing nails at 2"	Fastening mult wide units	Debnis and organic material removed (CES) Water drainage: Natural Swale Pad Other

11/1	manufacturer's installation instructions and or R	is accurate and true based on the	Installer verifies all information given with this permit worksheet	
	offictions and or Rule 15C-1 & 2	d on the	this permit worksheet	The second secon

Installer Signature

independent water supply systems. Pg.

Connect all potable water supply piping to an existing water meter, water tap, or other

Connect all sewer drains to an existing sewer tap or septic tank. Pg

Plumbing

source. This includes the bonding wire between mult-wide units.

Pg


electrical conductors between multi-wide units, but not to the main power


Electrical

Other

Yes

Connec





STATE OF FLORIDA DEPARTMENT OF HEALTH

APPLICATION FOR ONSITE SEWAGE DISPOSAL SYSTEM CONSTRUCTION PERMIT

Permit Application Number

HUSCUSSON	PART II - SITEPLAN	210
Scale: 1 inch = 40 feet.		7
	85 SLOPE >>	
210		EASTING
	36 36 8" SPECT ON REAL TIME REXISTING	143'
Notes:		
100	10.04 ACRES SER ATTAC	hr I
Site Plan submitted by:		CONTRACTOR
Plan Approved	Not Approved	Date
Ву		County Health Department

ALL CHANGES MUST BE APPROVED BY THE COUNTY HEALTH DEPARTMENT





STATE OF FLORIDA DEPARTMENT OF HEALTH ONSITE SEWAGE TREATMENT AND DISPOSAL SYSTEM

PERMIT NO. 20 No 83
DATE PAID: 82 20 00
FEE PAID: 45535/8

APPLICATION FOR CONSTRUCTION PERMIT

APPLICATION FOR: [] New System [/] [] Repair []	Existing System Abandonment	1] Holding Tank] Temporary	[] Innovative
APPLICANT: Wanda Huscusson				
AGENT: Dale Burd Dale Burd LLC			TELI	EPHONE: 386-365-7674
MAILING ADDRESS: 20619 County				
TO BE COMPLETED BY APPLICAN BY A PERSON LICENSED PURSUA APPLICANT'S RESPONSIBILITY PLATTED (MM/DD/YY) IF REQUE PROPERTY INFORMATION	T OR APPLICANT'S NT TO 489.105(3) TO PROVIDE DOCUM STING CONSIDERAT	(m) OR 4 (ENTATION CION OF S	ZED AGENT. SYSTE 89.552, FLORIDA S OF THE DATE THE PATUTORY GRANDFAT	EMS MUST BE CONSTRUCTED STATUTES. IT IS THE LOT WAS CREATED OR THER PROVISIONS
LOT: NA BLOCK: NA	SUBDIVISION: N	A		PLATTED: NA
PROPERTY ID #: 13-7S-16-04207-				
PROPERTY SIZE: 10.04 ACRES IS SEWER AVAILABLE AS PER 3 PROPERTY ADDRESS: 129 Majestic DIRECTIONS TO PROPERTY: SR	81.0065, FS? [N Lane, Fort White, FL, 3	No 1 32038	DISTANC	CE TO SEWER: na FT
BUILDING INFORMATION	[✓] RESIDENT	IAL	[] COMMERCIA	L
Unit Type of No Establishment	No. of Bui	lding C	ommercial/Institu	utional System Design 64E-6, FAC
SF Residential			BR to 2 BR Like for Lik	
3				
4				
[] Floor/Equipment Drains	[] Other (Specify)		
SIGNATURE:			D.A	ATE: 8 21 2020

STATE OF FLORIDA DEPARTMENT OF HEALTH

SIGNETHEPLAN

Permit Application Number

APPLICATION FOR ONSITE SEWAGE DISPOSAL SYSTEM CONSTRUCTION PERMIT

HUSKU-"ON	PART II - SITEPLAN	·
Scale: 1 inch = 40 feet.		.711
	35	
1	5100 min	
316		EXITAL
	40 252	
	1950	
	15 St.	142
	1/ [460]	
	EXECUTIVE WESTERN	
Notes:		
1 1	10.04 April	
	SEE FORD	/ue
Site Plan submitted by		CONTRACTOR
Plan Approved	Not Approved	Date 8/24/70
By	Columbia CHD	County Health Departmen

DH 4015, 08/09 (Obsoletes previous editions which may not be used) Incorporated: 64E-6 001 FAC (Stock Number: 5744-002-4015-6)