

**Columbia County Building Department
Culvert Permit**

**Culvert Permit No.
000002482**

DATE 10/03/2017 PARCEL ID # 03-4S-17-02732-203

APPLICANT MARK BAUER PHONE 352.283.2002

ADDRESS 20267 NW 248TH WAY HIGH SPRINGS FL 32643

OWNER MILLENNIA CAPITAL, INC. PHONE 386.438.4442

ADDRESS 269 SW BIRCH GLN LAKE CITY FL 32024

CONTRACTOR MARK BAUER PHONE 352.283.2002

LOCATION OF PROPERTY 90-W TO C-252-B, TL TO DEPUTY J. DAVIS, TR TO RED MAPLE
TO BIRCH, TL AND ITS @ END OF CUL-DE-SAC.

SUBDIVISION/LOT/BLOCK/PHASE/UNIT LAUREL LAKE 7 2

INSTALLATION INFORMATION

SIGNATURE

- (A) A culvert shall be required to be installed as part of any newly constructed private driveway or road, or public road, which connects to a county road in Columbia County. Culvert installation for residential use shall require a permit issued by the Building and Zoning Department. Prior to any culvert permit being issued, an inspection by the Public Works Department shall be required to determine the proper size, length, and location for installation. Culvert installation for commercial, industrial, and other uses shall conform to the approved site plan or to the specifications of a registered engineer. Joint use culverts will comply with Florida Department of Transportation specifications.
- (B) The culvert shall comply and be installed in accordance with Columbia County Land Development Regulation, Access Control: Section 4.2.3 standards. Proper installation of the culvert shall be verified by a final inspection performed by the Public Works Department.
- (C) All culverts required by this policy shall be installed prior to the Building Department granting permission to connect permanent electrical service to the facility or facilities being serviced by newly constructed private driveway or road. In cases where no electrical service exists, installation shall be completed prior to final inspection approval.
- (D) Mitered-end culverts shall be used in the following applications:
(1) When the culvert is to be placed giving access to a paved street.; (2) When the road is contained within a subdivision (recorded or unrecorded) that has not reached a "build out" of fifty percent (50%) or more.; (3) In all new subdivisions for residential use. New subdivisions shall be required as part of the final plat to specify culvert diameter and length.; (4) When the predominant use already established by the use of mitered-end culverts period.

☐

Culvert installation shall conform to the approved site plan standards.

☐

Department of Transportation Permit installation approved standards.

☒

Shall conform to Public Works Determinations as Stated Below:

INSTALL MIN 24" X 18" CORR METAL CULVERT, W/ CONCRETE MITERED ENDS.
W/ 6" X 6" WELDED WIRE, REBAR OR CULVERT BOLTS.

P W Inspectors Name: DAVID M. SCORMICK Date: 10/6/17

Final Inspection Date: _____ P W Inspectors Name: _____ Signature: _____

CONTACT FOR REQUIREMENTS AND INSPECTIONS:

PUBLIC WORKS DEPARTMENT

Phone: 386-758-1019

Amount Paid 25.00

Check No. 3186

All Proper Safety Requirements Should Be Followed During The Installation Of The Culvert