## FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name: Lot 29 Turkey Creek Street: City, State, Zip: Lake City, FL, Owner: Design Location: FL, Gainesville	Builder Name: Lipscomb & Eagle Permit Office: Columbia County Permit Number: Jurisdiction: County: Columbia (Florida Climate Zone 2)
1. New construction or existing 2. Single family or multiple family 3. Number of units, if multiple family 4. Number of Bedrooms 5. Is this a worst case? 6. Conditioned floor area above grade (ft²) Conditioned floor area below grade (ft²) 7. Windows (209.0 sqft.) Description a. U-Factor: Dbl, U=0.36 SHGC: SHGC=0.25 b. U-Factor: N/A SHGC: c. U-Factor: N/A SHGC: Area Weighted Average Overhang Depth: Area Weighted Average SHGC: 8. Skylights c. U-Factor:(AVG) SHGC(AVG): N/A 9. Floor Types (1703.0 sqft.) a. Slab-On-Grade Edge Insulation b. N/A C. N/A  R= ft² R= ft² R= ft² R= ft²	10. Wall Types(2007.0 sqft.) a. Frame - Wood, Exterior b. Frame - Wood, Adjacent c. N/A d. N/A H. Ceiling Types (1788.0 sqft.) b. N/A L. Ceiling Types (1788.0 sqft.) b. N/A C. N/A R. H. Ceiling Types (1788.0 sqft.) b. N/A R. H. Ceiling Types (1788.0 sqft.) c. N/A R. H. Ceiling Types (1788.0 sqft.) b. N/A R. H. Ceiling Types (1788.0 sqft.) c. N/A R. H. Ceiling Types (1788.0 sqft.) R. H. L. H. Ceiling Types (1788.0 sqft.) R. H. L. Ceiling Types (1788.0 sqft.) R. H. Ceiling Types (1788.0 sqft.) R. H. L. Ceiling Types (1788.0 sqft.) R. H. L. Ceiling Types (1788.0 sqft.) R. H. L.
Glass/Floor Area: 0.123 Total Proposed Modified Total Baseline	
I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.  PREPARED BY:  DATE:  I hereby certify that this building, as designed, is in compliance with the Florida Energy Code.  OWNER/AGENT:	Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.

- Compliance requires certification by the air handler unit manufacturer that the air handler enclosure qualifies as certified factory-sealed in accordance with R403.3.2.1.
- Compliance requires an Air Barrier and Insulation Inspection Checklist in accordance with R402.4.1.1 and this project requires an envelope leakage test report with envelope leakage no greater than 5.00 ACH50 (R402.4.1.2).

DATE: \_\_

DATE:

				PROJEC	Т							
Title: Building Ty Owner Nan # of Units: Builder Nar Permit Offic Jurisdiction Family Type New/Existir Comment:	ne:  1 me: Lipscomb & E ce: Columbia Cou i: e: Detached	agle unty	Bedrooms Conditione Total Storic Worst Cas Rotate Ang Cross Ven Whole Hou	ed Area: 17 es: 1 e: N ple: 0 tilation: Ye	703 o es		Lot # Bloc Plate Stree Cour	k/Subdivi Book: et:	ision: 1	Lot Informa 29 Furkey Cred Columbia Lake City ,		
				CLIMATI	E							
<b>/</b>	Design Location	TMY Site		97.5	gn Temp % 2.5 %	Int De Winte	esign Tem er Sumn		leating gree Day	Desig vs Moistu		y Temp ange
	FL, Gainesville	FL_GAINESVILLE	_REGI	32	92	70	75		1305.5	51	N	ledium
				BLOCKS	<del></del>							
Number	Name	Area	Volume									
1	Block1	1703	15327									
				SPACES	3							
Number	Name	Area			ccupants	Bedroo		nfil ID	Finishe	2000		Heat
1	Main	1703	15327	Yes	6	3	1	li .	Yes	Yes		Yes
				FLOORS	<u> </u>							
V #		Space		V-1	-Value	Area						arpet
	Slab-On-Grade Edge	e insulation Ma	ain 223		0	1703 ft²				0	0	1
			D(	ROOF	D		0.014-07-0		-		-	
√ #	t Type	Materials	Roof Area	Gable Area	Roof Color	Rad Barr	Solar Absor.	SA Tested	Emitt	Emitt Tested	Deck Insul.	Pito (deg
1	Gable or shed	Composition shing!	es 2047 ft²	568 ft²	Medium	Y	0.96	No	0.9	No	0	33.7
				ATTIC								
√ #	Туре	Ventila	ation	Vent Ratio (1	in)	Area	RBS	IR	cc			
1	Partial cathedr	al ceili Vent	ed	300	1	703 ft²	Υ	1	N			
				CEILING	6							
√ #	Ceiling Type		Space	R-Value	Ins Ty	ре	Area	Fran	ning Fra	c Truss	Туре	
1	Under Attic (Ve	antad)	Main	38	Double B	-11 -	1788 ft²		0.11	Wo		

# Orr 1 W 2 W 3 S 4 E 5 S 6 E	nt Ti / Exte / Exte Exte Exte Exte	rior Fra rior Fra rior Fra	Il Type ame - Wood ame - Wood ame - Wood	Space Main Main	Cavity R-Value 13	Wid Ft	th In	Height Ft In	Area	Sheathing	Framing Fraction	Solar Absor.	Below
2 W 3 S 4 E 5 S	Exte	rior Fra rior Fra rior Fra	ame - Wood ame - Wood			601			Alea	r-value	Fraction		Grade%
3 S	Exte	rior Fra		Main		8		9	72.0 ft²	71 70100	0.23	0.75	0
4 E	Exte		ame - Wood		13	8		9	72.0 ft <sup>2</sup>		0.23	0.75	0
5 S	Exte	rior Fra		Main	13	20		9	180.0 ft <sup>2</sup>		0.23	0.75	0
			ame - Wood	Main	13	8		9	72.0 ft <sup>2</sup>		0.23	0.75	0
6 E	Evto	rior Fra	ame - Wood	Main	13	12	4	9	111.0 ft²		0.23	0.75	0
	LAIC	rior Fra	ame - Wood	Main	13	33	4	9	300.0 ft <sup>2</sup>		0.23	0.75	0
7 N	Exte	rior Fra	ame - Wood	Main	13	12	8	9	114.0 ft <sup>2</sup>		0.23	0.75	0
8 V	/ Exte	rior Fra	ame - Wood	Main	13	10		9	90.0 ft <sup>2</sup>		0.23	0.75	0
9 N	Exte	rior Fra	ame - Wood	Main	13	21	8	9	195.0 ft²		0.23	0.75	0
10 W	/ Exte	rior Fra	ame - Wood	Main	13	8		9	72.0 ft <sup>2</sup>		0.23	0.75	0
11 N	Exte	rior Fra	ame - Wood	Main	13	28		9	252.0 ft <sup>2</sup>		0.23	0.75	0
12 W	/ Exte	rior Fra	ame - Wood	Main	13	22		9	198.0 ft²		0.23	0.75	0
13 S	Gara	age Fra	ame - Wood	Main	13	22		9	198.0 ft²		0.23	0.75	0
14 W	/ Gara	age Fra	ame - Wood	Main	13	9		9	81.0 ft <sup>2</sup>		0.23	0.75	0
DOORS													
√ #	(	Ornt	Door Type	Space			Storms	U-Valu	ue Fi	Width t In	Height Ft	n	Area
1		S	Insulated	Main			None	.46	3		6	8 2	20 ft²
2		S	Insulated	Main			None	.46	3	C.	6	8 2	20 ft²
			0.	riontation sho		oows		l orientation					
,	W	all	01	rientation sho	wii is the ei	iterea, P	Toposed	onentation.		rhang			- W - V -
√ #	Ornt I		Panes	NFRC	U-Factor	SHGC	Imp	Area		Separation	Int Sha	de S	Screening
1	W	1 Vinyl	Low-E Double	Yes	0.36	0.25	N	15.0 ft²	1 ft 6 in	1 ft 0 in	None		None
2	s :	3 Vinyl	Low-E Double	Yes	0.36	0.25	N	45.0 ft <sup>2</sup>	6 ft 10 in	1 ft 0 in	None	1	None
3	S :	5 Vinyl	Low-E Double	Yes	0.36	0.25	N	15.0 ft²	1 ft 6 in	1 ft 0 in	None		None
4	Е (	6 Vinyl	Low-E Double	Yes	0.36	0.25	N	4.0 ft <sup>2</sup>	1 ft 0 in	5 ft 0 in	None		None
5	N	7 Vinyl	Low-E Double	Yes	0.36	0.25	Ν	15.0 ft <sup>2</sup>	1 ft 6 in	1 ft 0 in	None		None
6	N S	Vinyl	Low-E Double	Yes	0.36	0.25	Ν	40.0 ft <sup>2</sup>	9 ft 6 in	1 ft 0 in	None		None
7	N S	Vinyl	Low-E Double	Yes	0.36	0.25	N	8.0 ft <sup>2</sup>	9 ft 6 in	1 ft 0 in	None		None
8	W 1	0 Vinyl	Low-E Double	Yes	0.36	0.25	N	15.0 ft <sup>2</sup>	5 ft 6 in	1 ft 0 in	None	!	None
9	N 1	1 Vinyl	Low-E Double	Yes	0.36	0.25	N	20.0 ft <sup>2</sup>	1 ft 6 in	1 ft 0 in	None		None
10	N 1	1 Vinyl	Low-E Double	Yes	0.36	0.25	N	16.0 ft <sup>2</sup>	1 ft 6 in	1 ft 0 in	None	i	None
11	. W 1	2 Vinyl	Low-E Double	Yes	0.36	0.25	Ν	16.0 ft <sup>2</sup>		1 ft 0 in	None		None

FORM R405-2020

					GAR	AGE							
V	/ #	Floor Area	(	Ceiling Area	Exposed W	all Perimeter	r Avg.	Wall H	leight	Expose	d Wall Insu	ılation	
	1	491.26 ft²		491.26 ft <sup>2</sup>	57.6	33 ft		9 ft			1		
					INFILTE	ATION							
#	Scope	Method		SLA	CFM 50	ELA	EqLA	А	СН	ACH	50		
1	Wholehouse	Proposed AC	CH(50)	.000286	1277.3	70.07	131.56	.1	027	5			
					HEATING	SYSTEM							
V	/ #	System Type		Subtype	Speed	Efficie	ency	Сар	acity		В	ock [	Ducts
	1	Electric Heat Pur	mp/	None	Single	HSPF	F:8.2	29.38 k	Btu/hr		1		sys#1
					COOLING	SYSTEM							
V	/ #	System Type		Subtype	Subtype	Efficie	ncy Car	acity	Air	Flow SI	HR BI	ock [	Ducts
	1	Central Unit/		None	Single	SEER:	14 20.43	kBtu/h	600	cfm 0	.7 1		sys#1
					HOT WATE	R SYSTE	M						
V	/ #	System Type	SubType	Location	EF	Сар	Use		SetPnt		Consen	ation	
_	1	Electric	None	Garage	0.92	50 gal	40 gal		120 deg		Non	е	
				SOL	AR HOT W	TER SYS	STEM						
V	FSEC Cert #		ıme		System Model	#	Collector	Model#		ollector Area	Storage Volume	FEF	
	None	None								ft²			
					DUC	TS							
1/	/	Supp		Ret					CFM 25				VAC #
V	#	Location R-	Value Area	Location	Area	_eakageTyp	e Ha	andler	тот	OUT	QN R	LF Hea	t Cod

					TEM	PERATUR	RES						
ProgramableTherm	ostat: Y			Ce	eiling Fans	s:							
Cooling Jan Heating Jan Venting Jan	X Feb E Feb	[ ] Mar [X] Mar [X] Mar	Apr Apr Apr		] May ] May ] May	[X] Jun [ ] Jun [ ] Jun	[X] Jul   Jul   Jul	[X] Aug [ ] Aug [ ] Aug	[X] S	ep ep ep	Oct Oct Oct	X Nov X Nov X Nov	X Dec
Thermostat Schedule:	HERS 200	6 Reference	)				Но	urs					
Schedule Type		1	2	3	4	5	6	7	8	9	10	11	12
Cooling (WD)	AM PM	78 80	78 80	78 78	78 78	78 78	78 78	78 78	78 78	80 78	80 78	80 78	80 78
Cooling (WEH)	AM PM	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78
Heating (WD)	AM PM	66 68	66 68	66 68	66 68	66 68	68 68	68 68	68 68	68 68	68 68	68 66	68 66
Heating (WEH)	AM PM	66 68	66 68	66 68	66 68	66 68	68 68	68 68	68 68	68 68	68 68	68 66	68 66
						MASS							
Mass Type			Area			Thickness		Furniture Fra	ction		Space		
Default(8 lbs/s	q.ft.		O ft²			O ft		0.3			Main		

# **ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD**

#### ESTIMATED ENERGY PERFORMANCE INDEX\* = 96

The lower the EnergyPerformance Index, the more efficient the home.

, Lake City, FL,

1. New construction or existing			New (Fr	om Plans)	10. Wall Type and Insulation	Insulation	Area
2.	. Single family or multiple family		Detache	ed	a. Frame - Wood, Exterior	R=13.0	1728.00 ft²
3.	. Number of units, if multiple family		1		<ul><li>b. Frame - Wood, Adjacent</li><li>c. N/A</li></ul>	R=13.0 R=	279.00 ft² ft²
	Number of Bedrooms		3		d. N/A	R=	ft²
-	Is this a worst case?		No		<ol> <li>Ceiling Type and insulation level a. Under Attic (Vented)</li> </ol>	Insulation R=38.0	Area 1788.00 ft <sup>2</sup>
6.	Conditioned floor area (fl	t²)	1703		b. N/A	R=	ft²
7	Windows**	Description		Area	c. N/A	R=	ft²
	a. U-Factor: SHGC:	Dbl, U=0.36 SHGC=0.25		209.00 ft²	<ol> <li>Ducts, location &amp; insulation level</li> <li>Sup: Attic, Ret: Attic, AH: Garage</li> </ol>		R ft <sup>2</sup> 6 425.75
	b. U-Factor:	N/A		ft²			
	SHGC:				13. Cooling systems	kBtu/hr	Efficiency
	c. U-Factor: SHGC:	N/A		ft²	a. Central Unit	20.4	SEER:14.00
	d. U-Factor: SHGC:	N/A		ft²	14. Heating systems	kBtu/hr	Efficiency
	Area Weighted Average Overhang Depth: Area Weighted Average SHGC:			4.763 ft. 0.250	a. Electric Heat Pump	29.4	HSPF:8.20
,	8. Skylights a. U-Factor(AVG): SHGC(AVG):	Description N/A N/A		Area ft²	15. Hot water systems a. Electric	Ca	ap: 50 gallons EF: 0.92
3	9. Floor Types	Insulation	Area	<ul> <li>b. Conservationfeatures</li> <li>None</li> </ul>			
	<ul><li>a. Slab-On-Grade Edge Insulation</li><li>b. N/A</li></ul>		R=0.0 1703.00 ft <sup>2</sup> R= ft <sup>2</sup>		Credits (Performance method)		CV, Pstat
	c. N/A		R=	ft <sup>2</sup>			

I certify that this home has complied with the Florida Energy Efficiency Code for Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature:	Date:
Address of New Home:	City/FL Zip:



\*Note: This is not a Building Energy Rating. If your Index is below 70, your home may qualify for energy efficient mortgage (EEM) incentives if you obtain a Florida Energy Rating. For information about the Florida Building Code, Energy Conservation, contact the Florida Building Commission's support staff.

\*\*Label required by Section R303.1.3 of the Florida Building Code, Energy Conservation, if not DEFAULT.

# Envelope Leakage Test Report (Blower Door Test) Residential Prescriptive, Performance or ERI Method Compliance 2020 Florida Building Code, Energy Conservation, 7th Edition

Jurisdiction:	Permit #:							
Job Information								
Builder: Lipscomb & Eagle Community:	Lot: 29							
Address:								
City: Lake City State:	FL Zip:							
Air Leakage Test Results Passing results must meet e	either the Performance, Prescriptive, or ERI Method							
PRESCRIPTIVE METHOD-The building or dwelling unit shall be tested changes per hour at a pressure of 0.2 inch w.g. (50 Pascals) in Clima  PERFORMANCE or ERI METHOD-The building or dwelling unit shall the solested ACH/EO value as a beauty of the performance.	te Zones 1 and 2.  I be tested and verified as having an air leakage rate of not exceeding							
the selected ACH(50) value, as shown on Form R405-2020 (Performance) of ACH(50) specified on Form R405-2020-Energy Calc								
CFM(50) × 60 ÷ 15327 = ACH(50)  PASS  When ACH(50) is less than 3, Mechanical Ventilation insmust be verified by building department.	Method for calculating building volume:  Retrieved from architectural plans Code software calculated  Field measured and calculated							
R402.4.1.2 Testing. Testing shall be conducted in accordance with ANSI/RESNET/ICC 380 and reported at a pressure of 0.2 inch w.g. (50 Pascals). Testing shall be conducted by either individuals as defined in Section 553.993(5) or (7%)orida Statuesor individuals licensed as set forth in Section 489.105(3)(f), (g), or (i) or an approved third party. A written report of the results of the test shall be signed by the party conducting the test and provided to theode official. Testing shall be performed at any time after creation of all penetrations of the intended weatherstripping or other infiltration control measures.  1. Exterior windows and doors, fireplace and stove doors shall be closed, but not sealed, beyond the intended weatherstripping or other infiltration control measures.  2. Dampers including exhaust, intake, makeup air, back draft and flue dampers shall be closed, but not sealed beyond intended infiltration control measures.  3. Interior doors, if installed at the time of the test, shall be open.								
4. Exterior doors for continuous ventilation systems and heat recovery ventila 5. Heating and cooling systems, if installed at the time of the test, shall be turn 6. Supply and return registers, if installed at the time of the test, shall be fully	ned off.							
Testing Company								
Company Name: I hereby verify that the above Air Leakage results are in accordance Energy Conservation requirements according to the compliance m	ce with the 2020 7th Edition Florida Building Code							
Signature of Tester:	Date of Test:							
Printed Name of Tester:								
License/Certification #:	Issuing Authority:							