



The diagrams illustrate the nailing zones for roof sheathing on different roof types. The left diagram shows a hip roof with zones labeled 'ROOF EDGE', 'RIDGE', and 'VALLEY'. The right diagram shows a gable roof with zones labeled 'ROOF EDGE', 'RIDGE', and 'VALLEY'. Both diagrams use numbers (1, 2, 3, 4) to indicate the nailing pattern and dimensions (4', 5', 6') to specify the extent of the zones.



SCALE: NONE

B

SCALE: 1/2" = 1'-0"



SCALE: AS NOTED



- SHEARWALL NOTES:**
1. ALL SHEARWALLS SHALL BE TYPE 2 SH-5 AS DEFINED BY STD 10-9.588C1 304.
2. THE WALL SHALL BE ENTIRELY SHEATHED 7/8" X 0.5.5. INCLUDING AREAS ABOVE OPENINGS.
3. ALL SHEATHING SHALL BE ATTACHED TO WALLS ALONG ALL FOUR EDGES WITH JOINTS FOR PANELS OCCURRING OVER COMMON FRAMES OR ALONG BLOCKING.
4. NAIL SPACING SHALL BE 6" O.C. EDGES AND 12" O.C. IN THE FIELD.
5. TYPE 2 SHEARWALLS ARE DESIGNED FOR IT CONTAINS. MAXIMUM HEIGHT OF OPENING SHALL BE THE WALL HEIGHT. THE MINIMUM SPACING OF OPENINGS SHALL BE THE WALL HEIGHT FOR A-2" WALLS.

OPENING WIDTH	SILL PLATES	16d EA
UP TO 6'-0"	(1) 2x4 OR (1) 2x6	
> 6' TO 9'-0"	(3) 2x4 OR (1) 2x6	
> 9' TO 12'-0"	(5) 2x4 OR (3) 2x6	

SCALE: NONE

(1)