



APA  
RATED SHEATHING  
32/16  
EXPOSURE 1  
THICKNESS 0.438 in.  
PSI 48  
15/32 CARTRIDGE  
547  
CUSTOM PRODUCT 4-500

APA  
RATED SHEATHING  
32/16  
EXPOSURE 1  
THICKNESS 0.438 in.  
PSI 48  
15/32 CARTRIDGE  
547  
CUSTOM PRODUCT 4-500

APA  
RATED SHEATHING  
32/16  
EXPOSURE 1  
THICKNESS 0.438 in.  
PSI 48  
15/32 CARTRIDGE  
547  
CUSTOM PRODUCT 4-500

SHIFT 2  
21

HUNT FOREST  
PRODUCTS LLC  
MILL 547  
TERMINATE FUR  
AND INSECT  
REQUIREMENTS  
EXCEEDS  
TEMPERATURE  
MANUFACTURING

WALLS/FLOORS  
SPACE PANELS  
1/2 INCH AT ENDS  
1/2 INCH AT SIDES  
1/2 INCH AT CORNERS  
1/2 INCH AT JOINTS  
1/2 INCH AT FASTENERS

SPANNING, RATES, AND  
CAPACITIES ARE BASED ON  
UNTESTED PANELS AND MAY NOT  
BE APPLIED TO OTHER  
SITUATIONS OR MATERIALS  
AND WATER RESISTANCE

APA  
RATED SHEATHING  
32/16  
EXPOSURE 1  
THICKNESS 0.438 in.  
PSI 48  
15/32 CARTRIDGE  
547  
CUSTOM PRODUCT 4-500

WALLS/FLOORS  
SPACE PANELS  
1/2 INCH AT ENDS  
1/2 INCH AT SIDES  
1/2 INCH AT CORNERS  
1/2 INCH AT JOINTS  
1/2 INCH AT FASTENERS

MANUFACTURING  
TEMPERATURE  
EXCEEDS  
REQUIREMENTS TO  
TERMINATE FUR  
AND INSECT  
HUNT FOREST  
PRODUCTS LLC  
MILL 547

12







OK 0715





