

COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST

MINIMUM PLAN REQUIREMENTS: FLORIDA BUILDING CODE RESIDENTIAL 2014 EFFECTIVE 1 JULY 2015 AND THE NATIONAL ELECTRICAL CODE 2011 EFFECTIVE 1 JULY 2015

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE WITH THE CURRENT 2014 FLORIDA BUILDING CODES RESIDENTIAL, EFFECTIVE 1 JULY 2015. NATIONAL ELECTRICAL CODE 2011 EFFECTIVE 1 JULY 2015. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FLORIDA BUILDING CODE FIGURE 1609-A THROUGH 1609-C ULTIMATE DESIGN WIND SPEEDS FOR RISK CATEGORY AND BUILDINGS AND OTHER STRUCTURES Revised 12/2016

GENERAL REQUIREMENTS:

APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

r . T		Select From the Dropbox			
1	Two (2) complete sets of plans containing the following:		155		
2	All drawings must be clear, concise, drawn to scale, details that are not used shall be marked void	- 3	100		
3	Condition space (Sq. Ft.) 1690 Total (Sq. Ft.) under roof 2557	YES	NO	N/A	
Des		1 02 1 1			
be a	signers name and signature shall be on all documents and a licensed architect or engine.,ure an affixed to the plans and documents as per the FLORIDA BUILDING CODES RESIDENTIAL R101.	d official	embossed	seal shal	
Sit	te Plan information including:	2 . l			
4	Dimensions of lot or parcel of land		185		
5	Dimensions of all building set backs	-	ec.		
6	Location of all other structures (include square footage of structures) on parcel, existing or proposed		->		
	well and septic tank and all utility easements.	- U	25		
7	Provide a full legal description of property.		PC	=	
Wi	nd-load Engineering Summary, calculations and any details are required.				
	GENERAL REQUIREMENTS:	Itom	ur to Imalus	To the second	
初度	APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Items to Include- Each Box shall be		
通题		Recommendation of the last of	Marked as	oe .	
2011		MINISTER STREET, STREE	plicable		
8	Plans or specifications must show compliance with FBCR Chapter 3	YES	NO	N/A	
			om the Di		
9	Basic wind speed (3-second gust), miles per hour		PS	1	
10	(Wind exposure – if more than one wind exposure				
	is used, the wind exposure and applicable wind direction shall be indicated)	- 11	es		
11	nd importance factor and nature of occupancy				
		- U	es		
12	The applicable internal pressure coefficient, Components and Cladding	-11	25		
	The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component				
13	cladding materials not specifally designed by the registered design professional.	- 1.1	R		
	vations Drawing including:				
14	All side views of the structure	1 - L	165		
15	Roof pitch		162		
16	Overhang dimensions and detail with attic ventilation	- 11		_	
17	Location, size and height above roof of chimneys	- 4			
18	Location and size of skylights with Florida Product Approval	- 11			
18	Number of stories	-	es	-	
20A	Building height from the established grade to the roofs highest peak	- u			
		1 1 1	TO PAGE		

Items to Include-Each Box shall be

Marked as

Applicable

Fle	por Plan including:	4
	Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, deck,	
20	balconies	- Hes
21	Raised floor surfaces located more than 30 inches above the floor or grade	- h/a
22	All exterior and interior shear walls indicated	- 4-65
23	Shear wall opening shown (Windows, Doors and Garage doors)	- yes
24	Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each	- S - S - S - S - S - S - S - S - S - S
- '	bedroom (net clear opening shown) and Show compliance with Section FBC 1405.13.2 where the	
	opening of an operable window is located more than 72 inches above the finished grade or surface	- 1484
	below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above	
	the finished floor of the room in which the window is located. Glazing between the floor and 24	
	inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass.	
25	Safety glazing of glass where needed	- nta
	Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth	
26	(see chapter 10 and chapter 24 of FBCR)	1017
		-11/4/
27	Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails	
	, ,	- n/2
28	Identify accessibility of bathroom (see FBCR SECTION 320)	- Ha
	()	
A II	motorials placed within enough on outs/jute outs/jute autorian wells as fifte an early shall	have Mandala and days
	materials placed within opening or onto/into exterior walls, soffits or roofs shall	
	proval number and mfg. installation information submitted with the plans (see Fl	orida product approv
for	em)	
	GENERAL REQUIREMENTS:	Items to Include-
	APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each Box shall be
		Marked as
	2. 1 · 1 · 1 · 1 · 1 · 1 · 1 · 1 · 1 · 1	Applicable
C. Chemic		
ED	CR 403: Foundation Plans	YES / NO / N/A
FD		
20		Select From the Dropbox
29	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size	- LIES
	and type of reinforcing.	
30	All posts and/or column footing including size and reinforcing	
		- des
31	Any special support required by soil analysis such as piling.	- yes
	Assumed load-bearing valve of soil Pound Per Square Foot	- hla
31		- hla
31 32	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure	- hla
31 32	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete	- hla
31 32	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system.	- hla
31 32	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete	- hla
31 32 33	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3	- hla
31 32 33	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE	- hla
31 32 33 FB	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)	- hla
31 32 33 FB0 34	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE	- hla
31 32 33 FB0 34	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)	- hla
31 32 33 FB 34 35	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)	- hla
31 32 33 FB 34 35	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES	- hla
31 32 33 FB 34 35	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or	- hla
31 32 33 FB0 34 35	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered	- hla
31 32 33 FB 34 35	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or	- hla
31 32 33 FB6 34 35	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides	- hla
31 32 33 33 FB6 34 35 FB6	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls)	- h a
31 32 33 33 FB6 34 35 FB6	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides	- hla
31 32 33 33 FB6 36	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type	- hla
31 32 33 34 35 FB6 36	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement	- nla - mla - mla - - mla - ml
31 32 33 34 35 FB6 36	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type	- nla - mla - mla - - mla - ml
31 32 33 33 FB0 36 FB0 37 38 Me	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement tal frame shear wall and roof systems shall be designed, signed and sealed by Florida Protection in the size of the structure of the size of the structure of the size of t	- nla - mla - mla - - mla - ml
31 32 33 33 FB0 36 FB0 37 38 Me	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement tal frame shear wall and roof systems shall be designed, signed and sealed by Florida Proof or Framing System: First and/or second story	- nla - mla - mla - - mla - ml
31 32 33 33 FB6 34 35 FB6 37 38 Me	Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement tal frame shear wall and roof systems shall be designed, signed and sealed by Florida Protection in the size of the structure of the size of the structure of the size of t	- nla - mla - mla - mla - mla - mla - mla - mla - mla - mla

	Show conventional floor joist type, size, span, spacing and attachment to load bearing walls,	
40	stem walls and/or priers	- 485
41		
42	Attachment of joist to girder	- 1163
43		Control of the party of the last of the la
44		- Up
45		- hiz
46		- 10/-0
47	Show the required access opening to access to under-floor spaces	- nia
	Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges &	+
48	intermediate of the areas structural panel sheathing	- Wes
49		1 3
50		19-61
51	Provide live and dead load rating of floor framing systems (psf).	+ U.e.
		1-423
FB	CR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION	YES / NO / N
	GENERAL REQUIREMENTS:	Items to Include- Each Box shall be
	APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Marked as Applicable
- T	See 14	elect From the Drop
52	Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls	- 485
53	Fastener schedule for structural members per table IRC 602.3 are to be shown	- ues
	Show Wood structural panel's sheathing attachment to study, joist, trusses, rafters and structural	
54	members, showing fastener schedule attachment on the edges & intermediate of the areas structural panel sheathing	- 462
	Show all required connectors with a max uplift rating and required number of connectors and	
55	oc spacing for continuous connection of structural walls to foundation and roof trusses or rafter systems	-4es
	Show sizes, type, span lengths and required number of support jack studs, king studs for shear	
6	wall opening and girder or header per IRC Table 502.5 (1)	- 1-62
7	Indicate where pressure treated wood will be placed	- 4-85
	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural	
8	panel sheathing edges & intermediate areas	- UPS
9	A detail showing gable truss bracing, wall balloon framing details or/ and wall hinge bracing detail	- hes
B	CR :ROOF SYSTEMS:	
	Truss design drawing shall meet section FBCR 802.1.6.1 Wood trusses	- 425
1	Include a layout and truss details, signed and sealed by Florida Professional Engineer	- 1123
2	Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters	- 470
3	Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details	
4	Provide dead load rating of trusses	- 1121
		- MR2
-	CR 802:Conventional Roof Framing Layout	2.47
B	Rafter and ridge beams sizes, span, species and spacing	- LIDE
5	tearter and ridge beams sizes, span, species and spacing	
5 (Connectors to wall assemblies' include assemblies' resistance to uplift rating	- 2 92 8
	Connectors to wall assemblies' include assemblies' resistance to uplift rating Valley framing and support details	- 100
5 (Connectors to wall assemblies' include assemblies' resistance to uplift rating	- 18
5 1 5 (7 1 8 J	Connectors to wall assemblies' include assemblies' resistance to uplift rating Valley framing and support details Provide dead load rating of rafter system	The state of the s
5 1 6 6 7 3 8 1	Connectors to wall assemblies' include assemblies' resistance to uplift rating Valley framing and support details Provide dead load rating of rafter system CR 803 ROOF SHEATHING	123
B(B(Connectors to wall assemblies' include assemblies' resistance to uplift rating Valley framing and support details Provide dead load rating of rafter system CR 803 ROOF SHEATHING Include all materials which will make up the roof decking, identification of structural panel	The second second second
BC I	Connectors to wall assemblies' include assemblies' resistance to uplift rating Valley framing and support details Provide dead load rating of rafter system CR 803 ROOF SHEATHING Include all materials which will make up the roof decking, identification of structural panel sheathing, grade, thickness	- Lies
BC S	Connectors to wall assemblies' include assemblies' resistance to uplift rating Valley framing and support details Provide dead load rating of rafter system CR 803 ROOF SHEATHING Include all materials which will make up the roof decking, identification of structural panel sheathing, grade, thickness Show fastener Size and schedule for structural panel sheathing on the edges & intermediate areas	125
**************************************	Connectors to wall assemblies' include assemblies' resistance to uplift rating Valley framing and support details Provide dead load rating of rafter system CR 803 ROOF SHEATHING Include all materials which will make up the roof decking, identification of structural panel sheathing, grade, thickness	- Lies

FBCR Chapter 11 Energy Efficiency Code for residential building

Residential construction shall comply with this code by using the following compliance methods in the FBCR chapter 11 Residential buildings compliance methods. Two of the required forms are to be submitted, N1100.1.1.1 As an alternative to the computerized Compliance Method A, the Alternate Residential Point System Method hand calculation, Alternate Form 600A, may be used. All requirements specific to this calculation are located in Sub appendix C to Appendix G. Buildings complying by this alternative shall meet all mandatory requirements of this chapter. Computerized versions of the Alternate Residential Point System Method shall not be acceptable for code compliance.

YES / NO / N/A

	TES / NO / N/A		
	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to Include- Each Box shall be Marked as Applicable	
		Select From the Dropbox	
73	Show the insulation R value for the following areas of the structure	1- 11-25	
74		LIPC	
75	Exterior wall cavity	- 110	
76	Crawl space	- 21-14	
H	VAC information		
77	Submit two copies of a Manual J sizing equipment or equivalent computation study		
78			
	20 cfm continuous required	- Lyes	
79	Show clothes dryer route and total run of exhaust duct	I- 1193	
Di			
80	ambing Fixture layout shown All fixtures waste water lines shall be shown on the foundation plan	1 24.6	
81	Show the location of water heater	- 1162	
82 83	Pump motor horse power Reservoir pressure tank gallon capacity Rating of cycle stop valve if used	-	
Ele	ectrical layout shown including		
85	The state of the state of the state of the country that of the cou	- U.ES	
86	Show all 120-volt, single phase, 15- and 20-ampere branch circuits outlets required to be protected by Ground-Fault Circuit Interrupter (GFCI) Article 210.8 A	- 4-62	
87	Show the location of smoke detectors & Carbon monoxide detectors	1 445	
88	Show service panel, sub-panel, location(s) and total ampere ratings	2010 -	
	On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type.	- UPC	
	For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an Grounding electrode system. Per the National Electrical Code article 250,52.3		
90	Appliances and HVAC equipment and disconnects	- N-77	
	Show all 120-volt, single phase, 15- and 20-ampere branch circuits supplying outlets installed in dwelling unit family rooms, dining rooms, living rooms, parlors, libraries, dens, bedrooms, sunrooms, recreation rooms, closets, hallways, or similar rooms or areas shall be protected by a listed Combination arc-fault circuit interrupter , Protection device.	E LIPES	

GENERAL REQUIREMENTS: APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

Items to Include-Each Box shall be Circled as Applicable

THE FOLLOWING ITEMS MUST BE SUBMITTED WITH BUILDING PLANS

0.0		YES	NO	N/A
92	Building Permit Application A current Building Permit Application is to be completed, by following the Checklist all supporting documents must be submitted. There is a \$15.00 application fee. The completed application with attached documents and application	NO		
	fee can be mailed.	4		1
93	Parcel Number The parcel number (Tax ID number) from the Property Appraisers Office (386) 758-1083 is required. A copy of property deed is also required. www.columbiacountyfla.com	NQ	1/0	2
94	Town of Fort White (386) 497-2321 If the parcel in the application for building permit is within the Corporate city limits of Fort White, an approval land use development letter issued by the Town of Fort is required to be submitted with the application for a building permit.	NO		
***	BELOW ITEMS ONLY NEEDED AFTER ZONING APPROVAL HAS GIVEN.	****	***	***
95	Environmental Health Permit or Sewer Tap Approval A copy of a approved Columbia County Environmental Health (386) 758-1058	NO	105	
96	City of Lake City A City Water and/or Sewer letter. Call 386-752-2031	NO		
97	Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers shall require permitting through the Suwannee River Water Management District, before submitting a application to this office. Any project located within a flood zone where the base flood elevation (100 year flood) has been established shall meet the requirements of Section 8,5.2 of the Columbia County Land Development Regulations. Any project located within a flood zone where the base flood elevation has not been established (Zone A) shall meet the requirements of Section 8.5.3 of the Columbia County Land Development Regulations	NO		
98	CERTIFIED FINISHED FLOOR ELEVATIONS will be required on any project where the approved FIRM Flood Maps show the property is in a AE, Floodway, and AH flood zones, Additionally One Foot Rise letters are required for AE and AH zones. In the Floodway Flood zones a Zero Rise letter is required.			
99	A Flood development permit is also required for AE, Floodway & AH. Development permit cost is \$50.00			
100	Driveway Connection: If the property does not have an existing access to a public road, then an application for a culvert permit (\$25.00) must be made. County Public Works Dept. determines the size and length of every culvert before instillation and completes a final inspection before permanent power is granted. If the applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00) Separate Check when issued. If the project is to be located on an F.D.O.T. maintained road, then an F.D.O.T. access permit is required.	NO		
101	911 Address: An application for a 911 address must be applied for and received through the Columbia County Emergency Management Office of 911 Addressing Department (386) 758-1125.	NO	1	

TOILET FACILITIES SHALL BE PROVIDED FOR ALL CONSTRUCTION SITES. NO

<u>Disclosure Statement for Owner Builders</u> If you as the applicant will be acting as an owner/builder under section 489.103(7) of the Florida Statutes, submit the required owner builder disclosure statement form.

Notice Of Commencement

A notice of commencement form recorded in the Columbia County Clerk Office is required to be filed with the building department Before Any Inspections can be preformed.

Section R101.2.1 of the Florida Building Code Residential:

The provisions of Chapter 1, Florida Building Code shall govern the administration and enforcement of the Florida Building Code, Residential.