FORM R405-2023

FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name:	Aspen Pest Control	Builder Name:	
Street:		Permit Office:	
City, State, Zip:	, FL,	Permit Number:	
Owner:		Jurisdiction:	
Design Location:	FL, Gainesville	County:	columbia (Florida Climate Zone 2)

1. New construction or existing				New (From Plans)
2. Single family or multiple family				Detached
3. Number of units, if multiple family				1
4. Number of Bedrooms				0
5. Is this a worst case?				No
6. Conditioned floor area above grade (ft²)				1043
Conditioned floor area below grade (ft²)				0
7. Windows(120.0 sqft.)	Description			Area
a. U-Factor:	Dbl, U=0.26			120.00 ft²
SHGC:	SHGC=0.20			
b. U-Factor:	N/A			ft²
SHGC:				
c. U-Factor:	N/A			ft²
SHGC:				
Area Weighted Average Overhang Depth:				1.500 ft
Area Weighted Average SHGC:				0.200
8. Skylights	Description			Area
U-Factor:(AVG)	N/A			N/A ft²
SHGC(AVG):	N/A			
9. Floor Types		Insulation		Area
a. Slab-On-Grade Edge Insulation		R= 0.0		1043.00 ft²
b. N/A		R=		ft²
c. N/A		R=		ft²

10. Wall Types(1224.0 sqft.)	Insulation		Area
a. Frame - Steel, Exterior	R=21.0		864.00 ft²
b. Frame - Wood, Adjacent	R=21.0		360.00 ft²
c. N/A			
d. N/A			
11. Ceiling Types(1043.0 sqft.)	Insulation		Area
a. Single assembly, no ai (Unvented)	R=21.0		1043.00 ft²
b. N/A			
c. N/A			
12. Roof(Metal, Unvent)	Deck R=21.0		1075 ft²
13. Ducts, location & insulation level		R	ft²
a. Sup: Office, Ret: Office, AH: Office		6	209
b.			
c.			
14. Cooling Systems	kBtu/hr		Efficiency
a. Central Unit	24.0		SEER2:15.00
15. Heating Systems	kBtu/hr		Efficiency
a. Electric Heat Pump	24.0		HSPF2:7.50
16. Hot Water Systems			
a. Electric			Cap: 40 gallons
			EF: 0.920
b. Conservation features			None
17. Credits			Pstat

Glass/Floor Area: 0.115

Total Proposed Modified Loads: 22.41

Total Baseline Loads: 26.21

PASS

NOTE: Proposed residence must have annual total normalized Modified Loads that are less than or equal to 95 percent of the annual total loads of the standard reference design in order to comply.

I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.

PREPARED BY: _____

DATE: 5-5-25

I hereby certify that this building, as designed, is in compliance with the Florida Energy Code.

OWNER/AGENT: _____

DATE: _____

Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.

BUILDING OFFICIAL: _____

DATE: _____

- Compliance requires certification by the air handler unit manufacturer that the air handler enclosure qualifies as certified factory-sealed in accordance with R403.3.2.1.

- Compliance with a proposed duct leakage Qn requires a PERFORMANCE Duct Leakage Test Report confirming duct leakage to outdoors, tested in accordance with ANSI/RESNET/ICC 380, is not greater than 0.030 Qn for whole house.

- Compliance requires an Air Barrier and Insulation Inspection Checklist in accordance with R402.4.1.1 and this project requires a PERFORMANCE envelope leakage test report with envelope leakage no greater than 4.00 ACH50 (R402.4.1.2).

FORM R405-2023

INPUT SUMMARY CHECKLIST REPORT

PROJECT

Title:	Aspen Pest Control			Address type:	Street Address
Building Type:	User	Bedrooms:	0	Lot #:	---
Owner:		Conditioned Area:	1043	Block/SubDivision:	---
Builder Home ID:		Total Stories:	1	PlatBook:	---
Builder Name:		Worst Case:	No	Street:	
Permit Office:		Rotate Angle:	0	County:	columbia
Jurisdiction:		Cross Ventilation:		City, State, Zip:	,
Family Type:	Detached	Whole House Fan:			FL,
New/Existing:	New (From Plans)	Terrain:	Rural		
Year Construct:	2025	Shielding:	Moderate/Rural		
Comment:					

CLIMATE

√	Design Location	Tmy Site	Design Temp 97.5%	Design Temp 2.5%	Int Design Temp Winter	Int Design Temp Summer	Heating Degree Days	Design Moisture	Daily temp Range
___	FL, Gainesville	FL_GAINESVILLE_REGIONA	32	92	70	75	1305.5	51	Medium

BLOCKS

√	Number	Name	Area	Volume
___	1	Block1	1043	9387 cu ft

SPACES

√	Number	Name	Area	Volume	Kitchen	Occupants	Bedrooms	Finished	Cooled	Heated
___	1	Office	1043	9387	Yes	1		Yes	Yes	Yes

FLOORS (Total Exposed Area = 1043 sq.ft.)

√	#	Floor Type	Space	Exposed Perim(ft)	Area	R-Value Perim.	R-Value Joist	U-Factor	Slab Insul. Vert/Horiz	Tile	Wood	Carpet
___	1	Slab-On-Grade Edge Ins	Office	96	1043 sqft	0.0	---	0.405	0 (ft)/0 (ft)	0.00	0.50	0.50

ROOF

√	#	Type	Materials	Roof Area	Gable Area	Framing. Fract.	Roof Color	Rad Barr	Solar Absor.	SA Tested	Emitt	Emitt Tested	Deck Insul.	Pitch (deg)
___	1	Gable or shed	Metal	1075 ft²	130 ft²	0.11	Unf, Gal.	N	0.7	No	0.7	No	21	14.04

ATTIC

√	#	Type	Ventilation	Vent Ratio (1 in)	Area	RBS	IRCC
___	1	No attic	Unvented	0	1043 ft²	N	N

CEILING (Total Exposed Area = 1043 sq.ft.)

√	#	Ceiling Type	Space	R-Value	Ins. Type	Area	U-Factor	Framing Frac.	Truss Type
___	1	Single assembly, no airspace(Unvented)	Office	21.0	Blown	1043.0ft²	0.039	0.11	Wood

FORM R405-2023

INPUT SUMMARY CHECKLIST REPORT

WALLS (Total Exposed Area = 1224 sq.ft.)

√ #	Ornt	Adjacent To	Wall Type	Space	Cavity R-Value	Width Ft	Width In	Height Ft	Height In	Area sq.ft.	U-Factor	Sheath R-Value	Frm. Frac.	Solar Absor.	Below Grade
___ 1	N	Exterior	Frame - Steel	Office	21.0	28.0	0	9.0	0	252.0	0.176		0.23	0.75	0 %
___ 2	E	Garage	Frame - Wood	Office	21.0	40.0	0	9.0	0	360.0	0.068		0.23	0.75	0 %
___ 3	S	Exterior	Frame - Steel	Office	21.0	28.0	0	9.0	0	252.0	0.176		0.23	0.75	0 %
___ 4	W	Exterior	Frame - Steel	Office	21.0	40.0	0	9.0	0	360.0	0.176		0.23	0.75	0 %

DOORS (Total Exposed Area = 60 sq.ft.)

√ #	Ornt	Adjacent To	Door Type	Space	Storms	U-Value	Width Ft	Width In	Height Ft	Height In	Area
___ 1	E	Garage	Insulated	Office	None	0.46	3.00	0	6.00	8	20.0ft²
___ 2	W	Exterior	Insulated	Office	None	0.46	6.00	0	6.00	8	40.0ft²

WINDOWS (Total Exposed Area = 120 sq.ft.)

√ #	Ornt	Wall ID	Frame	Panes	NFRC	U-Factor	SHGC	Imp	Storm	Total Area (ft²)	Same Units	Width (ft)	Height (ft)	--Overhang-- Depth (ft)	Sep. (ft)	Interior Shade	Screen
___ 1	N	1	Vinyl	Low-E Double	Y	0.26	0.20	N	N	30.0	2	3.00	5.00	1.5	1.3	None	None
___ 2	S	3	Vinyl	Low-E Double	Y	0.26	0.20	N	N	30.0	2	3.00	5.00	1.5	1.3	None	None
___ 3	W	4	Vinyl	Low-E Double	Y	0.26	0.20	N	N	60.0	4	3.00	5.00	1.5	1.3	None	None

INFILTRATION

√ #	Scope	Method	SLA	CFM50	ELA	EqLA	ACH	ACH50	Space(s)	Infiltration Test Volume
___ 1	Wholehouse	Proposed ACH(50)	0.00023	626	34.33	64.46	0.0822	4.0	All	9387 cu ft

GARAGE

√ #	Floor Area	Length	Width	Roof Area	Exposed Perimeter	Area Under Uncond.	Avg. Wall Height	Exposed Wall Insulation
___ 1	1360 ft²	34.0 ft²	40.0 ft²	1360 ft²	108 ft	1360 ft	9 ft	13

MASS

√ #	Mass Type	Area	Thickness	FurnitureFraction	Space
___ 1	Default(8 lbs/sq.ft.)	0 ft²	0 ft	0.30	Office

HEATING SYSTEM

√ #	System Type	Subtype/Speed	AHRI #	Efficiency	Capacity kBtu/hr	----GeothermalHeatPump---- Entry	Power	Volt	Current	Ducts	Block
___ 1	Electric Heat Pump	None/Single		HSPF2: 7.50	24.0		0.00	0.00	0.00	sys#1	1

COOLING SYSTEM

√ #	System Type	Subtype/Speed	AHRI #	Efficiency	Capacity kBtu/hr	Air Flow cfm	SHR	Duct	Block
___ 1	Central Unit	None/Single		SEER2:15.0	24.0	720	0.75	sys#1	1

FORM R405-2023

INPUT SUMMARY CHECKLIST REPORT

HOT WATER SYSTEM

√	#	System Type	Subtype	Location	EF(UEF)	Cap	Use	SetPnt	Fixt. Flow	Trap	Pipe Ins.	Pipe length
___	1	Electric	None	Garage	0.92 (0.92)	40.0 gal	60 gal	120 deg	Standard	Yes	None	99

	Recirculation System	Recirc Control Type	Loop length	Branch length	Pump power	DWHR	Facilities Connected	Equal Flow	DWHR Eff	Other Credits
___ 1	No		NA	NA	NA	No	NA	NA	NA	None

DUCTS

√	Duct #	Supply Location	Supply R-Value	Supply Area	Return Location	Return R-Value	Return Area	Leakage Type	AHU Location	CFM 25 TOT|OUT	QN OUT	AHU SEALED	RLF	HVAC # Heat	HVAC # Cool
___	1	Office	6.0	209 ft²	Office	6.0	52 ft²	Prop. Leak Free	Office	---|---	0.030	Yes	0.50	1	1

TEMPERATURES

Programable Thermostat: Y Ceiling Fans: N

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Cooling	[ ]	[ ]	[ ]	[ ]	[ ]	[X]	[X]	[X]	[X]	[ ]	[ ]	[ ]
Heating	[X]	[X]	[X]	[ ]	[ ]	[ ]	[ ]	[ ]	[ ]	[ ]	[X]	[X]
Venting	[ ]	[ ]	[X]	[X]	[ ]	[ ]	[ ]	[ ]	[ ]	[X]	[X]	[ ]

√	Thermostat Schedule: HERS 2006 Reference Schedule Type		Hours 1	2	3	4	5	6	7	8	9	10	11	12
___	Cooling (WD)	AM	78	78	78	78	78	78	78	78	80	80	80	80
		PM	80	80	78	78	78	78	78	78	78	78	78	78
___	Cooling (WEH)	AM	78	78	78	78	78	78	78	78	78	78	78	78
		PM	78	78	78	78	78	78	78	78	78	78	78	78
___	Heating (WD)	AM	66	66	66	66	66	68	68	68	68	68	68	68
		PM	68	68	68	68	68	68	68	68	68	68	66	66
___	Heating (WEH)	AM	66	66	66	66	66	68	68	68	68	68	68	68
		PM	68	68	68	68	68	68	68	68	68	68	66	66