

ROOFING AFFIDAVIT

Columbia County, Florida Building Department 135 NE Hernando Avenue Lake City, Florida 32055 Phone: 386-758-1008

www.columbiacountyfla.com

JOB ADDRESS: 4895 SW PINE	MOUNT RD LAKE CITY FL
DARYLE FLESHER License # CCC057848	Licensed as a Contractor, Engineer, or Architect, with
permit is true and accurate and that the	do hereby affirm that all of the information provided to obtain this ne sheathing, nailing, dry-in, venting and flashings at the above
installation instructions and standards	accordance with the applicable codes, Florida product approval set forth in the most current edition of the Florida Building Code-
Residential and the Florida Building Co (Affient Signature)	ue-Existing bunding.
STATE OF FLORIDA COUNTY MARION	
	ged before me by means of physical presence or online
	(Seal) ANGIE M DAWSON Notary Public - State of Florida Commission # HH 364946

FINAL INSPECTION & CERTIFICATE OF COMPLETION:

This completed form and photographs must be uploaded to your permit via online at the Application Submission login (link) <u>Welcome to Columbia County Online (columbiacountyfla.com)</u>.

Clearly visible in the Photographs must be the permit number or address, must include a ruler or measuring device to confirm nail spacing and overlaps including drip edge, valley flashing and attic venting.



ROOFING UNDERLAYMENT AFFIDAVIT

DARYI E EL ECHER

Columbia County, Florida Building Department

135 NE Hernando Avenue Lake City, Florida 32055 Phone: 386-758-1008

www.columbiacountyfla.com

REQUIRED FOR WALK-IN OR	PAPER SUBMITTALS			
4895 S	W PINEMOL	INT RD I	AKE (CITY FL

(Print Name), as a Florida license Roofing Contractor or an Owner
Builder, I understand to comply with the 2020 Florida Building Code 7th Edition underlayment requirements, I
must select an option for sealing the roof deck.
The options are summarized below
a self-adhering polymer-modified bitumen underlayment complying with ASTM D1970 applied over the entire roof.
a minimum 4-inch wide strip of selfadhering polymer-modified bitumen complying with ASTM D1970 or a minimum 3 % - inch wide strip of selfadhering flexible flashing tape complying with AAMA 711, applied over all joints in the roof decking. A felt underlayment complying with ASTM D226 Type II, ASTM D4869 Type III or IV, or ASTM D6757, or a synthetic underlayment meeting the performance requirements specified, is required to be applied over the strips/tape over the entire roof.
two layers of felt underlayment comply ASTM 0226 Type II or ASTM D4869 Type III or IV, or two layers of a synthetic underlayment meeting the performance requirements specified, lapped and fastened as specified.
X Other (explain) BITUMEN UNDERLAYMENT OVER LOW SLOPE AND VALLEYS IN ADDITION
BITUMEN UNDERLAYMENT OVER LOW SLOPE AND VALLEYS IN ADDITION

FINAL INSPECTION & CERTIFICATE OF COMPLETION:

Contractor/Owners Signature

This completed form and photographs must be uploaded to your permit via online at the Application Submission login (link) Welcome to Columbia County Online (columbiacountyfla.com).

Clearly visible in the Photographs must be the permit number or address and must include a ruler or measuring device to confirm nail spacing and overlaps including drip edge and valley flashing.