

Florida Department of
Business & Professional
Regulation

BCIS Home | Log In | User Registration | Hot Topics | Submit Surcharge | Stats & Facts | Publications | FBC Staff | BCIS Site Map | Links | Search |



Product Approval
USER: Public User

License efficiently. Regulate fairly.

[Product Approval Menu](#) > [Product or Application Search](#) > [Application List](#) > **Application Detail**



FL #	FL12328-R3										
Application Type	Editorial Change										
Code Version	2010										
Application Status	Approved										
Comments											
Archived	<input type="checkbox"/>										
Product Manufacturer	TAMKO Building Products, Inc.										
Address/Phone/Email	PO Box 1404 Joplin, MO 64802 (417) 624-6644 Ext 2305 kerri_eden@tamko.com										
Authorized Signature	Kerri Eden kerri_eden@tamko.com										
Technical Representative	Kerri Eden										
Address/Phone/Email	PO Box 1404 Joplin, MO 64802 (417) 624-6644 Ext 2305 kerri_eden@tamko.com										
Quality Assurance Representative											
Address/Phone/Email											
Category	Roofing										
Subcategory	Underlayments										
Compliance Method	Test Report										
Testing Lab	PRI Construction Materials Technologies, LLC										
Quality Assurance Entity	UL LLC										
Quality Assurance Contract Expiration Date	02/26/2016										
Validated By	Robert J. M. Nieminen, PE <input checked="" type="checkbox"/> Validation Checklist - Hardcopy Received										
Certificate of Independence	FL12328_R3_COI_PRI_CMT_Cert of Independence.pdf										
Referenced Standard and Year (of Standard)	<table border="0"> <thead> <tr> <th>Standard</th> <th>Year</th> </tr> </thead> <tbody> <tr> <td>ASTM D1970</td> <td>2001</td> </tr> <tr> <td>ASTM D226</td> <td>2006</td> </tr> <tr> <td>ASTM D4869</td> <td>2005</td> </tr> <tr> <td>ASTM D6380</td> <td>2003</td> </tr> </tbody> </table>	Standard	Year	ASTM D1970	2001	ASTM D226	2006	ASTM D4869	2005	ASTM D6380	2003
Standard	Year										
ASTM D1970	2001										
ASTM D226	2006										
ASTM D4869	2005										
ASTM D6380	2003										
Equivalence of Product Standards Certified By											
Product Approval Method	Method 1 Option B										

Date Submitted	03/04/2013
Date Validated	03/11/2013
Date Pending FBC Approval	04/15/2013
Date Approved	06/11/2013

Summary of Products

FL #	Model, Number or Name	Description
12328.1	ASTM Slate Surfaced Roll Roofing	Roll roofing surfaced with mineral granules
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: For use on roofs with slopes greater than 2:12. Not approved for use in HVHZ. Refer to FRSA/TRI 07320/8 for underlayment options with tile roof systems.		Installation Instructions FL12328_R3_II_sl_surf_app_ins.pdf Verified By: Robert J. M. Nieminen 59166 Test Reports FL12328_R3_TR_2010 Referenced Standards Evaluation for TAMKO 10 03 2011.pdf FL12328_R3_TR_astm_slate_surfaced_roll_rfq.pdf
12328 2	ASTM Tile Underlayment	Coated organic underlayment
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: For use under discontinuous roofing systems i.e. asphalt shingles with slopes greater than 2:12. Not approved for use in HVHZ. Refer to FRSA/TRI 07320/8 for underlayment options with tile roof systems Maximum 30 day exposure.		Installation Instructions FL12328_R3_II_UNDERLAYMENT.pdf Verified By: Robert J. M. Nieminen 59166 Test Reports FL12328_R3_TR_2010 Referenced Standards Evaluation for TAMKO 10 03 2011.pdf FL12328_R3_TR_astm_tile_underlayment_report.pdf
12328 3	Master Smooth	Asphalt saturated organic underlayment.
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: For use under discontinuous roofing systems i.e. asphalt shingles with slopes greater than 2:12. Not approved for use in HVHZ. Not for use as a substrate for adhesive-set roof tile. Refer to FRSA/TRI 07320/8 for underlayment options with tile roof systems. Maximum 30 day exposure		Installation Instructions FL12328_R3_II_UNDERLAYMENT.pdf Verified By: Robert J. M. Nieminen 59166 Test Reports FL12328_R3_TR_2010 Referenced Standards Evaluation for TAMKO 10 03 2011.pdf FL12328_R3_TR_master_smooth_report.pdf
12328.4	Moisture Guard Plus	A self-adhering modified bitumen underlayment
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: For use under discontinuous roofing systems i.e. asphalt shingles with slopes greater than 2:12. Not approved for use in HVHZ. Not for use as a substrate for adhesive-set roof tile Refer to FRSA/TRI 07320/8 for underlayment options with tile roof systems. Maximum 90 day exposure.		Installation Instructions FL12328_R3_II_mgp_app_inst.pdf Verified By: Robert J. M. Nieminen 59166 Test Reports FL12328_R3_TR_moisture_guard_plus_report.pdf
12328 5	Nail Fast	SBS modified utility underlayment
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: For use under discontinuous roofing systems i.e. asphalt shingles with slopes greater than 2:12. Not approved for use in HVHZ. Not for use as a substrate for adhesive-set roof tile. Refer to FRSA/TRI 07320/8 for underlayment options with tile roof systems Maximum 30 day exposure.		Installation Instructions FL12328_R3_II_nailfast_app_ins.pdf Verified By: Robert J. M. Nieminen 59166 Test Reports FL12328_R3_TR_2010 Referenced Standards Evaluation for TAMKO 10 03 2011.pdf FL12328_R3_TR_nailfast_report.pdf
12328.6	No. 15 ASTM D4869	Asphalt saturated organic felt
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: For use under discontinuous roofing systems i.e. asphalt shingles with slopes greater than 2:12. Not		Installation Instructions FL12328_R3_II_UNDERLAYMENT.pdf Verified By: Robert J. M. Nieminen 59166 Test Reports FL12328_R3_TR_no_15_astm_d4869_report.pdf

approved for use in HVHZ. Not for use as a substrate for adhesive-set roof tile. Refer to FRSA/TRI 07320/8 for underlayment options with tile roof systems. Shall be covered as soon as possible after installation; exposure for more than 24 hours could affect performance.		
12328.7	No. 15 UL	Asphalt saturated organic felt
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: For use under discontinuous roofing systems i.e. asphalt shingles with slopes greater than 2:12. Not approved for use in HVHZ. Not for use as a substrate for adhesive-set roof tile. Refer to FRSA/TRI 07320/8 for underlayment options with tile roof systems. Shall be covered as soon as possible after installation; exposure for more than 24 hours could affect performance.		Installation Instructions FL12328_R3_II_UNDERLAYMENT.pdf Verified By: Robert J. M. Nieminen 59166 Test Reports FL12328_R3_TR_no_15_ul_report.pdf
12328.8	No. 30 ASTM	Asphalt saturated organic felt
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: For use under discontinuous roofing systems i.e. asphalt shingles with slopes greater than 2:12. Not approved for use in HVHZ. Not for use as a substrate for adhesive-set roof tile. Refer to FRSA/TRI 07320/8 for underlayment options with tile roof systems. Shall be covered as soon as possible after installation; exposure for more than 24 hours could affect performance.		Installation Instructions FL12328_R3_II_UNDERLAYMENT.pdf Verified By: Robert J. M. Nieminen 59166 Test Reports FL12328_R3_TR_no_30_astm_report.pdf
12328.9	No. 30 ASTM D4869	Asphalt saturated organic felt
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: For use under discontinuous roofing systems i.e. asphalt shingles with slopes greater than 2:12. Not approved for use in HVHZ. Not for use as a substrate for adhesive-set roof tile. Refer to FRSA/TRI 07320/8 for underlayment options with tile roof systems. Shall be covered as soon as possible after installation; exposure for more than 24 hours could affect performance.		Installation Instructions FL12328_R3_II_UNDERLAYMENT.pdf Verified By: Robert J. M. Nieminen 59166 Test Reports FL12328_R3_TR_no_30_astm_d_4869_report.pdf
12328.10	No. 30 UL	Asphalt saturated organic felt
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: For use under discontinuous roofing systems i.e. asphalt shingles with slopes greater than 2:12. Not approved for use in HVHZ. Not for use as a substrate for adhesive-set roof tile. Refer to FRSA/TRI 07320/8 for underlayment options with tile roof systems. Shall be covered as soon as possible after installation; exposure for more than 24 hours could affect performance.		Installation Instructions FL12328_R3_II_UNDERLAYMENT.pdf Verified By: Robert J. M. Nieminen 59166 Test Reports FL12328_R3_TR_no_30_ul_report.pdf


[Back](#) [Next](#)



[Contact Us](#) 1940 North Monroe Street, Tallahassee FL 32399 Phone: 850-487-1824

The State of Florida is an AA/EEO employer [Copyright 2007-2013 State of Florida](#), [Privacy Statement](#), [Accessibility Statement](#), [Refund Statement](#)

Under Florida law, email addresses are public records. If you do not want your e-mail address released in response to a public-records request, do not send electronic mail to this entity. Instead, contact the office by phone or by traditional mail. If you have any questions, please contact 850.487.1395. *Pursuant to Section 455.275(1), Florida Statutes, effective October 1, 2012, licensees licensed under Chapter 455, F.S. must provide the Department with an email address if they have one. The emails provided may be used for official communication with the licensee. However email addresses are public record. If you do not wish to supply a personal address, please provide the Department with an email address which can be made available to the public. To determine if you are a licensee under Chapter 455, F.S., please click [here](#).

Product Approval Accepts:





Florida Department of
Business & Professional
Regulation

BCIS Home | Log In | User Registration | Hot Topics | Submit Surcharge | Stats & Facts | Publications | FBC Staff | BCIS Site Map | Links | Search |



Product Approval
USER Public User

License efficiently. Regulate fairly.

[Product Approval Menu](#) > [Product or Application Search](#) > [Application List](#) > **Application Detail**



FL #	FL1956-R8								
Application Type	Revision								
Code Version	2010								
Application Status	Approved								
	*Approved by DBPR. Approvals by DBPR shall be reviewed and ratified by the POC and/or the Commission if necessary.								
Comments									
Archived	<input type="checkbox"/>								
Product Manufacturer	TAMKO Building Products, Inc.								
Address/Phone/Email	PO Box 1404 Joplin, MO 64802 (417) 624-6644 Ext 2305 kerri_eden@tamko.com								
Authorized Signature	Kerri Eden kerri_eden@tamko.com								
Technical Representative	Kerri Eden								
Address/Phone/Email	PO Box 1404 Joplin, MO 64802 (417) 624-6644 Ext 2305 kerri_eden@tamko.com								
Quality Assurance Representative									
Address/Phone/Email									
Category	Roofing								
Subcategory	Asphalt Shingles								
Compliance Method	Certification Mark or Listing								
Certification Agency	UL LLC								
Validated By	Robert J. M Niemlnen, PE <input checked="" type="checkbox"/> Validation Checklist - Hardcopy Received								
Referenced Standard and Year (of Standard)	<table border="0"> <thead> <tr> <th><u>Standard</u></th> <th><u>Year</u></th> </tr> </thead> <tbody> <tr> <td>ASTM D3161</td> <td>2006</td> </tr> <tr> <td>ASTM D3462</td> <td>2007</td> </tr> <tr> <td>ASTM D7158</td> <td>2007</td> </tr> </tbody> </table>	<u>Standard</u>	<u>Year</u>	ASTM D3161	2006	ASTM D3462	2007	ASTM D7158	2007
<u>Standard</u>	<u>Year</u>								
ASTM D3161	2006								
ASTM D3462	2007								
ASTM D7158	2007								
Equivalence of Product Standards									
Certified By									
Product Approval Method	Method 1 Option A								
Date Submitted	09/27/2012								
Date Validated	10/15/2012								
Date Pending FBC Approval									

Date Approved
Date Revised

10/16/2012
05/14/2014

Summary of Products

FL #	Model, Number or Name	Description
1956.1	Elite Glass-Seal	A three tab asphalt shingle
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Asphalt shingles shall be used only on roof slopes of 2:12 or greater. Nails must be used as the method of attachment		Certification Agency Certificate FL1956 R8 C CAC Tamko Serv Conf FL 1956 2012.pdf FL1956 R8 C CAC UL certification 10-11-12.pdf Quality Assurance Contract Expiration Date 10/10/2015 Installation Instructions FL1956 R8 II glass seal elite app inst april 10.pdf FL1956 R8 II glass seal elite app inst f april 10.pdf FL1956 R8 II TAMKO Glass-Seal Elite Glass-Seal (Frederick Joplin Tuscaloosa).pdf Verified By: Robert Nieminen 59166 Created by Independent Third Party: No Evaluation Reports Created by Independent Third Party:
1956.2	Glass-Seal	A three tab asphalt shingle.
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Asphalt shingles shall be used only on roof slopes of 2:12 or greater. Nails must be used as the method of attachment.		Certification Agency Certificate FL1956 R8 C CAC Tamko Serv Conf FL 1956 2012.pdf FL1956 R8 C CAC UL certification 10-11-12.pdf Quality Assurance Contract Expiration Date 10/10/2015 Installation Instructions FL1956 R8 II glass seal elite app inst april 10.pdf FL1956 R8 II TAMKO Glass-Seal Elite Glass-Seal (Frederick Joplin Tuscaloosa).pdf Verified By: Robert Nieminen PE 59166 Created by Independent Third Party: No Evaluation Reports Created by Independent Third Party:
1956.3	Heritage	A dimensional asphalt shingle
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Asphalt shingles shall be used only on roof slopes of 2:12 or greater. Nails must be used as the method of attachment.		Certification Agency Certificate FL1956 R8 C CAC Tamko Serv Conf FL 1956 2012.pdf FL1956 R8 C CAC UL certification 10-11-12.pdf Quality Assurance Contract Expiration Date 10/10/2015 Installation Instructions FL1956 R8 II heritage app inst - sept 12.pdf FL1956 R8 II heritage app inst frederick.pdf Verified By: Robert J. M. Nieminen FL 59166 Created by Independent Third Party: No Evaluation Reports Created by Independent Third Party:
1956.4	Heritage 30	A dimensional asphalt shingle
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Asphalt shingles shall be used only on roof slopes of 2:12 or greater. Nails must be used as the method of attachment.		Certification Agency Certificate FL1956 R8 C CAC Tamko Serv Conf FL 1956 2012.pdf FL1956 R8 C CAC UL certification 10-11-12.pdf Quality Assurance Contract Expiration Date 10/10/2015 Installation Instructions FL1956 R8 II heritage 30 app inst april 10.pdf FL1956 R8 II heritage 30 app inst f april 10.pdf Verified By: Robert Nieminen PE 59166 Created by Independent Third Party: No Evaluation Reports Created by Independent Third Party:
1956.5	Heritage 50	A dimensional asphalt shingle
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Asphalt shingles shall be used only on roof slopes of 2:12 or greater. Nails must be used as the method of attachment.		Certification Agency Certificate FL1956 R8 C CAC Tamko Serv Conf FL 1956 2012.pdf FL1956 R8 C CAC UL certification 10-11-12.pdf Quality Assurance Contract Expiration Date 10/10/2015 Installation Instructions FL1956 R8 II heritage 50 app inst april 10.pdf FL1956 R8 II heritage 50 app inst f april 10.pdf Verified By: Robert Nieminen PE 59166 Created by Independent Third Party: No Evaluation Reports Created by Independent Third Party:

1956.6	Heritage Premium	A dimensional asphalt shingle.
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Asphalt shingles shall be used only on roof slopes of 2:12 or greater. Nails must be used as the method of attachment.		Certification Agency Certificate FL1956_R8_C_CAC_Tamko_Serv_Conf_FL_1956_2012.pdf FL1956_R8_C_CAC_UL_certification_10-11-12.pdf Quality Assurance Contract Expiration Date 10/10/2015 Installation Instructions FL1956_R8_II_heritage_prem_app_inst.pdf FL1956_R8_II_heritage_prem_app_inst_frederick.pdf Verified By: Robert Nieminen 59166 Created by Independent Third Party: No Evaluation Reports Created by Independent Third Party:
1956.7	Heritage Woodgate	A dimensional asphalt shingle.
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Asphalt shingles shall be used only on roof slopes of 2:12 or greater. Nails must be used as the method of attachment.		Certification Agency Certificate FL1956_R8_C_CAC_Tamko_Serv_Conf_FL_1956_2012.pdf FL1956_R8_C_CAC_UL_certification_10-11-12.pdf Quality Assurance Contract Expiration Date 10/10/2015 Installation Instructions FL1956_R8_II_Woodgate_app_inst_D_Oct_11.pdf FL1956_R8_II_Woodgate_app_inst_F_Oct_11.pdf Verified By: Robert Nieminen 59166 Created by Independent Third Party: No Evaluation Reports Created by Independent Third Party:
1956.8	Heritage XL	A dimensional asphalt shingle.
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Asphalt shingles shall be used only on roof slopes of 2:12 or greater. Nails must be used as the method of attachment.		Certification Agency Certificate FL1956_R8_C_CAC_Tamko_Serv_Conf_FL_1956_2012.pdf FL1956_R8_C_CAC_UL_certification_10-11-12.pdf Quality Assurance Contract Expiration Date 10/10/2015 Installation Instructions FL1956_R8_II_heritage_xl_app_inst_d_april_10.pdf FL1956_R8_II_heritage_xl_app_inst_f_april_10.pdf Verified By: Robert Nieminen PE 59166 Created by Independent Third Party: No Evaluation Reports Created by Independent Third Party:
1956.9	Hip and Ridge Shingles	Hip and ridge shingles
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Hip and Ridge shingles shall be used only on roof slopes of 2:12 or greater. Nails must be used as the method of attachment		Certification Agency Certificate FL1956_R8_C_CAC_Tamko_Serv_Conf_FL_1956_2012.pdf FL1956_R8_C_CAC_UL_certification_10-11-12.pdf Quality Assurance Contract Expiration Date 10/10/2015 Installation Instructions FL1956_R8_II_12_25_x_12_Hip_Ridge_Application_Instructions.pdf FL1956_R8_II_12_x_12_Hip_Ridge_Application_Instructions.pdf FL1956_R8_II_12-1-4x12_HipRidge_Sealant_Dab_Illustrations.pdf FL1956_R8_II_12x12_HipRidge_Sealant_Dab_Illustrations.pdf Verified By: Robert Nieminen 59166 Created by Independent Third Party: No Evaluation Reports Created by Independent Third Party:

[Back](#) [Next](#)
[Contact Us](#) 1940 North Monroe Street, Tallahassee FL 32399 Phone: 850-487-1824

 The State of Florida is an AA/EEO employer [Copyright 2007-2013 State of Florida](#), [Privacy Statement](#), [Accessibility Statement](#), [Refund Statement](#)

Under Florida law, email addresses are public records. If you do not want your e-mail address released in response to a public-records request, do not send electronic mail to this entity. Instead, contact the office by phone or by traditional mail. If you have any questions, please contact 850.487.1395. *Pursuant to Section 455.275(1), Florida Statutes, effective October 1, 2012, licensees licensed under Chapter 455, F.S. must provide the Department with an email address if they have one. The emails provided may be used for official communication with the licensee. However email addresses are public record. If you do not wish to supply a personal address, please provide the Department with an email address which can be made available to the public. To determine if you are a licensee under Chapter 455, F.S., please click [here](#).

Product Approval Accepts:

