

Roof Replacement or Repair Application #72785



Tuesday, August 19, 2025 9:15 AM

Checklist:

___ Address	___ Application Submitted	
___ Drive/ROW	___ Zoning Review	___ Legal Lot of Record
___ Septic	___ Plans Reviewed	___ Flood Zone
___ Site Use Approved	___ Required Inspections Assigned	___ FDEP Needed
___ Docs Reviewed/Accepted	___ Invoiced	

APPLICANT: Marc Boutilier

PHONE: (407) 216-2782

ADDRESS: 10245 E Colonial dr Orlando, FL 32817

OWNER: PARKER-HAYNES TERRI G

PHONE: (704) 618-1710

ADDRESS: 195 SW NIGHTSHADE DR LAKE CITY, FL 32024

PARCEL ID: 30-4S-17-08898-109

SUBDIVISION: WESTER WOODS PHASE 1

LOT: 9 BLOCK: PHASE: UNIT: ACRES: 1.04

CONTRACTOR	TYPE	LIC#	BUSINESS NAME
MARC BOUTILIER	General	ccc1333919	FLORIDA PREMIER ROOFING

ROOFING JOB DETAILS

Type Roofing Job	Replacement - Tear off Existing and Replace
Further Job Details (Explain if decking is being replaced and or Repairs are being done.)	Tear off Existing shingles and Replace with New shingles. Add new Underlayment.
Type of structure	House
Further Structure Details (if needed)	
Total Estimated Cost	20000
Commercial or Residential	Residential
Roof Area (for this job) Sq Ft	
No. of Stories	1
Ventilation:	Ridge Vent
Flashing:	Replace All
Drip Edge:	Replace All
Valley Treatment:	New Metal
Roof Pitch	4:12 or Greater
Second Roof Pitch (if applicable)	
Any cable and/or race-way wiring located on or within the roof assembly?	
Is the existing roof being removed?	Yes
Explain if not removing the existing roofing material?	
Type of New Roofing Product	Asphalt Shingles
Florida Product Approval Number	FL18355-R5
Product Manufacturer	Tamko
Product Description	Asphalt Shingles
Other Roofing Product Type Not Listed	

Sealed roof decking options: (Must select an option.)

a self-adhering polymer-modified bitumen underlayment complying with ASTM D1970 applied over the entire roof.;a minimum 4-inch wide strip of selfadhering polymer-modified bitumen complying with ASTM D1970 or a minimum 3 ¾ - inch wide strip of selfadhering flexible flashing tape complying with AAMA 711, applied over all joints in the roof decking. A felt underlayment complying with ASTM D226 Type II, ASTM D4869 Type III or IV, or ASTM D6757, or a synthetic underlayment meeting the performance requirements specified, is required to be applied over the strips/tape over the entire roof.;two layers of felt underlayment comply ASTM 0226 Type II or ASTM D4869 Type III or IV, or two layers of a synthetic underlayment meeting the performance requirements specified, lapped and fastened as specified.

Sealed roof decking explanation for other option.

Review Notes: