

























TE NO.2
881.1001 SYP

TE NO.2
881.1001 SYP

RATED SHEATHING
32/16
EXPOSURE 1
THICKNESS 0.451 in.

404
PSI-22 400-406
15/32 CATEGORY

HECHO A LA MEDIDA
PARA EL MONTAJE DE
LA LAMINA EN BORDES
USAR SIN CLAVOS
O ESPALMOS

SIZED FOR SPACING
1/8 INCH AT ENDS
1/4 INCH AT SIDES
USE F-CLIPS









TP NO. 2
881 ADHLSIP

2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23









2 ON 1L
188









OSB SHEATHING
32116
EXPOSURE 1
THICKNESS 0.451
404
PSI-22 MID-RANGE
15/32 CATEGORY

SPACING
SIZED FOR
1/8 INCH
USE
HECHO A LA
PARA CUBRIR
1/8 INCH
USE

RATED SHEATHING
32116
EXPOSURE 1
THICKNESS 0.451 IN.
404
APA 15/32 CATEGORY

SIZED FOR SPACING
1/8 INCH AT ENDS
1/4 INCH AT SIDES
USE PLYCLIPS
HECHO A LA MEDIDA
PARA ESPACIOS DE
1/8 INCH EN LOS BORDOS
1/4 INCH A LOS LADOS
USE SUS PLYCLIPS
O LOS ESPACIOS





















