

BEARING HEIGHT SCHEDULE

9' PLATE

10' PLATE

3/12 PITCH

8/12 PITCH

1'-4" OVERHANG

NOTES:

- 1) REFER TO HB 91 (RECOMMENDATIONS FOR HANDLING INSTALLATION AND TEMPORARY BRACING) REFER TO ENGINEER DRAWINGS FOR PERMANENT BRACING REQUIRED
- 2) ALL TRUSSES (INCLUDING TRUSSES UNDER VALLEY FRAMING) MUST BE COME ELEVY DETAIL OR REFER TO HB 91 FOR ALTERNATE BRACING REQUIREMENTS
- 3) ALL VALLEYS ARE TO BE CONVENTIONALLY FRAMED BY BUILDER
- 4) ALL TRUSSES ARE DESIGNED FOR 2.06 MAXIMUM SPACING, UNLESS OTHERWISE NOTED
- 5) ALL WALLS SHOWN ON PLACEMENT PLAN ARE CONSIDERED TO BE LOAD BEARING, UNLESS OTHERWISE NOTED
- 6) SY42 TRUSSES MUST BE INSTALLED WITH THE TOP BEING UP
- 7) ALL ROOF TRUSSES HANGERS TO BE SIMPSON HUS26 UNLESS OTHERWISE NOTED. ALL FLOOR TRUSSES HANGERS TO BE SIMPSON TRH422 UNLESS OTHERWISE NOTED
- 8) BEAM/HEADQUARTER (RQR) TO BE FURNISHED BY BUILDER

SHOP DRAWING APPROVAL

THIS LAYOUT IS THE SOLE SOURCE FOR FABRICATION OF TRUSSES AND VOIDS. ALL PREVIOUS ARCHITECTURAL OR OTHER TRUSS LAYOUTS, REVIEW AND APPROVAL OF THIS LAYOUT MUST BE RECEIVED BEFORE ANY TRUSSES WILL BE BUILT. VERIFY ALL CONDITIONS TO PROTECT AGAINST CHANGES THAT WILL RESULT IN EXTRA CHARGES TO YOU.

Accepted: _____ Date: _____



Dunnell

PHONE 904-437-3349 FAX 904-437-3994

Jacksonville

PHONE 904-772-6100 FAX 904-772-1973

Lake City

PHONE 904-795-6644 FAX 904-795-7973

Sanford

PHONE 407-322-0059 FAX 407-322-5553

BUILDER

AARON SIMQUE

10/1/15

LOT 5 HUNTER RIDGE

SHIRCLIFF RESIDENT

DATE 3/7/05 DRAWN BY PLQ/UNT L106508

