



This home has been professionally insulated with

Owens Corning® PROPINK® L77 Loosefill Insulation

(Job Site Address)

Name 1942 Wood (Lot 8)
Address 303 SW Cadence Glen
City Lake City State FL Zip 32024

Owens Corning® PROPINK® L77 Loosefill Insulation

Owens Corning Insulating Systems, LLC will accept no responsibility when the product is not installed in accordance with the product label. Stated R-value is provided by installing the required number of bags at a thickness not less than the labeled minimum thickness. Installation of the required number of bags may yield more than the specified minimum thickness. Failure by the installer to provide both the required bags and at least the minimum thickness will result in lower insulation R-value.

Specification for Open Blow Attics

New Construction ☒
Retrofit N/A
Number of bags used 32
Estimated R-value of previous insulation N/A
Area of coverage (sq. ft.) 1917
Other type(s) of insulation in attic N/A
Thickness of insulation 13.25"
Depth of previous insulation N/A

Attics

R-value	Minimum Initial Installed Thickness (inches)	Minimum Settled Thickness	Maximum Coverage Per Bag (sq. ft.)	Minimum Bags Per 1000 sq. ft.	Minimum Weight (lbs per sq. ft.)
13	4.75	4.75	184.6	5.4	0.173
19	7.00	7.00	125.0	8.0	0.266
22	8.00	8.00	106.3	9.4	0.301
26	9.25	9.25	89.6	11.2	0.367
30	10.50	10.50	77.0	13.0	0.410
38	13.25	13.25	59.9	16.7	0.534
44	15.00	15.00	50.7	19.7	0.631
49	16.75	16.75	45.0	22.2	0.711
60	20.00	20.00	35.8	28.0	0.895

Cathedral Ceiling

R-value	Framing	Minimum Initial Installed Thickness (inches)	Installed Density (lbs per cu. ft.)	Maximum Coverage Per Bag (sq. ft.)	Minimum Bags Per 1000 sq. ft.	Minimum Weight (lbs per sq. ft.)
30	2x8	7.25	1.35	39.2	25.5	0.816
36	2x10	9.25	1.35	30.8	32.5	1.041
49	2x12	11.25	1.35	18.5	54.2	1.734

Coverage charts are based on a nominal net bag weight of 32 lbs.

Walls

R-value	Framing	Minimum Initial Installed Thickness (inches)	Installed Density (lbs per cu. ft.)	Maximum Coverage Per Bag (sq. ft.)	Minimum Bags Per 1000 sq. ft.	Minimum Weight (lbs per sq. ft.)
14	2x4	3.5	1.25	87.3	11.4	0.364
15	2x4	3.5	1.45	75.7	13.2	0.423
16	2x4	3.5	2.20	49.9	20.1	0.642
22	2x6	5.5	1.25	65.9	17.9	0.573
23	2x6	5.5	1.35	61.7	19.3	0.619
24	2x6	5.5	1.76	40.0	26.0	0.802

Floors

R-value	Framing	Minimum Initial Installed Thickness (inches)	Installed Density (lbs per cu. ft.)	Maximum Coverage Per Bag (sq. ft.)	Minimum Bags Per 1000 sq. ft.	Minimum Weight (lbs per sq. ft.)
30	2x8	7.25	1.35	39.2	25.5	0.816
36	2x10	9.25	1.35	30.8	32.5	1.041
46	2x12	11.25	1.35	26.3	39.6	1.266

Owens Corning® glass fiber blanket and loosefill thermal insulations, when installed per the manufacturers' coverage charts and recommendations, will provide the labeled R-value.

THE FOLLOWING PRODUCTS HAVE BEEN INSTALLED IN THIS HOUSE.

	Kraft	Unfaced	Foil	Loosefill	FS-25	R-value	Thickness	No. pkgs.	Coverage Area
Roof Deck	☐	☐	☐	☐	☐				
Ceilings	☐	☐	☐	☐	☐				
Floors	☐	☐	☐	☐	☐				
Walls	☐	☐	☐	☐	☐				
Basement	☐	☐	☐	☐	☐				
Crawlspace	☐	☐	☐	☐	☐				
Attic	☐	☐	☐	☒	☐	R-38	13.25"	32	1917

Contractor American Residential Products Date 11/21/25 Builder Maronda Homes Inc of Florida Date 11/21/25

Company Trenni Meyer Company

Address 6460 SE 110th St. Belleview, FL 34420 Address

Phone Phone



OWENS CORNING INSULATING SYSTEMS, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO, USA 43659
1-800-GET-PINK®
www.owenscorning.com

Pub. No. 10018804-D. Printed in U.S.A. March 2019. The color PINK is a registered trademark of Owens Corning. © 2019 Owens Corning Insulating Systems, LLC. All Rights Reserved.