

Residential System Sizing Calculation

Summary

Project Title:
1580 Model

Lake City, FL 32024


3/25/2020

Location for weather data: Gainesville, FL - Defaults: Latitude(29.7) Altitude(152 ft.) Temp Range(M)			
Humidity data: Interior RH (50%) Outdoor wet bulb (77F) Humidity difference(51gr.)			
Winter design temperature(TMY3 99%)	30 F	Summer design temperature(TMY3 99%)	94 F
Winter setpoint	70 F	Summer setpoint	75 F
Winter temperature difference	40 F	Summer temperature difference	19 F
Total heating load calculation	24575 Btuh	Total cooling load calculation	17966 Btuh
Submitted heating capacity	% of calc Btuh	Submitted cooling capacity	% of calc Btuh
Total (Electric Heat Pump)	122.1 30000	Sensible (SHR = 0.85)	166.3 25500
Heat Pump + Auxiliary(0.0kW)	122.1 30000	Latent	171.0 4500
		Total (Electric Heat Pump)	167.0 30000

WINTER CALCULATIONS

Winter Heating Load (for 1522 sqft)


Load component		Load	
Window total	182 sqft	2402 Btuh	
Wall total	1501 sqft	5198 Btuh	
Door total	68 sqft	1203 Btuh	
Ceiling total	1522 sqft	1939 Btuh	
Floor total	1522 sqft	9251 Btuh	
Infiltration	41 cfm	1804 Btuh	
Duct loss		2778 Btuh	
Subtotal		24575 Btuh	
Ventilation	0 cfm	0 Btuh	
TOTAL HEAT LOSS		24575 Btuh	



SUMMER CALCULATIONS

Summer Cooling Load (for 1522 sqft)

Load component		Load	
Window total	182 sqft	2912 Btuh	
Wall total	1501 sqft	3180 Btuh	
Door total	68 sqft	902 Btuh	
Ceiling total	1522 sqft	2133 Btuh	
Floor total		0 Btuh	
Infiltration	31 cfm	643 Btuh	
Internal gain		2580 Btuh	
Duct gain		2984 Btuh	
Sens. Ventilation	0 cfm	0 Btuh	
Blower Load		0 Btuh	
Total sensible gain		15334 Btuh	
Latent gain(ducts)		366 Btuh	
Latent gain(infiltration)		1066 Btuh	
Latent gain(ventilation)		0 Btuh	
Latent gain(internal/occupants/other)		1200 Btuh	
Total latent gain		2632 Btuh	
TOTAL HEAT GAIN		17966 Btuh	



8th Edition

EnergyGauge® System Sizing

PREPARED BY: _____

DATE: _____

[Signature]
3-24-20