

## Columbia County, Florida **Building Department**

135 NE Hernando Avenue Lake City, Florida 32055 Phone: 386-758-1008

www.columbiacountyfla.com

## **ROOFING AFFIDAVIT**

This completed form and photographs must be uploaded to your permit via online at the Application Submission login (link) Welcome to Columbia County Online (columbiacountyfla.com).

Clearly visible in the Photographs must be the permit number or address, must include a ruler or measuring device to confirm nail spacing and overlaps including drip edge, valley flashing and attic venting.



## ROOFING UNDERLAYMENT AFFIDAVIT

Columbia County, Florida Building Department 135 NE Hernando Avenue Lake City, Florida 32055

Phone: 386-758-1008

www.columbiacountyfla.com

DEPOLICE CONTROL CONTR
REQUIRED FOR WALK-IN OR PAPER SUBMITTALS
Job Address: 232 SW Crest Gln Lace City FL 32024
Thirtyame) / JANNIII (1.10
Builder, I understand to comply with the 2020 Florida Building Code 7 <sup>th</sup> Edition underlayment requirements, I
The options are summarized below
a self-adhering polymer-modified bitumen underlayment complying with ASTM D1970 applied over the entire roof.
a minimum 4-inch wide strip of selfadhering polymer-modified bitumen complying with ASTM D1970 or a minimum 3 % - inch wide strip of selfadhering flexible flashing tape complying with AAMA 711, applied over all joints in the roof decking. A felt underlayment complying with ASTM D226 Type II, ASTM D4869 Type III or IV, or ASTM D6757, or a synthetic underlayment meeting the performance requirements specified, is required to be applied over the strips/tape over the entire
two layers of felt underlayment comply ASTM 0226 Type II or ASTM D4869 Type III or IV, or and fastened as specified.
Other (explain)
Contractor/Owners Signature

## FINAL INSPECTION & CERTIFICATE OF COMPLETION:

This completed form and photographs must be uploaded to your permit via online at the Application Submission login (link) Welcome to Columbia County Online (columbia county fia.com).

Clearly visible in the Photographs must be the permit number or address and must include a ruler or measuring device to confirm nail spacing and overlaps including drip edge and valley flashing.