

Columbia County Building Permit Application

For Office Use Only Application # 6712-65 Date Received 12-20-07 By LH Permit # 1503/26560
 Zoning Official B2H Date 28.12.07 Flood Zone X FEMA Map # N/A Zoning A-1
 Land Use A-1 Elevation N/A MFE 1st above easement River N/A Plans Examiner OKJTH Date 12-26-07

Comments _____
☐ NOC ☒ EH ☒ Deed or PA ☒ Site Plan ☐ State Road Info ☐ Parent Parcel # _____
☐ Dev Permit # _____ ☐ In Floodway ☐ Letter of Authorization from Contractor
☒ Unincorporated area ☐ Incorporated area ☐ Town of Fort White ☐ Town of Fort White Compliance letter

Fax 752-2282

Name Authorized Person Signing Permit Linda or Melanie Roden Phone 752-2281

Address 307 SW Kemp St Lake City FL 32024

Owners Name Ottis Kennedy & Brenda Kennedy Phone 941-322-2251

911 Address 912 NE Fallow Dr, White Springs, FL

Contractors Name Seth Heitzman Phone 867-1295

Address POB 1046 Lake City FL 32025

Fee Simple Owner Name & Address NA

Bonding Co. Name & Address NH

Architect/Engineer Name & Address Will Myers / Nick Geisler

Mortgage Lenders Name & Address NA

Circle the correct power company - FL Power & Light - Clay Elec. - Suwannee Valley Elec. - Progress Energy

Property ID Number 05-15-17-04492-014 Estimated Cost of Construction 290K

Subdivision Name Deer Run Preserves Lot 6 Block _____ Unit _____ Phase _____

Driving Directions 1/4 mile Hwy 491 N, 13 miles past I-10, Turn R into subdivision, follow around Lot on R, (this on an unnamed unmarked road) 4th lot on right Seth Heitzman sign
 Number of Existing Dwellings on Property 0

Construction of Single family dwelling Total Acreage 20.05 Lot Size 20.05

Do you need a - Culvert Permit or Culvert Waiver or Have an Existing Drive Total Building Height 21'

Actual Distance of Structure from Property Lines - Front 1093' Side 250' Side 370' Rear 175'

Number of Stories 1 Heated Floor Area 2140 Total Heated Floor Area 2140 Roof Pitch 6-12

Application is hereby made to obtain a permit to do work and installations as indicated. I certify that no work or installation has commenced prior to the issuance of a permit and that all work be performed to meet the standards of all laws regulating construction in this jurisdiction.

Columbia County Building Permit Application

Application # _____

WARNING TO OWNER: YOUR FAILURE TO RECORD A NOTICE OF COMMENCEMENT MAY RESULT IN YOU PAYING TWICE FOR IMPROVEMENTS TO YOUR PROPERTY. A NOTICE OF COMMENCEMENT MUST BE RECORDED AND POSTED ON THE JOB SITE BEFORE THE FIRST INSPECTION. IF YOU INTEND TO OBTAIN FINANCING, CONSULT WITH YOUR LENDER OR ATTORNEY BEFORE RECORDING YOUR NOTICE OF COMMENCEMENT.

FLORIDA'S CONSTRUCTION LIEN LAW: Protect Yourself and Your Investment

According to Florida Law, those who work on your property or provide materials, and are not paid-in-full, have a right to enforce their claim for payment against your property. This claim is known as a construction lien. If your contractor fails to pay subcontractors or material suppliers or neglects to make other legally required payments, then people who are owed money may look to your property for payment, even if you have paid your contractor in full. This means if a lien is filed against your property, it could be sold against your will to pay for labor, materials or other services which your contractor may have failed to pay.

NOTICE OF RESPONSIBILITY TO BUILDING PERMITTEE:

YOU ARE HEREBY NOTIFIED as the recipient of a building permit from Columbia County, Florida, you will be held responsible to the County for any damage to sidewalks and/or road curbs and gutters, concrete features and structures, together with damage to drainage facilities, removal of sod, major changes to lot grades that result in ponding of water, or other damage to roadway and other public infrastructure facilities caused by you or your contractor, subcontractors, agents or representatives in the construction and/or improvement of the building and lot for which this permit is issued. No certificate of occupancy will be issued until all corrective work to these public infrastructures and facilities has been corrected.

OWNER'S AFFIDAVIT: I hereby certify that all the foregoing information is accurate and all work will be done in compliance with all applicable laws and regulating construction and zoning. I further understand the above written responsibilities in Columbia County for obtaining this Building Permit.

[Signature]
Owner's Signature

Affirmed under penalty of perjury to by the Owner and subscribed before me this 19 day of Dec 2007
Personally known ☒ or Produced Identification ☐

[Signature]
State of Florida Notary Signature (For the Owner)

SEAL:



Linda R. Roder
Commission #DD303275
Expires: Mar 24, 2008
Bonded Thru
Atlantic Bonding Co., Inc

CONTRACTOR'S AFFIDAVIT: By my signature I understand and agree that I have informed and provided this written statement to the owner of all the above written responsibilities in Columbia County for obtaining this Building Permit.

[Signature]
Contractor's Signature (Permittee)

Contractor's License Number CBP#1251065
Columbia County
Competency Card Number _____

Affirmed under penalty of perjury to by the Contractor and subscribed before me this 19 day of Dec 2007
Personally known ☒ or Produced Identification ☐

[Signature]
Notary Signature

SEAL:

CANON



Linda R. Roder
Commission #DD303275
Expires: Mar 24, 2008
Bonded Thru
Atlantic Bonding Co., Inc

0712-65

COLUMBIA COUNTY 9-1-1 ADDRESSING

P. O. Box 1787, Lake City, FL 32056-1787
PHONE: (386) 758-1125 * FAX: (386) 758-1365 * Email: ron_croft@columbiacountyfla.com

Addressing Maintenance

To maintain the Countywide Addressing Policy you must make application for a 9-1-1 Address at the time you apply for a building permit. The established standards for assigning and posting numbers to all principal buildings, dwellings, businesses and industries are contained in Columbia County Ordinance 2001-9. The addressing system is to enable Emergency Service Agencies to locate you in an emergency, and to assist the United States Postal Service and the public in the timely and efficient provision of services to residents and businesses of Columbia County.

DATE REQUESTED: 12/20/2007 DATE ISSUED: 12/21/2007

ENHANCED 9-1-1 ADDRESS:

972 NE FALLOW DR
WHITE SPRINGS FL 32096
PROPERTY APPRAISER PARCEL NUMBER:
05-15-17-04492-014

Remarks:

LOT 6 DEER RUN PRESERVES UNR

Address Issued By: 
Columbia County 9-1-1 Addressing / GIS Department

NOTICE: THIS ADDRESS WAS ISSUED BASED ON LOCATION INFORMATION RECEIVED FROM THE REQUESTER. SHOULD, AT A LATER DATE, THE LOCATION INFORMATION BE FOUND TO BE IN ERROR, THIS ADDRESS IS SUBJECT TO CHANGE

Approved Address

1089

DEC 21 2007


911Addressing/GIS Dept

(0712-65)

**Application for Onsite Sewage Disposal System
Construction Permit. Part II Site Plan**
Permit Application Number: 07-01023

ALL CHANGES MUST BE APPROVED BY THE COUNTY HEALTH UNIT

KENNEDY/CR 07-4205



Site Plan Submitted By Paul D. [Signature] Date 12/20/07
 Plan Approved ☒ Not Approved ☐ Date 12-24-07
 By M. [Signature] C. [Signature] CPHU

Notes: _____

Notice of Authorization

I Seth Hritzman, do hereby authorize Linda Roder or Melanie Roder,
to be my representative and act on my behalf in all aspects of applying for any

Building permit to be located in Columbia county.

Any homeowner and legal description Buddy & Brenda Kennedy

[Signature]
Contractor's signature

12-19-07
Date



Linda R. Roder
Commission #DD303275
Expires: Mar 24, 2008
Bonded Thru
Atlantic Bonding Co., Inc.

Sworn and subscribed before me this 19 day of Dec, 2007

[Signature]
Notary Public

My commission expires: _____
Commission No. _____
Personally known _____
Produced ID (Type): _____

ATN - Webbie

**Columbia County Building Department
Culvert Waiver**

**Culvert Waiver No.
000001503**

DATE: 12/28/2007 BUILDING PERMIT NO. 26560

APPLICANT LINDA RODER PHONE 752-2281

ADDRESS 387 SW KEMP COURT LAKE CITY FL 32024

OWNER OTTIS & BRENDA KENNEDY PHONE 941 322-2251

ADDRESS 972 NE FALLOW DRIVE WHITE SPRINGS FL 32096

CONTRACTOR SETH HEITZMAN PHONE 867-1295

LOCATION OF PROPERTY 441N. 13 MILES PAST I-10, TR ON FALLOW DR. 4TH LOT ON RIGHT(1/4 MILE)

SETH HEITZMAN SIGN _____

SUBDIVISION/LOT/BLOCK/PHASE/UNIT DEER RUN PRESERVE 6

PARCEL ID # 05-15-17-04492-014

I HEREBY CERTIFY THAT I UNDERSTAND AND WILL FULLY COMPLY WITH THE DECISION OF THE COLUMBIA COUNTY PUBLIC WORKS DEPARTMENT IN CONNECTION WITH THE HEREIN PROPOSED APPLICATION.

SIGNATURE: [Signature]

A SEPARATE CHECK IS REQUIRED
MAKE CHECKS PAYABLE TO BCC

Amount Paid 50.00

PUBLIC WORKS DEPARTMENT USE ONLY

I HEREBY CERTIFY THAT I HAVE EXAMINED THIS APPLICATION AND DETERMINED THAT THE
CULVERT WAIVER IS:

✓ APPROVED _____ NOT APPROVED - NEEDS A CULVERT PERMIT

COMMENTS: Private Rd

SIGNED: [Signature] DATE: 1-3-08

ANY QUESTIONS PLEASE CONTACT THE PUBLIC WORKS DEPARTMENT AT 386-752-5955.

135 NE Hernando Ave., Suite B-21
Lake City, FL 32055
Phone: 386-758-1008 Fax: 386-758-2160



Linda Roder
387 SW Hwy Ct Lake City FL 32024

NOTICE OF COMMENCEMENT

Tax Parcel Identification Number 05-15-17-04492-014

County Clerk's Office Stamp or Seal

THE UNDERSIGNED hereby gives notice that improvements will be made to certain real property, and in accordance with Section 713.13 of the Florida Statutes, the following information is provided in this NOTICE OF COMMENCEMENT.

1. Description of property (legal description): 05-15-17-04492-014
a) Street (job) Address: 912 NE Fallon Dr White Springs, FL 32096
2. General description of improvements: Single family dwelling
3. Owner Information
a) Name and address: Ottis & Brenda Kennedy
b) Name and address of fee simple titleholder (if other than owner) 8009 262nd St. East Myakka City FL 34251
c) Interest in property home site
4. Contractor Information
a) Name and address: Seth Hestemari
b) Telephone No.: 868-1295 Fax No. (Opt.) _____
5. Surety Information
a) Name and address: NA
b) Amount of Bond: _____
c) Telephone No.: _____
6. Lender
a) Name and address: NA Inst: 200712028546 Date: 12/28/2007 Time: 3:33 PM
b) Phone No. _____ DC, P. DeWitt Cason, Columbia County Page 1 of 1
7. Identity of person within the State of Florida designated by owner upon whom notices or other documents may be served
a) Name and address: NA
b) Telephone No.: _____ Fax No. (Opt.) _____
8. In addition to himself, owner designates the following person to receive a copy of the Lienor's Notice as provided in Section 713.13(1)(b), Florida Statutes:
a) Name and address: NA
b) Telephone No.: _____ Fax No. (Opt.) _____
9. Expiration date of Notice of Commencement (the expiration date is one year from the date of recording unless a different date is specified): _____

WARNING TO OWNER: ANY PAYMENTS MADE BY THE OWNER AFTER THE EXPIRATION OF THE NOTICE OF COMMENCEMENT ARE CONSIDERED IMPROPER PAYMENTS UNDER CHAPTER 713, PART 1, SECTION 713.13, FLORIDA STATUTES, AND CAN RESULT IN YOUR PAYING TWICE FOR IMPROVEMENTS TO YOUR PROPERTY; A NOTICE OF COMMENCEMENT MUST BE RECORDED AND POSTED ON THE JOB SITE BEFORE THE FIRST INSPECTION. IF YOU INTEND TO OBTAIN FINANCING, CONSULT YOUR LENDER OR AN ATTORNEY BEFORE COMMENCING WORK OR RECORDING YOUR NOTICE OF COMMENCEMENT.

STATE OF FLORIDA
COUNTY OF COLUMBIA



Linda R. Roder
Commission #DD303275
Expires: Mar 24, 2008
Bonded Thru
Atlantic Bonding Co., Inc.

10. [Signature]
Signature of Owner or Owner's Authorized Office/Director/Partner/Manager
Ottis L. Kennedy
Print Name

The foregoing instrument was acknowledged before me, a Florida Notary, this 27 day of Dec, 2007, by:
Linda Roder as Notary (type of authority, e.g. officer, trustee, attorney
fact) for Ottis Kennedy (name of party on behalf of whom instrument was executed).

Personally Known _____ OR Produced Identification ✓ Type DL

Notary Signature [Signature] Notary Stamp or Seal: _____

—AND—

11. Verification pursuant to Section 92.525, Florida Statutes. Under penalties of perjury, I declare that I have read the foregoing and that the facts stated in it are true to the best of my knowledge and belief.

Inst. Number: 200712024189 Book: 1134 Page: 1880 Date: 10/29/2007 Time: 1:27:00 PM Page 1 of 3

This instrument prepared by:
William J. Haley, Esquire
Brannon, Brown,
Haley & Bullock, P. A.
P. O. Box 1029
Lake City, FL 32056-1029

Inst:200712024189 Date:10/29/2007 Time:1:27 PM
Doc Stamp-Deed:896.00
DC, P. DeWitt Cason, Columbia County Page 1 of 3

WARRANTY DEED

THIS INDENTURE, made this 29th day of October, 2007, between **ZACHARIAH P. COOK A/K/A ZAC COOK and KIM N. HEITZMAN**, not residing on the property, but who reside at 263 SW Erin Glen, Lake City, Florida 32024, and 7199 SW State Road 47, Lake City, Florida 32024, respectively, hereinafter referred to as Grantors and **OTTIS L. KENNEDY and BRENDA T. KENNEDY**, husband and wife, having a mailing address of 8009 262nd Street East, Myakka City, Florida 34251, hereinafter referred to as Grantees.

WITNESSETH: That said Grantor, for and in consideration of the sum of \$10.00 and other good and valuable considerations to said Grantor in hand paid by said Grantees, the receipt and sufficiency of which are hereby acknowledged, have granted, bargained and sold to the said Grantees, and Grantees' successors and assigns forever, the following described land, situate, lying and being in **Columbia County, Florida**, to-wit:

**SEE EXHIBIT "A" ATTACHED HERETO
AND INCORPORATED HEREIN BY THIS REFERENCE.**

PARCEL I.D. NO.: 05-1S-17-04492-006

SUBJECT TO: Taxes and special assessments for the year 2007 and subsequent years; restrictions, reservations, rights of way for public roads, and easements of record, if any; and zoning and any other governmental restrictions regulating the use of the lands.

and said Grantor does hereby fully warrant the title to said lands and will defend the same against the lawful claims of all persons whomsoever.

Inst. Number: 200712024189 Book: 1134 Page: 1881 Date: 10/29/2007 Time: 1:27:00 PM Page 2 of 3

IN WITNESS WHEREOF, Grantor has hereunto set his hand and seal the day and year first above written.

Signed, sealed and delivered
in the presence of:

Print Name: William J. HeleyZachariah P. Cook a/k/a Zac CookPrint Name: Debbie G. MooreKim N. Heitzman

**STATE OF FLORIDA
COUNTY OF COLUMBIA**

The foregoing instrument was acknowledged before me this 29th day of October, 2007, by Zachariah P. Cook a/k/a Zac Cook and Kim N. Heitzman, who are personally known to me, or whom produced Florida Driver's Licenses as identification.

Debbie G. Moore
Print Name: Debbie G. Moore
Notary Public, State of Florida



Debbie G. Moore
Commission # DD400475
Expires March 16, 2009
Bonded Troy Fair - Insurance, Inc. 800-385-7019

SCHEDULE "A"**LOT 6 OF DEER RUN PRESERVES, UNRECORDED:**

COMMENCE AT THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 5, TOWNSHIP 1 SOUTH, RANGE 17 EAST, COLUMBIA COUNTY, FLORIDA, AND RUN SOUTH 88 DEG. 09 MIN. 53 SEC. WEST ALONG THE NORTH LINE OF THE SOUTHEAST 1/4 OF SAID SECTION 5, A DISTANCE OF 655.0 FEET FOR A POINT OF BEGINNING; THENCE CONTINUE SOUTH 88 DEG. 09 MIN. 53 SEC. WEST, A DISTANCE OF 655.0 FEET; THENCE SOUTH 01 DEG. 57 MIN. 24 SEC. EAST, A DISTANCE OF 1333.26 FEET; THENCE NORTH 88 DEG. 14 MIN. 14 SEC. EAST, A DISTANCE OF 655.0 FEET; THENCE NORTH 01 DEG. 57 MIN. 24 SEC. WEST, A DISTANCE OF 1334.08 FEET TO THE POINT OF BEGINNING.

SUBJECT TO: EASEMENT FOR INGRESS, EGRESS AND UTILITIES OVER AND ACROSS THE SOUTH 50.00 FEET THEREOF AND THE SOUTH 909.58 FEET OF THE EAST 50.00 FEET THEREOF AND THE WEST 215.00 FEET TO THE NORTH 80.00 FEET THEREOF, AND ALSO THAT PART OF THE 100.00 FOOT WIDE EASEMENT OTHERWISE CONTAINED WITHIN THE BOUNDS OF THIS PARCEL DESCRIBED BELOW:

A PART OF THE SOUTH 1/2 OF SECTION 5, TOWNSHIP 1 SOUTH, RANGE 17 EAST, COLUMBIA COUNTY, FLORIDA, BEING A 60 FOOT WIDE EASEMENT FOR INGRESS AND EGRESS AND FOR UTILITIES, 30 FEET LEFT AND 30 FEET RIGHT OF THE FOLLOWING DESCRIBED CENTERLINE: COMMENCE AT THE SOUTHEAST CORNER OF SAID SECTION 5, AND RUN NORTH 01 DEG. 57 MIN. 24 SEC. WEST, ALONG THE EAST LINE OF SAID SECTION 5, A DISTANCE OF 1334.91 FEET FOR A POINT OF BEGINNING. THENCE SOUTH 88 DEG. 14 MIN. 14 SEC. WEST, A DISTANCE OF 655 FEET TO A POINT HEREINAFTER KNOWN AS POINT "A"; THENCE CONTINUE NORTH 88 DEG. 14 MIN. 14 SEC. WEST, A DISTANCE OF 716.92 FEET; THENCE RETURN TO A POINT "A" AND RUN NORTH 01 DEG. 57 MIN. 24 SEC. WEST, A DISTANCE OF 909.58 FEET; THENCE NORTH 50 DEG. 12 MIN. 22 SEC. WEST, A DISTANCE OF 593.41 FEET TO A POINT THAT LIES 30 FEET SOUTH OF THE NORTH LINE OF THE SOUTH 1/4 OF SAID SECTION 5; THENCE SOUTH 88 DEG. 09 MIN. 22 SEC. WEST, PARALLEL WITH THE NORTH LINE OF THE SOUTH 1/2 OF SAID SECTION 5, A DISTANCE OF 1537.22 FEET; THENCE SOUTH 88 DEG. 10 MIN. 06 SEC. WEST, STILL PARALLEL WITH THE NORTH LINE OF THE SAID SOUTH 1/2 OF SECTION 5, A DISTANCE OF 1051.05 FEET; THENCE SOUTH 01 DEG. 39 MIN. 41 SEC. EAST, A DISTANCE OF 276.94 FEET; THENCE SOUTH 46 DEG. 46 MIN. 15 SEC. WEST, A DISTANCE OF 480.67 FEET; THENCE SOUTH 88 DEG. 20 MIN. 19 SEC. WEST, A DISTANCE OF 1042.87 FEET TO THE EASTERLY RIGHT OF WAY LINE OF U.S. HIGHWAY NO. 441 FOR A POINT OF TERMINATION OF SAID CENTERLINE.

Lot 6

Deer Run

Offis + Brenda

Kennedy


20.05 Acres

Deer Run


Preserves

05-15-17-04492-014

1333'



unmarked road



Revised site plan

unmarked road

Lot 6

Deer Run Preserves

05-15-17-64492-014

20 acres

Ottis + Brenda
Kennedy

1333'

1093'

300'

drive

250'

well

175'


370'


1333'

655'

N

655'





0712-65

FROM :

FRX NO. : 386-755-7022

Sep. 17 2002 01:52PM P1

HALL'S PUMP & WELL SERVICE, INC.

SPECIALIZING IN 4" & 6" WELLS



DONALD AND MARY HALL
OWNERS

PHONE (804) 783-1004
FAX (804) 783-7000
JENNIFER HALL, OWNER
LAKE CITY, FLORIDA 33508
904 NW Main Blvd.


June 12, 2002

NOTICE TO ALL CONTRACTORS

Please be advised that due to the new building codes we will use a large capacity diaphragm tank on all new wells. This will insure a minimum of one (1) minute draw down or one (1) minute refill. If a smaller diaphragm tank is used then we will install a cycle stop valve which will produce the same results.

If you have any questions please feel free to call our office anytime.

Thank you,


Donald D. Hall
DDH/jk

FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Community Affairs
Residential Whole Building Performance Method A

Project Name: **Seth Heitzman Construction - Kennedy**
Address: **Lot: 6, Sub: Deer Run, Plat:**
City, State: **Lake City, FL 32055-**
Owner: **Buddy & Brenda Kennedy**
Climate Zone: **North**

Builder: **Seth Heitzman Const.**
Permitting Office: **Columbia**
Permit Number: **26560**
Jurisdiction Number: **221000**

1. New construction or existing New
2. Single family or multi-family Single family
3. Number of units, if multi-family 1
4. Number of Bedrooms 2
5. Is this a worst case? No
6. Conditioned floor area (ft²) 2140 ft²
7. Glass type¹ and area: (Label reqd. by 13-104.4.5 if not default)

a. U-factor:	Description	Area
(or Single or Double DEFAULT)	7a. (Dble Default)	224.0 ft ²
b. SHGC:		
(or Clear or Tint DEFAULT)	7b. (Clear)	224.0 ft ²
8. Floor types

a. Slab-On-Grade Edge Insulation	R=5.0.	193.0(p) ft
b. N/A		
c. N/A		
9. Wall types

a. Frame, Wood, Exterior	R=19.0.	1214.0 ft ²
b. Frame, Wood, Adjacent	R=13.0.	259.0 ft ²
c. N/A		
d. N/A		
e. N/A		
10. Ceiling types

a. Under Attic	R=30.0.	2140.0 ft ²
b. N/A		
c. N/A		
11. Ducts

a. Sup: Unc. Ret: Unc. Att: Garage	Sup. R=6.0.	60.0 ft
b. N/A		

12. Cooling systems

a. Central Unit	Cap: 41.0 kBtu/hr
	SEER: 13.00
b. N/A	
c. N/A	
13. Heating systems

a. Electric Heat Pump	Cap: 41.0 kBtu/hr
	HSPF: 7.70
b. N/A	
c. N/A	
14. Hot water systems

a. Electric Resistance	Cap: 80.0 gallons
	EF: 0.90
b. N/A	
c. Conservation credits	
(IIR-Heat recovery, Solar	
DHP-Dedicated heat pump)	
15. HVAC credits PT:

(CF-Ceiling fan, CV-Cross ventilation,	
IIF-Whole house fan,	
PT-Programmable Thermostat,	
MZ-C-Multizone cooling,	
MZ-H-Multizone heating)	

Glass/Floor Area: 0.10

Total as-built points: 20118

Total base points: 24621

PASS

I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.

PREPARED BY: *[Signature]*

DATE: 12-4-07

I hereby certify that this building, as designed, is in compliance with the Florida Energy Code.

OWNER/AGENT: *[Signature]*

DATE: 12-18-07

Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.

BUILDING OFFICIAL: _____

DATE: _____



¹ Predominant glass type. For actual glass type and areas, see Summer & Winter Glass output on pages 2&4.

SUMMER CALCULATIONS

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 6, Sub: Deer Run, Plat: , Lake City, FL, 32055-

PERMIT #:

BASE				AS-BUILT								
GLASS TYPES												
.18 X Conditioned X BSPM = Points Floor Area				Type/SC	Overhang Ornt Len Hgt		Area X SPM X SOF = Points					
.18	2140.0	18.59	7161.0	1.Double, Clear	W	16.5	9.0	120.0	38.52	0.42	1928.0	
				2.Double, Clear	W	16.5	9.0	9.0	38.52	0.42	144.0	
				3.Double, Clear	N	1.5	9.0	30.0	19.20	0.98	561.0	
				4.Double, Clear	N	1.5	9.0	16.0	19.20	0.98	299.0	
				5.Double, Clear	E	6.5	9.0	30.0	42.06	0.60	762.0	
				6.Double, Clear	S	1.5	9.0	4.0	35.87	0.94	135.0	
				7.Double, Clear	S	1.5	9.0	15.0	35.87	0.94	507.0	
				As-Built Total:		224.0			4336.0			
WALL TYPES		Area X BSPM = Points		Type	R-Value		Area X SPM = Points					
Adjacent	259.0	0.70	181.3	1. Frame, Wood, Exterior	19.0		1214.0	0.90	1092.6			
Exterior	1214.0	1.70	2063.8	2. Frame, Wood, Adjacent	13.0		259.0	0.60	155.4			
Base Total:		1473.0	2245.1	As-Built Total:		1473.0			1248.0			
DOOR TYPES		Area X BSPM = Points		Type	Area X SPM = Points							
Adjacent	20.0	2.40	48.0	1.Exterior Insulated				20.0	4.10	82.0		
Exterior	20.0	6.10	122.0	2.Adjacent Insulated				20.0	1.60	32.0		
Base Total:		40.0	170.0	As-Built Total:		40.0			114.0			
CEILING TYPES		Area X BSPM = Points		Type	R-Value		Area X SPM X SCM = Points					
Under Attic	2140.0	1.73	3702.2	1. Under Attic	30.0		2140.0	1.73 X 1.00		3702.2		
Base Total:		2140.0	3702.2	As-Built Total:		2140.0			3702.2			
FLOOR TYPES		Area X BSPM = Points		Type	R-Value		Area X SPM = Points					
Slab	193.0(p)	-37.0	-7141.0	1. Slab-On-Grade Edge Insulation	5.0		193.0(p)	-36.20		-6986.6		
Raised	0.0	0.00	0.0									
Base Total:		-7141.0		As-Built Total:		193.0			-6986.6			
INFILTRATION		Area X BSPM = Points		Area X SPM = Points								
		2140.0	10.21			2140.0			10.21		21849.4	

SUMMER CALCULATIONS

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 6, Sub: Deer Run, Plat: , Lake City, FL, 32055-

PERMIT #:

BASE				AS-BUILT							
Summer Base Points: 27986.7				Summer As-Built Points: 24263.0							
Total Summer Points	X System Multiplier	=	Cooling Points	Total Component (System - Points)	X Cap Ratio	X Duct Multiplier (DM x DSM x AHU)	X System Multiplier	X Credit Multiplier	=	Cooling Points	
27986.7	0.3250		9095.7	(sys 1: Central Unit 41000btuh, SEER/EFF(13.0) Ducts:Unc(S),Unc(R),Gar(AH),R6.0(INS) 24263 1.00 (1.09 x 1.147 x 1.00) 0.260 0.950 7492.6 24263.0 1.00 1.250 0.260 0.950 7492.6							

WINTER CALCULATIONS

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 6, Sub: Deer Run, Plat: , Lake City, FL, 32055-

PERMIT #:

BASE				AS-BUILT								
GLASS TYPES												
.18 X Conditioned X BWPM = Points Floor Area				Type/SC	Overhang Ornt Len Hgt		Area X WPM X WOF = Points					
.18	2140.0	20.17	7769.0	1.Double, Clear	W	16.5	9.0	120.0	20.73	1.22	3031.0	
				2.Double, Clear	W	16.5	9.0	9.0	20.73	1.22	227.0	
				3.Double, Clear	N	1.5	9.0	30.0	24.58	1.00	737.0	
				4.Double, Clear	N	1.5	9.0	16.0	24.58	1.00	393.0	
				5.Double, Clear	E	6.5	9.0	30.0	18.79	1.20	677.0	
				6.Double, Clear	S	1.5	9.0	4.0	13.30	1.02	54.0	
				7.Double, Clear	S	1.5	9.0	15.0	13.30	1.02	204.0	
				As-Built Total:				224.0		5323.0		
WALL TYPES Area X BWPM = Points				Type	R-Value		Area X WPM = Points					
Adjacent	259.0	3.60	932.4	1. Frame, Wood, Exterior	19.0		1214.0	2.20	2670.8			
Exterior	1214.0	3.70	4491.8	2. Frame, Wood, Adjacent	13.0		259.0	3.30	854.7			
Base Total: 1473.0 5424.2				As-Built Total:				1473.0		3525.5		
DOOR TYPES Area X BWPM = Points				Type	Area X WPM = Points							
Adjacent	20.0	11.50	230.0	1.Exterior Insulated				20.0	8.40	168.0		
Exterior	20.0	12.30	246.0	2.Adjacent Insulated				20.0	8.00	160.0		
Base Total: 40.0 476.0				As-Built Total:					40.0		328.0	
CEILING TYPES Area X BWPM = Points				Type	R-Value		Area X WPM X WCM = Points					
Under Attic	2140.0	2.05	4387.0	1. Under Attic	30.0		2140.0	2.05 X 1.00		4387.0		
Base Total: 2140.0 4387.0				As-Built Total:					2140.0		4387.0	
FLOOR TYPES Area X BWPM = Points				Type	R-Value		Area X WPM = Points					
Slab	193.0(p)	8.9	1717.7	1. Slab-On-Grade Edge Insulation	5.0		193.0(p)	7.60	1466.8			
Raised	0.0	0.00	0.0									
Base Total: 1717.7				As-Built Total:					193.0		1466.8	
INFILTRATION Area X BWPM = Points				Area X WPM = Points								
2140.0 -0.59 -1262.6				2140.0 -0.59 -1262.6								

WINTER CALCULATIONS

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 6, Sub: Deer Run, Plat: , Lake City, FL, 32055-

PERMIT #:

BASE			AS-BUILT						
Winter Base Points: 18511.3			Winter As-Built Points: 13767.7						
Total Winter Points	X System Multiplier	= Heating Points	Total Component (System - Points)	X Cap Ratio	X Duct Multiplier (DM x DSM x AHU)	X System Multiplier	X Credit Multiplier	= Heating Points	
18511.3	0.5540	10255.3	(sys 1: Electric Heat Pump 41000 btuh ,EFF(7.7) Ducts:Unc(S),Unc(R),Gar(AH),R6.0 13767.7 1.000 (1.069 x 1.169 x 1.00) 0.443 0.950 7238.4 13767.7 1.00 1.250 0.443 0.950 7238.4						

WATER HEATING & CODE COMPLIANCE STATUS**Residential Whole Building Performance Method A - Details**

ADDRESS: Lot: 6, Sub: Deer Run, Plat: , Lake City, FL, 32055-

PERMIT #:

BASE				AS-BUILT					
WATER HEATING									
Number of Bedrooms	X	Multiplier	= Total	Tank Volume	EF	Number of Bedrooms	X	Tank X Ratio	Multiplier X Credit = Total Multiplier
2		2635.00	5270.0	80.0	0.90	2		1.00	2693.58 1.00
				As-Built Total:					5387.1

CODE COMPLIANCE STATUS							
BASE				AS-BUILT			
Cooling Points	+	Heating Points	= Total Points	Cooling Points	+	Heating Points	= Total Points
9096		10255	24621	7493		7238	20118

PASS

Code Compliance Checklist

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 6, Sub: Deer Run, Plat: , Lake City, FL, 32055-

PERMIT #:

6A-21 INFILTRATION REDUCTION COMPLIANCE CHECKLIST

COMPONENTS	SECTION	REQUIREMENTS FOR EACH PRACTICE	CHECK
Exterior Windows & Doors	606.1.ABC.1.1	Maximum: 3 cfm/sq.ft. window area; 5 cfm/sq.ft. door area.	
Exterior & Adjacent Walls	606.1.ABC.1.2.1	Caulk, gasket, weatherstrip or seal between: windows/doors & frames, surrounding wall; foundation & wall sole or sill plate; joints between exterior wall panels at corners; utility penetrations; between wall panels & top/bottom plates; between walls and floor. EXCEPTION: Frame walls where a continuous infiltration barrier is installed that extends from, and is sealed to, the foundation to the top plate.	
Floors	606.1.ABC.1.2.2	Penetrations/openings > 1/8" sealed unless backed by truss or joint members. EXCEPTION: Frame floors where a continuous infiltration barrier is installed that is sealed to the perimeter, penetrations and seams.	
Ceilings	606.1.ABC.1.2.3	Between walls & ceilings; penetrations of ceiling plane of top floor; around shafts, chases, soffits, chimneys, cabinets sealed to continuous air barrier; gaps in gyp board & top plate; attic access. EXCEPTION: Frame ceilings where a continuous infiltration barrier is installed that is sealed at the perimeter, at penetrations and seams.	
Recessed Lighting Fixtures	606.1.ABC.1.2.4	Type IC rated with no penetrations, sealed; or Type IC or non-IC rated, installed inside a sealed box with 1/2" clearance & 3" from insulation; or Type IC rated with < 2.0 cfm from conditioned space, tested.	
Multi-story Houses	606.1.ABC.1.2.5	Air barrier on perimeter of floor cavity between floors.	
Additional Infiltration reqts	606.1.ABC.1.3	Exhaust fans vented to outdoors, dampers; combustion space heaters comply with NFPA, have combustion air.	

6A-22 OTHER PRESCRIPTIVE MEASURES (must be met or exceeded by all residences.)

COMPONENTS	SECTION	REQUIREMENTS	CHECK
Water Heaters	612.1	Comply with efficiency requirements in Table 612.1.ABC.3.2. Switch or clearly marked circuit breaker (electric) or cutoff (gas) must be provided. External or built-in heat trap required.	
Swimming Pools & Spas	612.1	Spas & heated pools must have covers (except solar heated). Non-commercial pools must have a pump timer. Gas spa & pool heaters must have a minimum thermal efficiency of 78%.	
Shower heads	612.1	Water flow must be restricted to no more than 2.5 gallons per minute at 80 PSIG.	
Air Distribution Systems	610.1	All ducts, fittings, mechanical equipment and plenum chambers shall be mechanically attached, sealed, insulated, and installed in accordance with the criteria of Section 610. Ducts in unconditioned attics: R-6 min. insulation.	
HVAC Controls	607.1	Separate readily accessible manual or automatic thermostat for each system.	
Insulation	604.1, 602.1	Ceilings-Min. R-19. Common walls-Frame R-11 or CBS R-3 both sides. Common ceiling & floors R-11.	

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE SCORE* = 87.9

The higher the score, the more efficient the home.

Buddy & Brenda Kennedy, Lot: 6, Sub: Deer Run, Plat: , Lake City, FL, 32055-

1. New construction or existing	New	___	12. Cooling systems	
2. Single family or multi-family	Single family	___	a. Central Unit	Cap: 41.0 kBtu/hr
3. Number of units, if multi-family	1	___		SEER: 13.00
4. Number of Bedrooms	2	___	b. N/A	___
5. Is this a worst case?	No	___	c. N/A	___
6. Conditioned floor area (ft ²)	2140 ft ²	___		___
7. Glass type ¹ and area: (Label reqd. by 13-104.4.5 if not default)		___	13. Heating systems	
a. U-factor:	Description Area		a. Electric Heat Pump	Cap: 41.0 kBtu/hr
(or Single or Double DEFAULT)	7a. (Dble Default) 224.0 ft ²	___		HSPF: 7.70
b. SHGC:		___	b. N/A	___
(or Clear or Tint DEFAULT)	7b. (Clear) 224.0 ft ²	___	c. N/A	___
8. Floor types		___	14. Hot water systems	
a. Slab-On-Grade Edge Insulation	R=5.0, 193.0(p) ft ²	___	a. Electric Resistance	Cap: 80.0 gallons
b. N/A	___	___		EF: 0.90
c. N/A	___	___	b. N/A	___
9. Wall types		___	c. Conservation credits	___
a. Frame, Wood, Exterior	R=19.0, 1214.0 ft ²	___	(HR-Heat recovery, Solar	
b. Frame, Wood, Adjacent	R=13.0, 259.0 ft ²	___	DHP-Dedicated heat pump)	
c. N/A	___	___	15. HVAC credits	PT, ___
d. N/A	___	___	(CF-Ceiling fan, CV-Cross ventilation,	
e. N/A	___	___	HF-Whole house fan,	
10. Ceiling types		___	PT-Programmable Thermostat,	
a. Under Attic	R=30.0, 2140.0 ft ²	___	MZ-C-Multizone cooling,	
b. N/A	___	___	MZ-H-Multizone heating)	
c. N/A	___	___		
11. Ducts		___		
a. Sup: Unc. Ret: Unc. AH: Garage	Sup. R=6.0, 60.0 ft ²	___		
b. N/A	___	___		

I certify that this home has complied with the Florida Energy Efficiency Code For Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature: _____

Date: _____

Address of New Home: _____

City/FL Zip: _____



**NOTE: The home's estimated energy performance score is only available through the FLA/RES computer program. This is not a Building Energy Rating. If your score is 80 or greater (or 86 for a US EPA/DOE EnergyStar™ designation), your home may qualify for energy efficiency mortgage (EEM) incentives if you obtain a Florida Energy Gauge Rating. Contact the Energy Gauge Hotline at 321/638-1492 or see the Energy Gauge web site at www.fsec.ucf.edu for information and a list of certified Raters. For information about Florida's Energy Efficiency Code For Building Construction, contact the Department of Community Affairs at 850/487-1824.*

¹ Predominant glass type. For actual glass type and areas, see Summer & Winter Glass output on pages 2&4.
EnergyGauge® (Version: FLRCPB v4.5.2)

Residential System Sizing Calculation

Summary

Buddy & Brenda Kennedy

Project Title:
Seth Heitzman Construction - Kennedy

Code Only
Professional Version
Climate: North

Lake City, FL 32055-


12/4/2007

Location for weather data: Gainesville - Defaults: Latitude(29) Altitude(152 ft.) Temp Range(M)			
Humidity data: Interior RH (50%) Outdoor wet bulb (77F) Humidity difference(54gr.)			
Winter design temperature	33 F	Summer design temperature	92 F
Winter setpoint	70 F	Summer setpoint	75 F
Winter temperature difference	37 F	Summer temperature difference	17 F
Total heating load calculation	34168 Btuh	Total cooling load calculation	46319 Btuh
Submitted heating capacity	% of calc Btuh	Submitted cooling capacity	% of calc Btuh
Total (Electric Heat Pump)	120.0 41000	Sensible (SHR = 0.75)	86.0 30750
Heat Pump + Auxiliary(0.0kW)	120.0 41000	Latent	97.1 10250
		Total (Electric Heat Pump)	88.5 41000

WINTER CALCULATIONS

Winter Heating Load (for 2140 sqft)


Load component		Load	
Window total	224 sqft	7211	Btuh
Wall total	1473 sqft	4322	Btuh
Door total	40 sqft	518	Btuh
Ceiling total	2140 sqft	2522	Btuh
Floor total	193 sqft	3158	Btuh
Infiltration	257 cfm	10402	Btuh
Duct loss		6038	Btuh
Subtotal		34168	Btuh
Ventilation	0 cfm	0	Btuh
TOTAL HEAT LOSS		34168	Btuh



SUMMER CALCULATIONS

Summer Cooling Load (for 2140 sqft)

Load component		Load	
Window total	224 sqft	13189	Btuh
Wall total	1473 sqft	2211	Btuh
Door total	40 sqft	392	Btuh
Ceiling total	2140 sqft	3544	Btuh
Floor total		0	Btuh
Infiltration	225 cfm	4182	Btuh
Internal gain		3320	Btuh
Duct gain		8926	Btuh
Sens. Ventilation	0 cfm	0	Btuh
Total sensible gain		35763	Btuh
Latent gain(ducts)		1544	Btuh
Latent gain(infiltration)		8212	Btuh
Latent gain(ventilation)		0	Btuh
Latent gain(internal/occupants/other)		800	Btuh
Total latent gain		10556	Btuh
TOTAL HEAT GAIN		46319	Btuh



Version 8
For Florida residences only

EnergyGauge® System Sizing

PREPARED BY: [Signature]

DATE: 12-4-07

EnergyGauge® FLRCPB v4.5.2

System Sizing Calculations - Winter

Residential Load - Whole House Component Details

Buddy & Brenda Kennedy

Project Title:

Seth Heitzman Construction - Kennedy

Code Only

Professional Version

Climate: North

Lake City, FL 32055-

Reference City: Gainesville (Defaults) Winter Temperature Difference: 37.0 F

12/4/2007

Component Loads for Whole House

Window	Panes/SHGC/Frame/U	Orientation	Area(sqft)	X	HTM=	Load
1	2, Clear, Metal, 0.87	W	120.0		32.2	3863 Btuh
2	2, Clear, Metal, 0.87	W	9.0		32.2	290 Btuh
3	2, Clear, Metal, 0.87	N	30.0		32.2	966 Btuh
4	2, Clear, Metal, 0.87	N	16.0		32.2	515 Btuh
5	2, Clear, Metal, 0.87	E	30.0		32.2	966 Btuh
6	2, Clear, Metal, 0.87	S	4.0		32.2	129 Btuh
7	2, Clear, Metal, 0.87	S	15.0		32.2	483 Btuh
Window Total			224(sqft)			7211 Btuh
Walls	Type	R-Value	Area	X	HTM=	Load
1	Frame - Wood - Ext(0.08)	19.0	1214		2.9	3471 Btuh
2	Frame - Wood - Adj(0.09)	13.0	259		3.3	851 Btuh
Wall Total			1473			4322 Btuh
Doors	Type		Area	X	HTM=	Load
1	Insulated - Exterior		20		12.9	259 Btuh
2	Insulated - Adjacent		20		12.9	259 Btuh
Door Total			40			518 Btuh
Ceilings	Type/Color/Surface	R-Value	Area	X	HTM=	Load
1	Vented Attic/D/Shin	30.0	2140		1.2	2522 Btuh
Ceiling Total			2140			2522 Btuh
Floors	Type	R-Value	Size	X	HTM=	Load
1	Slab On Grade	5	193.0 ft(p)		16.4	3156 Btuh
Floor Total			193			3156 Btuh
Envelope Subtotal:						17728 Btuh
Infiltration	Type	ACH X Volume(cuft)	walls(sqft)	CFM=		Load
	Natural	0.80	19260	1473	256.8	10402 Btuh
Ductload					(DLM of 0.215)	6038 Btuh
All Zones	Sensible Subtotal All Zones					34168 Btuh

WHOLE HOUSE TOTALS

	Subtotal Sensible	34168 Btuh
	Ventilation Sensible	0 Btuh
	Total Btuh Loss	34168 Btuh

Manual J Winter Calculations

Residential Load - Component Details (continued)

Buddy & Brenda Kennedy

Project Title:

Seth Heitzman Construction - Kennedy

Code Only
Professional Version
Climate: North

Lake City, FL 32055-

12/4/2007

EQUIPMENT

1. Electric Heat Pump	#	41000 Btuh
-----------------------	---	------------

Key: Window types (SHGC - Shading coefficient of glass as SHGC numerical value or as clear or tint)
(Frame types - metal, wood or insulated metal)
(U - Window U-Factor or 'DEF' for default)
(HTM - ManualJ Heat Transfer Multiplier)

Key: Floor size (perimeter(p) for slab-on-grade or area for all other floor types)



Version 8
For Florida residences only

System Sizing Calculations - Winter

Residential Load - Room by Room Component Details

Buddy & Brenda Kennedy

Project Title:

Code Only

Seth Heitzman Construction - Kennedy

Professional Version

Lake City, FL 32055-

Climate: North

Reference City: Gainesville (Defaults) Winter Temperature Difference: 37.0 F

12/4/2007

Component Loads for Zone #1: Main

Window	Panes/SHGC/Frame/U	Orientation	Area(sqft)	X	HTM=	Load
1	2, Clear, Metal, 0.87	W	120.0		32.2	3863 Btuh
2	2, Clear, Metal, 0.87	W	9.0		32.2	290 Btuh
3	2, Clear, Metal, 0.87	N	30.0		32.2	966 Btuh
4	2, Clear, Metal, 0.87	N	16.0		32.2	515 Btuh
5	2, Clear, Metal, 0.87	E	30.0		32.2	966 Btuh
6	2, Clear, Metal, 0.87	S	4.0		32.2	129 Btuh
7	2, Clear, Metal, 0.87	S	15.0		32.2	483 Btuh
Window Total			224(sqft)			7211 Btuh
Walls	Type	R-Value	Area	X	HTM=	Load
1	Frame - Wood - Ext(0.08)	19.0	1214		2.9	3471 Btuh
2	Frame - Wood - Adj(0.09)	13.0	259		3.3	851 Btuh
Wall Total			1473			4322 Btuh
Doors	Type		Area	X	HTM=	Load
1	Insulated - Exterior		20		12.9	259 Btuh
2	Insulated - Adjacent		20		12.9	259 Btuh
Door Total			40			518 Btuh
Ceilings	Type/Color/Surface	R-Value	Area	X	HTM=	Load
1	Vented Attic/D/Shin	30.0	2140		1.2	2522 Btuh
Ceiling Total			2140			2522 Btuh
Floors	Type	R-Value	Size	X	HTM=	Load
1	Slab On Grade	5	193.0 ft(p)		16.4	3156 Btuh
Floor Total			193			3156 Btuh
Zone Envelope Subtotal:						17728 Btuh
Infiltration	Type	ACH X	Volume(cuft)	walls(sqft)	CFM=	
	Natural	0.80	19260	1473	256.8	10402 Btuh
Ductload	Average sealed, Supply(R6.0-Attic), Return(R6.0-Attic) (DLM of 0.215)					8038 Btuh
Zone #1	Sensible Zone Subtotal					34168 Btuh

Manual J Winter Calculations

Residential Load - Component Details (continued)

Buddy & Brenda Kennedy

Project Title:

Seth Heitzman Construction - Kennedy

Code Only

Professional Version

Climate: North

Lake City, FL 32055-

12/4/2007

WHOLE HOUSE TOTALS

	Subtotal Sensible	34168 Btuh
	Ventilation Sensible	0 Btuh
	Total Btuh Loss	34168 Btuh

EQUIPMENT

1. Electric Heat Pump	#	41000 Btuh
-----------------------	---	------------

Key: Window types (SHGC - Shading coefficient of glass as SHGC numerical value or as clear or tint)
 (Frame types - metal, wood or insulated metal)
 (U - Window U-Factor or 'DEF' for default)
 (HTM - ManualJ Heat Transfer Multiplier)
 Key: Floor size (perimeter(p) for slab-on-grade or area for all other floor types)



Version 8
For Florida residences only

System Sizing Calculations - Summer

Residential Load - Whole House Component Details

Buddy & Brenda Kennedy

Project Title:

Seth Heitzman Construction - Kennedy

Code Only

Professional Version

Climate: North

Lake City, FL 32055-

Reference City: Gainesville (Defaults)

Summer Temperature Difference: 17.0 F

12/4/2007

Component Loads for Whole House

Type*		Overhang		Window Area(sqft)			HTM		Load	
Window	Pn/SHGC/U/InSh/ExSh/IS	Ornt	Len	Hgt	Gross	Shaded	Unshaded	Shaded	Unshaded	
1	2, Clear, 0.87, None,N,N	W	18.5f	9ft.	120.0	120.0	0.0	29	80	3475 Btuh
2	2, Clear, 0.87, None,N,N	W	18.5f	9ft.	9.0	9.0	0.0	29	80	261 Btuh
3	2, Clear, 0.87, None,N,N	N	1.5ft	9ft.	30.0	0.0	30.0	29	29	869 Btuh
4	2, Clear, 0.87, None,N,N	N	1.5ft	9ft.	18.0	0.0	16.0	29	29	463 Btuh
5	2, Clear, 0.87, None,N,N	E	6.5ft	9ft.	30.0	8.4	21.6	29	80	1962 Btuh
6	2, Clear, 0.87, None,N,N	S	1.5ft	9ft.	4.0	4.0	0.0	29	34	116 Btuh
7	2, Clear, 0.87, None,N,N	S	1.5ft	9ft.	15.0	15.0	0.0	29	34	434 Btuh
Excursion										5608 Btuh
Window Total					224 (sqft)					13189 Btuh
Walls	Type	R-Value/U-Value		Area(sqft)		HTM		Load		
1	Frame - Wood - Ext	19.0/0.08		1214.0		1.5		1820 Btuh		
2	Frame - Wood - Adj	13.0/0.09		259.0		1.5		391 Btuh		
Wall Total				1473 (sqft)				2211 Btuh		
Doors	Type			Area (sqft)		HTM		Load		
1	Insulated - Exterior			20.0		9.8		196 Btuh		
2	Insulated - Adjacent			20.0		9.8		196 Btuh		
Door Total				40 (sqft)				392 Btuh		
Ceilings	Type/Color/Surface	R-Value		Area(sqft)		HTM		Load		
1	Vented Attic/DarkShingle	30.0		2140.0		1.7		3544 Btuh		
Ceiling Total				2140 (sqft)				3544 Btuh		
Floors	Type	R-Value		Size		HTM		Load		
1	Slab On Grade	5.0		193 (ft(p))		0.0		0 Btuh		
Floor Total				193.0 (sqft)				0 Btuh		
Envelope Subtotal:									19336 Btuh	
Infiltration	Type	ACH	Volume(cuft)	wall area(sqft)	CFM=	Load				
	SensibleNatural	0.70	19260	1473	256.8	4182 Btuh				
Internal gain		Occupants	Btuh/occupant	Appliance	Load					
		4	X 230	+	2400	3320 Btuh				
Sensible Envelope Load:									26838 Btuh	
(DGM of 0.333)									8926 Btuh	
Sensible Load All Zones									35763 Btuh	
Duct load										

Manual J Summer Calculations

Residential Load - Component Details (continued)

Buddy & Brenda Kennedy

Project Title:

Seth Heitzman Construction - Kennedy

Code Only

Professional Version

Climate: North

Lake City, FL 32055-

12/4/2007

WHOLE HOUSE TOTALS

Whole House Totals for Cooling	Sensible Envelope Load All Zones	26838 Btuh
	Sensible Duct Load	8926 Btuh
	Total Sensible Zone Loads	35763 Btuh
	Sensible ventilation	0 Btuh
	Blower	0 Btuh
	Total sensible gain	35763 Btuh
	Latent infiltration gain (for 54 gr. humidity difference)	8212 Btuh
	Latent ventilation gain	0 Btuh
	Latent duct gain	1544 Btuh
	Latent occupant gain (4 people @ 200 Btuh per person)	800 Btuh
	Latent other gain	0 Btuh
	Latent total gain	10556 Btuh
	TOTAL GAIN	46319 Btuh

EQUIPMENT

1. Central Unit	#	41000 Btuh
-----------------	---	------------

*Key: Window types (Pn - Number of panes of glass)

(SHGC - Shading coefficient of glass as SHGC numerical value or as clear or tint)

(U - Window U-Factor or 'DEF' for default)

(InSh - Interior shading device: none(N), Blinds(B), Draperies(D) or Roller Shades(R))

(ExSh - Exterior shading device: none(N) or numerical value)

(BS - Insect screen: none(N), Full(F) or Half(H))

(Ornt - compass orientation)



Version 8
For Florida residences only

System Sizing Calculations - Summer

Residential Load - Room by Room Component Details

Buddy & Brenda Kennedy

Project Title:

Code Only

Lake City, FL 32055-

Seth Heitzman Construction - Kennedy

Professional Version

Climate: North

Reference City: Gainesville (Defaults)

Summer Temperature Difference: 17.0 F

12/4/2007

Component Loads for Zone #1: Main

Window	Type*	Ornt	Overhang		Window Area(sqft)			HTM		Load	
	Pn/SHGC/U/InSh/ExSh/IS		Len	Hgt	Gross	Shaded	Unshaded	Shaded	Unshaded		
1	2, Clear, 0.87, None,N,N	W	16.5f	9ft.	120.0	120.0	0.0	29	80	3475	Btuh
2	2, Clear, 0.87, None,N,N	W	16.5f	9ft.	9.0	9.0	0.0	29	80	261	Btuh
3	2, Clear, 0.87, None,N,N	N	1.5ft	9ft.	30.0	0.0	30.0	29	29	869	Btuh
4	2, Clear, 0.87, None,N,N	N	1.5ft	9ft.	16.0	0.0	16.0	29	29	463	Btuh
5	2, Clear, 0.87, None,N,N	E	6.5ft	9ft.	30.0	8.4	21.6	29	80	1962	Btuh
6	2, Clear, 0.87, None,N,N	S	1.5ft	9ft.	4.0	4.0	0.0	29	34	116	Btuh
7	2, Clear, 0.87, None,N,N	S	1.5ft	9ft.	15.0	15.0	0.0	29	34	434	Btuh
Window Total					224 (sqft)					7581 Btuh	
Walls	Type	R-Value/U-Value		Area(sqft)		HTM		Load			
1	Frame - Wood - Ext	19.0/0.08		1214.0		1.5		1820 Btuh			
2	Frame - Wood - Adj	13.0/0.09		259.0		1.5		391 Btuh			
Wall Total				1473 (sqft)				2211 Btuh			
Doors	Type			Area (sqft)		HTM		Load			
1	Insulated - Exterior			20.0		9.8		196 Btuh			
2	Insulated - Adjacent			20.0		9.8		196 Btuh			
Door Total				40 (sqft)				392 Btuh			
Ceilings	Type/Color/Surface	R-Value		Area(sqft)		HTM		Load			
1	Vented Attic/DarkShingle	30.0		2140.0		1.7		3544 Btuh			
Ceiling Total				2140 (sqft)				3544 Btuh			
Floors	Type	R-Value		Size		HTM		Load			
1	Slab On Grade	5.0		193 (ft(p))		0.0		0 Btuh			
Floor Total				193.0 (sqft)				0 Btuh			
Zone Envelope Subtotal:										13728 Btuh	
Infiltration	Type	ACH		Volume(cuft) wall area(sqft)		CFM=		Load			
	SensibleNatural	0.70		19260 1473		224.7		4182 Btuh			
Internal gain	Occupants	4		Btuh/occupant		Appliance		Load			
				X 230 +		2400		3320 Btuh			
Sensible Envelope Load:										21230 Btuh	
Duct load	Average sealed, Supply(R6.0-Attic), Return(R6.0-Attic)							(DGM of 0.333)		7061 Btuh	
Sensible Zone Load										28290 Btuh	

The following window Excursion will be assigned to the system loads.

Windows	July excursion for System 1	Excursion Subtotal:	5608 Btuh 5608 Btuh
Duct load			1865 Btuh
Sensible Excursion Load			7473 Btuh

Manual J Summer Calculations

Residential Load - Component Details (continued)

Buddy & Brenda Kennedy

Project Title:

Seth Heitzman Construction - Kennedy

Code Only

Professional Version

Climate: North

Lake City, FL 32055-

12/4/2007

WHOLE HOUSE TOTALS

Whole House Totals for Cooling	Sensible Envelope Load All Zones	26838 Btuh
	Sensible Duct Load	8926 Btuh
	Total Sensible Zone Loads	35763 Btuh
	Sensible ventilation	0 Btuh
	Blower	0 Btuh
	Total sensible gain	35763 Btuh
	Latent infiltration gain (for 54 gr. humidity difference)	8212 Btuh
	Latent ventilation gain	0 Btuh
	Latent duct gain	1544 Btuh
	Latent occupant gain (4 people @ 200 Btuh per person)	800 Btuh
	Latent other gain	0 Btuh
	Latent total gain	10556 Btuh
	TOTAL GAIN	46319 Btuh

EQUIPMENT

1. Central Unit	#	41000 Btuh
-----------------	---	------------

*Key: Window types (Pn - Number of panes of glass)

(SHGC - Shading coefficient of glass as SHGC numerical value or as clear or tint)

(U - Window U-Factor or 'DEF' for default)

(InSh - Interior shading device: none(N), Blinds(B), Draperies(D) or Roller Shades(R))

(ExSh - Exterior shading device: none(N) or numerical value)

(BS - Insect screen: none(N), Full(F) or Half(H))

(Ornt - compass orientation)



Version 8
For Florida residences only

Residential Window Diversity

MidSummer

Buddy & Brenda Kennedy

Lake City, FL 32055-

Project Title:
Seth Heitzman Construction - Kennedy


Code Only
Professional Version
Climate: North

12/4/2007

Weather data for: Gainesville - Defaults

Summer design temperature	92 F	Average window load for July	10040 Btu
Summer setpoint	75 F	Peak window load for July	19206 Btu
Summer temperature difference	17 F	Excursion limit(130% of Ave.)	13052 Btu
Latitude	29 North	Window excursion (July)	6155 Btuh

WINDOW Average and Peak Loads



This application has glass areas that produce large heat gains for part of the day. Variable air volume devices are required to overcome spikes in solar gain for one or more rooms. Install a zoned system or provide zone control for problem rooms. Single speed equipment may not be suitable for the application.

EnergyGauge® System Sizing for Florida residences only

PREPARED BY: _____

DATE: _____

EnergyGauge® FLRCPB v4.5.2



Shingle

FLORIDA DEPARTMENT OF Community Affairs

BCIS Home | Log In | Hot Topics | Submit Surcharge | Stats & Facts | Publications | FBC Staff | BCIS Site Map | Links | Search



Product Approval
USER: Public User

[Product Approval Menu](#) > [Product or Application Search](#) > [Application List](#) > [Application Detail](#)

- COMMUNITY PLANNING
- HOUSING & COMMUNITY DEVELOPMENT
- EMERGENCY MANAGEMENT
- OFFICE OF THE SECRETARY

FL # FL1956-R1
Application Type Revision
Code Version 2004
Application Status Approved
Comments
Archived ☐

Product Manufacturer TAMKO Building Products, Inc.
Address/Phone/Email PO Box 1404
 Joplin, MO 64802
 (800) 641-4691 ext 2394
 fred_oconnor@tamko.com

Authorized Signature Frederick J. O'Connor
 fred_oconnor@tamko.com

Technical Representative Frederick J. O'Connor
Address/Phone/Email PO Box 1404
 Joplin, MO 64802
 (800) 641-4691
 fred_oconnor@tamko.com

Quality Assurance Representative
Address/Phone/Email

Category
Subcategory

Roofing
Asphalt Shingles

Compliance Method

Certification Mark or Listing

Certification Agency

Underwriters Laboratories Inc.

Referenced Standard and Year (of
Standard)

Standard
ASTM D 3462

Year
2001

Equivalence of Product Standards
Certified By

Product Approval Method

Method 1 Option A

Date Submitted
Date Validated
Date Pending FBC Approval
Date Approved

06/09/2005
06/20/2005
06/25/2005
06/29/2005

Summary of Products

FL #	Model, Number or Name	Description
------	-----------------------	-------------

slopes of 2:12 or greater. Not approved for use in HVHZ.

[Back](#)

[Next](#)

DCA Administration
Department of Community Affairs
Florida Building Code Online
Codes and Standards

2555 Shumard Oak Boulevard
 Tallahassee, Florida 32399-2100
 (850) 487-1824, Suncom 277-1824, Fax (850) 414-8436

© 2000-2005 The State of Florida. All rights reserved. [Copyright and Disclaimer](#)

Product Approval Accepts:





Underwriters Inc.

June 17, 2005

Tamko Roofing Products
Mr. Keith Eden
P.O. Box 1404
220 W. 4th Street
Joplin, MO 64802-1404

Our Reference: R2919

This is to confirm that "Elite Glass-Seal AR", "Heritage 30 AR", "Heritage 50 AR", "Glass-Seal AR" manufactured at Tuscaloosa, AL and "Elite Glass-Seal AR", "Heritage 30 AR", "Heritage XL AR", "Heritage 50 AR" manufactured at Proderick, MD and "Heritage 30 AR", "Heritage XL AR", and "Heritage 50 AR" manufactured in Dallas, TX are UL Listed asphalt glass mat shingles and have been evaluated in accordance with ANSI/UL 790, Class A (ASTM E108), ASTM D3462, ASTM D3161 or UL 997 modified to 110 mph when secured with four nails.

Let me know if you have any further questions.

Very truly yours,

Alpesh Patel (Ext. 42522)
Engineer Project
Fire Protection Division

Reviewed by,

Randall K. Laymon (Ext. 42687)
Engineer Sr Staff
Fire Protection Division

333 Piquette Road
Northbrook, IL 60062-2008 USA
www.ul.com
Tel: 1 847 272 8800

4

THESE ARE THE MANUFACTURER'S APPLICATION INSTRUCTIONS FOR THE ROOFING CONDITIONS DESCRIBED. TALKO BUILD-ING PRODUCTS, INC. ASSUMES NO RESPONSIBILITY FOR LEAKS OR OTHER ROOFING DEFECTS RESULTING FROM FAILURE TO FOLLOW THE MANUFACTURER'S INSTRUCTIONS.

THIS PRODUCT IS COVERED BY A LIMITED WARRANTY, THE TERMS OF WHICH ARE PRINTED ON THE WRAPPER.

IN COLD WEATHER (BELOW 40°F), CARE MUST BE TAKEN TO AVOID DAMAGE TO THE EDGES AND CORNERS OF THE SHINGLES.

IMPORTANT: It is not necessary to remove the plastic strip from the back of the shingles.

2001 2001 1

These snags are for application to root decks capable of receiving and retaining fasteners, and to inches of not less than 2 in. per foot. For roots having pitches 2 in. per foot to less than 4 in. per foot, refer to special instructions titled "Low Slope Application". Shingles must be applied properly. TALLK-O assumes no responsibility for leaks or defects resulting from improper application, or failure to properly prepare the surface to be roofed over.

NEW ROOF DECK CONSTRUCTION: Roof deck must be smooth,

Any use of the non-waxed surfaces is not recommended. It is recommended that metal drip edges be installed at eaves and rakes.

PLANTWOOD: All plywood shall be exterior grade as defined by the American Plywood Association. Plywood shall be a minimum of 3/8 in. thickness and applied in accordance with the recommendations of the American Plywood Association.

SHEATHING BOARDS: Boards shall be well-seasoned tongue-and-

groove boards and not over 6 in. nominal width. Boards shall be a 1 in. nominal minimum thickness. Boards shall be properly spaced and nailed.

INSTRUMENTAL

THANKS does not recommend re-roofing over existing roof.


adequate ventilation of attic spaces can cause accumulation of moisture in winter months and a build up of heat in the summer. These conditions can lead to:

1. Vapour condensation
2. Buckling of shingles due to deck movement
3. Rotting of wood members.
4. Premature failure of roof.

to insure adequate ventilation and circulation of air, place of sufficient size high in the gable ends and/or install continuous ridge and soffit vents. "A minimum property standards require one square foot of net free ventilation area to each 150 square feet of space to be vented, or one square foot per 300 square feet if it is a vapor barrier. It is installed on the warm side of the ceiling or it at least one half of the ventilation is provided near the ridge." The ventilation openings are screened, and total area should be doubled.

~~IT IS PARTICULARLY IMPORTANT TO PROVIDE ADEQUATE VENTILATION~~

(2) **Handrail or Stair Slope Fastening Pattern.** (For use on decks with slopes greater than 2:1 in. per foot.) Use standard railing hardware with four additional nails placed 6 in. from the butt end of the stringer making certain nails are covered by the next successive course of stringers.



(1) **Standard Fastening Pattern.**—(For use on decks with slopes 2 in. per foot to 21 in. per foot. One fastener 1-1/2 in. back from each end, one 10-3/4 in. back from each end and one 20 in. from one end of the stringer for a total of 5 fasteners. (See standard fastening pattern illustrated below).)

3. POSTTEST

WIND CAUTION: Extreme wind velocities can damage these shingles after application when proper sealing of the shingles does not occur. This can especially be a problem if the shingles are applied in cooler months or in areas on the roof that do not receive direct sunlight. These conditions may impede the sealing of the adhesive strips on the shingles. The inability to seal down may be compounded by prolonged cold weather conditions and/or blowing dust. In these situations, hand sealing of the shingles is recommended. Shingles must also be fastened according to the fastening instructions described below.

FASTENING PATTERNS: Fasteners must be placed 6 in. from the top edge of the shingle located horizontally as follows:

top edge of the shingle located horizontally as follows:

1) Standard Fastening Pattern. (For use on decks with slopes 2 in. per foot to 2 1/2 in. per foot.) One fastener 1-1/2 in. back from each end, one 10-3/4 in. back from each end and one 20 in. from one end of the stringer for a total of 5 fasteners. (See standard fastening pattern illustrated below.)

• (more detailed)

(Continued)

Visit Our Web Site at
www.iamko.com

Central District
Northeast District
Southeast District
Southwest District
Western District

220 West 4th St., Joplin, MO 64801
4500 Tamko Dr., Frederick, MD 21701
2300 35th St., Tuscaloosa, AL 35401
7910 S. Central Exp., Dallas, TX 75216
5300 East 43rd Ave., Denver, CO 80216

800-641-4691
800-368-2055
800-228-2656
800-443-1834
800-530-8868

Visit Our Web Site at
www.tamko.com

Central District
Northeast District
Southeast District
Southwest District
Western District

220 West 4th St., Joplin, MO 64801
4500 Tamko Dr., Frederick, MD 21701
2300 35th St., Tuscaloosa, AL 35401
7910 S. Central Exp., Dallas, TX 75216
5300 East 43rd Ave., Denver, CO 80216


800-841-4691
800-368-2055
800-228-2656
800-443-1834
800-530-8888

90/90

(Continued)

**HERITAGE VINTAGE STAKTR AR
12 1/2" x 36" 20 PIECES PER BUNDLE
60 LINEAL FT. PER BUNDLE**

Note: Do not allow Vintage Starter AR joints to be visible between shingle tabs. Cutting of the starter may be required.




The first starter course may consist of TAMIKO Shingles Starter, three tab self-sealing type shingles or a 9 inch wide strip of mineral surface roll roofing. If three tab self-sealing shingles are used, remove the exposed tab portion and install with the factory applied adhesive dependent to the eaves. If using three tab self-sealing shingles or shingle starter, remove 1 3/8 in. from first shingle to offset the end joints of the Vantage Starter. Attach the first starter course with approved fasteners along a line parallel to and 3 in. to 4 in. above the eave edge. The starter course should overhang both the eave and rake edge 1/4 in. to 3/8 in. Over the first starter course, install Heritage Vantage Starter AR and begin at the left rake edge with a full size shingle and continue across the roof nailing the Heritage Vantage Starter AR along a line parallel to and 6 in. from the eave edge.

SMALLCELLS IN


in areas where ice builds up along the eaves or a back-up of water from frozen or clogged gutters is a potential problem, TAAK-O's Moisture Guard Plus® waterproofing underlayment (or any specially eaves flash- ing product) may be applied to eaves, rakes, ridges, valleys, around chimneys, skylights or dormers to help prevent water damage. Contact TAAK-O's Technical Services Department for more information. TAAK-O does not recommend the use of any substitute products as shingle underlayment.

Products which are acceptable for use as underlayment are:

UNDERLAYMENT: An underlayment consisting of asphalt saturated felt must be applied over the entire deck before the installation of TALKO's shingles. Failure to add underlayment can cause premature failure of the shingles and leaks which are not covered by TALKO's limited warranty. Apply the felt when the deck is dry. On roof decks 4 in. per foot or greater apply the felt parallel to the eaves lapping each course of the felt over the lower course at least 2 in. Where ends join, lap the felt 4 in. If left exposed, the underlayment felt may be adversely affected by moisture and weathering. Laying of the underlayment and the shingle application must be done together.

[illegible]


NALB's TANKO recommends the use of nails as the preferred method of application. Standard type roofing nails should be used. Nail shanks should be made of minimum 12 gauge wire, and a minimum head diameter of 3/8 in. Nails should be long enough to penetrate 3/4 in. into the roof deck. Where the deck is less than 3/4 in. thick, the nails should be long enough to penetrate completely through plywood decking and extend at least 1/8 in. through the roof deck. Drive nail head flush with the shingle surface.



MANSARD FASTENING PATTERN

Each shingle tab must be sealed underneath with quick setting asphalt adhesive cement immediately upon installation. Spots of cement must be equivalent in size to a \$.25 piece and applied to shingles with a 5 in. exposure, use 6 fasteners per shingle.

SHINGLE APPLICATION: Start the first course at the left rake edge with a full size shingle and overlap the rake edge 1/4 in. to 3/8 in. To begin the second course, align the right side of the shingle making sure to 5-1/2 in. alignment notch on the first course shingle making sure to align the exposure notch. (See shingle illustration on next page) Cut the appropriate amount from the rake edge so the overhang is 1/4" to 3/8". For the third course, align the shingle with the 15-1/2 in. alignment notch at the top of the second course shingle, again being sure to align the exposure notch. Cut the appropriate amount from the rake edge. To begin the fourth course, align the shingle within the 5-1/2 in. alignment notch from the third course shingle while aligning the exposure notch. Cut the appropriate amount from the rake edge. Continue up the rake in as many rows as necessary using the same formula as outlined above. Cut pieces may be used to complete courses at the right side. As you work across the roof, install full size shingles taking care to align the exposure notches. Shingle joints should be no closer than 4 in.



8. LOW SLOPE APPLICATION

On pitches 2 in. per foot to 4 in. per foot cover the deck with two layers of underlayment. Begin by applying the underlayment in a 18 in. wide strip along the eaves and overlapping the drip edge by 1/4 to 3/4 in. Place a full 36 in. wide sheet over the 18 in. wide starter piece, completely overlapping it. All succeeding courses will be positioned to overlap the preceding course by 18 in. If winter temperatures average 25°F or less, thoroughly cement the laps of the entire underlayment to each other with plastic cement from eaves and raises to a point of at least 24 in. inside the interior wall line of the building. As an alternative, TAMKO's Moisture Guard Plus self-adhering waterproofing underlayment may be used in lieu of the cemented felts.

7. VALLEY APPLICATION

TAMKO recommends an open valley construction with Heritage Vintage AR shingles.

To begin, center a sheet of TAMKO Moisture Guard Plus, TW Underlayment or TW Metal & Tile Underlayment in the valley.


After the underlayment has been secured, install the recommended corrosion resistant metal (26 gauge galvanized metal or an equivalent) in the valley. Secure the valley metal to the roof deck. Overlaps should be 12" and cemented.

Following valley metal application, a 6" to 12" wide strip of TAMKO Moisture Guard Plus, TW Underlayment or TW Metal & Tile Underlayment should be applied along the edges of the metal valley flashing (max. 6" onto metal valley flashing) and on top of the valley underlayment. The valley will be completed with shingle application.

SHINGLE APPLICATION INSTRUCTIONS (OPEN VALLEY)

- Snap two chalk lines, one on each side of the valley centerline over the full length of the valley flashing. Locate the upper ends of the chalk lines 3" to either side of the valley centerline. The lower end should diverge from each other by 1/8" per foot. Thus, for an 8' long valley, the chalk lines should be 7" either side of the centerline at the eaves and for a 16' valley 8".
- As shingles are applied toward the valley, trim the last shingle in each course to fit on the chalk line. Never use a shingle trimmed to less than 12" in length to finish a course running into a valley. If necessary, trim the adjacent shingle in the course to allow a longer portion to be used.
- Clip 1" from the upper corner of each shingle on a 45° angle to direct water into the valley and prevent it from penetrating between the courses.
- Form a tight seal by cementing the shingle to the valley lining with a 3" width of asphalt plastic cement (conforming to ASTM D 4586).

VINTAGE Open Valley Detail



• **CAUTION:** Adhesive must be applied in smooth, thin, even layers. Excessive use of adhesive will cause blistering to this product.

TAMKO assumes no responsibility for blistering.

(CONTINUED from Pg. 3)

TAMKO • **HERITAGE™ VINYL AR** - Phillipsburg, KS
LAMINATED ASPHALT SHINGLES


TAMKO
 BUILDING PRODUCTS

8. HIP AND RIDGE FASTENING DETAIL

Apply the shingles with a 5 in. exposure beginning at the bottom of the hip or from the end of the ridge opposite the direction of the prevailing winds. Secure each shingle with one fastener on each side, 5-1/2 in. back from the exposed end and 1 in. up from the edge. TAMKO recommends the use of TAMKO Heritage Vinyl Hip & Ridge shingle products.

Fasteners should be 1/4 in. longer than the ones used for shingles.

IMPORTANT: PRIOR TO INSTALLATION, CARE NEEDS TO BE TAKEN TO PREVENT DAMAGE WHICH CAN OCCUR WHILE BENDING SHINGLE IN COLD WEATHER.



THESE ARE THE MANUFACTURER'S APPLICATION INSTRUCTIONS FOR THE ROOFING CONDITIONS DESCRIBED. TAMKO BUILDING PRODUCTS, INC. ASSUMES NO RESPONSIBILITY FOR LEAKS OR OTHER ROOFING DEFECTS RESULTING FROM FAILURE TO FOLLOW THE MANUFACTURER'S INSTRUCTIONS.

TAMKO® Moisture Guard Plus®, Nail Fast® and Heritage® are registered trademarks and Vintage™ is a trademark of TAMKO Building Products, Inc.

Visit Our Web Site at

www.tamko.com

Central District
 Northeast District
 Southeast District
 Southwest District
 Western District

220 West 4th St., Joplin, MO 64801
 4500 Tamko Dr., Frederick, MD 21701
 2300 35th St., Tuscaloosa, AL 35401
 7910 S. Central Exp., Dallas, TX 75216
 5300 East 43rd Ave., Denver, CO 80216

800-641-4691
 800-368-2055
 800-228-2866
 800-443-1834
 800-530-8888

05/03

4

JP66905



FLORIDA BUILDING CODE

Overview User Organization User Organization Organization
Registration Registration Registration Search Search Accreditation

Select the organization type, status, or name to find an organization

Organization Type: Product Manufacturer

Approval Status: (All)

Organization Name: General American Door - Product Manufacturer

Cancel

Search

Result List for Organizations

Displaying 1-1 of 1

Name	City	Contact	Phone	Type	Expiry	Status
General American Door	Montgomery	James Campbell	6308591000	Product Manufacturer	01/01/2009	Approved
Org Code FDM	System ID# 3365	Site Link: http://www.gadco.com				

Displaying 1-1 of 1


Search Results: 1-1 of 1 organizations found. 1-1 of 1 organizations found.

http://www.floridabuilding.org/Codesonline_org.asp_SROCH.asp

NOTES:

1. TESTED TO POSITIVE AND NEGATIVE 20 PSF PER SECTION AND POSITIVE AND NEGATIVE 28 PSF TEST PRESSURES FOR ASTM E-136
2. WINDOW SECTION HEIGHT: 21'
3. SECTION HEIGHTS OF 21' AND 19' ARE AVAILABLE AND MAY BE USED IN ANY COMBINATION TO ACHIEVE VARIOUS KNEE HEIGHTS.
4. WINDOWS MAY BE INSTALLED IN THE TOP SECTION, AS TESTED WITH 1/4" INS GLASS OR EQUIVALENT, OR IN THE SECTION IMMEDIATELY BELOW THE TOP SECTION.
5. WINDOW LENGTH OF 60" OR LESS FROM 24" OR AS TESTED
6. THE STRUT PLACEMENT ON DOOR MUST BE CONSISTENT WITH THE ROOM SCHEDULE.
7. STRUTS SECURED AT ALL LOCATIONS WITH TIE SCOWLS.
8. QUANTITY OF SILEN LOCKS MAY BE ALL OR AS TESTED.
9. DEEP IN TYPE OF INSULATION IS OPTIONAL.

NOT PART OF VAND LOAD SYSTEM
EXTENSION SPRING COUNTERBALANCE
TENSION SPRING COUNTERBALANCE



SEC C-C
VERTICAL
TRACK, (16 GA)

IF GA. JAMB BRACKETS, MAXIMUM SPACING = 19-1/2" WITH
LOWEST BRACKET APPROX. 3" FROM FLUOR, 2ND BRACKET
NEAR THE HORIZONTAL E OF THE BOTTOM SECTION, AND 3RD
BRACKET NEAR THE TOP OF THE BOTTOM SECTION

INSIDE ELEVATION

16'-0" MAX WIDTH

ALL ROLLER CARRIERS
AND HINGES ARE 14 GA.

TEST REPORTS ON FILE [VIDEO 10/19/00 0062933]


DESIGN LOAD +200 PSF & -200 PSF
TEST LOAD +300 PSF & -300 PSF

The seal on this drawing only
certifies that the product(s)
illustrated and described herein
conform(s) to the installation(s)
and configuration(s) of the door as tested.



GAUDED JOISTS			
SERIES 7400, EXTERIOR STEEL	~0.75" MAX CAS	TESTED	
SERIES 7425, EXTERIOR STEEL	~0.75" MAX CAS	TESTED	
SERIES 7524, EXTERIOR STEEL	~0.75" MAX CAS	TESTED	
TESTED WITH VARIOUS			
MAXIMUM DOOR WIDTH	16'	MAXIMUM DOOR HEIGHT	7'
TYPICAL CTR. STILE SPACING	23"	STRUTS TO BE 14 GA	5
VERTICAL TRACK	2 IN.		

GENERAL AMERICAN DOOR COMPANY			
5050 BASELINE ROAD			
MONTICELLO, IL 60053			
DESIGNED BY	APPROVED BY	ISSUED BY	REVISIONS
16' X 7' MAX. RAISED PANEL STEEL DOOR - VERTICAL TRACK			
PAGE 1 OF 2			
DATE			
1/3/2001			




2x6 JAMB TO SUPPORTING STRUCTURE ATTACHMENT

2x6 PRESSURE TREATED GRADE #2 OR BETTER SOUTHERN PINE) WOOD JAMB SHALL BE ANCHORED TO BUILDING WOOD FRAME. GROUTED AND REINFORCED CONCRETE MASONRY UNIT (CMU) WALLS OR COLUMNS, OR REINFORCED CONCRETE COLUMNS.

NOTES

- 1) ALL DOOR OPENING STRUCTURE TO BE DESIGNED BY REGISTERED ENGINEER OR ARCHITECT WITH DUE CONSIDERATION GIVEN TO INSTALLATIONS USING CENTER "HURRICANE" POSTS.
- 2) ALL DOOR OPENING STRUCTURE AND FASTENERS TO COMPLY WITH ALL APPLICABLE CODES INCLUDING SBCI "STANDARD FOR HURRICANE RESISTANT RESIDENTIAL CONSTRUCTION" SSTB 10, CURRENT EDITION.
- 3) ALL FASTENERS TO BE INSTALLED IN STRICT ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS, INSTRUCTIONS AND RECOMMENDATIONS.
- 4) WOOD FRAME BUILT UP STUDS AT EACH SIDE OF DOOR OPENING SHALL BE PROPERLY DESIGNED, CONNECTED, ANCHORED AND SHALL CONSIST OF A MINIMUM OF THREE (3) LAMINATIONS OF 2x6 PRESSURE TREATED SOUTHERN PINE (2x6 GRADE OR BETTER) WALL STUDS CONTINUOUS FROM FOOTING TO DOUBLE TOP PLATE.
- 5) REINFORCED CMU OR CONCRETE 2x6 WOOD JAMB SHALL BE ANCHORED TO SOLIDLY GROUTED AND REINFORCED CONCRETE MASONRY UNIT (CMU) WALLS OR COLUMNS, OR REINFORCED CONCRETE COLUMNS. ANCHOR SPACING AND EMBEDMENT IS BASED ON CONCRETE MASONRY UNITS COMPLYING WITH ASTM C90 WITH A MINIMUM NET AREA COMPRESSIVE STRENGTH OF 2000 PSI. GROUT WITH A MINIMUM COMPRESSIVE STRENGTH OF 2000 PSI REINFORCED CONCRETE COLUMNS WITH A MINIMUM COMPRESSIVE STRENGTH OF 2500 PSI.
- 6) EMBEDMENTS LISTED ARE THE MINIMUM ALLOWABLE EMBEDMENTS.
- 7) ANCHORS FOR CONCRETE AND CONCRETE MASONRY UNITS (CMU) SHALL HAVE A MINIMUM 3" EDGE DISTANCE FROM ALL EDGES OF CONCRETE OR CONCRETE MASONRY UNITS. ANCHORS FOR CONCRETE AND CMU SHALL HAVE A MINIMUM SPACING OF 3-3/4"
- 8) LAG SCREWS SHALL BE CENTERED IN ONE OF THE 1-1/2" DIMENSION FACES OF THE TRIPLE 2x6 WALL STUDS.
- 9) WASHERS ARE REQUIRED ON ALL FASTENERS.
- 10) THE WIND LOAD VS. ANCHOR SPACING CHART IS FOR A MAXIMUM DOOR SIZE OF 18' X 8' AT A MAXIMUM 42 PSF DESIGN WIND LOAD.
- 11) FOR THE UPPER THREE INDIVIDUAL STEEL JAMB BRACKETS, BRACKETS SHALL BE CENTERED BETWEEN THE TWO CLOSEST 2x6 WOOD JAMB ANCHORS. IF THE STEEL JAMB BRACKET IS NOT CENTERED BETWEEN THE TWO CLOSEST 2x6 WOOD JAMB ANCHORS, ADD AN ADDITIONAL 2x6 WOOD JAMB ANCHOR NEAR THAT STEEL BRACKET TO INSURE THAT THE LOAD FROM THE STEEL BRACKET IS EQUALLY TRANSFERRED TO TWO WOOD JAMB ANCHORS.

WIND LOAD VS. ANCHOR SPACING



MAXIMUM ANCHOR SPACING (INCHES) PER EACH JAMB

DESIGN (LBS) X GARAGE DOOR AREA (WIDTH-FT X HEIGHT-FT) = WIND LOAD (LBS)

EXAMPLE


30 LBS/FT² X 16 FT WIDE X 8 FT HIGH = 3840 LBS

- ① USE 22" SPACING
 ② USE 24" SPACING
 ③ USE 26" SPACING
 SEE NOTE 8 FOR ADDITIONAL
 REINFORCED 2x6 WOOD JAMB ANCHORS



GENERAL AMERICAN DOOR COMPANY 1000 N. WILSON BLVD. NORTH GADSDEN, AL 36050	
ORDER NO. 8-30-99	QUANTITY 1
JAMB TO STRUCTURE ATTACHMENT FOR WIND LOADED GARAGE DOORS	
DATE 6/28/04	

Windows



BCIS Home | Log In | Hot Topics | Submit Surcharge | Stats & Facts | Publications | FBC Staff | BCIS Site Map | Links | Search



Product Approval
USER: Public User

[Product Approval Menu](#) > [Product or Application Search](#) > [Application List](#) > [Application Detail](#)

FL #	FL5108
Application Type	New
Code Version	2004
Application Status	Approved
Comments	
Archived	☐
Product Manufacturer Address/Phone/Email	MI Windows and Doors 650 W Market St Gratz, PA 17030 (717) 365-3300 ext 2101 surich@miwd.com
Authorized Signature	Steven Ulrich surich@miwd.com
Technical Representative Address/Phone/Email	
Quality Assurance Representative Address/Phone/Email	

(Validator / Operations Administration)

AAMA
CERTIFICATION PROGRAM

AUTHORIZATION FOR PRODUCT CERTIFICATION

MI Windows & Doors, Inc.
P.O. Box 370
Graft, PA 17030-0370

Attn: Bill Emley

The product described below is hereby approved for listing in the next issue of the AAMA Certified Products Directory. The approval is based on successful completion of tests, and the reporting to the Administrator of the results of tests, accompanied by related drawings, by an AAMA Accredited Laboratory.

1. The listing below will be added to the next published AAMA Certified Products Directory.

SPECIFICATION		RECORD OF PRODUCT TESTED				LABEL ORDER NO.
AAMA 101/S. 2-87 H-155-3082						
COMPANY AND PLANT LOCATION		CODE NO.	SERIES MODEL & PRODUCT DESCRIPTION		MAXIMUM SIZE TESTED	
MI Windows & Doors, Inc. (Grafton, PA)		MI-6	185/2105 SH 614 (ASTM)		EMSE 30" x 52"	
					SABJ 210" x 27"	
					Request by	

2. This Certification will expire May 14, 2008 and requires validation until then by continued listing in the current AAMA Certified Products Directory.

3. Product Tested and Reported by: Architectural Testing, Inc.

Report No.: 01-50360.02

Date of Report: June 14, 2004

NOTE: PLEASE REVIEW,
AND ADVISE MI IMMEDIATELY
IF DATA AS SHOWN, NEEDS
CORRECTION.

Date: August 1, 2005

cc: AAMA
JCS/dt

ACP-04 (Rev. 5/03)

American Architectural Manufacturers Association


Authorized for Certification:

Associated Laboratories, Inc.

Validated for Certification:

'ONE BY' (3/4") BUCKS (SHOWN)

1. Before installation, check back of flange, or face of buck.
2. 3/16" dia. masonry Tapcon must be of a length to have 1 1/4" embedment into masonry or concrete.
3. Shim as required with load bearing shims at each installation anchor as shown.
4. All factory applied holes not designated for Tapcon anchor should be filled with #10 screws of sufficient length to provide min. 5/8" embedment into wood buck.
5. Label designations on the Tapcon location chart indicate where anchors are to be installed using the elevation as a key.
6. If exact window size is not given, use anchor quantity for next larger window in chart.
7. For continuous head and sill units, use the same fastener schedule for each unit in the main frame except ignore the intermediate jamb.



'TWO BY' (1 1/2) BUCKS

'TWO BY' bucks are engineered and fastened to the masonry opening BY OTHERS.

Follow the same fastenings and fastener requirements for 'one by' bucks except use #10 screws of sufficient length for 1 1/4" minimum embedment into buck.

TAPCON LOCATION CHART		FASTENER LOCATIONS	
CHUCK SIZE	WINDOW ID SIZE	UP TO ONE	UP TO THREE
13	18 1/2 x 25	18 1/2 x 25	18 1/2 x 25
14	18 1/2 x 25	18 1/2 x 25	18 1/2 x 25
15	18 1/2 x 25	18 1/2 x 25	18 1/2 x 25
16	18 1/2 x 25	18 1/2 x 25	18 1/2 x 25
17	18 1/2 x 25	18 1/2 x 25	18 1/2 x 25
18	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
19	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
20	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
21	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
22	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
23	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
24	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
25	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
26	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
27	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
28	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
29	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
30	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
31	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
32	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
33	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
34	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
35	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
36	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
37	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
38	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
39	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
40	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
41	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
42	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
43	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
44	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
45	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
46	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
47	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
48	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
49	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
50	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
51	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
52	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
53	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
54	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
55	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
56	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
57	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
58	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
59	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
60	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
61	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
62	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
63	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
64	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
65	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
66	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
67	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
68	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
69	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
70	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
71	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
72	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
73	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
74	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
75	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
76	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
77	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
78	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
79	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
80	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
81	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
82	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
83	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
84	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
85	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
86	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
87	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
88	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
89	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
90	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
91	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
92	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
93	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
94	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
95	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
96	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
97	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
98	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
99	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25
100	25 1/2 x 25	25 1/2 x 25	25 1/2 x 25

MI HOME PRODUCTS
GRATZ, PA

18/3185 SINGLE HUNG FLANGE FRAME
INSTALLATION DETAILS & FASTENER SCHEDULE

DATE	08/18/04
BY	N.T.S.
CHKD	WHP0059
REV	1 OF 1


* 'TAPCON' TYPE HARDENED MASONRY SCREWS INCLUDE TAPCON, RAIL, & SUPCON

XX

Glazed Outswing Unit

WOOD-EDGE STEEL DOORS

APPROVED ARRANGEMENT:



Note:

Units of other sizes are covered by this report as long as the panels used do not exceed 3'0" x 6'0".

Double Door
Maximum unit size = 6'0" x 6'0"

Design Pressure
+40.5/-40.5
Limited water unless special threshold design is used.

Large Missile Impact Resistance

Hurricane protective system (shutters) is REQUIRED.

Actual design pressure and impact resistant requirements for a specific building design and geographic location is determined by ASCE 7-sections, state or local building codes specify the edition required.

MINIMUM ASSEMBLY DETAIL:

Compliance requires that minimum assembly details have been followed – see MAD-WL-MA0012-02 and MAD-WL-MA0041-02.

MINIMUM INSTALLATION DETAIL:

Compliance requires that minimum installation details have been followed – see MID-WL-MA0002-02.

APPROVED DOOR STYLES:

1/4 GLASS:



100 Series



120, 130 Series



130 Series



400 Series



420 Series

1/2 GLASS:



100 Series*



100, 140 Series*



120 Series*



200 Series*



12 RL, 20 RL, 24 RL
Series*



100 Series*



100 Series



304 Series

*This glass kit may also be used in the following door styles: 5-panel; 5-panel with accent; System 5-panel; System 5-panel with accent.

Johnson
Entry Systems

March 28, 2002
Our continuing program of product improvement includes specifications, design and product detail subject to change without notice.




Exclusively from


Masonite
Masonite International Corporation

WAD-VL-MAS041-02

GLASS INSERT IN DOOR OR SIDELITE PANEL



SECTION A-A TYPICAL RIGID PLASTIC LIP LITE SURROUND



March 25, 2002
Our continuing program of product improvement makes specifications, design and product detail subject to change without notice.



Exclusively from

Masonite International Corporation

XX**Glazed Outswing Unit**

BCCP VLL 304-100-02

WOOD-EDGE STEEL DOORS**APPROVED DOOR STYLES:****3/4 GLASS:**

404 Series



406 Series



408 Series

FULL GLASS:

100 Series

114, 120, 122
Series

102 Series



140 Series



300 Series

CERTIFIED TEST REPORTS:

NCTL 210-1887-7, 8, 9, 10, 11, 12; NCTL 210-1884-5, 6, 7, 8; NCTL 210-2178-1, 2, 3

Certifying Engineer and License Number: Barry D. Portney, P.E. / 16258.

Unit Tested in Accordance with Miami-Dade BCCO PA202.

Evaluation report NCTL-210-2794-1

Door panels constructed from 26-gauge 0.017" thick steel skins. Both stiles constructed from wood. Top end rails constructed of 0.041" steel. Bottom end rails constructed of 0.021" steel. Interior cavity of slab filled with rigid polyurethane foam core. Slab glazed with insulated glass mounted in a rigid plastic lip like surround.

Frame constructed of wood with an extruded aluminum bumper threshold.

PRODUCT COMPLIANCE LABELING:

TESTED IN
ACCORDANCE WITH
MIAMI-DADE BCCO PA202

COMPANY NAME
CITY, STATE

To the best of my knowledge and ability the above side-hinged
exterior door unit conforms to the requirements of the 2001 Florida
Building Code, Chapter 17 (Structural Tests and Inspections).

Kurt L. Balthazor

State of Florida, Professional Engineer
Kurt Balthazor, P.E. - License Number 55533

Johnson
Entry Systems

March 29, 1992

Our continuing program of product improvement makes specifications, designs and product
data subject to change without notice.

PREMIERE
Premium Quality Doors




Exclusively from

Masonite
Masonite International Corporation


XX
Unit

OUTSWING UNITS WITH DOUBLE DOOR

TYPICAL HINGE ATTACHMENT




TYPICAL ASTRAGAL PROFILES




ALUMINUM EXTRUDED ASTRAGAL (3/16" MINIMUM WALL THICKNESS) WITH ADDED REINFORCEMENT INCREASING AT TOP EXTENSION BOLT, BOTTOM EXTENSION BOLT AND CYLINDRICAL DOORSTOP LATCHING LOCATIONS. ATTACH WITH #8 X 1" PAN HEAD SCREWS - LOCATE 1" FROM EACH END MINIMUM AND 22" O.C. MAXIMUM.

TYPICAL THRESHOLD & SIDE JAMB ATTACHMENT



TYPICAL HEADER & SIDE JAMB ATTACHMENT



March 25, 2002
Our continuing program of product improvement makes specifications, design and product detail subject to change without notice.




Exclusively from

Masonite International Corporation

XX
Unit

END OF PRODUCT

DOUBLE DOOR



- 6 per vertical framing member.
- 6 per horizontal framing member

Hinge and strike plates require two 2-1/2" long screws per location.

Latching Hardware:

- Compliance requires that GRADE 2 or better (ANSI/BHMA A156.2) cylindrical and deadlock hardware be installed.

Notes:

1. Anchor calculations have been carried out with the lowest (least) fastener rating from the different fasteners being considered for use. Fasteners analyzed for this unit include #6 and #10 wood screws or 3/16" Tapcons.
2. The wood screw single shear design values come from Table 11.3A of ANSI/APA NDS for southern pine lumber with a side member thickness of 1-1/4" and achievement of minimum embedment. The 3/16" Tapcon single shear design values come from the ITW and EICO Dade County approvals respectively, each with minimum 1-1/4" embedment.
3. Wood bucks by others, must be anchored properly to transfer loads to the structure.

March 29, 2002
Our continuing program of product improvement makes specifications, design and product detail subject to change without notice.



New Construction Subterranean Termite Soil Treatment Record

OMB Approval No. 2502-0525

This form is completed by the licensed Pest Control Company.

Public reporting burden for this collection of information is estimated to average 15 minutes per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. This information is mandatory and is required to obtain benefits. HUD may not collect this information, and you are not required to complete this form, unless it displays a currently valid OMB control number.

Section 24 CFR 200.926d(b)(3) requires that the sites for HUD insured structures must be free of termite hazards. This information collection requires the builder to certify that an authorized Pest Control company performed all required treatment for termites, and that the builder guarantees the treated area against infestation for one year. Builders, pest control companies, mortgage lenders, homebuyers, and HUD as a record of treatment for specific homes will use the information collected. The information is not considered confidential.

This report is submitted for informational purposes to the builder on proposed (new) construction cases when soil treatment for prevention of subterranean termite infestation is specified by the builder, architect, or required by the lender, architect, FHA, or VA.

All contracts for services are between the Pest Control Operator and builder, unless stated otherwise.

#26560

Section 1: General Information (Treating Company Information)

Company Name: Aspen Pest Control, Inc.
Company Address: 321 N.W. Cole Terrace, Suite 107 City Lake City State FL Zip 32055
Company Business License No. JB103478 Company Phone No. 386-755-3611 • 352-494-5751
FHA/VA Case No. (if any) _____

Section 2: Builder Information

Company Name: W.H. Hesterman Company Phone No. _____

Section 3: Property Information

Location of Structure(s) Treated (Street Address or Legal Description, City, State and Zip) 972 Fallow Dr. White Springs, FL

Type of Construction (More than one box may be checked) ☒ Slab ☐ Basement ☐ Crawl ☐ Other _____
Approximate Depth of Footing: Outside 12 Inside 36 Type of Fill Back

Section 4: Treatment Information

Date(s) of Treatment(s) 1-24-09
Brand Name of Product(s) Used B-Terminator
EPA Registration No. 53843-199
Approximate Final Mix Solution % 0.6
Approximate Size of Treatment Area: Sq. ft. 3904 Linear ft. 348 Linear ft. of Masonry Voids 320
Approximate Total Gallons of Solution Applied 1046
Was treatment completed on exterior? ☐ Yes ☐ No
Service Agreement Available? ☐ Yes ☐ No

Note: Some state laws require service agreements to be issued. This form does not preempt state law.

Attachments (List) _____

Comments _____

Name of Applicator(s) Steve Brennan Certification No. (if required by State law) _____

The applicator has used a product in accordance with the product label and state requirements. All treatment materials and methods used comply with state and federal regulations.

Authorized Signature _____ Date 1-24-09

Warning: HUD will prosecute false claims and statements. Conviction may result in criminal and/or civil penalties. (18 U.S.C. 1001, 1010, 1012; 31 U.S.C. 3729, 3802)

Form NPCA-99-B may still be used

form HUD-NPCA-99-B (04/2003)

COLUMBIA COUNTY OFFICE OF OCCUPANCY

COLUMBIA COUNTY, FLORIDA

Department of Building and Zoning Inspection

This Certificate of Occupancy is issued to the below named permit holder for the building and premises at the below named location, and certifies that the work has been completed in accordance with the Columbia County Building Code.

Parcel Number 05-1S-17-04492-014

Building permit No. 000026560

Use Classification SFD, UTILITY

Fire: 36.63

Permit Holder SETH HEITZMAN


Waste: 50.25

Owner of Building OTTIS & BRENDA KENNEDY

Total: 86.88

Location: 972 NE FALLOW DRIVE, WHITE SPRINGS, FL

Date: 07/14/2008



Building Inspector

POST IN A CONSPICUOUS PLACE
(Business Places Only)



ITW Building Components Group, Inc.

1950 Marley Drive Haines City, FL 33844
Florida Engineering Certificate of Authorization Number: 0 278
Florida Certificate of Product Approval # FL1999
Page 1 of 1 Document ID:1TD98228Z0113150821

Truss Fabricator: Anderson Truss Company
Job Identification: 7-369--Seth Heitzman Kennedy -- Lot 6 Deer Run Lake City, **
Truss Count: 11
Model Code: Florida Building Code 2004 and 2006 Supplement
Truss Criteria: ANSI/TPI-2002(STD)/FBC
Engineering Software: Alpine Software, Versions 7.36, 7.37.
Structural Engineer of Record: The identity of the structural EOR did not exist as of
Address: the seal date per section 61G15-31.003(5a) of the FAC
Minimum Design Loads: Roof - 40.0 PSF @ 1.25 Duration
Floor - N/A
Wind - 110 MPH ASCE 7-02 -Closed



Notes:

1. Determination as to the suitability of these truss components for the structure is the responsibility of the building designer/engineer of record, as defined in ANSI/TPI 1
2. The drawing date shown on this index sheet must match the date shown on the individual truss component drawing.
3. As shown on attached drawings; the drawing number is preceded by: HCUSR8228

Seal Date: 12/13/2007


-Truss Design Engineer-
James F. Collins Jr.

Florida License Number: 52212
1950 Marley Drive
Haines City, FL 33844

Details: BRCLBSUB-A11015EE-GBLLETIN-140GC-PIGBACKA-PIGBACKB-A11030EE-

#	Ref	Description	Drawing#	Date
1	77395--A1		07347056	12/13/07
2	77396--A2		07347057	12/13/07
3	77397--A3		07347058	12/13/07
4	77398--A-GE		07347059	12/13/07
5	77399--AA-GE		07347060	12/13/07
6	77400--B-GE		07347061	12/13/07
7	77401--B1		07347054	12/13/07
8	77402--M1		07347055	12/13/07
9	77403--M-GE		07347062	12/13/07
10	77404--PB2		07347063	12/13/07
11	77405--PB1		07347064	12/13/07





#7-369
 SETH HEITZMAN-
 KENNEDY

Roof Plane Sheathing Area = 4785 sq. ft
 Gable Sheathing Area = 862 sq. ft
 Total Sheathing Area = 5667 sq. ft
 Fascia Material = 302 linear ft
 Valley Flashing Material = 47 linear ft
 Ridge Cap Material = 99 linear ft
 Hip Ridge Material = 0 linear ft

JOB DESCRIPTION:: Seth Heitzman
 /: Kennedy

JOB NO:

7-369


PAGE NO

1 OF 1

Top	chord	2x4	SP	#2	Dense
Bot	chord	2x4	SP	#2	Dense
	Wbs	2x4	SP	#3	

In lieu of structural panels use purlins to brace all flat TC @ 24" OC.

Wind reactions based on MWFRS pressures.
Right end vertical not exposed to wind pressure



Design Crit: $TPI-2002(STD)/FBC$
 $Cq/RT=1.00(1.25)$

QTY:1 FL/-/4/-/-/R/-

Scale = .1875"/Ft.

WARNING—RISKS OF INJURY FROM EXPOSURE TO CARBON DIOXIDE, HANDLING, SHIPPING, UNLOADING AND BRACING OF CHORDS. CHORDS BEING CONSIDERED A HAZARDOUS MATERIAL. PUBLISHED BY THE (TRUSS PANEAL INSTITUTE), 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA 22314, AND WICK CHORD TRUSS COMPANY, 6500 COUNTRY CENTER DRIVE, FAIRFAX, VA 22031. FOR SAFETY PRACTICES PRIOR TO REPAIRING THESE STRUCTURES, INTERESTED PARTIES SHOULD HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERTY ATTACHED RIGID CELLING.

****IMPORTANT** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. THE RFG, INC. SHALL NOT**


BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN; ANY FAILURE TO BUILD THE TROSS IN CONFORMANCE WITH THE SPECIFICATIONS OF THIS DESIGN SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN; ANY FAILURE TO BUILD THE TROSS IN CONFORMANCE WITH THE SPECIFICATIONS OF THIS DESIGN SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.

DESIGN CONDITIONS WITH APPLICABLE PROVISIONS OF AISC (NATIONAL DESIGN SPEC., BY AISC) AND IP1 (IN BOLTS).
CONDUCTOR PLATES ARE MADE OF 20/19/16GA (M./H./55/K) ASTM A653 GRADE 40/60 (M./K/H./55) GALV. STEEL. APPLY
PLATES TO EACH FACE OF TOWER AND
SURFACE LOCATED ON THE EXTERIOR. POSITION AND NUMBER OF

ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A3 OF IP11-2002 SEC.3. A SEAL ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY. SEE TROUS CONSTRUCTION DETAILS TO EACH OF CROSS AND, UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 1604A

DESIGN SHOW. THE SUSTAINABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/IFP 1 SEC. 2.

ITW Building Components Group, Inc.
Haines City, FL 33844
FI Certificate of Authorization # 000700



TC LL	20.0 PSF	REF	R8228- 77395
TC DL	10.0 PSF	DATE	12/13/07
BC DL	10.0 PSF	DRW	HCSR8228 07347056
BC LL	0.0 PSF	HC-ENG	JB/DLJ
TOT.LD.	40.0 PSF	SEQN	66387
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF	1TD98228Z01


(A) Continuous lateral bracing equally spaced on member.

In lieu of structural panels use purlins to brace all flat TC @ 24" OC.

Wind reactions based on MMFRS pressures.

Right end vertical not exposed to wind pressure.

Deflection meets $L/240$ live and $L/180$ total load. Creep increase factor for dead load is 1.50.



PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC

$$Cq/RT=1.00(1.25)/0(0)$$

7.36.0424

QTY:1 FL/-/4/-/-/R/-


Scale = .1875"/Ft.

WARNING (BUILDING COMPONENT SAFETY INFORMATION). PUBLISHED BY THE FIBERGLASS PANEL INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314 AND 4600 TRUSS COURT, OF AMERICA, 6500 W. INTERSTATE LANE, MIDLAND, TX, 79701 (512) 791-5119 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. INSPECTIONS INDICATED THAT GROUND SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIDGECAP CEILING.

ALPINE

ITW Building Components Group, Inc.

Haines City, FL 33844
F1 scale of Adultization 2007



TC LL	20.0 PSF	REF	R8228- 77396
TC DL	10.0 PSF	DATE	12/13/07
BC DL	10.0 PSF	DRW	HCSUR8228 07347057
BC LL	0.0 PSF	HC-ENG	JB/DLJ
TOT. LD.	40.0 PSF	SEQN-	66409
DUR. FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TD98228201

החוקים נכנסו לתוקף והחל מ-1954, כל המצביעים על המועמדים חתמו על פנקס המצביעים, וכל המצביעים חתמו על פנקס המצביעים.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, located anywhere in roof, CAT 11, EXP 8, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ GCPI(+/-)=0.18

Wind reactions based on M/FRS pressures.

Right end vertical not exposed to wind pressure.

Deflection meets $L/240$ live and $L/180$ total load. Creep increase factor for dead load is 1.50.



Scale = .1875"/Ft.

SHALL HAVE

SHALL NOT

1112 M. J. Griffin

APPLY

AL ON THIS
COMPONENT

ITY OF THE

1

TC LL	20.0 PSF	REF	R8228- 77397
TC DL	10.0 PSF	DATE	12/13/07
BC DL	10.0 PSF	DRW	HCSUR8228 07347058
BC LL	0.0 PSF	HC-ENG	JB/DLJ
TOT.LD.	40.0 PSF	SEQN-	66404
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	UREF-	1TD98228Z01

Scale of 1/4" = 1'-0"

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Truss spaced at 24.0" OC designed to support 1-0-0 top chord
outlookers. Cladding load shall not exceed 10.00 PSF. Top chord
must not be cut or notched.

See DWGS A11015EE0207 & GBLLETIN0207 for more requirements.

(B) #3 or better scab brace. Same size & 80% length of web
member. Attach with 10d Box or Gun (0.128"x3", min.) nails @ 6" OC.

In lieu of structural panels use purlins to brace all flat TC @
24" OC.

The building designer is responsible for the design of the
roof and ceiling diaphragms, gable end shear walls, and
supporting shear walls. Shear walls must provide continuous
lateral restraint to the gable end. All connections to be
designed by the building designer.



110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, located
anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC
DL=5.0 psf. $W=1.00 GCP(+/ -) = 0.18$

Wind reactions based on MMFRS pressures.

Right end vertical not exposed to wind pressure.

(A) 1x4 #3 or better "L" brace, 80% length of web member. Attach
with 8d Box or Gun (0.113"x2.5", min.) nails @ 6" OC.

Deflection meets L/240 live and L/180 total load. Creep increase
factor for dead load is 1.50.



Note: All Plates Are 1.5X4 Except As Shown.

PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC

QTY: 1 FL/-/4/-/R/-



Scale = .1875"/ft.

****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING.
REFER TO BC51 (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI TRUSS SYSTEMS, INC., 6800
NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22304 AND WOOD TRUSS COUNCIL OF AMERICA, UNLESS
ENTERPRISE LABEL, MADISON, WI 53719 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS
OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE
A PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT**** FINISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. THE BCG, INC. SHALL NOT
BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH
TPI: OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

DESIGN CONDITIONS WITH APPLICABLE PROVISIONS OF AOS (NATIONAL DESIGN SPEC., BY AREA) AND TPI.
CONNECTIONS TO BE MADE BY 20/10/10d (W/5/5/5) ASH 1653 GRADE 40/60 (W, K/1/5/5) GALV. STEEL. APPLY
PLATES TO EACH END OF TRUSS AND, UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 160A, 2,
160B, 160C, 160D, 160E, 160F, 160G, 160H, 160I, 160J, 160K, 160L, 160M, 160N, 160O, 160P, 160Q, 160R, 160S, 160T, 160U, 160V, 160W, 160X, 160Y, 160Z.

DRAWING INDICATES THE SUFFICIENCY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE
BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



Alpine Building Components Group, Inc.
Haines City, FL 33844
Toll Free 1-800-441-4444

TC LL	20.0 PSF	REF	R8228-77398
TC DL	10.0 PSF	DATE	12/13/07
BC DL	10.0 PSF	DRW	HCUSR8228 07347059
BC LL	0.0 PSF	HC-ENG	JB/DLJ
TOT.LD.	40.0 PSF	SEON-	66430
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TD98228Z01

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Truss spaced at 24.0" OC designed to support 1-0-0 top chord
outlookers. Cladding load shall not exceed 10.00 PSF. Top chord
must not be cut or notched.

See DWGS A11015EE0207 & GBLLETINO207 for more requirements.

(B) #3 or better scab brace. Same size & 80% length of web
member. Attach with 10d Box or Gun (0.128"x3", min.) nails @ 6" OC.

In lieu of structural panels use purlins to brace all flat TC @
24" OC.



The building designer is responsible for the design of the
roof and ceiling diaphragms, gable end shear walls, and
supporting shear walls. Shear walls must provide continuous
lateral restraint to the gable end. All connections to be
designed by the building designer.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, located
anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC
DL=5.0 psf. $W=1.00 G C p f (+/-) = 0.18$

Wind reactions based on MMFRS pressures.
Right end vertical not exposed to wind pressure.

(A) 1x4 #3 or better "L" brace, 80% length of web member. Attach
with 8d Box or Gun (0.113"x2.5", min.) nails @ 6" OC.

Deflection meets L/240 live and L/180 total load. Creep increase
factor for dead load is 1.50.



R=86 PLF W=5-0-0
R=165 PLF U=11 PLF W=34-10-0

Note: All Plates Are 1.5X4 Except As Shown.

PLT TYP. Wave

Design Cmt: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)/0.00

7.36.0424 QTY:1 FL/-/4/-/R/-

Scale = .1875"/ft.

ITW Building Components Group, Inc. Haines City, FL 33844 Phone: 888-333-7770		ALPINE		Professional Engineer STATE OF FLORIDA No. 12212 F. COLLINS JR. Dec 13 07		TC LL	20.0 PSF	REF	R8228-77399
						TC DL	10.0 PSF	DATE	12/13/07
						BC DL	10.0 PSF	DRW	HCUSR8228 07347060
						BC LL	0.0 PSF	HC-ENG	JB/DLJ
						TOT.LD.	40.0 PSF	SEON-	66437
						DUR.FAC.	1.25	FROM	AH
						SPACING	24.0"	JREF-	1TD98228201

```

:Stack Chord SC1 2x4 SP #2 Dense:
:Stack Chord SC2 2x4 SP #2 Dense:

```

Truss spaced at 24.0" OC designed to support 1-0-0 top chord outlookers. Cladding load shall not exceed 10.00 PSF. Top chord must not be cut or notched.

In lieu of structural panels use purlins to brace TC @ 24" OC.

Deflection meets $L/240$ live and $L/180$ total load. Creep increase factor for dead load is 1.50.


The building designer is responsible for the design of the roof and ceiling diaphragms, gable end shear walls, and supporting shear walls. Shear walls must provide continuous lateral restraint to the gable end. All connections to be designed by the building designer.

110 mph wind, 15.00 ft mean hgt., ASCE 7-02, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. lw=1.00 GCpi (+/-)=0.18

Wind reactions based on MFRS pressures.

See DWGS A11015EE0207 & GBLLETIN0207 for more requirements.

Stacked top chord must NOT be notched or cut in area (NN1).
Dropped top chord braced at 24" o.c. intervals. Attach stacked top chord (5C) to dropped top chord in notchable area using 3x4 tie-plats 24" o.c. Center plate on stacked/dropped chord interface, plate length perpendicular to chord length. Splice top chord in notchable area using 3x6.



Note: All Plates Are 1.5X4 Except As Shown.

PLT TYP. Wave

Design Crit: $TP1-2002(STD)/FBC$
 $Cq/RT=1.00(1.25)$

7.36.0424
FL/ - /4/- /- /R/-

Scale = .25"/Ft.




ITW Building Components Group, Inc.
Haines City, FL 33844
For more information, call 800-368-2222

WARNING: THESE BRIDGE EXISTENCE, CARE IN INSTALLATION, HANDLING, SHIPPING, TRAILING, AND PROTECTION OF THE BRIDGE COMPONENTS ARE THE RESPONSIBILITY OF THE USER. THIS DOCUMENT IS NOT TO BE USED AS A SUBSTITUTE FOR THE DESIGN AND CONSTRUCTION OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER USE OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER MAINTENANCE OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REPAIR OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REPLACEMENT OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REMOVAL OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER STORAGE OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER DISPOSAL OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REUSE OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER RECYCLING OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REFINISHING OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REPAINTING OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER RESEALING OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REGRADING OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER RECONSTRUCTION OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REINFORCEMENT OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REPAIR OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REPLACEMENT OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REMOVAL OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER STORAGE OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER DISPOSAL OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REUSE OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER RECYCLING OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REFINISHING OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REPAINTING OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER RESEALING OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REGRADING OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER RECONSTRUCTION OF THE BRIDGE. THE USER SHALL BE RESPONSIBLE FOR THE PROPER REINFORCEMENT OF THE BRIDGE.

* * * IMPORTANT * * * FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ELY BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH THIS OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

DESIGN CONDITIONS FOR APPLICABLE PROVISIONS OF MOST NATIONAL BUILDING CODES (e.g., AIAA AND TPI). CONDUCTOR PLATS ARE MADE OF 20/26/18 GAUGE (K-H/55/25) ASH ALLOY GAGE 40/60 (K-H/55) GALV. STEEL. APPLICABLE PLANTS TO EACH FACE OF TRUSS AND UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 1606-2. AN INSPECTION OF PLATS FOLLOWED BY (1) SHALL BE PER AMEX A3 OF JULY 2002 SEC 3. A SEAL ON THIS DESIGN INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY. SOUTHERN THE TRUSS COMPANY OF THE DESIGN SHOWS THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE USER.




Dec 13 '07

TC LL	20.0 PSF	REF	R8228 - 77400
TC DL	10.0 PSF	DATE	12/13/07
BC DL	10.0 PSF	DRW	HCUSR8228 07347061
BC LL	0.0 PSF	HC-ENG	JB/DLJ
TOT.LD.	40.0 PSF	SEQN-	66354
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TD98228Z01

(7 369--Seth Heitzman Kennedy Lot 6 Deer Run Lake City, ** B1)
Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. 1w=1.00 GCPI (+/-) 0.18
Wind reactions based on MMFRS pressures.



PLT TYP. Wave

Design Crit: TPI 2002(STD)/FBC
Cq/RT=1.00(1.25)/0.0)

7.36.042 F.COLLINS
QTY:1 FL/-/4/-/R/-


Scale = .25"/Ft.

ALPINE		TYP Building Components Group, Inc. Haines City, FL 33844	
F.T. 1.00		Indicate of 1.00	
T.C. LL		20.0 PSF	
T.C. DL		10.0 PSF	
B.C. DL		10.0 PSF	
B.C. LL		0.0 PSF	
TOT. LD.		40.0 PSF	
DUR. FAC.		1.25	
SPACING		24.0"	
REF		R8228-77401	
DATE		12/13/07	
DRW		HCUSR8228 07347054	
HC-ENG		JB/DLJ	
SEON		66359	
FROM		AH	
JREF		1TD98228Z01	

Top	chord	2x4	SP	#2	Dense
Bot	chord	2x4	SP	#2	Dense
	Webbs	2x4	SP	#3	

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, PART. ENC. bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ GCpf(+/-)=0.55


Wind reactions based on MWFRS pressures.
Right end vertical not exposed to wind pressure.


$$\sqrt{V_{0-9-1}}$$

15-6-0 Over 2 Supports
R=750 U=116 W=3.5"

$$R=626 \quad U=187 \quad W=6$$

PLT TYP. Wave



ITW Building Components Group, Inc.
Haines City, FL 33844
FL Certificate of Authorization # 0070

Design Crit: $TPI-2002(STD)/FBC$
 $Cq/RT=1.00(1.25)/$

$$Cq/RT=1.00(1.25)/0(0)$$

7.36.0424

QTY:1 FL/-/4/-/-/R/-/


Scale = .3125"/Ft.

WARNING THE FOLLOWING REQUIRE EXISTENCE OF AN ELEVATION, IMMOVING, SHUTTING, INSTALLING AND BRACING REFER TO REPAIR BUILDING COMPONENTS SAFELY THROUGHOUT THESE CONSTRUCTION DATE INSTITUTE, THE BOTTOM LEFT STREET, SUITE 312, ALEXANDRIA, VA 22314 AND VICA (VIRGINIA COMMUNITY COLLEGE) UNLESS OTHERWISE CALLED. MODISON, INC. 563197 FOR SAFETY PRACTICES PERTAINING TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED TOP CEILING.

IMPORTANT JAPANESE A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITM BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TROUS IN CONFORMANCE WITH THE DRAWING, HANDLING, SLIPPING, INSTALLING, A BRACING OF TROUSERS.

DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF MOST NATIONAL DESIGN SPEC. BY AIAPIA) AND FBI. THE BCG
CONNECTION PLATES ARE MADE OF 20/18/1664 (M.H.S./K) ASH A653 GRADE 40/60 (M, K/H/SS) GALV. STEEL. APPLY
PLATES TO EACH FACE OF IRONS AND, UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 160A 2.
ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A.3 OF FBI 11 2002 SEC.3. A SEAL ON THIS

DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



TC LL	20.0 PSF	REF	R8228- 77402
TC DL	10.0 PSF	DATE	12/13/07
BC DL	10.0 PSF	DRW	HCSUR8228 07347055
BC LL	0.0 PSF	HC-ENG	JB/DLJ *
TOT.LD.	40.0 PSF	SEQN-	66364
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TD98228201

```
Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3
:Stack Chord SC1 2x4 SP #
```

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, PART_ENC, bldg, located anywhere in roof, CAT 11, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 GCpi(+/-)=0.55


Wind reactions based on MIFRS pressures.

Right end vertical not exposed to wind pressure.

Deflection meets $L/240$ live and $L/180$ total load. Creep increase factor for dead load is 1.50.

SEE DRW HCUSR001 02086015 FOR GABLE DETAILS.

The building designer is responsible for the design of the roof and ceiling diaphragms, gable end shear walls, and supporting shear walls. Shear walls must provide continuous lateral restraint to the gable end. All connections to be designed by the building designer.


$$2.5 \times 6 (C5) \equiv$$

✓ 0-9-0 ✓

$3\ 1\cdot9\text{(NNL)}$
 $3\ 1\cdot9$
 $13\cdot10\cdot7$
 $13\ 10\cdot7$
 $15\cdot6\cdot0$ Over Continuous Support
 $R=89\ PLF\ U=16\ PLF\ W=15\cdot6\ 0$

Note: All Plates Are 1.5X4 Except As Shown.

PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)

7.36.0424 QTY:1 FL/-/4/-/-/R/-


Scale = .3125"/Ft.

WARNING PRIOR TO REMOVAL, HANDLING, SHIPPING, INSTALLING AND BRACING REFER TO THESE BUILDING CONTROL SAFETY INFORMATION. PUBLISHED BY THE TRUSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA 22314 AND WOOD TRUSS COMPANY OF AMERICA, 6500 ENTERPRISE LANE, MIDLOTHIAN, VA 53179 FOR SAFETY PRECAUTIONS PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED TOP CEILING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITR BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH ITR1, OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

ALPINE

ITW Building Components Group, Inc.
Haines City, FL 33844
F1 Certificate of Authorization #0077



TC LL	20.0 PSF	REF	R8228 - 77403
TC DL	10.0 PSF	DATE	12/13/07
BC DL	10.0 PSF	DRW	HCUSR8228 07347062
BC LL	0.0 PSF	HC-ENG	JB/DLJ
TOT.LD.	40.0 PSF	SEQN -	66417
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF -	1TD98228Z01

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

110 mph wind, 21.38 ft mean hgt, ASCE 7 02, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL 5.0 psf, wind BC DL 1.2 psf.


Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.

Refer to DWG PIGBACKA0207 or PIGBACKB0207 for piggyback details.

SPECIAL LOADS

TC - From	DUR.FAC. = 1.25 / PLATE DUR.FAC. = 1.25	62 PLF at 0.00 to 7.19
TC - From	62 PLF at 7.19 to 14.39	62 PLF at 14.39
BC - From	4 PLF at 0.00 to 14.39	4 PLF at 14.39

Wind reactions based on MMFRS pressures.



PLT TYP. Wave



Design Crit: TP1-2002 (STD)
Cq/RT=1.00(1.25)/0(0)

7.37.0521

QTY: 1 FL/-/4/-/R/-

Scale = .5"/ft.

****WARNING**** TRUSSES ARE NOT TO BE USED IN CONNECTION WITH ANY OTHER BUILDING COMPONENTS. THE TRUSS DESIGNER SHALL BE RESPONSIBLE FOR THE TRUSS DESIGN AND THE BUILDING DESIGNER SHALL BE RESPONSIBLE FOR THE BUILDING DESIGN. THE TRUSS DESIGNER SHALL BE RESPONSIBLE FOR THE TRUSS DESIGN AND THE BUILDING DESIGNER SHALL BE RESPONSIBLE FOR THE BUILDING DESIGN. THE TRUSS DESIGNER SHALL BE RESPONSIBLE FOR THE TRUSS DESIGN AND THE BUILDING DESIGNER SHALL BE RESPONSIBLE FOR THE BUILDING DESIGN.



TC LL	20.0 PSF	REF	R8228-77404
TC DL	10.0 PSF	DATE	12/13/07
BC DL	10.0 PSF	DRW	HCSR8228 07347063
BC LL	0.0 PSF	HC-ENG	JB/DLU
TOT. LD.	40.0 PSF	SEON-	8537 REV
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TD98228Z01

110 mph wind, 21.22 ft mean hgt, ASCE 7-02, CLOSED bldg, located anywhere in roof, CAT 11, EXP B, wind TC DL=5.0 psf, wind BC DL=2.0 psf. $I_w=1.00$ $G_{CPI}(+/-)=0.18$

See DWGS A11030EE0207 & GBULLETIN0207 for more requirements.

Deflection meets $L/240$ live and $L/180$ total load. Creep increase factor for dead load is 1.50.


Refer to DWG PIGBACKA0207 or PIGBACKB0207 for piggyback details.

SPECIAL LOADS

-----	(LUMBER DUR.FAC.=1.25 / PLATE DUR.FAC.=1.25)
TC - From	62 PLF at 0.00 to 62 PLF at 6.54
TC - From	62 PLF at 6.54 to 62 PLF at 13.08
BC - From	4 PLF at 0.00 to 4 PLF at 13.08

Truss spaced at 24.0" OC designed to support 1-0 0 top chord
outlookers. Cladding load shall not exceed 10.00 PSF. Top chord
must not be cut or notched.

In lieu of rigid ceiling use purlins to brace BC @ 24" OC.


$$R=28 \quad R_w=33 \quad U=30 \quad W=7.826^{\circ}$$

R=102 PLF U=27 PLF W=11-1-6

Note: All Plates Are 1.5X4 Except As Shown.

PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)

$$Cq/RT=1.00(1.25)/0(0)$$

7.36.0424 13

QTY:1 FL/-/4/-/-/R/-


Scale = .5"/Ft.

"WARNING" - FRAMES ROUTINE EXISTENCE CASE IN IDENTIFICATION, HANDLING, SHIPPING, INSTALLING AND BRACING REFER TO 6051 (CONTINUING COMPONENT SAFETY INFORMATION) - PUBLISHED BY THE (RISPS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA 22314) AND MICA (4000 TRUSS COMPANY OF AMERICA, 6300 ENTERPRISE LANE, HOUSTON, TX 77079) FOR SAFETY PRACTICES PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED RIGID CEILING.

ALPINE

ITW Building Components Group, Inc.

File case of organization



FL/-/4/-/-/R/-		Scale=.5"/Ft.
TC LL	20.0 PSF	REF R8228- 77405
TC DL	10.0 PSF	DATE 12/13/07
BC DL	10.0 PSF	DRW HCUR8228 07347064
BC LL	0.0 PSF	HC-ENG JB/DLJ
TOT.LD.	40.0 PSF	SEQN- 66381
DUR.FAC.	1.25	FROM AH
SPACING	24.0"	JREF- 1TD98228Z01

THIS DETAIL IS TO BE USED WHEN CONTINUOUS LATERAL BRACING (CLB) IS SPECIFIED ON AN ALPINE TRUSS DESIGN BUT AN ALTERNATIVE WEB BRACING METHOD IS DESIRED.

THIS DETAIL IS ONLY APPLICABLE FOR CHANGING THE SPECIFIED CLIB SHOWN ON SINGLE PLY SEALED DESIGNS TO T-BRACING OR SCAB BRACING.

ALTERNATIVE BRACING SPECIFIED IN CHART BELOW MAY BE CONSERVATIVE.
FOR MINIMUM ALTERNATIVE BRACING, RE-RUN DESIGN WITH APPROPRIATE
BRACING.

WEB MEMBER SIZE	SPECIFIED CLB BRACING	ALTERNATIVE BRACING T OR L-BRACE	SCAB BRACE
2X3 OR 2X4 2X3 OR 2X4	1 ROW 2 ROWS	2X4 2X6	1-2X4 2-2X4
2X6 2X6	1 ROW 2 ROWS	2X4 2X6	1-2X6 2-2X4(*)
2XB 2XB	1 ROW 2 ROWS	2X6 2X6	1-2XB 2-2X6(*)


T-BRACE, L-BRACE AND SCAB BRACE TO BE SAME SPECIES AND GRADE OR BETTER THAN WEB MEMBER UNLESS SPECIFIED OTHERWISE ON ENGINEER'S SEALED DESIGN.

(*) CENTER SCAB ON WIDE FACE OF WEB. APPLY (1) SCAB TO EACH FACE OF WEB.

APPLY TO EITHER SIDE OF WEB NARROW FACE
ATTACH WITH 10d BOX OR GUN
(0.128" x 3".MIN) NAILS.
AT 6" O.C. BRACE IS A
MINIMUM 80% OF WEB
MEMBER LENGTH



APPLYSCAB(S) TO WIDE FACE OF WEB
NO MORE THAN (1) SCAB PER FACE.
ATTACH WITH 10d BOX OR GUN
(0.128" x 3." MIN) NAILS.
AT 6" O.C. BRACE IS A MINIMUM
80% OF WEB MEMBER LENGTH




THIS DRAWING REPLACES DRAWING 579,640

ALPINE

ITW BUILDING COMPONENTS GROUP, INC.
POMPANO BEACH, FLORIDA

1. WARNING: THESE REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCSI BUILDING COMPONENT SAFETY INFORMATION, PUBLISHED BY TPI TRUSS PLATE INSTITUTE, 218 NORTH LEE STE. SUITE 312, ALEXANDRIA, VA 22304 AND VITA GOOD TRUSS CONNECTIONS, 6300 ENTERPRISE LN, MADISON, WI 53719 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TWO CHORD SHALL HAVE PROPERLY ATTACHED STRUTS OR PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CELLING.

2. NOTICE: FURNISH COPY OF THIS DESIGN TO INSTALLATION CONTRACTOR. TYPICAL TPI BG, IND. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN; ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. DESIGN CHANGES WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY AIAA) AND TPI. TYPICAL TPI BG CONNECTOR PLATES ARE MADE OF 20/19/16 GA. (A/SSS) ASTM A653 GRADE 40/60 (A/SSS) GALV. STEEL. APPLY PLATES TO EACH FACE OF TRUSS AND, UNLESS OTHERWISE LIMITED ON THIS DESIGN, POSITION PER SPACING 1606.5. FOR INSTALLATION OF INDICATED TRUSSES, THE PROFESSIONAL ENGINEER ASSUMES RESPONSIBILITY FOR THE TRUSS COMPONENT DESIGN SHOWN, THE SUITABILITY AND INSUFFICIENCY OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER. PER INS/TP1 I SEC. 2.



TC LL	PSF	REF	CLB	SUBST.
TC DL	PSF	DATE	2/23/07	
BC DL	PSF	DRWG	BRCIBSUB0207	
BC LL	PSF	-ENG	MLH/KAR	
TOT. LD.	PSF			
DUR. FAC.				
SPACING				

BRACING GROUP SPECIES AND GRADES:	
GROUP A:	
SPRUCE-PINE-FIR	HEM-FIR
#1 / #2 STANDARD	#2 STUD
#3 STUD	#3 STANDARD
DOUGLAS FIR-LARCH	
#3	
STUD	
STANDARD	
SOUTHERN PINE	
#3	
STUD	
STANDARD	

GROUP B:

HEM-FIR
#1 & BTR

DOUGLAS FIR-LARCH

SOUTHERN PINE

#1

#2

LIVE LOAD DEFLECTION CRITERIA IS $L/240$

PROVIDE UPLIFT CONNECTIONS FOR 80 PLF OVER
CONTINUOUS BEARING (5 PSF TC DEAD LOAD).

GABLE END SUPPORTS LOAD FROM 4'

PLYWOOD OVERHANG.

ATTACH EACH "L" BRACE WITH 10d NAILS.

IN 18" END ZONES AND 4" O.C. BETWEEN


IN 18" END ZONES AND 6" OC BETWEEN ZONES
++ FOR (2) L BRACES; STACE NAILS AT 3 O.C.

"L" BRACING MUST BE A MINIMUM OF 80% OF WEB

MEMBER LENGTH.

CABLE VERTICAL PLATE SIZES	
VERTICAL LENGTH	NO. SPLICE
LESS THAN 4' 0"	1X4 OR 2X3
GREATER THAN 4' 0", BUT LESS THAN 11' 6"	2X4
GREATER THAN 11' 6"	2.5X4

+ REFER TO COMMON TRUSS DESIGN FOR
PEAK, SPLICE, AND HEEL PLATES.



REFER TO CHART ABOVE FOR MAX CABLE VERTICAL LENGTH.

DIAGONAL BRACE OPTION-
VERTICAL LENGTH MAY BE
DOUBLED WHEN DIAGONAL
BRACE IS USED. CONNECT
DIAGONAL BRACE FOR 600#
AT EACH END. MAX WEB
TOTAL LENGTH IS 14'.

VERTICAL LENGTH SHOWN
IN TABLE ABOVE.

CONNECT DIAGONAL AT
MIDPOINT OF VERTICAL WEB.

ALPINE

ITW BUILDING COMPONENTS GROUP, INC.
POMPANO BEACH, FLORIDA

WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BEST BUILDING COMPONENT SAFETY INFORMATION, PUBLISHED BY THE TRUSS PLATE INSTITUTE, 218 NORTH LEE STR., SUITE #12, ALEXANDRIA, VA 22304) AND VIDA C/O/DI TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LN, MADISON, WI 53719 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, THIS CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOLTS CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT FURNISH COPY OF THIS DESIGN TO INSTALLATION CONTRACTOR. ITU BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN, OR FAILURE TO FOLLOW THE TRUSS IN CONFORMANCE WITH TPI OR FABRICATING, HANDLING, SHIPPING, INSTALLING, SPECIFIC, BY AREFA) AND TPI DESIGN COMPART WITH APPLICABLE PROVISIONS OF NOS NATIONAL DESIGN SPEC. BY AREFA) AND TPI TPI BCG CONNECTOR PLATES ARE MADE OF 2018/1816GA C/H/SXSS ASTM A653 GRADE 40/60 (C/H/A/SS) GALV. STEEL. APPLY PLATES TO EACH FACE OF ROSS) AND UNLESS OTHERWISE LOCATED ON THIS PER ANKAGE AS OF TPI 1-2002 SEC. 1603.01. SEE PLAN ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SILENTLY FOR THE TRUSS COMPONENT DESIGN SHOWN, THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER, PER INST/TPI 1 SEC. 2

A circular professional engineer seal for James A. Collins. The outer ring contains the text "JAMES A. COLLINS, P.E." at the top and "PROFESSIONAL ENGINEER" at the bottom, separated by stars. The inner circle contains "STATE OF FLORIDA" and "No. 52212" with a star between them. The seal is stamped over a document with handwritten text.

MAX. TOT. LD. 60 PSF

MAX. SPACING 24.0"

REF ASCF7-02-GAB1014

DATE 2/23/07

DRWG A11015EE0207

FENG

Diagram illustrating the arrangement of cables and the placement of splice, web, and single plate connections on a bridge structure.

The diagram shows a cross-section of a bridge with multiple cables. The central vertical axis is labeled "SYM. ABOUT". The vertical distance from the top of the bridge deck to the bottom of the cable connections is labeled "GABLE VERTICAL LENGTH TYP.". Circled plus signs (+) indicate the locations of splice, web, and single plate connections.

Legend:

- (+) REFERENCE TO ENGINEER
- (+) SPICE, WEB AND SINGLE PLATE TO

EXAMPLE:



LESS THAN 4' 0"	BETWEEN CHOR
GREATER THAN 4' 0"	BETWEEN CHOR
LESS THAN 11' 6"	BETWEEN CHOR
GREATER THAN 11' 6"	BETWEEN CHOR

GABLE VERTICAL PLATE SIZES		
VERTICAL LENGTH BETWEEN CHORDS	PLATE SIZE	IF PLATES OVERLAP*
LESS THAN 4' 0"	1X4 OR 2X3	2X6
GREATER THAN 4' 0" BUT LESS THAN 11' 6"	2X4	2X8
GREATER THAN 11' 6"	2.5X4	2.5X8

④ REFER TO ENGINEERED TRUSS DESIGN FOR PEAK, SPLICE, WEB AND HEEL PLATES.

* IF CABLE VERTICAL PLATES OVERLAP, USE A SINGLE PLATE TO SPAN THE WEB.

EXAMPLE:



PROVIDE CONNECTIONS FOR UPLIFT SPECIFIED ON THE ENGINEERED TRUSS DESIGN
ATTACH EACH "J" REINFORCING MEMBER WITH

HAND DRIVEN NAILS:

(4) 16d COMMON (0.162" X 3.5".MIN) TOENAILS IN TOP AND BOTTOM CHORD

GUN DRIVEN NAILS:

8d COMMON (0.131"X 2.5",MIN) TOENAILS AT 4" O.C. PLUS
(4) TOENAILS IN TOP AND BOTTOM CHORD.

THIS DETAIL TO BE USED WITH THE APPROPRIATE ALPINE CABLE DETAIL FOR ASCE OR SBCCI WIND LOAD.

ASCE 7-93 CABLE DETAIL DRAWINGS

ASCE 7-98 CABLE DETAIL DRAWINGS

ASCE 7-98 CABLE DETAIL DRAWINGS

A13015EC0207, A12015EC0207, A11015EC0207, A10015EC0207, A08515EC0207

ASCE 7-03 CABLE DETAIL DRAWINGS

ASCE 7-02 CABLE DETAIL DRAWINGS
A13015FE0207 A12015FE0207 A11

A13030EE0207, A12030EE0207, A11030EE0207, A10030EE0207, A08530EE0207

ASCE 7-05 CABLE DETAIL DRAWINGS

A13015E50207, A12015E50207, A11015E50207, A10015E50207, A08515E50207,

A13030E50207, A12030E50207, A11030E50207, A10030E50207, A08530E50207

SEE APPROPRIATE ALPINE CABLE DETAIL (ASCE OR SBCC)

WIND LOAD) FOR
VERTICAL LENGTH.


THIS DRAWING REPLACES DRAWINGS GAB98117 876,719 & HC26294035

ALPINE

ITW BUILDING COMPONENTS GROUP, INC.
POMPANO BEACH, FLORIDA

*VARNING- TESTES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BEST BUILDING COMPONENT SAFETY INFORMATION, INCLUDING THE TYPICAL TRUSS PLATE INSTRUMENT, 218 NORTH LEE ST., SUITE 310, ALEXANDRIA, VA 22314 AND VICA GOOD TRUSS COUNCIL OF AMERICA, 6300 ERIE STREET, MADISON, WI 53797 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

**IMPORTANT- FURNISH COPY OF THIS DESIGN TO INSTALLATION CONTRACTOR. ITY BEG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN AND CONTRACTOR TO BUILD THE TRUSS OR COMBINATION WITH THE ROOF FABRICATING, HANDLING, SHIPPING, INSTALLING, DESIGN & SPEC' BY AR&PA AND THE DESIGN CONFRMS WITH APPLICABLE PROVIDINGS OF NDS NATIONAL DESIGN SPEC. BY AR&PA AND THE TTY, BEG CONNECTER PLATES ARE MADE OF 2X10/16GA UHSS/AS 151A A653 GRADE 40/60 (U.H.S.S) STEEL W/CONNECTER PLATES ON EACH FACE OF TROSS/AO, UNLESS OTHERWISE LOCATED ON (U.H.S.S) ANCHORS AT JOINTS. ALL BOLTS MUST BE PREVIOUSLY DRILLED AND CLEANED UP. IT SHALL BE PERMITTED TO USE ONE (1) 1-200Z SEC. 3 160MSEAL DN THIS DRAWING IS INTENDED TO SHOW THE SUTABILITY AND ENGINEERING RESPONSE SOLELY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE LIABILITY AND USE OF THIS COMPIMENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER, PER ANSI/TPI 1 SEC. 2



2x4 "r"
REINFORCING MEMBER
TOENAIL

2x6 "r"
REINFORCING MEMBER
TOENAIL

TO CONVERT FROM "L" TO "T" REINFORCING MEMBERS
MULTIPLY "T" FACTOR BY LENGTH (BASED ON CABLE
VERTICAL SPECIES, GRADE AND SPACING) FOR (1)
2X4 "L" BRACE, GROUP A, OBTAINED FROM THE
APPROPRIATE ALPINE CABLE DETAIL FOR ASCE OR
SECCI WIND LOAD.

MAXIMUM ALLOWABLE "T" REINFORCED GABLE VERTICAL LENGTH IS 14' FROM TOP TO BOTTOM CHORD.

WEB LENGTH INCREASE $W / "T"$ BRACE

WIND SPEED AND MRH	"T" REIN- FORCING SIZE	SBCI	ASCE
110 MPH	2x4	10 %	10 %
15 FT	2x6	40 %	50 %
110 MPH	2x4	10 %	10 %
30 FT	2x6	50 %	50 %
100 MPH	2x4	10 %	10 %
15 FT	2x6	30 %	50 %
100 MPH	2x4	10 %	10 %
30 FT	2x6	40 %	40 %
90 MPH	2x4	20 %	10 %
15 FT	2x6	20 %	40 %
90 MPH	2x4	10 %	10 %
30 FT	2x6	30 %	50 %
80 MPH	2x4	10 %	20 %
15 FT	2x6	10 %	30 %
80 MPH	2x4	20 %	10 %
30 FT	2x6	20 %	40 %
70 MPH	2x4	0 %	20 %
15 FT	2x6	0 %	20 %
70 MPH	2x4	10 %	20 %
30 FT	2x6	10 %	30 %

EXAMPLE:

ASCE WIND SPEED = 100 MPH

MEAN ROOF HEIGHT = 30 FT

CABLE VERTICAL = 24" O.C. SP #3

1 REINFORCING MEMBER SIZE = 2X4

(1) 2X4 "L" BRACE LENGTH = 6' 7"

MAXIMUM "T" REINFORCED CABLE VERTICAL LENGTH

1.10 x 6' 7" = 7' 3"

REF	LET-IN VERT
DATE	2/23/07
DRWG	GBLLETIN0207
-ENG	DLJ/KAR
MAX TOT. LD. 60 PSF	
DUR. FAC.	ANY
MAX SPACING	24.0"

PIGGYBACK DETAIL


100 MPH WIND, 30.00 FT. MEAN HGT. ASCE 7-02 OR ASCE 7-05, CLOSED BLDG. LOCATED ANYWHERE IN ROOF, CAT II, EXP. C, WIND TC DL=5.0 PSF, WIND BC DL=5.0 PSF.

80 MPH WIND, 30.00 FT. MEAN HGT, SBC, ENCLOSED BLDG, LOCATED ANYWHERE IN ROOF WIND TC DL=5.0 PSF, WIND BC DL=5.0 PSF.

100 MPH WIND, 30.00 FT. MEAN HGT, ASCE 7-98, CLOSED BLDG, LOCATED ANYWHERE IN ROOF, CAT II, EXP. C, WIND TC DL=5.0 PSF, WIND BC DL=5.0 PSF.

NOTE: TOP CHORDS OF TRUSSES SUPPORTING PIGGYBACK CAP TRUSSES MUST BE ADEQUATLY BRACED BY SHEATHING OR PURLINS. PROVIDE DIAGONAL BRACING OR OTHER SUITABLE ANCHORAGE TO PERMANENTLY RESTRAIN PURLINS.


DETAIL A



PIGGYBACK CAP TRUSS TOENAILED TO ALL TOP CHORD BRACING WITH (2) 10d COMMON (0.148"x3") NAILS.


* 12" MIN RIGID SHEATHING OVERLAP WITH 8d COMMON (0.131"x2.5") OR GUN NAILS IN OVERLAP ZONE SPACED AT 4" O.C.

DETAIL B




PIGGYBACK CAP TRUSS TOENAILED TO ALL TOP CHORD BRACING WITH (2) 10d COMMON (0.148"x3") NAILS AND SECURED WITH 2x4 #3 GRADE SCAB (1 SIDE ONLY) ATTACHED WITH 10d COMMON NAILS AT 4" O.C.


DETAIL C



IN LIEU OF TRULOX CONNECTORS, ALPINE 62PB SPECIAL PIGGYBACK CONNECTORS MAY BE USED. SHOP APPLY TOOTHED PORTION FIELD ATTACH TO MATING TRUSS WITH (4) 0.120" X 0.375" NAILS MINIMUM EACH FACE.




THIS DRAWING REPLACES DRAWINGS 581.670 & 961.960



ITW BUILDING COMPONENTS GROUP, INC.
POMPAHO BEACH, FLORIDA

WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BEST BUILDING COMPONENT SAFETY INFORMATION, PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 210 NORTH LEE STR., SUITE 312, ALEXANDRIA, VA 22314) AND VITA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LN, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

INSTRUCTIONS FURNISH COPY OF THIS DESIGN TO INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. DESIGN CONFORMS WITH TPI, OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. ITW, BCG CONNECTOR PLATES ARE MADE OF 2018/1664 (A/H/SS)X40 40/60 (A/H/SS) UNLESS OTHERWISE LOCATED ON THE H/SS DESIGN SECTION PER PLATES TO EACH FACE OF ROSS AND UNLESS OTHERWISE LOCATED ON THE H/SS DESIGN SECTION PER PLATES TO EACH FACE OF ROSS AND UNLESS OTHERWISE LOCATED ON THE H/SS DESIGN SECTION PER PLATES TO EACH FACE OF ROSS. A SEAL ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER, PER ANSI/TPI 1 SEC. 2



TC LL	PSF	REF	PIGGYBACK
TC DL	PSF	DATE	2/23/07
BC DL	PSF	DRWG	PIGBACKA0207
BC LL	PSF	-ENG	DLJ/KAR
TOT. LD.	MAX 60 PSF		
DUR. FAC.	1.15		
SPACING	24.0"		

TOP	CHORD	2X4	#2	OR	BETTER
BOT	CHORD	2X4	#2	OR	BETTER
	WEBS	2X4	#3	OR	BETTER

SPACE PIGGYBACK VERTICALS AT 4' OC MAX.

PIGgyBACK BOTTOM CHORD MAY BE OMITTED. ATTACH VERTICAL WEBS TO TRUSS TOP CHORD WITH 1.5X3 PLATE.

MAY BE APPLIED BENEATH THE TOP CHORD OF SUPPORTING TRUSS


REFER TO ENGINEER'S SEALED DESIGN FOR REQUIRED PURLIN SPACING

THIS DETAIL IS APPLICABLE FOR THE FOLLOWING WIND CONDITIONS:


130 MPH WIND, 30' MEAN HGT, ASCE 7-98, ASCE 7-02 OR
ASCE 7-05, CLOSED BLDG, LOCATED ANYWHERE IN ROOF, CAT II
EXP C, WIND TC DL=5 PSF, WIND BC DL=5 PSF

110 MPH WIND, 30' MEAN HGT, SBC
ENCLOSED BLDG, LOCATED ANYWHERE IN ROOF
WIND TC DL=5 PSF, WIND BC DL=5 PSF

FRONT FACE (E,*) PLATES MAY BE OFFSET FROM BACK FACE PLATES AS LONG AS BOTH FACES ARE SPACED 4" OC MAX.



EITHER PLATE
LOCATION IS
ACCEPTABLE



*ATTACH PIGGYBACK WITH 3X8 TRULOX OR ALPINE PIGGYBACK SPECIAL PLATE


THIS DRAWING REPLACES DRAWINGS 634,016 634,017 & 847,045

JOINT TYPE	SPANS UP TO			
	30'	34'	38'	52'
A	2X4	2.5X4	2.5X4	3X5
B	4X6	5X6	5X6	5X6
C	1.5X3	1.5X4	1.5X4	1.5X4
D	5X4	5X5	5X5	5X6
E	4X6 OR 3X6 TRULOX AT 4' OC, ROTATED VERTICALLY			

WEB BRACING CHART	
WEB LENGTH	REQUIRED BRACING
0' TO 7'9"	NO BRACING
7'9" TO 10'	1x4 "T" BRACE. SAME GRADE, SPECIES AS WEB MEMBER, OR BETTER, AND 80% LENGTH OF WEB MEMBER. ATTACH WITH 6d BOX (0.113"X 2.5" MIN) NAILS AT 4" OC.
10' TO 14'	2x4 "T" BRACE. SAME GRADE, SPECIES AS WEB MEMBER, OR BETTER, AND 80% LENGTH OF WEB MEMBER. ATTACH WITH 16d BOX (0.135"X 3.5" MIN) NAILS AT 4" OC.

ATTACH TRULOX PLATES WITH (8) 0.120" X 1.375" NAILS OR EQUAL, PER FACE PER PLY. (4) NAILS IN EACH MEMBER TO BE CONNECTED. REFER TO DRAWING 160 TLR FOR TRULOX INFORMATION.

ATTACH TEETH TO THE PIGGYBACK AT THE TIME OF FABRICATION. ATTACH TO SUPPORTING TRUSS WITH (4) 0.120" X 1.375" NAILS PER FACE PER PLY. APPLY PIGGYBACK SPECIAL PLATE TO EACH TRUSS FACE AND SPACE 4' OC OR LESS.



*** PIGGYBACK SPECIAL, PLATE**

ALPINE

ITW BUILDING COMPONENTS GROUP, INC.
POMPANO BEACH, FLORIDA

WARNING - BUYERS REQUIRE EXTREME CARE FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCI BUILDING COMPONENTS SAFETY INFORMATION, PUBLISHED BY THE TRUSS PLATE INSTITUTE, 210 NORTH LEE ST., SUITE 312, ALEXANDRIA, VA 22314, AND VITA GOOD TRUSS COMPANY, 6200 ENTERPRISE LN., MADISON, WI 53719, FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE ACTIVITIES. ALL TRUSSES INDICATED IN THIS CHORD SHALL HAVE PROTECT, ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.


IMPORTANT - FURNISH COPY OF THIS DESIGN TO INSTALLATION CONTRACTOR. ITV, INC., SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN, ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH THE FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES DESIGN CONTRACTS OR ANY APPLICABLE PROVISIONS OF AISC, CHORD, DESIGN SPEC. BY AISC AND ITS DESIGN CONTRACTS OR ANY APPLICABLE PROVISIONS OF AISC, CHORD, DESIGN SPEC. BY AISC AND ITS DESIGN CONTRACTS. APPLY PLATES TO EACH FACE OF TRUSS AND, UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 1604-Z. ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER AMENAS AS OF TPI 1-2002 SEC. 3. A SEAL ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL, ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUSTAINABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER. PER AMENAS/TPI 1 SEC. 2

MAX LOADING	REF	PIGCYBACK
55 PSF AT	DATE	2/23/07
1.33 DUR. FAC.	DRWG	PIGBACKB0207
50 PSF AT	-ENG	DLJ/KAR
1.25 DUR. FAC.		
47 PSF AT		
1.15 DUR. FAC.		
SPACING		24.0"

2x4 CABLE TRUSS		BRACE		NO		(1) 1x4 "L" BRACE *		(1) 2x4 "L" BRACE *		(2) 2x4 "L" BRACE **		(1) 2x6 "L" BRACE *		(2) 2x6 "L" BRACE **	
GABLE SPACING	VERTICAL SPECIES	GRADE	BRACES	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B
12" O.C.	SPF	#1 / #2	STUD	3' 8"	6' 4"	5' 5"	5' 5"	7' 2"	7' 8"	8' 11"	8' 11"	11' 2"	11' 2"	14' 0"	14' 0"
			STUD	3' 7"	5' 5"	5' 5"	5' 5"	7' 1"	8' 11"	8' 11"	11' 1"	11' 1"	14' 0"	14' 0"	14' 0"
			STANDARD	3' 7"	4' 8"	4' 8"	6' 1"	6' 1"	8' 3"	8' 3"	9' 6"	9' 6"	12' 11"	12' 11"	14' 0"
			#1	4' 0"	6' 4"	6' 4"	6' 10"	7' 6"	8' 11"	8' 11"	9' 7"	11' 9"	12' 8"	14' 0"	14' 0"
16" O.C.	SPF	#1 / #2	STUD	3' 11"	6' 4"	5' 7"	5' 7"	7' 4"	8' 11"	8' 11"	9' 5"	11' 5"	11' 5"	14' 0"	14' 0"
			STUD	3' 9"	5' 6"	5' 6"	5' 6"	7' 3"	8' 11"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"
			STANDARD	3' 8"	4' 9"	4' 9"	4' 9"	6' 3"	8' 5"	8' 5"	9' 9"	9' 9"	13' 3"	13' 3"	14' 0"
			#1 / #2	4' 2"	7' 3"	7' 3"	7' 5"	8' 7"	8' 10"	10' 3"	10' 3"	13' 5"	13' 5"	14' 0"	14' 0"
24" O.C.	SPF	#1 / #2	STUD	4' 1"	6' 8"	6' 8"	6' 8"	8' 7"	8' 10"	10' 3"	10' 3"	13' 5"	13' 5"	14' 0"	14' 0"
			STUD	4' 1"	6' 0"	6' 0"	6' 0"	8' 7"	8' 7"	10' 3"	10' 3"	13' 5"	13' 5"	14' 0"	14' 0"
			STANDARD	4' 1"	5' 8"	5' 8"	5' 8"	7' 6"	7' 6"	10' 1"	10' 1"	11' 8"	11' 8"	14' 0"	14' 0"
			#1	4' 7"	7' 3"	7' 3"	7' 9"	8' 7"	9' 3"	10' 3"	11' 0"	13' 5"	14' 0"	14' 0"	14' 0"

BRACING GROUP SPECIES AND GRADES:	
GROUP A:	
SPRUCE-PINE-FIR	HEM-FIR
#1 / #2	#2
STANDARD	STUD
#3	#3
STUD	STANDARD
STANDARD	STANDARD
GROUP B:	
HEM-FIR	DOUGLAS FIR-LARCH
#1 & BTR	#1
#1	#2
SOUTHERN PINE	DOUGLAS FIR-LARCH
#1	#1
#2	#2

GABLE TRUSS DETAIL NOTES:
LIVE LOAD DEFLECTION CRITERIA IS L/240.
PROVIDE UPLIFT CONNECTIONS FOR 100 PLF OVER CONTINUOUS BEARING (5 PSF TO DEAD LOAD).
GABLE END SUPPORTS LOAD FROM 4' 0" OUTLOOKERS WITH 2' 0" OVERHANG, OR 12" PLYWOOD OVERHANG.
ATTACH EACH "L" BRACE WITH 10d NAILS.
* FOR (1) "L" BRACE: SPACE NAILS AT 2' 0" O.C.
IN 18" END ZONES AND 4" O.C. BETWEEN ZONES.
** FOR (2) "L" BRACES: SPACE NAILS AT 3' 0" O.C. IN 18" END ZONES AND 6" O.C. BETWEEN ZONES.
"L" BRACING MUST BE A MINIMUM OF 80% OF WEB MEMBER LENGTH.



GABLE VERTICAL PLATE SIZES	
VERTICAL LENGTH	NO SPLICE
LESS THAN 4' 0"	1x4 OR 2x3
GREATER THAN 4' 0", BUT LESS THAN 11' 6"	2x4
GREATER THAN 11' 6"	2.5x4
+ REFER TO COMMON TRUSS DESIGN FOR PEAK, SPLICE, AND HEEL PLATES.	

REFER TO CHART ABOVE FOR MAX GABLE VERTICAL LENGTH.

ALPINE

TRUSS BUILDING COMPONENTS GROUP, INC.
POMPAHO BEACH, FLORIDA

MAX. TOT. LD. 60 PSF

MAX. SPACING 24.0"

REF ASCE7-02 CAB1030

DATE 2/23/07

DRWG A11030DE0207

-ENG

STATE OF FLORIDA

PROFESSIONAL ENGINEER

JAMES E. LEE

License No. 68212

140 MPH WIND, 30.0 FT MEAN HGT, ASCE 7-98, PART. ENC. BLDG, LOCATED ANYWHERE IN ROOF, CAT II, EXP C, WIND TCOL=5.0 PSF, WIND BCOL=5.0 PSF.

140 MPH WIND, 30.0 FT MEAN HGT, ASCE 7-02, PART. ENC. BLDG, LOCATED ANYWHERE IN ROOF, CAT II, EXP C, WIND TCOL=5.0 PSF, WIND BCOL=5.0 PSF.

+ FOR VERTICAL WEBS LESS THAN 4'0": W1X4
FOR VERTICAL WEBS GREATER THAN 4'0" BUT NO MORE THAN 11'6": W2X4.

* SPLICE, PEAK, AND HEEL PLATES TO MATCH COMMON TRUSS.

** 2X4 OR GREATER CHORDS.

DROP GABLE WILL SUPPORT 4'0" OUTLOOKERS WITH 2'0" OVERHANG (DROP HEEL GABLE) SPACED 24" O.C., OR THE LOAD FROM 12" PLYWOOD OVERHANG (NOMINAL HEEL GABLE).

IT IS THE RESPONSIBILITY OF THE BUILDING DESIGNER TO DESIGN THE ROOF AND CEILING DIAPHRAGMS AND SPECIFY CONNECTIONS TO TRANSFER ALL OUT-OF-PLANE LOADS INTO THE ROOF AND CEILING DIAPHRAGMS.

THE BUILDING DESIGNER IS RESPONSIBLE FOR THE GABLE SHEAR WALL DESIGN, CEILING AND ROOF SHEATHING DIAPHRAGM CONNECTIONS, AND ALL TRUSS TO WALL CONNECTIONS.

++ 7/16 MINIMUM APA RATED SHEATHING PROPERLY ATTACHED WITH LONG DIMENSION PERPENDICULAR TO SUPPORTS.

R1 NOTE: NAIL STEPS OF LADDER TRUSS ONTO THE OUTSIDE PIECES WITH 2-16D NAILS AT EACH END.

R1 NOTE: ATTACH LADDER TRUSS TO TOP CHORD OF GABLE TRUSS WITH TWO ROWS OF 16D NAILS @ 8" O.C. STAGGERED 4"

ALT. GABLE SHAPES:



Note: All Plates Are 2X4 Except As Shown.

PLT TYP. Wave TPI-95

Design Crt: TPI-1995(STD)

WARNING TRUSSES ALONG EXTERIOR GABLE TO FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BC51.1.03 (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE), 503 D'ONOFRIO DR., SUITE 200, MADISON, WI 53719, AND WICA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS, UNLESS OTHERWISE INDICATED. FOR CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. PRODUCTS, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI: OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

DESIGN CONDITIONS WITH APPLICABLE PROVISIONS OF AISC (NATIONAL DESIGN SPEC. BY AISC) AND TPI: ALTHOUGH PLATES TO EACH END OF TRUSS AND, UNLESS OTHERWISE SPECIFIED ON THIS DESIGN, SECTIONS FOR END PLATES SHALL BE 2X4 OR 2X6 OR 2X8 OR 2X10 OR 2X12 OR 2X14 OR 2X16 OR 2X18 OR 2X20 OR 2X22 OR 2X24 OR 2X26 OR 2X28 OR 2X30 OR 2X32 OR 2X34 OR 2X36 OR 2X38 OR 2X40 OR 2X42 OR 2X44 OR 2X46 OR 2X48 OR 2X50 OR 2X52 OR 2X54 OR 2X56 OR 2X58 OR 2X60 OR 2X62 OR 2X64 OR 2X66 OR 2X68 OR 2X70 OR 2X72 OR 2X74 OR 2X76 OR 2X78 OR 2X80 OR 2X82 OR 2X84 OR 2X86 OR 2X88 OR 2X90 OR 2X92 OR 2X94 OR 2X96 OR 2X98 OR 2X100 OR 2X102 OR 2X104 OR 2X106 OR 2X108 OR 2X110 OR 2X112 OR 2X114 OR 2X116 OR 2X118 OR 2X120 OR 2X122 OR 2X124 OR 2X126 OR 2X128 OR 2X130 OR 2X132 OR 2X134 OR 2X136 OR 2X138 OR 2X140 OR 2X142 OR 2X144 OR 2X146 OR 2X148 OR 2X150 OR 2X152 OR 2X154 OR 2X156 OR 2X158 OR 2X160 OR 2X162 OR 2X164 OR 2X166 OR 2X168 OR 2X170 OR 2X172 OR 2X174 OR 2X176 OR 2X178 OR 2X180 OR 2X182 OR 2X184 OR 2X186 OR 2X188 OR 2X190 OR 2X192 OR 2X194 OR 2X196 OR 2X198 OR 2X200 OR 2X202 OR 2X204 OR 2X206 OR 2X208 OR 2X210 OR 2X212 OR 2X214 OR 2X216 OR 2X218 OR 2X220 OR 2X222 OR 2X224 OR 2X226 OR 2X228 OR 2X230 OR 2X232 OR 2X234 OR 2X236 OR 2X238 OR 2X240 OR 2X242 OR 2X244 OR 2X246 OR 2X248 OR 2X250 OR 2X252 OR 2X254 OR 2X256 OR 2X258 OR 2X260 OR 2X262 OR 2X264 OR 2X266 OR 2X268 OR 2X270 OR 2X272 OR 2X274 OR 2X276 OR 2X278 OR 2X280 OR 2X282 OR 2X284 OR 2X286 OR 2X288 OR 2X290 OR 2X292 OR 2X294 OR 2X296 OR 2X298 OR 2X300 OR 2X302 OR 2X304 OR 2X306 OR 2X308 OR 2X310 OR 2X312 OR 2X314 OR 2X316 OR 2X318 OR 2X320 OR 2X322 OR 2X324 OR 2X326 OR 2X328 OR 2X330 OR 2X332 OR 2X334 OR 2X336 OR 2X338 OR 2X340 OR 2X342 OR 2X344 OR 2X346 OR 2X348 OR 2X350 OR 2X352 OR 2X354 OR 2X356 OR 2X358 OR 2X360 OR 2X362 OR 2X364 OR 2X366 OR 2X368 OR 2X370 OR 2X372 OR 2X374 OR 2X376 OR 2X378 OR 2X380 OR 2X382 OR 2X384 OR 2X386 OR 2X388 OR 2X390 OR 2X392 OR 2X394 OR 2X396 OR 2X398 OR 2X400 OR 2X402 OR 2X404 OR 2X406 OR 2X408 OR 2X410 OR 2X412 OR 2X414 OR 2X416 OR 2X418 OR 2X420 OR 2X422 OR 2X424 OR 2X426 OR 2X428 OR 2X430 OR 2X432 OR 2X434 OR 2X436 OR 2X438 OR 2X440 OR 2X442 OR 2X444 OR 2X446 OR 2X448 OR 2X450 OR 2X452 OR 2X454 OR 2X456 OR 2X458 OR 2X460 OR 2X462 OR 2X464 OR 2X466 OR 2X468 OR 2X470 OR 2X472 OR 2X474 OR 2X476 OR 2X478 OR 2X480 OR 2X482 OR 2X484 OR 2X486 OR 2X488 OR 2X490 OR 2X492 OR 2X494 OR 2X496 OR 2X498 OR 2X500 OR 2X502 OR 2X504 OR 2X506 OR 2X508 OR 2X510 OR 2X512 OR 2X514 OR 2X516 OR 2X518 OR 2X520 OR 2X522 OR 2X524 OR 2X526 OR 2X528 OR 2X530 OR 2X532 OR 2X534 OR 2X536 OR 2X538 OR 2X540 OR 2X542 OR 2X544 OR 2X546 OR 2X548 OR 2X550 OR 2X552 OR 2X554 OR 2X556 OR 2X558 OR 2X560 OR 2X562 OR 2X564 OR 2X566 OR 2X568 OR 2X570 OR 2X572 OR 2X574 OR 2X576 OR 2X578 OR 2X580 OR 2X582 OR 2X584 OR 2X586 OR 2X588 OR 2X590 OR 2X592 OR 2X594 OR 2X596 OR 2X598 OR 2X600 OR 2X602 OR 2X604 OR 2X606 OR 2X608 OR 2X610 OR 2X612 OR 2X614 OR 2X616 OR 2X618 OR 2X620 OR 2X622 OR 2X624 OR 2X626 OR 2X628 OR 2X630 OR 2X632 OR 2X634 OR 2X636 OR 2X638 OR 2X640 OR 2X642 OR 2X644 OR 2X646 OR 2X648 OR 2X650 OR 2X652 OR 2X654 OR 2X656 OR 2X658 OR 2X660 OR 2X662 OR 2X664 OR 2X666 OR 2X668 OR 2X670 OR 2X672 OR 2X674 OR 2X676 OR 2X678 OR 2X680 OR 2X682 OR 2X684 OR 2X686 OR 2X688 OR 2X690 OR 2X692 OR 2X694 OR 2X696 OR 2X698 OR 2X700 OR 2X702 OR 2X704 OR 2X706 OR 2X708 OR 2X710 OR 2X712 OR 2X714 OR 2X716 OR 2X718 OR 2X720 OR 2X722 OR 2X724 OR 2X726 OR 2X728 OR 2X730 OR 2X732 OR 2X734 OR 2X736 OR 2X738 OR 2X740 OR 2X742 OR 2X744 OR 2X746 OR 2X748 OR 2X750 OR 2X752 OR 2X754 OR 2X756 OR 2X758 OR 2X760 OR 2X762 OR 2X764 OR 2X766 OR 2X768 OR 2X770 OR 2X772 OR 2X774 OR 2X776 OR 2X778 OR 2X780 OR 2X782 OR 2X784 OR 2X786 OR 2X788 OR 2X790 OR 2X792 OR 2X794 OR 2X796 OR 2X798 OR 2X800 OR 2X802 OR 2X804 OR 2X806 OR 2X808 OR 2X810 OR 2X812 OR 2X814 OR 2X816 OR 2X818 OR 2X820 OR 2X822 OR 2X824 OR 2X826 OR 2X828 OR 2X830 OR 2X832 OR 2X834 OR 2X836 OR 2X838 OR 2X840 OR 2X842 OR 2X844 OR 2X846 OR 2X848 OR 2X850 OR 2X852 OR 2X854 OR 2X856 OR 2X858 OR 2X860 OR 2X862 OR 2X864 OR 2X866 OR 2X868 OR 2X870 OR 2X872 OR 2X874 OR 2X876 OR 2X878 OR 2X880 OR 2X882 OR 2X884 OR 2X886 OR 2X888 OR 2X890 OR 2X892 OR 2X894 OR 2X896 OR 2X898 OR 2X900 OR 2X902 OR 2X904 OR 2X906 OR 2X908 OR 2X910 OR 2X912 OR 2X914 OR 2X916 OR 2X918 OR 2X920 OR 2X922 OR 2X924 OR 2X926 OR 2X928 OR 2X930 OR 2X932 OR 2X934 OR 2X936 OR 2X938 OR 2X940 OR 2X942 OR 2X944 OR 2X946 OR 2X948 OR 2X950 OR 2X952 OR 2X954 OR 2X956 OR 2X958 OR 2X960 OR 2X962 OR 2X964 OR 2X966 OR 2X968 OR 2X970 OR 2X972 OR 2X974 OR 2X976 OR 2X978 OR 2X980 OR 2X982 OR 2X984 OR 2X986 OR 2X988 OR 2X990 OR 2X992 OR 2X994 OR 2X996 OR 2X998 OR 2X1000 OR 2X1002 OR 2X1004 OR 2X1006 OR 2X1008 OR 2X1010 OR 2X1012 OR 2X1014 OR 2X1016 OR 2X1018 OR 2X1020 OR 2X1022 OR 2X1024 OR 2X1026 OR 2X1028 OR 2X1030 OR 2X1032 OR 2X1034 OR 2X1036 OR 2X1038 OR 2X1040 OR 2X1042 OR 2X1044 OR 2X1046 OR 2X1048 OR 2X1050 OR 2X1052 OR 2X1054 OR 2X1056 OR 2X1058 OR 2X1060 OR 2X1062 OR 2X1064 OR 2X1066 OR 2X1068 OR 2X1070 OR 2X1072 OR 2X1074 OR 2X1076 OR 2X1078 OR 2X1080 OR 2X1082 OR 2X1084 OR 2X1086 OR 2X1088 OR 2X1090 OR 2X1092 OR 2X1094 OR 2X1096 OR 2X1098 OR 2X1100 OR 2X1102 OR 2X1104 OR 2X1106 OR 2X1108 OR 2X1110 OR 2X1112 OR 2X1114 OR 2X1116 OR 2X1118 OR 2X1120 OR 2X1122 OR 2X1124 OR 2X1126 OR 2X1128 OR 2X1130 OR 2X1132 OR 2X1134 OR 2X1136 OR 2X1138 OR 2X1140 OR 2X1142 OR 2X1144 OR 2X1146 OR 2X1148 OR 2X1150 OR 2X1152 OR 2X1154 OR 2X1156 OR 2X1158 OR 2X1160 OR 2X1162 OR 2X1164 OR 2X1166 OR 2X1168 OR 2X1170 OR 2X1172 OR 2X1174 OR 2X1176 OR 2X1178 OR 2X1180 OR 2X1182 OR 2X1184 OR 2X1186 OR 2X1188 OR 2X1190 OR 2X1192 OR 2X1194 OR 2X1196 OR 2X1198 OR 2X1200 OR 2X1202 OR 2X1204 OR 2X1206 OR 2X1208 OR 2X1210 OR 2X1212 OR 2X1214 OR 2X1216 OR 2X1218 OR 2X1220 OR 2X1222 OR 2X1224 OR 2X1226 OR 2X1228 OR 2X1230 OR 2X1232 OR 2X1234 OR 2X1236 OR 2X1238 OR 2X1240 OR 2X1242 OR 2X1244 OR 2X1246 OR 2X1248 OR 2X1250 OR 2X1252 OR 2X1254 OR 2X1256 OR 2X1258 OR 2X1260 OR 2X1262 OR 2X1264 OR 2X1266 OR 2X1268 OR 2X1270 OR 2X1272 OR 2X1274 OR 2X1276 OR 2X1278 OR 2X1280 OR 2X1282 OR 2X1284 OR 2X1286 OR 2X1288 OR 2X1290 OR 2X1292 OR 2X1294 OR 2X1296 OR 2X1298 OR 2X1300 OR 2X1302 OR 2X1304 OR 2X1306 OR 2X1308 OR 2X1310 OR 2X1312 OR 2X1314 OR 2X1316 OR 2X1318 OR 2X1320 OR 2X1322 OR 2X1324 OR 2X1326 OR 2X1328 OR 2X1330 OR 2X1332 OR 2X1334 OR 2X1336 OR 2X1338 OR 2X1340 OR 2X1342 OR 2X1344 OR 2X1346 OR 2X1348 OR 2X1350 OR 2X1352 OR 2X1354 OR 2X1356 OR 2X1358 OR 2X1360 OR 2X1362 OR 2X1364 OR 2X1366 OR 2X1368 OR 2X1370 OR 2X1372 OR 2X1374 OR 2X1376 OR 2X1378 OR 2X1380 OR 2X1382 OR 2X1384 OR 2X1386 OR 2X1388 OR 2X1390 OR 2X1392 OR 2X1394 OR 2X1396 OR 2X1398 OR 2X1400 OR 2X1402 OR 2X1404 OR 2X1406 OR 2X1408 OR 2X1410 OR 2X1412 OR 2X1414 OR 2X1416 OR 2X1418 OR 2X1420 OR 2X1422 OR 2X1424 OR 2X1426 OR 2X1428 OR 2X1430 OR 2X1432 OR 2X1434 OR 2X1436 OR 2X1438 OR 2X1440 OR 2X1442 OR 2X1444 OR 2X1446 OR 2X1448 OR 2X1450 OR 2X1452 OR 2X1454 OR 2X1456 OR 2X1458 OR 2X1460 OR 2X1462 OR 2X1464 OR 2X1466 OR 2X1468 OR 2X1470 OR 2X1472 OR 2X1474 OR 2X1476 OR 2X1478 OR 2X1480 OR 2X1482 OR 2X1484 OR 2X1486 OR 2X1488 OR 2X1490 OR 2X1492 OR 2X1494 OR 2X1496 OR 2X1498 OR 2X1500 OR 2X1502 OR 2X1504 OR 2X1506 OR 2X1508 OR 2X1510 OR 2X1512 OR 2X1514 OR 2X1516 OR 2X1518 OR 2X1520 OR 2X1522 OR 2X1524 OR 2X1526 OR 2X1528 OR 2X1530 OR 2X1532 OR 2X1534 OR 2X1536 OR 2X1538 OR 2X1540 OR 2X1542 OR 2X1544 OR 2X1546 OR 2X1548 OR 2X1550 OR 2X1552 OR 2X1554 OR 2X1556 OR 2X1558 OR 2X1560 OR 2X1562 OR 2X1564 OR 2X1566 OR 2X1568 OR 2X1570 OR 2X1572 OR 2X1574 OR 2X1576 OR 2X1578 OR 2X1580 OR 2X1582 OR 2X1584 OR 2X1586 OR 2X1588 OR 2X1590 OR 2X1592 OR 2X1594 OR 2X1596 OR 2X1598 OR 2X1600 OR 2X1602 OR 2X1604 OR 2X1606 OR 2X1608 OR 2X1610 OR 2X1612 OR 2X1614 OR 2X1616 OR 2X1618 OR 2X1620 OR 2X1622 OR 2X1624 OR 2X1626 OR 2X1628 OR 2X1630 OR 2X1632 OR 2X1634 OR 2X1636 OR 2X1638 OR 2X1640 OR 2X1642 OR 2X1644 OR 2X1646 OR 2X1648 OR 2X1650 OR 2X1652 OR 2X1654 OR 2X1656 OR 2X1658 OR 2X1660 OR 2X1662 OR 2X1664 OR 2X1666 OR 2X1668 OR 2X1670 OR 2X1672 OR 2X1674 OR 2X1676 OR 2X1678 OR 2X1680 OR 2X1682 OR 2X1684 OR 2X1686 OR 2X1688 OR 2X1690 OR 2X1692 OR 2X1694 OR 2X1696 OR 2X1698 OR 2X1700 OR 2X1702 OR 2X1704 OR 2X1706 OR 2X1708 OR 2X1710 OR 2X1712 OR 2X1714 OR 2X1716 OR 2X1718 OR 2X1720 OR 2X1722 OR 2X1724 OR 2X1726 OR 2X1728 OR 2X1730 OR 2X1732 OR 2X1734 OR 2X1736 OR 2X1738 OR 2X1740 OR 2X1742 OR 2X1744 OR 2X1746 OR 2X1748 OR 2X1750 OR 2X1752 OR 2X1754 OR 2X1756 OR 2X1758 OR 2X1760 OR 2X1762 OR 2X1764 OR 2X1766 OR 2X1768 OR 2X1770 OR 2X1772 OR 2X1774 OR 2X1776 OR 2X1778 OR 2X1780 OR 2X1782 OR 2X1784 OR 2X1786 OR 2X1788 OR 2X1790 OR 2X1792 OR 2X1794 OR 2X1796 OR 2X1798 OR 2X1800 OR 2X1802 OR 2X1804 OR 2X1806 OR 2X1808 OR 2X1810 OR 2X1812 OR 2X1814 OR 2X1816 OR 2X1818 OR 2X1820 OR 2X1822 OR 2X1824 OR 2X1826 OR 2X1828 OR 2X1830 OR 2X1832 OR 2X1834 OR 2X1836 OR 2X1838 OR 2X1840 OR 2X1842 OR 2X1844 OR 2X1846 OR 2X1848 OR 2X1850 OR 2X1852 OR 2X1854 OR 2X1856 OR 2X1858 OR 2X1860 OR 2X1862 OR 2X1864 OR 2X1866 OR 2X1868 OR 2X1870 OR 2X1872 OR 2X1874 OR 2X1876 OR 2X1878 OR 2X1880 OR 2X1882 OR 2X1884 OR 2X1886 OR 2X1888 OR 2X1890 OR 2X1892 OR 2X1894 OR 2X1896 OR 2X1898 OR 2X1900 OR 2X1902 OR 2X1904 OR 2X1906 OR 2X1908 OR 2X1910 OR 2X1912 OR 2X1914 OR 2X1916 OR 2X1918 OR 2X1920 OR 2X1922 OR 2X1924 OR 2X1926 OR 2X1928 OR 2X1930 OR 2X1932 OR 2X1934 OR 2X1936 OR 2X1938 OR 2X1940 OR 2X1942 OR 2X1944 OR 2X1946 OR 2X1948 OR 2X1950 OR 2X1952 OR 2X1954 OR 2X1956 OR 2X1958 OR 2X1960 OR 2X1962 OR 2X1964 OR 2X1966 OR 2X1968 OR 2X1970 OR 2X1972 OR 2X1974 OR 2X1976 OR 2X1978 OR 2X1980 OR 2X1982 OR 2X1984 OR 2X1986 OR 2X1988 OR 2X1990 OR 2X1992 OR 2X1994 OR 2X1996 OR 2X1998 OR 2X2000 OR 2X2002 OR 2X2004 OR 2X2006 OR 2X2008 OR 2X2010 OR 2X2012 OR 2X2014 OR 2X2016 OR 2X2018 OR 2X2020 OR 2X2022 OR 2X2024 OR 2X2026 OR 2X2028 OR 2X2030 OR 2X2032 OR 2X2034 OR 2X2036 OR 2X2038 OR 2X2040 OR 2X2042 OR 2X2044 OR 2X2046 OR 2X2048 OR 2X2050 OR 2X2052 OR 2X2054 OR 2X2056 OR 2X2058 OR 2X2060 OR 2X2062 OR 2X2064 OR 2X2066 OR 2X2068 OR 2X2070 OR 2X2072 OR 2X2074 OR 2X2076 OR 2X2078 OR 2X2080 OR 2X2082 OR 2X2084 OR 2X2086 OR 2X2088 OR 2X2090 OR 2X2092 OR 2X2094 OR 2X2096 OR 2X2098 OR 2X2100 OR 2X2102 OR 2X2104 OR 2X2106 OR 2X2108 OR 2X2110 OR 2X2112 OR 2X2114 OR 2X2116 OR 2X2118 OR 2X2120 OR 2X2122 OR 2X2124 OR 2X2126 OR 2X2128 OR 2X2130 OR 2X2132 OR 2X2134 OR 2X2136 OR 2X2138 OR 2X2140 OR 2X2142 OR 2X2144 OR 2X2146 OR 2X2148 OR 2X2150 OR 2X2152 OR 2X2154 OR 2X2156 OR 2X2158 OR 2X2160 OR 2X2162 OR 2X2164 OR 2X2166 OR 2X2168 OR 2X2170 OR 2X2172 OR 2X2174 OR 2X2176 OR 2X2178 OR 2X2180 OR 2X2182 OR 2X2184 OR 2X2186 OR 2X2188 OR 2X2190 OR 2X2192 OR 2X2194 OR 2X2196 OR 2X2198 OR 2X2200 OR 2X2202 OR 2X2204 OR 2X2206 OR 2X2208 OR 2X2210 OR 2X2212 OR 2X2214 OR 2X2216 OR 2X2218 OR 2X2220 OR 2X2222 OR 2X2224 OR 2X2226 OR 2X2228 OR 2X2230 OR 2X2232 OR 2X2234 OR 2X2236 OR 2X2238 OR 2X2240 OR 2X2242 OR 2X2244 OR 2X2246 OR 2X2248 OR 2X2250 OR 2X2252 OR 2X2254 OR 2X2256 OR 2X2258 OR 2X2260 OR 2X2262 OR 2X2264 OR 2X2266 OR 2X2268 OR 2X2270 OR 2X2272 OR 2X2274 OR 2X2276 OR 2X2278 OR 2X2280 OR 2X2282 OR 2X2284 OR 2X2286 OR 2X2288 OR 2X2290 OR 2X2292 OR 2X2294 OR 2X2296 OR 2X2298 OR 2X2300 OR 2X2302 OR 2X2304 OR 2X2306 OR 2X2308 OR 2X2310 OR 2X2312 OR 2X2314 OR 2X2316 OR 2X2318 OR 2X2320 OR 2X2322 OR 2X2324 OR 2X2326 OR 2X2328 OR 2X2330 OR 2X2332 OR 2X2334 OR 2X2336 OR 2X2338 OR 2X2340 OR 2X2342 OR 2X2344 OR 2X2346 OR 2X2348 OR 2X2350 OR 2X2352 OR 2X2354 OR 2X2356 OR 2X2358 OR 2X2360 OR 2X2362 OR 2X2364 OR 2X2366 OR 2X2368 OR 2X2370 OR 2X2372 OR 2X2374 OR 2X2376 OR 2X2378 OR 2X2380 OR 2X2382 OR 2X2384 OR 2X2386 OR 2X2388 OR 2X2390 OR 2X2392 OR 2X2394 OR 2X2396 OR 2X2398 OR 2X2400 OR 2X2402 OR 2X2404 OR 2X2406 OR 2X2408 OR 2X2410 OR 2X2412 OR 2X2414 OR 2X2416 OR 2X2418 OR 2X2420 OR 2X2422 OR 2X2424 OR 2X2426 OR 2X2428 OR 2X2430 OR 2X2432 OR 2X2434 OR 2X2436 OR 2X2438 OR 2X2440 OR 2X2442 OR 2X2444 OR 2X2446 OR 2X2448 OR 2X2450 OR 2X2452 OR 2X2454 OR 2X2456 OR 2X2458 OR 2X2460 OR 2X2462 OR 2X2464 OR 2X2466 OR 2X2468 OR 2X2470 OR 2X2472 OR 2X2474 OR 2X2476 OR 2X2478 OR 2X2480 OR 2X2482 OR 2X2484 OR 2X2486 OR 2X2488 OR 2X2490 OR 2X2492 OR 2X2494 OR 2X2496 OR 2X2498 OR 2X2500 OR 2X2502 OR 2X2504 OR 2X2506 OR 2X2508 OR 2X2510 OR 2X2512 OR 2X2514 OR 2X2516 OR 2X2518 OR 2X2520 OR 2X2522 OR 2X2524 OR 2X2526 OR 2X2528 OR 2X2530 OR 2X2532 OR 2X2534 OR 2X2536 OR 2X2538 OR 2X2540 OR 2X2542 OR 2X2544 OR 2X2546 OR 2X2548 OR 2X2550 OR 2X2552 OR 2X2554 OR 2X2556 OR 2X2558 OR 2X2560 OR 2X2562 OR 2X2564 OR 2X2566 OR 2X2568 OR 2X2570 OR 2X2572 OR 2X2574 OR 2X2576 OR 2X2578 OR 2X2580 OR 2X2582 OR 2X2584 OR 2X2586 OR 2X2588 OR 2X2590 OR 2X2592 OR 2X2594 OR 2X2596 OR 2X2598 OR 2X2600 OR 2X2602 OR 2X2604 OR 2X2606 OR 2X2608 OR 2X2610 OR 2X2612 OR 2X2614 OR 2X2616 OR 2X2618 OR 2X2620 OR 2X2622 OR 2X2624 OR 2X2626 OR 2X2628 OR 2X2630 OR 2X2632 OR 2X2634 OR 2X2636 OR 2X2638 OR 2X2640 OR 2X2642 OR 2X2644 OR 2X2646 OR 2X2648 OR 2X2650 OR 2X2652 OR 2X2654 OR 2X2656 OR 2X2658 OR 2X2660 OR 2X2662 OR 2X2664 OR 2X2666 OR 2X2668 OR 2X2670 OR 2X2672 OR 2X2674 OR 2X2676 OR 2X2678 OR 2X2680 OR 2X2682 OR 2X2684 OR 2X2686 OR 2X2688 OR 2X2690 OR 2X2692 OR 2X2694 OR 2X2696 OR 2X2698 OR 2X2700 OR 2X2702 OR 2X2704 OR 2X2706 OR 2X2708 OR 2X2710 OR 2X2712 OR 2X2714 OR 2X2716 OR 2X2718 OR 2X2720 OR 2X2722 OR 2X2724 OR 2X2726 OR 2X2728 OR 2X2730 OR 2X2732 OR 2X2734 OR 2X2736 OR 2X2738 OR 2X2740 OR 2X2742 OR 2X2744 OR 2X2746 OR 2X2748 OR 2X2750 OR 2X2752 OR 2X2754 OR 2X2756 OR 2X2758 OR 2X2760 OR 2X2762 OR 2X2764 OR 2X2766 OR 2X2768 OR 2X2770 OR 2X2772 OR 2X2774 OR 2X2776 OR 2X2778 OR 2X2780 OR 2X2782 OR 2X2784 OR 2X2786 OR 2X2788 OR 2X2790 OR 2X2792 OR 2X2794 OR 2X2796 OR 2X2798 OR 2X2800 OR 2X2802 OR 2X2804 OR 2X2806 OR 2X2808 OR 2X2810 OR 2X2812 OR 2X2814 OR 2X2816 OR 2X2818 OR 2X2820 OR 2X2822 OR 2X2824 OR 2X2826 OR 2X2828 OR 2X2830 OR 2X2832 OR 2X2834 OR 2X2836 OR 2X2838 OR 2X2840 OR 2X2842 OR 2X2844 OR 2X2846 OR 2X2848 OR 2X2850 OR 2X2852 OR 2X2854 OR 2X2856 OR 2X2858 OR 2X2860 OR 2X2

