

## FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name: Street: City, State, Zip: Owner:	1815 Model  Lake City, FL, 3202 Gator & Lori David		Builder Name: Permit Office: Permit Number Jurisdiction:	PY of Florida a Climate Zone 2)
Design Location:	FL, Gainesville		County: Columbia (Florida	(Minate Zone Z)
1. New constructio 2. Single family or 3. Number of units, 4. Number of Bedre 5. Is this a worst ca 6. Conditioned floo Conditioned floo 7. Windows(163.0 a. U-Factor: SHGC: b. U-Factor: SHGC: c. U-Factor: SHGC: Area Weighted Av Area Weighted Av 8. Skylights U-Factor:(AVG) SHGC(AVG): 9. Floor Types	on or existing multiple family s, if multiple family rooms ase? or area above grade (for area below grade (for area below grade) SHGC=0.22 N/A N/A N/A Verage Overhang Dep	ft²) 0 Area 163.00 ft² ft² ft² ft²  pth: 1.500 ft 0.220 Area N/A ft²  Insulation R= 0.0 1815.00 ft² R= ft²	10. Wall Types(1584.0 sqft.) a. Frame - Wood, Exterior b. Frame - Wood, Adjacent c. N/A d. N/A  11. Ceiling Types(1815.0 sqft.) a. Under Attic (Vented) b. N/A c. N/A  12. Ducts, location & insulation lev a. a. Sup: Attic, Ret: Attic, AH: N b. c. 13. Cooling Systems a. Central Unit  14. Heating Systems a. Electric Heat Pump  15. Hot Water Systems a. Electric b. Conservation features	Insulation Area R=13.0 1398.00 ft² R=13.0 186.00 ft² R= ft² R= ft² Insulation Area R=30.0 1815.00 ft² R= ft² R= ft² R= ft² Nain 6 351.2  kBtu/hr Efficiency 36.0 SEER:14.00  kBtu/hr Efficiency 36.0 HSPF:8.50  Cap: 40 gallons EF: 0.920  None
			16. Credits	CF, Pstat
Glass/Floor Area: 0.	.090	Total Proposed Modifie Total Baselin		PASS
this calculation are code.  PREPARED BY:  DATE:	this building, as designed Code.		Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.  BUILDING OFFICIAL:  DATE:	

- Compliance requires certification by the air handler unit manufacturer that the air handler enclosure qualifies as certified factory-sealed in accordance with R403.3.2.1.
- Compliance with a proposed duct leakage Qn requires a PERFORMANCE Duct Leakage Test Report confirming duct leakage to outdoors, tested in accordance with ANSI/RESNET/ICC 380, is not greater than 0.030 Qn for whole house.
- Compliance requires an Air Barrier and Insulation Inspection Checklist in accordance with R402.4.1.1 and this project requires a PERFORMANCE envelope leakage test report with envelope leakage no greater than 5.00 ACH50 (R402.4.1.2).

## **INPUT SUMMARY CHECKLIST REPORT**

	PROJECT												
	Build Perm Juris Fami New Year	ling Type:	1815 Model User Gator & Lori Dav Detached New (From Plans 2022		Bedroom Condition Total Sto Worst Ca Rotate Al Cross Ve Whole He Terrain: Shielding	ned Area: ries: use: ngle: ntilation: ouse Fan:	3 1815 1 No 0 Rural Moderate	Lot # Block PlatB Stree Coun City,	d/SubDivision look: et:	Street Addr  n: Columbia Lake City, FL, 32024	ess		£
	CLIMATE												
<b>V</b>	/ Des	ign ation		Tmy Site		Desig 97.5%	n Temp 2.5%	Int Design		Heating Degree Days	Design Moisture		ily temp nge
_	_ FL	, Gainesville		FL_GAINESVILLE	_REGION/	32	92	70	75	1305.5	51	Medi	um
						BLOC	KS						
$\vee$	Nun	nber	Name	Area	Vol	ume							
_	_1		Block1	1815	1633	5							
	SPACES												
$\vee$	Nun	nber	Name	Area	Volume	Kitchen	Occupants	s Bedro	ooms	Finished	Coole	d H	leated
_	_1		Main	1815	16335	Yes	6	3		Yes	Yes		Yes
						FLOO	RS	Τ)	otal Exp	osed Are	a = 181	5 sq	.ft.)
$\vee$	#	Floor Typ	е	Space	Exposed	Perim Pe	erimeter R-V	alue Area	U-Factor	Joist R-Value	Tile W	ood	Carpet
-	_ 1	Slab-On-Gr	ade Edge Ins	Main	176	3	0	1815 f	t 0.600		0.33	0.33	0.34
	.015=					ROC	F						
$\checkmark$	#	Туре		Materials			Sable Root Area Colo		Solar Absor. T	SA Emitt Tested	Emitt Tested	Deck Insul.	Pitch (deg)
_	_ 1	Gable or sh	ed	Composition shingle	es 202	29 ft² 45	4 ft² Mediu	m N	0.85	No 0.9	No	0	26.57
	ATTIC												
$\vee$	#	Туре		Ventilation		Vent Ra	tio (1 in)	Area	RBS	IRCC			
_	_ 1	Full attic		Vented		30	00	1815 ft²	N	N			
	CEILING (Total Exposed Area = 1815 sq.ft.)												
$\vee$	#	Ceiling Ty	ре	(	Space	R-Valu	ue Ins. Ty	pe Area	a U-Fac	tor Framing	Frac.	Truss	Туре
	_1	Under Attic(	Vented)		Main	30.0	Blown	n 1815.0	Oft² 0.05	3 0.11		W	ood

## **INPUT SUMMARY CHECKLIST REPORT**

WALLS (Total Exposed Area = 1584 sq.ft.)																	
<b>\</b> /#	Ornt		acent To	Wall Type		Space		Cavity R-Value	Wid Ft	lth In	Height Ft In	Area sq.ft.	U- Factor	Sheath R-Value		Solar Absor.	Below Grade
12345	N E S W S		Exterior Exterior Exterior Exterior Garage	Frame - Wood Frame - Wood Frame - Wood Frame - Wood Frame - Wood	i i i	Mai Mai Mai Mai Mai	n n n	13.0 13.0 13.0 13.0 13.0	56.0 31.0 36.0 31.0 20.0	0 4 0 0 4	9.0 0 9.0 0 9.0 0 9.0 0 9.0 0	510.0 282.0 324.0 282.0 186.0	0.087 0.087 0.087	7 0.625 7 0.625 7 0.625	0.23 0.23 0.23 0.23 0.23	0.75 0.75 0.75 0.75 0.75	0 % 0 % 0 % 0 %
DOORS (Total Exposed Area = 78 sq.ft.)																	
V# (	Ornt		Adjacent	To Door Type		Space		Sto	orms		U-Value		/idth t In		ight In	Are	a
1 2 3	N S S		Exterio Exterio Garage	r Insulated		Main Main Main		N	lone lone lone		0.40 0.40 0.40	6.00 3.00 2.00	0	6.00 6.00 6.00	8 8 8	40.0 20.0 17.8	ft²
WINDOWS (Total Exposed Area = 163 sq.ft.)										t.)							
V# (	Ornt	Wall ID	Frame	Panes	NFRC	U-Factor	SHGC	Imp S	torm	Area	Dept	Overhar h Sepa	-	Interior S	hade	Scree	ening
1	N = 66	1 1 1 2 3 3 4	Vinyl Vinyl Vinyl Vinyl Vinyl Vinyl Vinyl	Low-E Double Low-E Double Low-E Double Low-E Double Low-E Double Low-E Double	Yes Yes Yes Yes Yes Yes	0.33 0.33 0.33 0.33 0.33 0.33	0.22 0.22 0.22 0.22 0.22 0.22 0.22	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	222222	45.0ft <sup>2</sup> 20.0ft <sup>2</sup> 9.0ft <sup>2</sup> 16.0ft <sup>2</sup> 54.0ft <sup>2</sup> 4.0ft <sup>2</sup>	1.0 ft 6 1.0 ft 6 1.0 ft 6 1.0 ft 6	S in 1.0 fi S in 1.0 fi	t 4 in t 4 in t 4 in t 4 in t 4 in	Nor Nor Nor Nor Nor Nor	ne ne ne ne	No No No No No No	ne ne ne ne
	1000						INFIL	TRA	TION	N N							
V# 5	Scope	9	Me	thod	SL	A CF	M50	ELA	E	qLA	ACH	ACH50	)	;	Space(	s)	
1	Wh	olehou	use Prop	osed ACH(50)	0.00	029 13	61	74.68	14	0.21	0.1027	5.0			All		
							G	ARAG	E								
√#		F	Floor Area	F	Roof Area	a	Expos	sed Wall I	Perime	eter	Avg	Wall Hei	ght	Expos	ed Wa	II Insulati	on
1			420 ft <sup>2</sup>		420 ft²	60 ft					9 ft 1						
							ľ	VIASS									
<b>V</b> #	Mas	ss Typ	е		Are	ea		Thickne	ss	Fu	rniture Fra	ction	5	Space			
1	Def	ault(8	lbs/sq.ft.)		0 1	ft²		0 ft			0.30			Main		- 0.65	
						HE	EATII	NG SY	STI	EM							
<b>√</b> #	Sys	tem T	уре	Si	ubtype/S	peed	AHRI#	Effic	ciency		acity u/hr En			eatPump- Volt Cu		ucts B	llock
1	Elec	ctric H	eat Pump		None/Sir	ngle		HSP	F: 8.50	36	3.0	0	.00	0.00 0	.00 sy	s#1	1

FORM R405-2020

## **INPUT SUMMARY CHECKLIST REPORT**

					СО	OLI	NG SY	STEM						
<b>V</b> #	System Type		Su	btype/Spee	d /	AHRI#	Effi	ciency	Capacity kBtu/hr		r Flow cfm	SHR	Duct	Block
1	Central Unit			None/Sing	le		SEE	R:14.0 3	6.0	1	1080	0.85	sys#1	1
					НОТ	WA	TER S	YSTEM						
<b>V</b> #	System Type	Subtype		Location		EF(UE	F) Cap	Use	SetPnt	Fixture	Flow	Pipe Ins	. Pipe	length
_1	Electric	None		Main	)	0.92 (0	.92) 40.00	gal 60 gal	120 deg	Stan	dard	None		95
	Recirculation System		c Control Type		Loop length	Brand			R Faciliti Connec			DWHR Eff	Other	Credits
1	No				NA	NA	NA	No	NA	N.	A	NA	Non	е
						D	UCTS							
√ <sup>Duc</sup>		pply R-Value A	rea Loc	Retication	um R-Value		Leakage	е Туре	Air Handler	CFM 25 TOT	CFM 25 OUT	QN		HVAC # eat Cool
1/	Attic	6.0 351	ft <sup>2</sup> Attic		6.0	38 ft²	Prop. Lea	ak Free	Main			0.03	0.50	1 1
V) - 31 - GO - 1					TE	MP	ERATU	RES						
Prog Cool Heat Vent	ting [X] Jan	ostat: Y [] Feb [X] Feb [] Feb	[] Mar [X] Mar [X] Mar	[] Apr [] Apr [X] Apr	O M[] M[]	ay ay	Fans: N [X] Jun [] Jun [] Jun	[X] Jul [] Jul [] Jul	[X] Aug [] Aug [] Aug	[X] Sep [] Sep [] Sep	[X] O	ct [X	] Nov [] Nov [] Nov	[] Dec [X] Dec [] Dec
	ermostat Sched hedule Type	lule: HERS	2006 Refere 1	ence 2	3	4	5	Ho 6	urs 7	8	9	10	11	12
Co	poling (WD)	AM PM	78 80	78 80	78 80	78 80	78 78	78 78	78 78	78 78	80 78	80 78	80 78	80 78
Co	poling (WEH)	AM PM	78 80	78 80	78 80	78 80	78 78	78 78	78 78	78 78	80 78	80 78	80 78	80 78
Не	eating (WD)	AM PM	65 68	65 68	65 68	65 68	65 68	65 68	65 68	68 68	68 68	68 68	68 68	68 68
He	eating (WEH)	AM PM	65 68	65 68	65 68	65 68	65 68	65 68	65 68	68 68	68 68	68 68	68 68	68 68

# ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD ESTIMATED ENERGY PERFORMANCE INDEX\* = 94

The lower the EnergyPerformance Index, the more efficient the home.

,Lake City,FL,32024

1. New construction or existing	New (Fro	m Plans)	10. Wall Types(1584.0 sqft.)	Insulatio	2007
2. Single family or multiple family	[	Detached	a. Frame - Wood, Exterior	R=13.0	1398.00 ft <sup>2</sup>
3. Number of units, if multiple family		1	<ul><li>b. Frame - Wood, Adjacent</li><li>c. N/A</li></ul>	R=13.0 R=	186.00 ft <sup>2</sup>
Number of Bedrooms		3	d. N/A	R=	ft <sup>2</sup>
5. Is this a worst case?		No	11. Ceiling Types(1815.0 sqft.)	Insulatio	
<ol><li>Conditioned floor area above grad Conditioned floor area below grad</li></ol>		1815 0	a. Under Attic (Vented) b. N/A c. N/A	R=30.0 R= R=	ft <sup>2</sup>
7. Windows** Description a. U-Factor: Dbl, U=0.3 SHGC: SHGC=0.3 b. U-Factor: N/A	33	Area 163.00 ft <sup>2</sup>	12. Ducts, location & insulation level a. a. Sup: Attic, Ret: Attic, AH: Mair b.	5-55	R ft <sup>2</sup> 6 351.2
SHGC: c. U-Factor: N/A SHGC:		ft <sup>2</sup>	13. Cooling Systems a. Central Unit	kBtu/hr 36.0	Efficiency SEER:14.00
Area Weighted Average Overhang I Area Weighted Average SHGC:	Depth:	1.500 ft 0.220	14. Heating Systems	kBtu/hr	Efficiency
8. Skylights Descriptio U-Factor:(AVG) N/A SHGC(AVG): N/A	n	Area N/A ft <sup>2</sup>	a. Electric Heat Pump	36.0	HSPF:8.50
Floor Types     a. Slab-On-Grade Edge Insulation	Insulation R= 0.0	Area 1815.00 ft <sup>2</sup>	<ol> <li>Hot Water Systems</li> <li>Electric</li> </ol>	Car	o: 40 gallons EF: 0.920
b. N/A c. N/A	R= R=	ft² ft²	b. Conservation features		
C. INA	125	ı	16. Credits		None CF, Pstat

I certify that this home has complied with the Florida Energy Efficiency Code for Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature:

Address of New Home:

City/FL Zip: Lake City,FL,32024

\*Note: This is not a Building Energy Rating. If your Index is below 70, your home may qualify for energy efficient mortgage (EEM) incentives if you obtain a Florida Energy Rating. For information about the Florida Building Code, Energy Conservation, contact the Florida Building Commission's support staff.

\*\*Label required by Section R303.1.3 of the Florida Building Code, Energy Conservation, if not DEFAULT.