

COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST

MINIMUM PLAN REQUIREMENTS: FLORIDA BUILDING CODE RESIDENTIAL 2023 EFFECTIVE 1 JANUARY 2024 AND THE NATIONAL ELECTRICAL 2020 EFFECTIVE 1 JANUARY 2024

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE WITH THE CURRENT FLORIDA BUILDING CODES RESIDENTIAL AND THE NATIONAL ELECTRICAL CODE. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS, FBC 1609.1 THRU 1609.6.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FLORIDA BUILDING CODE FIGURE 1609.3(1)
THROUGH 1609.3(4) ULTIMATE DESIGN WIND SPEEDS FOR RISK CATEGORY AND BUILDINGS AND OTHER
STRUCTURES Revised 7/1/20

Aura		**********		AND AND DESCRIPTION OF THE PROPERTY AND ADDRESS OF THE PARTY AND ADDRES	
- 8	Submit Online at- http://www.columbiacountyfla.com/BuildingandZoning.	asp)	Item	s to Inclu	
L	GENERAL REQUIREMENTS:		Each	^a Box ^a shal	p. 19 3741 - 1003 Sq.
Ŕ	APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL			Circled as p p licable	
12	二、主义、1925年,中国大学的大学的大学的大学的大学的大学的大学的大学的大学的大学的大学的大学的大学的大	"清晰"			
		Sele	et Fr	om Drop	down
L	1 Two (2) complete sets of plans containing the following:	V			
	All drawings must be clear, concise, drawn to scale, details that are not used shall be marked void				
	Condition space (Sq. Ft.) 1530 sq ft Total (Sq. Ft.) under roof	7	es	No	NA

Designers name and signature shall be on all documents and a licensed architect or engineer, signature and official embossed seal shall be affixed to the plans and documents as per the FLORIDA BUILDING CODES BUILDING 107.1.

Site Plan information including:

4	Dimensions of lot or parcel of land	Yes	7	S
5	Dimensions of all building set backs	Yes		M
6	Location of all other structures (include square footage of structures) on parcel, existing or proposed well and septic tank and all utility easements.	Yes		
7	Provide a full legal description of property.	Yes		M

Wind-load Engineering Summary, calculations and any details are required.

		Each	stó/Includ Boxishall ircledias olicable	be
8	Plans or specifications must show compliance with FBCR Chapter 3	Yes	No	NA
		Select Fro	m Drop	down
9	Basic wind speed (3-second gust), miles per hour	NA		
10	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated)	NA		
11	Wind importance factor and nature of occupancy	NA		図
12	The applicable internal pressure coefficient, Components and Cladding	NA		
13	The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component, cladding materials not specifally designed by the registered design professional.	NA		[]
Ele	evations Drawing including:			
14	All side views of the structure	Yes		M
15	Roofpitch	Yes		
16	Overhang dimensions and detail with attic ventilation	Yes		
17	Location, size and height above roof of chimneys	NA		
18	Location and size of skylights with Florida Product Approval	NA		
19	Number of stories	Yes		[24]
20	Building height from the established grade to the roofs highest peak	Yes		

Floor Plan Including:

Toron Street,			
21	Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, deck, balconies	Yes	
22	Raised floor surfaces located more than 30 inches above the floor or grade	Yes	
23	All exterior and interior shear walls indicated	Yes	
24	Shear wall opening shown (Windows, Doors and Garage doors)	Yes	
25	Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each		•
	bedroom (net clear opening shown) and Show compliance with Section FBCR 312.2.1 where the opening of an operable window is located more than 72 inches above the finished grade or surface below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above the finished floor of the room in which the window is located. Glazing between the floor and 24 inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass.	Yes	M
26	Safety glazing of glass where needed	NA	 12
27	Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 and chapter 24 of FBCR)	NA	M
28	Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails	NA	M
29	Identify accessibility of bathroom (see FBCR SECTION 320)	Yes	 2 2

All materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida product approval number and mfg. installation information submitted with the plans (see Florida product approval form)

GENERAL/REQUIREMENT APPLICANT – PLEASE/CHECK-ALL APPLICABLE)	S: BOXES BEFORE SUBMITTAL Each Box shall be Circled as Applicable
FBCR 403: Foundation Plans	

		Select From	Drop down
30	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.	Yes	2
31	All posts and/or column footing including size and reinforcing	Yes	
32		NA	
33	Assumed load-bearing valve of soil Pound Per Square Foot	NA	
34	Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3	Yes	

FBCR 506: CONCRETE SLAB ON GRADE

35 Show Va or retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed)

36 Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports

NA

FBCR 318: PROTECTION AGAINST TERMITES

Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or
Submit other approved termite protection methods. Protection shall be provided by registered termiticides

Yes

FBCR 606: Masonry Walls and Stem walls (load bearing & shear Walls)

38 Show all materials making up walls, wall height, and Block size, mortar type

39 Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement

Yes

Metal frame shear wall and roof systems shall be designed, signed and sealed by Florida Prof. Engineer or Architect

Floor Framing System: First and/or second story

Floor truss package shall including layout and details, signed and sealed by Florida Registered

Professional Engineer

Show conventional floor joist type, size, span, spacing and attachment to load bearing walls, stem walls and/or priers

All Girder type, size and spacing to load bearing walls, stem wall and/or priers

NA

42 Girder type, size and spacing to load bearing walls, stem wall and/or priers

43 Attachment of joist to girder

44 Wind load requirements where applicable

45 Show required under-floor crawl space

46 Show required amount of ventilation opening for under-floor spaces

47 Show required covering of ventilation opening

47 Show required covering of ventilation opening
48 Show the required access opening to access to under-floor spaces

Show the gulf floor structural panel shoothing tune, thickness and fortener schedule on the adapt &

Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges & NA intermediate of the areas structural panel sheathing

50 Show Draftstopping, Fire caulking and Fire blocking

NA Show fireproofing requirements for garages attached to living spaces, per FBCR section 302.6

NA STATE OF THE PROOF OF THE PROOF

FBCR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION

MULL CLIP A LI	210 11 0 0 2 11 22 2 2 2 2 2 2 2 2 2 2 2	
THE RESERVE OF THE PARTY OF THE		
		Itemsitö Include-
	The state of the s	
	GENERALIREQUIREMENTS:	II Each Box shall be
Α ΟΡΙΙΟ ΔΝΊ	F-PLEASE/CHECK ALL APPLICABLE/BOXES)	REFORESTIRMITTAL
		DELOIG GENERAL
		Applicable 4
A THE RESERVE AND A PROPERTY OF THE PARTY OF	DESCRIPTION OF THE PERSON OF T	The state of the s

54	Fastener schedule for structural members per table FBC 2304.10.1 are to be shown	Yes	22
55	panel sheathing	Yes	
56	Show all required connectors with a max uplift rating and required number of connectors and oc spacing for continuous connection of structural walls to foundation and roof trusses or rafter systems	Yes	M
57	Show sizes, type, span lengths and required number of support jack studs, king studs for shear wall opening and girder or header per FBC 2304.3.	Yes	M
58		Yes	
59	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural panel sheathing edges & intermediate areas	Yes	M
60	A detail showing gable truss bracing, wall balloon framing details or/and wall hinge bracing detail	Yes	M

FRC :ROOF SYSTEMS:

61	Truss design drawing shall meet section FBC 2303.1 Wood trusses	Yes	M
62	Include a layout and truss details, signed and sealed by Florida Professional Engineer	Yes	 M
63	Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters	Yes	M
64	Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details	Yes	
65	Provide dead load rating of trusses	Yes	 122

FBC 2304.4:Conventional Roof Framing Layout

66	Rafter and ridge beams sizes, span, species and spacing	Y-es-	図
67	Connectors to wall assemblies' include assemblies' resistance to uplift rating	Yes	
68	Valley framing and support details	Yes	52
69	Provide dead load rating of rafter system	Yes	V

FBC 2304.8 ROOF SHEATHING

70	Include all materials which will make up the roof decking, identification of structural panel sheathing, grade, thickness	Yes	
71	Show fastener Size and schedule for structural panel sheathing on the edges & intermediate areas	Yes	NZ

N.

NA

ROOF ASSEMBLIES FRC Chapter 9

72	Include all materials which will make up the roof assembles covering	Yes	<u> </u>	
73	Submit Florida Product Approval numbers for each component of the roof assembles covering	Yes		52

FBC Energy Chapter 4

Residential construction shall comply with this code by using the following compliance methods in the FBC Chapter 4, Residential buildings compliance methods. Two of the required forms are to be submitted, N1100.1.1.1 As an alternative to the computerized Compliance Method A, the Alternate Residential Point System Method hand calculation, Alternate Form 600A, may be used. All requirements specific to this calculation are located in Sub appendix C to Appendix G. Buildings complying by this alternative shall meet all mandatory requirements of this chapter. Computerized versions of the Alternate Residential Point System Method shall not be acceptable for code compliance.

	GENERAL REQUIREMENTS: APREICANIC → REEASE CHECK ALL ARRUICABLE BOXES BEFORE SUBMITTAL	Items to U Each Box Circle	shallibe
		Applic	
·		elect from Di	
74	Show the insulation R value for the following areas of the structure	Yes	M
	Attic space	Yes	
76	Exterior wall cavity	Yes	
77	Crawl space	NA .	M
HV	AC information		
78	Submit two copies of a Manual J sizing equipment or equivalent computation study	Yes	
79	Exhaust fans shown in bathrooms Mechanical exhaust capacity of 50 cfm intermittent or		
'´	20 cfm continuous required	Yes	
80	Show clothes dryer route and total run of exhaust duct	Yes	
		<u> </u>	L_Lissadi,
Plu	imbing Fixture layout shown		
81	All fixtures waste water lines shall be shown on the foundationplan	Yes	
82	Show the location of water heater	Yes	
Name of Street, or other Designation of the last of th	vate Potable Water Pump motor horse power	INA I	
	Reservoir pressure tank gallon capacity	NA	
	Rating of cycle stop valve if used	NA NA	
Elg	ectrical layout shown including		
86	Show Switches, receptacles outlets, lighting fixtures and Ceiling fans	Yes	
87	Show all 120-volt, single phase, 15- and 20-ampere branch circuits outlets required to be protected by Ground-Fault Circuit Interrupter (GFCI) Article 210.8 A	Yes	
88	Show the location of smoke detectors & Carbon monoxide detectors	Yes	
89	Show service panel, sub-panel, location(s) and total ampere ratings	Yes	
90	On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type. For structures with foundation which establish new electrical utility companies service	Yes	
	connection a Concrete Encased Electrode will be required within the foundation to serve as an Grounding electrode system. Per the National Electrical Code article 250.52.3		
91	Appliances and HVAC equipment and disconnects	Yes	<u></u>
92	Show all 120-volt, single phase, 15- and 20-ampere branch circuits supplying outlets installed in dwelling unit family rooms, dining rooms, living rooms, parlors, libraries, dens, bedrooms, sunrooms, recreation rooms, closets, hallways, or similar rooms or areas shall be protected by a listed Combination arc-fault circuit interrupter, Protection device.	Yes	

Notice Of Commencement:

A notice of commencement form RECORDED in the Columbia County Clerk Office is required to be filed with the Building Department BEFORE ANY INSPECTIONS can be performed.

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK-ALL APPLICABLE BOXES BEFORE SUBMITTAL Circled as Applicable

ITEMS 95, 96, & 98 Are Required After APPROVAL from the ZONING DEPT:

Select from Drop down

		elect from	Drop down
93	Building Permit Application A current Building Permit Application is to be completed, by following the Checklist all supporting documents must be submitted.	Yes	
94	Parcel Number The parcel number (Tax ID number) from the Property Appraisers Office (386) 758-1083 is required. A copy of property deed is also required. www.columbiacountyfla.com	Yes	M
95	Environmental Health Permit or Sewer Tap Approval A copy of a approved Columbia County Environmental Health (386) 758-1058	-	
96	City of Lake City A City Water and/or Sewer letter. Call 386-752-2031	-	M
97	Toilet facilities shall be provided for all construction sites	Yes	
98	Town of Fort White (386) 497-2321 If the parcel in the application for building permit is within the Corporate city limits of Fort White, an approval land use development letter issued by the Town of Fort is required to be submitted with the application for a building permit.	NA	
99	Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers shall require permitting through the Suwannee River Water Management District, before submitting a application to this office. Any project located within a flood zone where the base flood elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the Columbia County Land Development Regulations. Any project located within a flood zone where the base flood elevation has not been established (Zone A) shall meet the requirements of Section 8.5.3 of the Columbia County Land Development Regulations (Municode.com)	NA	M
100	FIRM Flood Maps show the property is in a AE, Floodway, and AH flood zones. Additionally One Foot Rise letters are required for AE and AH zones. In the Floodway Flood zones a Zero Rise letter is required	NA	
101	A Flood development permit is also required for AE, Floodway & AH. Development permit cost is \$50.0) NA	
102	Driveway Connection: A Right-of-way application must be applied for with all new structures If drive is confirmed to be existing, a fee may not be applied If it is determined a connection is necessary, the fee is \$150 00 If the project is to be located on an F D O T maintained road, then an F D O T access permit is required. If the project is to be located on an F.D.O.T. maintained road, then an F.D.O.T. access permit is required.	NA	M
103	911 Address: An application for a 911 address must be applied for and received through the Columbia County Office of 911 Addressing Department poline.	Yes	

Ordinance Sec. 90-75. - Construction debris. (e) It shall be unlawful for any person to dispose of or discard solid waste, including construction or demolition debris at any place within the county other than on an authorized disposal site or at the county's solid waste facilities. The temporary storage, not to exceed seven days of solid waste (excluding construction and demolition debris) on the premises where generated or vegetative trash pending disposition as authorized by law or ordinance, shall not be deemed a violation of this section. The temporary storage of construction and demolition debris on the premises where generated or vegetative trash pending disposition as authorized by law or ordinance shall not be deemed in violation of this section, provided, however, such construction and demolition debris must be disposed of in accordance with this article prior to the county's issuance of a certificate of occupancy for the premises. The burning of lumber from a construction or demolition project or vegetative trash when done so with legal and proper permits from the authorized agencies and in accordance with such agencies' rules and regulations, shall not be deemed a violation of this section. No person shall bury, throw, place, or deposit, or cause to be buried, thrown, placed, or deposited, any solid waste, special waste, or debris of any kind into or on any of the public streets, road right-of-way, highways, bridges, alleys, lanes, thoroughfares, waters, canals, or vacant lots or lands within the county. No person shall bury any vegetative trash on any of the public streets, road right-of-way, highways, bridges, lanes, thoroughfares, waters, canals, or lots less than ten acres in size within the county.