

COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST

MINIMUM PLAN REQUIREMENTS: FLORIDA BUILDING CODE RESIDENTIAL 2014 EFFECTIVE 1 JULY 2015 AND THE NATIONAL ELECTRICAL 2011 EFFECTIVE 1 JULY 2015

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE WITH THE CURRENT 2014 FLORIDA BUILDING CODES RESIDENTIAL, EFFECTIVE 1 JULY 2015. NATIONAL ELECTRICAL CODE 2011 EFFECTIVE 1 JULY 2015. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FLORIDA BUILDING CODE FIGURE 1609-A
THROUGH 1609-C ULTIMATE DESIGN WIND SPEEDS FOR RISK CATEGORY AND BUILDINGS AND OTHER STRUCTURES
Revised 7/1/15

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTA	Items to l Each Box Circle AL Applie	shall be
	Yes/ N	o N/A
1 Two (2) complete sets of plans containing the following:		
2 All drawings must be clear, concise, drawn to scale, details that are not used shall be man	rked void	
3 Condition space (Sq. Ft.) 1153 Total (Sq. Ft.) under roof 15	12	IIII IIIII

Designers name and signature shall be on all documents and a licensed architect or engineer, signature and official embossed seal shall be affixed to the plans and documents as per the FLORIDA BUILDING CODES RESIDENTIAL R101.2.1

S	ite Plan information including:				
4	Dimensions of lot or parcel of land	V		1	
5	Dimensions of all building set backs		/	,	
6	Location of all other structures (include square footage of structures) on parcel, existing or proposed				
	well and septic tank and all utility easements.		Y,		
7	Provide a full legal description of property.		/		

Wind-load Engineering Summary, calculations and any details are required.

GENERAL REQUIREMENTS.

	APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each	Box shall ircled as	l be
			plicable	
8	Plans or specifications must show compliance with FBCR Chapter 3	ШШ	ШШ	ШШ
		YES	NO	N/A
9	Basic wind speed (3-second gust), miles per hour			
10	(Wind exposure – if more than one wind exposure			
	is used, the wind exposure and applicable wind direction shall be indicated)			
11	Wind importance factor and nature of occupancy	/		
12	The applicable internal pressure coefficient, Components and Cladding	V		
	The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component,			
13	cladding materials not specifally designed by the registered design professional.			
Ele	evations Drawing including:			
14	All side views of the structure	Y		
15	Roof pitch	/		
16	Overhang dimensions and detail with attic ventilation			
17	Location, size and height above roof of chimneys			
18	Location and size of skylights with Florida Product Approval			
18	Number of stories			
20A	Building height from the established grade to the roofs highest peak	V		

Items to Include-

Floor Plan including: Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, deck, 20 balconies Raised floor surfaces located more than 30 inches above the floor or grade 21 22 All exterior and interior shear walls indicated 23 Shear wall opening shown (Windows, Doors and Garage doors) Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each bedroom (net clear opening shown) and Show compliance with Section FBC 1405.13.2 where the opening of an operable window is located more than 72 inches above the finished grade or surface below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above the finished floor of the room in which the window is located. Glazing between the floor and 24 inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass. 25 Safety glazing of glass where needed Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth

All materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida product approval number and mfg. installation information submitted with the plans (see Florida product approval form)

Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to Include- Each Box shall be
	Circled as Applicable

FBCR 403: Foundation Plans

(see chapter 10 and chapter 24 of FBCR)

Identify accessibility of bathroom (see FBCR SECTION 320)

26

27

		YES	NO	N/A
29	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size	. /		
	and type of reinforcing.	V /		
30	All posts and/or column footing including size and reinforcing	V /		
31	Any special support required by soil analysis such as piling.			
32	Assumed load-bearing valve of soil Pound Per Square Foot			
33	Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3	/		

I	BCR 506: CONCRETE SLAB ON GRADE			
3	4 Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)	V		
3	5 Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports			

FBCR 318: PROTECTION AGAINST TERMITES

36	Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides	/		:
----	---	----------	--	---


FB	CR 606: Masonry Walls and Stem walls (load bearing & shear Walls)			
37	Show all materials making up walls, wall height, and Block size, mortar type	V		
38	Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement	V		

Metal frame shear wall and roof systems shall be designed, signed and sealed by Florida Prof. Engineer or Architect

Flo	oor Framing System: First and/or second story			
	Floor truss package shall including layout and details, signed and sealed by Florida Registered			
39	Professional Engineer	V		
	Show conventional floor joist type, size, span, spacing and attachment to load bearing walls,			
40	stem walls and/or priers			
41	Girder type, size and spacing to load bearing walls, stem wall and/or priers			
42	Attachment of joist to girder			
43	Wind load requirements where applicable			
44	Show required under-floor crawl space	\perp		V/
45	Show required amount of ventilation opening for under-floor spaces			V
46	Show required covering of ventilation opening			Y /
47	Show the required access opening to access to under-floor spaces			
	Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges &			
48	intermediate of the areas structural panel sheathing	V /		
49	Show Draftstopping, Fire caulking and Fire blocking			
50	Show fireproofing requirements for garages attached to living spaces, per FBCR section 302.6			
51	Provide live and dead load rating of floor framing systems (psf).			
Jelica - sa				
FB	CR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION			
			to Inclu	
	GENERAL REQUIREMENTS:	Each B		
	APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		cled as	
			plicable	
		YES	NO	N/A
52	Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls	V /		
53	Fastener schedule for structural members per table IRC 602.3 are to be shown	V		
	Show Wood structural panel's sheathing attachment to studs, joist, trusses, rafters and structural	1		
54	members, showing fastener schedule attachment on the edges & intermediate of the areas structural			
	panel sheathing			
	Show all required connectors with a max uplift rating and required number of connectors and			
55	oc spacing for continuous connection of structural walls to foundation and roof trusses or	V		
	rafter systems			
	Show sizes, type, span lengths and required number of support jack studs, king studs for shear			
56	wall opening and girder or header per FBCB 2308.9.5			
57	Indicate where pressure treated wood will be placed	V ,		
	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural			
58	panel sheathing edges & intermediate areas	V /		
59	A detail showing gable truss bracing, wall balloon framing details or/ and wall hinge bracing detail	V		
FI	BCR :ROOF SYSTEMS:			
60	Truss design drawing shall meet section FBCR 802.1.7.1 Wood trusses	V /		
61	Include a layout and truss details, signed and sealed by Florida Professional Engineer	V /		
62	Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters	V/		
63	Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details	V /		
64	Provide dead load rating of trusses			
1				
F	BCR 802:Conventional Roof Framing Layout			
65	Rafter and ridge beams sizes, span, species and spacing			
66	Connectors to wall assemblies' include assemblies' resistance to uplift rating	V /		
67	Valley framing and support details	V /		
68	Provide dead load rating of rafter system			
FI	BCR 803 ROOF SHEATHING			
69	Include all materials which will make up the roof decking, identification of structural panel			
לט	sheathing, grade, thickness	V ,		
70	Show fastener Size and schedule for structural panel sheathing on the edges & intermediate areas			
/ / /	Show rastener size and senedate for structural paner sheating on the edges & intermediate areas			

ROOF ASSEMBLIES FRC Chapter 9

71 Include all materials which will make up the roof assembles covering





FBCR Energy Conservation R.401

Residential construction shall comply with this code by using the following compliance methods in the Residential buildings compliance methods. Two of the required forms are to be submitted, R 402-2014 As an alternative to the computerized Compliance Method A, the Alternate Residential Point System Method hand calculation, Alternate Form R 402-2014, may be used. All requirements specific to this calculation are located in Sub appendix C to Appendix G. Buildings complying by this alternative shall meet all mandatory requirements of this chapter. Computerized versions of the Alternate Residential Point System Method shall not be acceptable for code compliance.

	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to Include- Each Box shall be Circled as Applicable		l be
		YES	NO	N/A
73	Show the insulation R value for the following areas of the structure			
74	Attic space	V/		
75	Exterior wall cavity			
76	Crawl space			V
Н	AC information	_		
77	Submit two copies of a Manual J sizing equipment or equivalent computation study			
78	Exhaust fans shown in bathrooms Mechanical exhaust capacity of 50 cfm intermittent or			
	20 cfm continuous required	V /		
79	Show clothes dryer route and total run of exhaust duct	V		
Ph	imbing Fixture layout shown	1		
	All fixtures waste water lines shall be shown on the foundation plan			
81	Show the location of water heater			
		V		
	ivate Potable Water Pump motor horse power		T I	
82		-		
	Reservoir pressure tank gallon capacity	-		
84	Rating of cycle stop valve if used			
Ele	ectrical layout shown including	/		
85		V .		
86	Show all 120-volt, single phase, 15- and 20-ampere branch circuits outlets required to be protected			
	by Ground-Fault Circuit Interrupter (GFCI) Article 210.8 A	V /		
87	Show the location of smoke detectors & Carbon monoxide detectors	V /		
88	Show service panel, sub-panel, location(s) and total ampere ratings	V		
89	On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type.	✓		
00	For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an Grounding electrode system. Per the National Electrical Code article 250.52.3			
90	Appliances and HVAC equipment and disconnects			
91	Show all 120-volt, single phase, 15- and 20-ampere branch circuits supplying outlets installed in dualling unit family reams, division reams, living reams, personal libraries, does be drawns.			
	in dwelling unit family rooms, dining rooms, living rooms, parlors, libraries, dens, bedrooms,			
	sunrooms, recreation rooms, closets, hallways, or similar rooms or areas shall be protected by	•		
	a listed Combination arc-fault circuit interrupter, Protection device. NEC 210.12A			

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

Items to Include-Each Box shall be Circled as Applicable

THE FOLLOWING ITEMS MUST BE SUBMITTED WITH BUILDING PLANS

		YES	NO	N/A
92	Building Permit Application A current Building Permit Application is to be completed,			
	by following the Checklist all supporting documents must be submitted.			
	There is a \$15.00 application fee. The completed application with attached documents and application	•		
	fee can be mailed.			
93	Parcel Number The parcel number (Tax ID number) from the Property Appraisers Office			
	(386) 758-1083 is required. A copy of property deed is also required. www.columbiacountyfla.com	V		
94	Environmental Health Permit or Sewer Tap Approval A copy of a approved			
	Columbia County Environmental Health (386) 758-1058	•		
95	City of Lake City A City Water and/or Sewer letter. Call 386-752-2031			
96	Toilet facilities shall be provided for all construction sites			
97	Town of Fort White (386) 497-2321 If the parcel in the application for building permit is			
	within the Corporate city limits of Fort White, an approval land use development letter issued by the			
	Town of Fort is required to be submitted with the application for a building permit.			
98	Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers			
	shall require permitting through the Suwannee River Water Management District, before submitting			
	a application to this office. Any project located within a flood zone where the base flood			
	elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the			•
	Columbia County Land Development Regulations. Any project located within a flood zone			
	where the base flood elevation has not been established (Zone A) shall meet the requirements of			
	Section 8.5.3 of the Columbia County Land Development Regulations			
99	CERTIFIED FINISHED FLOOR ELEVATIONS will be required on any project where the approved			
	FIRM Flood Maps show the property is in a AE, Floodway, and AH flood zones. Additionally One Foot			V
	Rise letters are required for AE and AH zones. In the Floodway Flood zones a Zero Rise letter is required.			
100				
	Driveway Connection: If the property does not have an existing access to a public road, then			
	an application for a culvert permit (\$25.00) must be made. County Public Works Dept. determines the size			
101	and length of every culvert before instillation and completes a final inspection before permanent power is granted.			
	If the applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00) Separate	•		
	Check when issued. If the project is to be located on an F.D.O.T. maintained road, then an F.D.O.T. access permit			
	is required.			
103	911 Address: An application for a 911 address must be applied for and received through the Columbia	. /		
102	County Emergency Management Office of 911 Addressing Department (386) 758-1125.			

<u>Disclosure Statement for Owner Builders</u> If you as the applicant will be acting as an owner/builder under section 489.103(7) of the Florida Statutes, submit the required owner builder disclosure statement form.

Notice Of Commencement

A notice of commencement form **recorded** in the Columbia County Clerk Office is required to be filed with the building department Before Any Inspections can be preformed.

Section R101.2.1 of the Florida Building Code Residential:

The provisions of Chapter 1, Florida Building Code shall govern the administration and enforcement of the Florida Building Code, Residential.