

ELECTRICAL	COUNT	SYMBOL
electrical panel	1	17
meter	1	
220 Yolt Outlet	1	•
3 Way Switch	12	\$3
Can Light	12	U.L. LISTED CAN LIGHT
Ext.Fan	3	EXT. FAN
Light	11	
Outlet	50	Ф
Switch	33	\$
chandelier	1	900
clg fan spots 2	8	
fluor fixture	2	
spotlight-dbl	10	QD
outlet gfi	6	фая
smoke detector	5	•

ELECTRICAL PLAN NOTES

ALL RECEPTICALS IN ALL BEDROOMS SHALL BE AFIC CIRCUITS

WIRE ALL APPLIANCES, HVAC UNITS AND OTHER EQUIPMENT PER MANUF. SPECIFICATIONS.

CONSULT THE OWNER FOR THE NUMBER OF SEPERATE

TELEPHONE LINES TO BE INSTALLED. INSTALLATION SHALL BE PER NAT'L. ELECTRIC CODE.

ALL SMOKE DETECTORS SHALL BE 120V W/ BATTERY BACKUP OF THE PHOTOELECTRIC TYPE, AND SHALL BE INTERLOCKED TOGETHER. INSTALL INSIDE AND NEAR ALL BEDROOMS.

TELEPHONE, TELEVISION AND OTHER LOW VOLTAGE DEVICES OR OUTLETS SHALL BE AS PER THE OWNER'S DIRECTIONS, & IN ACCORDANCE W/ APPLICABLE SECTIONS OF NEC-LATEST EDITION.

ELECTRICAL CONT'R SHALL PREPARE "AS-BUILT" SHOP DWGS INDICATING ALL ELECTRICAL WORK, INCLUDING ANY CHANGES TO THE ELEC. PLAN, ADD'NS TO THE ELEC. PLAN, RISER DIAGRAM, AS-BUILT PANEL SCHEDULE W/ ALL CKTS IDENTIFIED W/ CKT Nr., DESCRIPTION & BRKR, SERVICE ENT. & ALL UNDERGROUND WIRE LOCATIONS/ROUTING/DEPTH. RISER DIA. SHALL INCLUDE WIRE SIZES/TYPE & EQUIPMENT TYPE W/ RATINGS & LOADS. CONTRACTOR SHALL PROVIDE 1 COPY OF AS-BUILT DWGS

TO OWNER & 1 COPY TO THE PERMIT ISSUING AUTHORITY.

A Joint

SHEET NUMBER



OF I SHEETS

