



SLAB NOTES:

SLABS ON GRADE,
3-1/2" CONC. SLAB - 3000 PSI
W/ FIBERMESH W/ 6 MIL VAPOR
BARRIER, OVER MECH.
COMPACTED FILL
TREAT SOIL W/ TERMITES
POISONING.

GENERAL NOTES:

SEE SHEET 6 FOR SPECIFIC
ELEV. DETAILS.

VERIFY DEPTH AND WIDTH OF
SLAB RECESS AT ALL DOORS
TO ACCOMMODATE PROPER
ALIGNMENT WITH THRESHOLDS
AND DOOR TRACKS WITH MFR.
REQUIREMENTS IN RELATION
TO FINISH FLOOR MATERIAL.

SEE SHEET 10 FOR OPTIONA
OUTDOOR LIVING PACKAGE
DETAILS.

PROVIDE SOLID FILLED CON-
CRETE BLOCK AT ALL SHOWER
SEATS.

FOUNDATION PLAN DISCLAIMER

THE FOUNDATION PLANS REPRESENTED IN THESE DRAWINGS ARE
INTENDED TO ESTABLISH GROUND FLOOR SURFACE CONDITIONS
AND ESTABLISH VERTICAL ELEVATION DATA. ALL POTENTIAL
BEARING LOCATIONS AND CONDITIONS ARE IN CONJUNCTION WITH
FOUNDATIONS PLANS CONTAINED WITHIN THIS DRAWING SET AND ARE
NOT INTENDED TO BE INTERPRETED AS STRUCTURAL ENGINEERING
DRAWINGS. THE CONTRACTOR (BUILDER) SHALL ASSURE THAT THE
STRUCTURE CONFORMS TO THOSE STANDARDS IN ALL RESPECTS
INCLUDING STRENGTH, STIFFNESS, STRAIN, LOADS, CONNECTION
AND STABILITY. REFER TO PLAN DISCLAIMERS LOCATED ON THE
SHEET FOR ADDITIONAL STIPULATIONS AND REQUIREMENTS.