



THE MATERIALS USED FOR THE EXTERIOR FINISH MUST BE APPROVED BY FAMILY DOLLAR STORE REPRESENTATIVE. MATCHING EXISTING NEARBY STRUCTURES STORE CONSIDERATION.

INSULATION NOTE:

WALLS TO ATTAIN INSULATION RATING WITH FOAM IN CMU, BATT INSULATION AND/OR RIGID INSULATION TO TOTAL R-13 MIN.
ROOF TO ATTAIN INSULATION RATING TO TOTAL R-19 MIN. WITH R5 THERMAL BLOCKS OR R30. EXPOSED FINISH IS TO BE WHITE VINYL.

ALL INSULATION WHERE EXPOSED SHALL HAVE A FLAME SPREAD INDEX OF NOT MORE THAN 25 AND A SMOKE DEVELOPED INDEX OF NOT MORE THAN 450.

FOUNDATION PERIMETER TO ATTAIN INSULATION RATING WITH RIGID INSULATION TO TOTAL R-9 MIN. IF REQUIRED BY CODE

FOLLOW LOCAL ENERGY CODE (IECC TYP) FOR ACTUAL REQUIREMENTS

SITE SOILS NOTE:

GEO TECHNICAL INVESTIGATION RECOMMENDATIONS OF THE SOIL BELOW THE BUILDING AND PARKING LOT ARE TO BE FOLLOWED, AS WELL AS ANY COMPLIANCE WITH DOT STANDARDS FOR SITE WORK, AS REQUIRED.
FOLLOW RECOMMENDATIONS OF SOILS REPORT FOR EACH SPECIFIC SITE. L.L. RESPONSIBLE FOR BORINGS AT FINAL BUILDING LOCATION CHOSEN. VERIFY GRADING PER CIVIL DRAWINGS.

