

COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST

MINIMUM PLAN REQUIREMENTS: FLORIDA BUILDING CODE RESIDENTIAL 2014 EFFECTIVE 1 JULY 2015 AND THE NATIONAL ELECTRICAL CODE 2011 EFFECTIVE 1 JULY 2015

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE WITH THE CURRENT 2014 FLORIDA BUILDING CODES RESIDENTIAL, EFFECTIVE 1 JULY 2015. NATIONAL ELECTRICAL CODE 2011 EFFECTIVE 1 JULY 2015. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FLORIDA BUILDING CODE FIGURE 1609-A
THROUGH 1609-C ULTIMATE DESIGN WIND SPEEDS FOR RISK CATEGORY AND BUILDINGS AND OTHER STRUCTURES
Revised 12/2016

	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Each Box shall be Marked as Applicable		
		Select F	_	Dropbox	
1	Two (2) complete sets of plans containing the following:		165		
2	All drawings must be clear, concise, drawn to scale, details that are not used shall be marked void	- 14	The state of the s		
3 (Condition space (Sq. Ft.) 700 Total (Sq. Ft.) under roof 700	YES	NO	N/A	
be a	gners name and signature shall be on all documents and a licensed architect or engineer, signature and ffixed to the plans and documents as per the FLORIDA BUILDING CODES RESIDENTIAL R101.2 e Plan information including:	l official	embosse	d seal sha	
	Dimensions of lot or parcel of land		18C		
	Dimensions of all building set backs	- \	es		
	Location of all other structures (include square footage of structures) on parcel, existing or proposed well and septic tank and all utility easements.	- y	PS		
7	Provide a full legal description of property.	- 11	PC		
8	APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL Plans or specifications must show compliance with FBCR Chapter 3	Each Box shall be Marked as Applicable YES NO N/A			
	i and of specifications must show comprisince with 120% onepower	Select F	om the	Dropbox	
9	Basic wind speed (3-second gust), miles per hour	- 4	PS		
10	(Wind exposure – if more than one wind exposure		80		
~	is used, the wind exposure and applicable wind direction shall be indicated)	F. L.	RS		
11	Wind importance factor and nature of occupancy	Eυ	E		
12	The applicable internal pressure coefficient, Components and Cladding	- 9	15		
	The design wind pressure in terms of psf (kN/m ²), to be used for the design of exterior component,		1		
13	cladding materials not specifally designed by the registered design professional.	- 1	185		
Ele	vations Drawing including:				
14	All side views of the structure		185		
15	Roof pitch		iles		
16	Overhang dimensions and detail with attic ventilation		€\$		
17	Location, size and height above roof of chimneys	-	67		
18	Location and size of skylights with Florida Product Approval	- 1	163		
18	Number of stories		185		
20A	Building height from the established grade to the roofs highest peak	- U	21		

Items to Include-

Flo	or Plan including:	×
20	Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, deck, balconies	- 485
21	Raised floor surfaces located more than 30 inches above the floor or grade	Fhla.
22	All exterior and interior shear walls indicated	- Vec
23	Shear wall opening shown (Windows, Doors and Garage doors)	- yes
24	Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each	
	bedroom (net clear opening shown) and Show compliance with Section FBC 1405.13.2 where the	
	opening of an operable window is located more than 72 inches above the finished grade or surface	
	below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above	- vier
	the finished floor of the room in which the window is located. Glazing between the floor and 24	
	inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass.	
25	Safety glazing of glass where needed	- hla
	Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth	975
26	(see chapter 10 and chapter 24 of FBCR)	2 4 2
•	(ver samples 20 miles 12 miles	-
2,7	Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails	Enla I
28	Identify accessibility of bathroom (see FBCR SECTION 320)	- ha
-	proval number and mfg. installation information submitted with the plans (see Fl m)	
	GENERAL REQUIREMENTS:	Items to Include-
	APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each Box shall be
		Marked as
		Applicable
FB 29	CR 403: Foundation Plans Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size	Select From the Dropbon
	and type of reinforcing.	
30	All posts and/or column footing including size and reinforcing	- 968
31	Any special support required by soil analysis such as piling.	- hla
32	Assumed load-bearing valve of soil Pound Per Square Foot	
33	Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure	es
	with foundation which establish new electrical utility companies service connection a Concrete	- W/2
	Encased Electrode will be required within the foundation to serve as an grounding electrode system.	
	Per the National Electrical Code article 250.52.3	
	CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)	-
34 35	Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports	
FΒ	CR 318: PROTECTION AGAINST TERMITES	
	Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or	- URS
36	Submit other approved termite protection methods. Protection shall be provided by registered	
	termiticides	
FB	CR 606: Masonry Walls and Stem walls (load bearing & shear Walls)	The state of the s
37	Show all materials making up walls, wall height, and Block size, mortar type	- UES
38	Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement	- '
M	etal frame shear wall and roof systems shall be designed, signed and sealed by Florida Pi	of. Engineer or Archit
	oor Framing System: First and/or second story	
T. T.	Floor truss package shall including layout and details, signed and sealed by Florida Registered	- LIES
39	Professional Engineer	- cle?

40	Show conventional floor joist type, size, span, spacing and attachment to load bearing walls,	- ues
40		1 1 1 2 1
41 42	Girder type, size and spacing to load bearing walls, stem wall and/or priers Attachment of joist to girder	- 1103
43	Wind load requirements where applicable	1-1167
44		- Up
45	Show required amount of ventilation opening for under-floor spaces	- h z.
		- Ma
46	Show required covering of ventilation opening	- hin
47	Show the required access opening to access to under-floor spaces	<u> </u>
48	Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges & intermediate of the areas structural panel sheathing	- yes
49	Show Draftstopping, Fire caulking and Fire blocking	- U-el
50	Show fireproofing requirements for garages attached to living spaces, per FBCR section 302.6	- ULDO
<u>51</u>	Provide live and dead load rating of floor framing systems (psf).	- hes
FB	CR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION	YES / NO / N/
	CAR CITE I TERRO WOOD WALLE FRANKING CONSTRUCTION	Items to Include-
	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each Box shall be Marked as
_		Applicable
-		lect From the Dropb
2	Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls	- 29 85
3	Fastener schedule for structural members per table IRC 602.3 are to be shown	- NEZ
	Show Wood structural panel's sheathing attachment to studs, joist, trusses, rafters and structural	
4	members, showing fastener schedule attachment on the edges & intermediate of the areas structural panel sheathing	- 482
	Show all required connectors with a max uplift rating and required number of connectors and	
55	oc spacing for continuous connection of structural walls to foundation and roof trusses or rafter systems	- yes
56	Show sizes, type, span lengths and required number of support jack studs, king studs for shear wall opening and girder or header per IRC Table 502.5 (1)	- 4.2s
57	Indicate where pressure treated wood will be placed	- 4-65
	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural	
58	panel sheathing edges & intermediate areas	- yes
9	A detail showing gable truss bracing, wall balloon framing details or/ and wall hinge bracing detail	- Lies
FI	BCR :ROOF SYSTEMS:	
_	Truss design drawing shall meet section FBCR 802.1.6.1 Wood trusses	- Ues
1		- 1128
2	Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters	- 425
3	Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details	- 1121
4	Provide dead load rating of trusses	- 4723
$\overline{}$	BCR 802:Conventional Roof Framing Layout	
5	Rafter and ridge beams sizes, span, species and spacing	- LIDS
6	Connectors to wall assemblies' include assemblies' resistance to uplift rating	- iles
7	Valley framing and support details	- 45
8	Provide dead load rating of rafter system	- 423
	SCR 803 ROOF SHEATHING	
59	Include all materials which will make up the roof decking, identification of structural panel	- Ues
	sheathing, grade, thickness	
70	Show fastener Size and schedule for structural panel sheathing on the edges & intermediate areas	1- URS
	OF ASSEMBLIES FRC Chapter 9	
1	Include all materials which will make up the roof assembles covering	- 11-67
72	Submit Florida Product Approval numbers for each component of the roof assembles covering	- UPS

FBCR Chapter 11 Energy Efficiency Code for residential building

Residential construction shall comply with this code by using the following compliance methods in the FBCR chapter 11 Residential buildings compliance methods. Two of the required forms are to be submitted, N1100.1.1.1 As an alternative to the computerized Compliance Method A, the Alternate Residential Point System Method hand calculation, Alternate Form 600A, may be used. All requirements specific to this calculation are located in Sub appendix C to Appendix G. Buildings complying by this alternative shall meet all mandatory requirements of this chapter. Computerized versions of the Alternate Residential Point System Method shall not be acceptable for code compliance.

YES / NO / N/A

	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to Include- Each Box shall be Marked as Applicable
		Select From the Dropbox
73	Show the insulation R value for the following areas of the structure	- LIES
74	Attic space	- 4100
	Exterior wall cavity	- 1185
	Crawl space	- Works
Н	VAC information	19
77	Submit two copies of a Manual J sizing equipment or equivalent computation study	- 2162
78	Exhaust fans shown in bathrooms Mechanical exhaust capacity of 50 cfm intermittent or	- LLS
	20 cfm continuous required	
79	Show clothes dryer route and total run of exhaust duct	- 11-25
Ph	umbing Fixture layout shown	
	All fixtures waste water lines shall be shown on the foundation plan	- (162
81	Show the location of water heater	- 1185
	ivate Potable Water	
82	Pump motor horse power	T- T
_	Reservoir pressure tank gallon capacity	
84	Rating of cycle stop valve if used	
	Show Switches, receptacles outlets, lighting fixtures and Ceiling fans	[- LJ-25]
86	Show all 120-volt, single phase, 15- and 20-ampere branch circuits outlets required to be protected by Ground-Fault Circuit Interrupter (GFCI) Article 210.8 A	- 4-5
87	Show the location of smoke detectors & Carbon monoxide detectors	
88	Show service panel, sub-panel, location(s) and total ampere ratings	- 177
89	On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type.	- 4125
	For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an Grounding electrode system. Per the National Electrical Code article 250.52.3	23.0
90	Appliances and HVAC equipment and disconnects	[- 1/1>
91	Show all 120-volt, single phase, 15- and 20-ampere branch circuits supplying outlets installed in dwelling unit family rooms, dining rooms, living rooms, parlors, libraries, dens, bedrooms, sunrooms, recreation rooms, closets, hallways, or similar rooms or areas shall be protected by a listed Combination arc-fault circuit interrupter , Protection device.	= 11-85

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

Items to Include-Each Box shall be Circled as Applicable

THE FOLLOWING ITEMS MUST BE SUBMITTED WITH BUILDING PLANS

		YES	NO	N/A
92	Building Permit Application A current Building Permit Application is to be completed, by following the Checklist all supporting documents must be submitted. There is a \$15.00 application fee. The completed application with attached documents and application fee can be mailed.	NO		
93	Parcel Number The parcel number (Tax ID number) from the Property Appraisers Office (386) 758-1083 is required. A copy of property deed is also required, www.columbiacountyfla.com	NÓ	Ue.	Z
94	Town of Fort White (386) 497-2321 If the parcel in the application for building permit is within the Corporate city limits of Fort White, an approval land use development letter issued by the Town of Fort is required to be submitted with the application for a building permit.	NO		
***	BELOW ITEMS ONLY NEEDED AFTER ZONING APPROVAL HAS GIVEN.	****	***	常在大
95	Environmental Health Permit or Sewer Tap Approval A copy of a approved Columbia County Environmental Health (386) 758-1058	NÓ	1 es	2
96	City of Lake City A City Water and/or Sewer letter. Call 386-752-2031	NO		
97	Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers shall require permitting through the Suwannee River Water Management District, before submitting a application to this office. Any project located within a flood zone where the base flood elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the Columbia County Land Development Regulations. Any project located within a flood zone where the base flood elevation has not been established (Zone A) shall meet the requirements of Section 8.5.3 of the Columbia County Land Development Regulations	NO		
98	CERTIFIED FINISHED FLOOR ELEVATIONS will be required on any project where the approved FIRM Flood Maps show the property is in a AE, Floodway, and AH flood zones. Additionally One Foot Rise letters are required for AE and AH zones. In the Floodway Flood zones a Zero Rise letter is required.			
99	A Flood development permit is also required for AE, Floodway & AH. Development permit cost is \$50.00			
100	Driveway Connection: If the property does not have an existing access to a public road, then an application for a culvert permit (\$25.00) must be made. County Public Works Dept. determines the size and length of every culvert before instillation and completes a final inspection before permanent power is granted. If the applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00) Separate Check when issued. If the project is to be located on an F.D.O.T. maintained road, then an F.D.O.T. access permit is required.	NO		
101	911 Address: An application for a 911 address must be applied for and received through the Columbia County Emergency Management Office of 911 Addressing Department (386) 758-1125.	NO	<u>\$</u>	

TOILET FACILITIES SHALL BE PROVIDED FOR ALL CONSTRUCTION SITES. NO

<u>Disclosure Statement for Owner Builders</u> If you as the applicant will be acting as an owner/builder under section 489.103(7) of the Florida Statutes, submit the required owner builder disclosure statement form.

Notice Of Commencement

A notice of commencement form **recorded** in the Columbia County Clerk Office is required to be filed with the building department Before Any Inspections can be preformed.

Section R101.2.1 of the Florida Building Code Residential:

The provisions of Chapter 1, Florida Building Code shall govern the administration and enforcement of the Florida Building Code, Residential.