

# Builders Statement

## InsulSafe® SP Fiberglass Blow-In Insulation

Lot 53 Aaron Simgue Const.

Homeowner Name / Jobsite Name

336 SW Bellflower Lake City FL

Home Address

J. Couson

Installer / Contractor (sign)

Moran Garage Door Sucs.

Company Name

Date

5/2/22

Builder (sign)

Company Name

Date

Inspected By (sign if required)

Date

### OPEN ATTIC APPLICATION

R-VALUE	NO. BAGS PER 1,000 SQ. FT. NET AREA	MAXIMUM NET COVERAGE	MINIMUM WEIGHT	INITIAL INSTALLED THICKNESS*	MINIMUM SETTLED THICKNESS
To obtain thermal resistance (R) of:	Number of bags	Contents of bag should not cover more than: (sq. ft.)	Weight per sq. ft. of installed insulation should not be less than: (lbs./sq. ft.)	Installed insulation should not be less than: (inches)	Installed insulation should not be less than: (inches)
11	5.0	200.5	0.155	4.50	4.50
13	5.9	170.4	0.182	5.25	5.25
19	8.6	116.2	0.267	7.50	7.50
22	9.9	101.4	0.306	8.50	8.50
26	11.8	84.8	0.366	10.00	10.00
30	13.8	72.5	0.427	11.50	11.50
38	17.9	55.7	0.556	14.50	14.50
44	20.8	48.0	0.646	16.50	16.50
49	23.5	42.6	0.727	18.25	18.25
60	28.9	34.5	0.897	21.75	21.75

	R-VALUE	THICKNESS	NET AREA (SQ. FT.)	INSULSAFE SP (4)	NUMBER OF BAGS USED	BATTS/ROLLS (4)
CEILINGS	30	11.5"	1995'	28	28	
WALLS						
FLOORS						

### THERMAL PERFORMANCE — ATTIC BLOW-IN APPLICATION

- In accordance with the chart above, you must install the minimum number of bags per 1,000 sq. ft. of net area for each R-Value listed.
- The maximum net coverage must not exceed that specified for each R-Value.
- The insulation must be installed at or above the specified installed thickness for each R-Value.
- Failure to install the required minimum weight per sq. ft. of insulation at or above the initial installed thickness will result in reduced R-Value.
- CertainTeed does not recommend or approve of blending or adding additional materials or adhesives with this product during installation. CertainTeed will accept no responsibilities or liabilities when the product is not installed in accordance with the product label and installation instructions. The installing contractor assumes sole responsibility and liability for proper application.