FORM 405-10

FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name Gasparrine Residence Street: City, State, Zip , FL , Owner Frank Gasparrini Design Location FL, Gainesville	Builder Name TBA Permit Office Columbia County Permit Number Jurisdiction
1 New construction or existing 2 Single family or multiple family 3 Number of units, if multiple family 4 Number of Bedrooms 5 Is this a worst case? 6 Conditioned floor area above grade (ft²) 7 Windows(303 0 sqft) Description Area a U-Factor Dbl, U=0.55 303 00 ft² SHGC SHGC=0 50 b U-Factor N/A ft² SHGC: c U-Factor N/A ft² SHGC: d U-Factor N/A ft² SHGC: d U-Factor N/A ft² SHGC Area Weighted Average Overhang Depth Area Weighted Average SHGC 8 Floor Types (2895 0 sqft) Insulation Area a. Slab-On-Grade Edge Insulation R=0.0 1800 00 ft² c N/A R= ft²	9 Wall Types (2720 0 sqft) Insulation Area a Frame - Steel, Exterior R=30.0 2720 00 ft² b. N/A R= ft² c N/A R= ft² d. N/A R= ft² 10 Ceiling Types (2895 0 sqft.) Insulation Area a. Cathedral/Single Assembly (Unvented) R=30 0 1835.00 ft² b Roof Deck (Unvented) R=30 0 1060 00 ft² c. N/A R= ft² 11 Ducts R ft² a Sup RoomsInBlock1, Ret RoomsInBlock1, AH 6 579 12 Cooling systems kBtu/hr Efficiency a Central Unit 36 0 SEER 13 00 13 Heating systems kBtu/hr Efficiency a. Electric Heat Pump 36 0 HSPF 7 70 14 Hot water systems a Electric Cap 50 gallons EF 0 920 b Conservation features None 15 Credits CF, Pstat
Glass/Floor Area: 0.105 Total Proposed Modified Total Standard Reference	
I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code. PREPARED BY:	Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes. BUILDING OFFICIAL: DATE.

			·····	PROJEC	T						
Title Building Type Owner # of Units Builder Name Permit Office Jurisdiction. Family Type New/Existing Comment	Frank Gasparrini 1 TBA Columbia County Single-family	ace	Bedrooms Conditioned Total Storie Worst Case Rotate Ang Cross Venti Whole Hous	s 2 e N le 0 ilation	895 Io		Address Lot # Block/Su PlatBook Street County City, Sta	bDivision	Street Ad Columbia , FL ,		
				CLIMAT	Е						in the second
√ D	esign Location	TMY Site	IEC: Zon		ign Temp % 25%		gn Temp Summer	Heating Degree Da		sign Da sture I	ily Temp Range
F	L, Gainesville FL	_GAINESVILLE_	REGI 2	32	92	70	75	1305.5	5	1	Medium
				BLOCK	S						
Number	Name	Area	Volume								-
1	Block1	2895	23160								
				SPACES	S						
Number	Name	Area	Volume K	itchen C	occupants	Bedroom	s Infil I	ID Finish	ed C	Cooled	Heat
1	RoomsInBlock1	2895	23160	Yes	4	4	1	Yes	١	'es	Yes
-				FLOOR	S						
#_	Floor Type	Space	Perin	neter Perime	eter R-Value	Area	Joist R	-Value	Tile	Wood (Carpet
18	Blab-On-Grade Edge Insu	latio RoomsIn	Block1 170	ft	0	1800 ft ²		-	1	0	0
2F	Raised Floor	RoomsIn	Block1	•		1095 ft²	19	9	0 1	09	0
			<u></u>	ROOF							<u></u>
√ #	Туре	Materials	Roof Area	Gable Area	Roof Color	Solar Absor	SA Teste	Em i tt d	Emitt Tested	Deck Insul	Pitch (deg
1	Gable or shed	Metal	1855 ft²	224 ft²	Medium	0 96	No	0 9	No	30	14
				ATTIC							
√ #	Туре	Ventilat	ion	Vent Ratio	(1 in)	Area	RBS	IRCC			
1	No attic	Unvent		0		1800 ft²	N	N			
			<u> </u>	CEILING	G	<u></u>					
√ #	Ceiling Type		Space	R-Value	A	rea	Framin	g Frac	Tr	uss Type	9
1	Cathedral/Single As	sembly (UnveRte	odmsInBlock1	30	7-	40 ft²	0 ′	11		Metal	
2	Under Attic (Unvent		omsInBlock1	30)60 ft²	0 ′			Metal	
3	Cathedral/Single As	sembly (Unve Rt	omsinBlock1	30	10)95 ft²	0 .	11		Metal	

						WΑ	LLS							
V #	_Ornt_	Adja To	acent Wa	all Type	Space	Cavity R-Value	Wid —Ft		Heigh tin		Sheathing R-Value	Framing	Solar Absor	Below Grade ^o
1	N	Exter		ame - Steel	RoomsInBlo		45		•	360 ft²		0.23	0.75	0
2	2 S	Exter	ior F	rame - Steel	RoomsinBlo	c 30	45	8	3	360 ft²		0 23	0 75	0
3	E	Exter	ior F	rame - Steel	RoomsinBlo	30	40	8	3	320 ft²		0 23	0 75	0
	W	Exter	ior F	rame - Steel	RoomsInBlo	30	40	8	3	320 ft ²		0 23	0 75	0
E	5 N	Exter	ior Fi	ame - Steel	RoomsInBlo	30	45	8	3	360 ft²		0 23	0 75	0
6	S	Exter	ior F	rame - Steel	RoomsinBlo	c 30	45	8	3	360 ft²		0 23	0.75	0
7	' E	Exter	ior F	rame - Steel	RoomsinBlo	c 30	40	{	3	320 ft²		0 23	0 75	0
8	8 W	Exter	ior F	rame - Steel	RoomsInBlo	c 30	40	8	3	320 ft²		0 23	0.75	C
						DO	ors							
\checkmark	#	0	rnt	Door Type	Space			Storms	U-	Value I	Width t In	Heigh Ft	t In	Area
	1	İ	N	Wood	RoomsInBloc			None	0 4	60000	12	7		84 ft²
	2		S	Wood	RoomsInBloc			None	0.4	60000	12	7		35 ft²
	3		E	Wood	RoomsInBloc			None	0.4	60000	12	7		21 ft ²
				0	rientation show		DOWS		orienta	ation				
. /		Wa	all							Ov	erhang			
V	# (Ornt I) Fram			U-Factor	SHGC	Storms	Are	ea Depth	Separation	Int Sha	ade	Screenir
	1	N 1	Meta	al Double (Tinted)	Yes	0 55	0 5	N	18	ft ² 2 ft 0 in	15 ft 0 in	HERS 2	2006	None
	2	N 1	Meta	al Double (Tinted)	Yes	0 55	0 5	N	60	ft² 2 ft 0 in	9 ft 4 in	HERS 2	2006	None
	3	N 1	Meta	l Double (Tinted)	Yes	0 55	0 5	N	30	ft² 2 ft 0 in	10 ft 0 in	HERS 2	2006	None
	4	S 2	Meta	,		0 55	0.5	N	30	ft ² 2 ft 0 in		HERS 2	2006	None
	5	N 5	Meta	al Double (Tinted)	Yes	0 55	0.5	N	90	ft ² 2 ft 0 in	9 ft 4 in	HERS 2	2006	None
	6	S 6	Meta	` ′		0 55	0.5	N	30	ft ² 2 ft 0 in	10 ft 4 in	HERS 2	2006	None
	7	W 4	Meta	al Double (Tinted)	Yes	0 55	0 5	N	30	ft ² 0 ft 6 in	16 ft 4 in	HERS 2	2006	None
	8	W 8	Meta	al Double (Tinted)	Yes	0 55	0 5	N	15	ft² 0 ft 6 in	8 ft 4 in	HERS 2	2006	None
						INFILT	RATIO	ON						
s	cope		Metho		SLA CF	M 50	ELA	E	qLA	ACH	AC	H 50		
	Spaces	Pr	oposed (SLA 00		399 7	93.312		'5 48	0 3412)821		
					Н	EATING	s sys	TEM					· · · · · · · · · · · · · · · · · · ·	
$\sqrt{}$	#	Syster	n Type	S	ubtype	***************************************		Efficienc	y	Capacity		_	Block	Ducts
v			c Heat P		lone			HSPF 7	•				1	sys#1

						COOLI	NG SYS	STEM						
\vee	#	System Type		Subty	ЭӨ			Efficiency	Capacity	Air F	ow	SHR	Block	Ducts
	1	Central Unit		None				SEER 13	36 kBtu/hr	1080	cfm	0 75	1	sys#1
						HOT WA	TER S	/STEM						
$\sqrt{}$	#	System Typ	e SubType	Loca	ation	EF	C	ар	Use	SetPnt		Co	nservatio	n
	1	Electric	None	Roo	msInB	lock10 92	50	gal	70 gal	120 deg			None	
	' ',				SOL	AR HOT	WATE	RSYSTE	М					
\checkmark	FSEC Cert 7		Name			System M	odel#	Co	llector Mode		lector rea	Stor Volu	-	FEF
	None	None									ft²			
		····	· · · · · · · · · · · · · · · · · · ·			E	UCTS			<u></u>				
\checkmark	#		pply R-Value Area		Reti ation	urn Area	Leaka	ge Type	Air Handler	CFM 25	Percei Leakag		RLF	HVAC # Heat Cod
	1	RoomsInBloc	6 579 ft	² Room	sInBlo	oc 144 75	DSE	=0 88	RoomsInl	31 0 0 cfm	0 00	% 0.0	0.60	1 1
						TEMP	ERATU	RES						
Program	nable Th	nermostat Y			Ce	eiling Fans		٠	<u> </u>					
Cooling Heating Venting	X	Jan [X] Fel Jan [X] Fel Jan [X] Fel	X] Mar X] Mar X] Mar X] Mar	[X] Apr [X] Apr [X] Apr		X] May X] May X] May	[X] Jun [X] Jun [X] Jun	[X] Jul [X] Jul [X] Jul	[X] Aug [X] Aug [X] Aug	[X] Sep X] Sep X] Sep	(X X X	Oct Oct Oct	[X] Nov [X] Nov [X] Nov	[X] Dec [X] Dec [X] Dec
Thermosta	at Sched	dule HERS 2	006 Reference					Ho	ours					
Schedule '			1	2	3	4	5	6	7	8	9	10	11	12
Cooling (V	VD)	AM PM	78 80	78 80	78 78	78 78	78 78	78 78	78 78	78 78	80 78	80 78	80 78	80 78
Cooling (V	VEH)	AM PM	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78
Heating (V	ND)	AM PM	66 68	66 68	66 68	66 68	66 68	68 68	68 68	68 68	68 68	68 68	68 66	68 66
Heating (V	NEH)	AM PM	66 68	66 68	66 68	66 68	66 68	68 68	68 68	68 68	68 68	68 68	68 66	68 66
		1 191				CHANIC					~~	00	- 00	
Гуре			Supply CFM	Exhaus	st CFM	1 Fan Wat	ts HR\	/ Heating	System	R	un Time	e Co	ooling Sys	tem
None			0		0	0	0	1 - Electric	Heat Pump		0%	1 - C	entral Uni	t

FORM 405-10

Florida Code Compliance Checklist
Florida Department of Business and Professional Regulations Residential Whole Building Performance Method

ADDRESS:		PERMIT #:	
, FL,	A10		

MANDATORY REQUIREMENTS SUMMARY - See individual code sections for full details.

COMPONENT	SECTION	SUMMARY OF REQUIREMENT(S)	CHECK
Air leakage	402 4	To be caulked, gasketed, weatherstripped or otherwise sealed. Recessed lighting IC-rated as meeting ASTM E 283. Windows and doors = 0.30 cfm/sq.ft. Testing or visual inspection required. Fireplaces: gasketed doors & outdoor combustion air. Must complete envelope leakage report or visually verify Table 402.4.2.	
Thermostat & controls	403.1	At least one thermostat shall be provided for each separate heating and cooling system. Where forced-air furnace is primary system, programmable thermostat is required. Heat pumps with supplemental electric heat must prevent supplemental heat when compressor can meet the load.	
Ducts	403.2.2	All ducts, air handlers, filter boxes and building cavities which form the primary air containment passageways for air distribution systems shall be considered ducts or plenum chambers, shall be constructed and sealed in accordance with Section 503.2.7.2 of this code.	
	403.3.3	Building framing cavities shall not be used as supply ducts.	
Water heaters	403.4	Heat trap required for vertical pipe risers. Comply with efficiencies in Table 403.4.3.2. Provide switch or clearly marked circuit breaker (electric) or shutoff (gas). Circulating system pipes insulated to = R-2 + accessible manual OFF switch.	
Mechanical ventilation	403.5	Homes designed to operate at positive pressure or with mechanical ventilation systems shall not exceed the minimum ASHRAE 62 level. No make-up air from attics, crawlspaces, garages or outdoors adjacent to pools or spas.	
Swimming Pools & Spas	403.9	Pool pumps and pool pump motors with a total horsepower (HP) of = 1 HP shall have the capability of operating at two or more speeds. Spas and heated pools must have vapor-retardant covers or a liquid cover or other means proven to reduce heat loss except if 70% of heat from site-recovered energy. Off/timer switch required. Gas heaters minimum thermal efficiency=78% (82% after 4/16/13). Heat pump pool heaters minimum COP= 4.0.	
Cooling/heating equipment	403.6	Sizing calculation performed & attached. Minimum efficiencies per Tables 503.2.3. Equipment efficiency verification required. Special occasion cooling or heating capacity requires separate system or variable capacity system. Electric heat >10kW must be divided into two or more stages.	
Ceilings/knee walls	405.2.1	R-19 space permitting.	

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE INDEX* = 68

The lower the EnergyPerformance Index, the more efficient the home.

, , FL,

	New construction or exis	•	New (F Single-	rom Plans) family	9	Wall Types a. Frame - Steel, Exterior	Insulatio R≃30.0	2720 00 ft ²
3	Number of units, if multi-	•	1	······· ,		b N/A c N/A d N/A	R= R= R=	ft² ft² ft²
5.	Is this a worst case? Conditioned floor area (f	it²)	No 2895		10	Ceiling Types a Cathedral/Single Assembly b Roof Deck (Unvented)	Insulatio (Unvented) R=30 0 R=30 0	n Area 1835.00 ft² 1060 00 ft²
7	Windows** a U-Factor SHGC:	Description Dbl, U=0 55 SHGC=0 50		Area 303 00 ft²	11	c. N/A I Ducts a Sup RoomsInBlock1, Ret	R= RoomsInBlock1, AH	ft² R ft² 6 579
	b U-Factor ⁻ SHGC ⁻ c. U-Factor ⁻ SHGC	N/A N/A		ft² ft²	12	2 Cooling systems a Central Unit	kBtu/hr 36 0	Efficiency SEER 13 00
	d U-Factor SHGC Area Weighted Average Area Weighted Average		n	ft² 1 777 ft. 0,500	13	Heating systems Electric Heat Pump	kBtu/hr 36 6	
8.	Floor Types a Slab-On-Grade Edge b Raised Floor c N/A			Area 1800 00 ft ² 1095 00 ft ² ft ²	14	Hot water systems a Electric Conservation features None	С	ap 50 gallons EF 0 92
					15	5 Credits		CF. Psta

I certify that this home has complied with the Florida Energy Efficiency Code for Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature: Date:

Address of New Home: City/FL Zip:



*Note: This is not a Building Energy Rating. If your Index is below 70, your home may qualify for energy efficient mortgage (EEM) incentives if you obtain a Florida EnergyGauge Rating. Contact the EnergyGauge Hotline at (321) 638-1492 or see the EnergyGauge web site at energygauge.com for information and a list of certified Raters. For information about the Florida Building Code, Energy Conservation, contact the Florida Building Commission's support staff.

**Label required by Section 303.1.3 of the Florida Building Code, Energy Conservation, if not DEFAULT.

Residential System Sizing Calculation

Summary Project Title:

Frank Gasparrini

Project Title: Gasparrine Residence

, FL


7/3/2012

Location for weather data: Gaine	Location for weather data: Gainesville, FL - Defaults: Latitude(29.7) Altitude(152 ft.) Temp Range(M)											
Humidity data: Interior RH (50%	Humidity data: Interior RH (50%) Outdoor wet bulb (77F) Humidity difference(54gr.)											
Winter design temperature(MJ8 99%) 33 F Summer design temperature(MJ8 99%) 92 F												
Winter setpoint	70	F	Summer setpoint	75	F							
Winter temperature difference 37 F Summer temperature difference 17 F												
Total heating load calculation	33177	Btuh	Total cooling load calculation	24340	Btuh							
Submitted heating capacity	% of calc	Btuh	Submitted cooling capacity	% of calc	Btuh							
Total (Electric Heat Pump)	108.5	36000	Sensible (SHR = 0.75)	144.2	27000							
Heat Pump + Auxiliary(0.0kW) 108.5 36000 Latent 160.3 9000												
			Total (Electric Heat Pump)	147.9	36000							

WINTER CALCULATIONS

Winter Heating Load (for 2895 sqft)


Load component			Load	
Window total	303	sqft	6166	Btuh
Wall total	2277	sqft	6273	Btuh
Door total	140	sqft	2383	Btuh
Ceiling total	2895	sqft	1786	Btuh
Floor total	See detail rep	ort	9454	Btuh
Infiltration	176	cfm	7115	Btuh
Duct loss			0	Btuh
Subtotal			33177	Btuh
Ventilation	0	cfm	0	Btuh
TOTAL HEAT LOSS	3		33177	Btuh



SUMMER CALCULATIONS

Summer Cooling Load (for 2895 sqft)

Load component			Load	
Window total	303	sqft	5926	Btuh
Wall total	2277	sqft	2933	Btuh
Door total	140	sqft	1803	Btuh
Ceiling total	2895	sqft	633	Btuh
Floor total			659	Btuh
Infiltration	132	cfm	2452	Btuh
Internal gain			4320	Btuh
Duct gain			0	Btuh
Sens Ventilation	0	cfm	0	Btuh
Blower Load			0	Btuh
Total sensible gain			18725	Btuh
Latent gain(ducts)			0	Btuh
Latent gain(Infiltration)			4814	Btuh
Latent gain(ventilation)			0	Btuh
Latent gain(internal/occu	pants/othe	er)	800	Btuh
Total latent gain			5614	Btuh
TOTAL HEAT GAIN			24340	Btuh





EnergyGauge® System Sizing
PREPARED BY: William H. Fuer
DATE 7/5/17