

Roof Replacement or Repair Application #73164

Tuesday, September 9, 2025 10:24 PM



Checklist:

___ Address	___ Application Submitted	
___ Drive/ROW	___ Zoning Review	___ Legal Lot of Record
___ Septic	___ Plans Reviewed	___ Flood Zone
___ Site Use Approved	___ Required Inspections Assigned	___ FDEP Needed
___ Docs Reviewed/Accepted	___ Invoiced	

APPLICANT: GT EXECUTIVE SERVICES LLC,

PHONE: (786) 236-8647

ADDRESS: 317 SW ERIN GLN LAKE CITY FL 32024

OWNER: GT EXECUTIVE SERVICES LLC,

PHONE: (786) 236-8647

ADDRESS: 588 SW WALTER AVE LAKE CITY, FL 32024

PARCEL ID: 02-5S-16-03425-013

SUBDIVISION:

LOT: TRACT 10 **BLOCK:** **PHASE:** **UNIT:** **ACRES:** 2.01

CONTRACTOR	TYPE	LIC#	BUSINESS NAME
GT EXECUTIVE SERVICES LLC,	General		

ROOFING JOB DETAILS

Type Roofing Job	Replacement - Tear off Existing and Replace
Further Job Details (Explain if decking is being replaced and or Repairs are being done.)	
Type of structure	House
Further Structure Details (if needed)	
Total Estimated Cost	8000
Commercial or Residential	Residential
Roof Area (for this job) Sq Ft	2100
No. of Stories	1
Ventilation:	Unvented
Flashing:	Replace All
Drip Edge:	Replace All
Valley Treatment:	New Metal
Roof Pitch	2:12 to 4:12
Second Roof Pitch (if applicable)	
Any cable and/or race-way wiring located on or within the roof assembly?	
Is the existing roof being removed?	Yes
Explain if not removing the existing roofing material?	
Type of New Roofing Product	Asphalt Shingles
Florida Product Approval Number	fl 10124
Product Manufacturer	timberline
Product Description	HDZ laminated
Other Roofing Product Type Not Listed	

Sealed roof decking options: (Must select an option.)

a minimum 4-inch wide strip of selfadhering polymer-modified bitumen complying with ASTM D1970 or a minimum 3 ¼ - inch wide strip of selfadhering flexible flashing tape complying with AAMA 711, applied over all joints in the roof decking. A felt underlayment complying with ASTM D226 Type II, ASTM D4869 Type III or IV, or ASTM D6757, or a synthetic underlayment meeting the performance requirements specified, is required to be applied over the strips/tape over the entire roof.

Sealed roof decking explanation for other option.

Review Notes: