



Lumber design values are in accordance with ANSI/TPI 1 section 6.3  
These truss designs rely on lumber values established by others.

RE: 3884251 - IC CONST. - CHILDERS RES.

MiTek, Inc.  
16023 Swingley Ridge Rd.  
Chesterfield, MO 63017  
314.434.1200

**Site Information:**

Customer Info: IC CONSTRUCTION Project Name: Childers Additiion Model: Custom  
Lot/Block: N/A Subdivision: N/A  
Address: TBD, TBD  
City: Columbia Cty State: FL

**Name Address and License # of Structural Engineer of Record, If there is one, for the building.**

Name: License #:  
Address:  
City: State:

**General Truss Engineering Criteria & Design Loads (Individual Truss Design Drawings Show Special Loading Conditions):**

Design Code: FBC2023/TPI2014 Design Program: MiTek 20/20 8.7  
Wind Code: ASCE 7-22 Wind Speed: 130 mph  
Roof Load: 37.0 psf Floor Load: N/A psf

This package includes 11 individual, Truss Design Drawings and 0 Additional Drawings.  
With my seal affixed to this sheet, I hereby certify that I am the Truss Design Engineer and this index sheet conforms to 61G15-31.003, section 5 of the Florida Board of Professional Engineers Rules.


No.	Seal#	Truss Name	Date
1	T33025973	CJ01	2/25/24
2	T33025974	CJ03	2/25/24
3	T33025975	CJ05	2/25/24
4	T33025976	EJ01	2/25/24
5	T33025977	HJ10	2/25/24
6	T33025978	T01	2/25/24
7	T33025979	T02	2/25/24
8	T33025980	T03	2/25/24
9	T33025981	T04	2/25/24
10	T33025982	T05	2/25/24
11	T33025983	T06	2/25/24



This item has been digitally signed and sealed by O'Regan, Philip, PE on the date  
Printed copies of this document are not considered signed and sealed and the signature must be formed on any electronic copies

The truss drawing(s) referenced above have been prepared by  
MiTek USA, Inc. under my direct supervision based on the parameters  
provided by Builders FirstSource-Lake City, FL.

Truss Design Engineer's Name: O'Regan, Philip  
My license renewal date for the state of Florida is February 28, 2025.



Philip J. O'Regan PE No.58126  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

**IMPORTANT NOTE:** The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

February 25, 2024

O'Regan, Philip

1 of 1

Job	Truss	Truss Type	Qty	Ply	IC CONST. - CHILDERS RES.	T33025973
3884251	CJ01	Jack-Open	4	1	Job Reference (optional)	

Builders FirstSource (Lake City,FL), Lake City, FL - 32055, 8.730 s Jan 4 2024 MiTek Industries, Inc. Thu Feb 22 14:11:14 2024 Page 1  
ID:BoWxe1HTNSW5Es2aMYFfUuyPvrZ-q37gvgop2Tcs5v1YniUh4HQDn?Sd6?QRql9sPeziZMR




Plate Offsets (X,Y)--		[2:0-4-5,0-0-4]										
LOADING	(psf)	SPACING-	2-0-0	CSL.	DEFL.	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL	20.0	Plate Grip DOL	1.25	TC	0.34	Vert(LL)	0.00	7	>999	240	MT20	244/190
TCDL	7.0	Lumber DOL	1.25	BC	0.08	Vert(CT)	0.00	7	>999	180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	2	n/a	n/a		
BCDL	10.0	Code	FBC2023/TPI2014	Matrix-MP							Weight: 7 lb	FT = 20%

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 1-0-0 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 3=Mechanical, 2=0-3-8, 4=Mechanical  
Max Horz 2=61(LC 12)  
Max Uplift 3=-26(LC 1), 2=-125(LC 12), 4=-49(LC 19)  
Max Grav 3=20(LC 16), 2=254(LC 1), 4=37(LC 16)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-22; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Zone3 zone; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 5) Refer to girder(s) for truss to truss connections.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 4 except (jt=lb) 2=125.

This item has been digitally signed and sealed by ORegan, Philip, PE on the date indicated here. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

Philip J. O'Regan PE No.58126  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

February 25,2024

Job	Truss	Truss Type	Qty	Ply	IC CONST. - CHILDERS RES.	T33025974
3884251	CJ03	Jack-Open	4	1	Job Reference (optional)	

Builders FirstSource (Lake City,FL), Lake City, FL - 32055, 8.730 s Jan 4 2024 MiTek Industries, Inc. Thu Feb 22 14:11:15 2024 Page 1  
ID:BoWxe1HTNSW5Es2aMYFfUuyPvrZ-IFh270pRpnkjj3ckKQ?wdUzOXPourSfa3PvPx5ziZMQ




Plate Offsets (X,Y)--		[2:0-4-5,0-0-4]			
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) I/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.25	TC 0.34	Vert(LL) -0.00 4-7 >999 240	MT20	244/190
TCDL 7.0	Lumber DOL 1.25	BC 0.08	Vert(CT) -0.01 4-7 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.00	Horz(CT) -0.00 3 n/a n/a		
BCDL 10.0	Code FBC2023/TPI2014	Matrix-MP		Weight: 13 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 3-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 3=Mechanical, 2=0-3-8, 4=Mechanical  
Max Horz 2=105(LC 12)  
Max Uplift 3=40(LC 12), 2=-88(LC 12), 4=-17(LC 9)  
Max Grav 3=54(LC 19), 2=253(LC 1), 4=48(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-22; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Zone3 -2-0-0 to 1-0-0, Zone1 1-0-0 to 2-11-4 zone; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 5) Refer to girder(s) for truss to truss connections.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 2, 4.

This item has been digitally signed and sealed by ORegan, Philip, PE on the date indicated here. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

Philip J. O'Regan PE No.58126  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

February 25,2024

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)


**MiTek®**  
16023 Swingley Ridge Rd.  
Chesterfield, MO 63017  
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	IC CONST. - CHILDERS RES.	T33025975
3884251	CJ05	Jack-Open	4	1	Job Reference (optional)	

Builders FirstSource (Lake City,FL), Lake City, FL - 32055,

8.730 s Jan 4 2024 MiTek Industries, Inc. Thu Feb 22 14:11:16 2024 Page 1

ID:BoWxe1HTNSW5Es2aMYFfUuyPvrZ-mSERKmp3a4saKDBxu7W99iVZHp6mavvkI3ezTXziZMP



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.34	Vert(LL)	0.03	4-7	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.23	Vert(CT)	-0.05	4-7	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Code FBC2023/TPI2014		Matrix-MP						Weight: 20 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 3=Mechanical, 2=0-3-8, 4=Mechanical  
Max Horz 2=150(LC 12)  
Max Uplift 3=-81(LC 12), 2=-90(LC 12)  
Max Grav 3=117(LC 19), 2=313(LC 1), 4=87(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-22; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Zone3 -2-0-0 to 1-0-0, Zone1 1-0-0 to 4-11-4 zone; porch right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 5) Refer to girder(s) for truss to truss connections.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 2.

This item has been digitally signed and sealed by ORegan, Philip, PE on the date indicated here. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

Philip J. O'Regan PE No.58126  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

February 25,2024


**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

**MiTek®**  
16023 Swingley Ridge Rd.  
Chesterfield, MO 63017  
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	IC CONST. - CHILDERS RES.	T33025976
3884251	EJ01	Jack-Partial	10	1	Job Reference (optional)	

Builders FirstSource (Lake City,FL), Lake City, FL - 32055, 8.730 s Jan 4 2024 MiTek Industries, Inc. Thu Feb 22 14:11:17 2024 Page 1  
ID:BoWxe1HTNSW5Es2aMYffUuyPvrZ-FeopYiqhKO\_RyMi7Sr1Oiv2gxDOfJM9tXjOW?zziZMO



LOADING (psf)	SPACING- 2'-0'-0	CSI.	DEFL.	in (loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.25	TC 0.60	Vert(LL) 0.18	4-7	>458	240	MT20	244/190
TCDL 7.0	Lumber DOL 1.25	BC 0.51	Vert(CT) -0.21	4-7	>389	180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.00	Horz(CT) -0.01	3	n/a	n/a		
BCDL 10.0	Code FBC2023/TPI2014	Matrix-MS					Weight: 26 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6'-0'-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10'-0'-0 oc bracing.

REACTIONS.	(size) 3=Mechanical, 2=0-3-8, 4=Mechanical
	Max Horz 2=188(LC 12)
	Max Uplift 3=106(LC 12), 2=100(LC 12), 4=47(LC 9)
	Max Grav 3=165(LC 19), 2=380(LC 1), 4=125(LC 3)

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
---------	--

- NOTES-
- 1) Wind: ASCE 7-22; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Zone3 -2'-0'-0 to 1'-0'-0, Zone1 1'-0'-0 to 6'-11'-4 zone; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-6'-0 tall by 2'-0'-0 wide will fit between the bottom chord and any other members.
  - 5) Refer to girder(s) for truss to truss connections.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4 except (jt=lb) 3=106.

This item has been digitally signed and sealed by O'Regan, Philip, PE on the date indicated here. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

Philip J. O'Regan PE No.58126  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

February 25,2024

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcsccomponents.com](http://www.sbcsccomponents.com))

**MiTek®**  
16023 Swingley Ridge Rd.  
Chesterfield, MO 63017  
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	IC CONST. - CHILDERS RES.	T33025977
3884251	HJ10	Diagonal Hip Girder	2	1	Job Reference (optional)	

Builders FirstSource (Lake City,FL), Lake City, FL - 32055, 8.730 s Jan 4 2024 MiTek Industries, Inc. Thu Feb 22 14:11:18 2024 Page 1  
ID:BoWxe1HTNSW5Es2aMYFfUuyPvrZ-jqMBI2rJ5i6laWKJ0YdF7brtch2k11IM73YPziZMN




Plate Offsets (X,Y)--		[2:0-2-7,0-1-8]			
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.25	TC 0.59	Vert(LL) 0.08 6-7 >999 240	MT20	244/190
TCDL 7.0	Lumber DOL 1.25	BC 0.65	Vert(CT) -0.14 6-7 >826 180		
BCLL 0.0 *	Rep Stress Incr NO	WB 0.34	Horz(CT) 0.01 5 n/a n/a		
BCDL 10.0	Code FBC2023/TPI2014	Matrix-MS		Weight: 45 lb	FT = 20%

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 9-1-6 oc bracing.
WEBS	2x4 SP No.3		

**REACTIONS.** (size) 4=Mechanical, 2=0-4-9, 5=Mechanical  
Max Horz 2=188(LC 8)  
Max Uplift 4=-95(LC 8), 2=-317(LC 4), 5=-162(LC 5)  
Max Grav 4=150(LC 1), 2=485(LC 38), 5=287(LC 37)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-767/337  
BOT CHORD 2-7=-391/615, 6-7=-391/615  
WEBS 3-7=-86/262, 3-6=-662/421

- NOTES-**
- 1) Wind: ASCE 7-22; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 5) Refer to girder(s) for truss to truss connections.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4 except (jt=lb) 2=317, 5=162.
  - 7) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 64 lb down and 102 lb up at 1-6-1, 64 lb down and 102 lb up at 1-6-1, 82 lb down and 44 lb up at 4-4-0, 82 lb down and 44 lb up at 4-4-0, and 116 lb down and 90 lb up at 7-1-15, and 116 lb down and 90 lb up at 7-1-15 on top chord, and 55 lb down and 75 lb up at 1-6-1, 55 lb down and 75 lb up at 1-6-1, 46 lb down and 23 lb up at 4-4-0, 46 lb down and 23 lb up at 4-4-0, and 73 lb down at 7-1-15, and 73 lb down at 7-1-15 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
  - 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard  
1) Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25  
Uniform Loads (plf)  
Vert: 1-4=-54, 5-8=-20  
Concentrated Loads (lb)  
Vert: 7=5(F=3, B=3) 11=49(F=25, B=25) 12=-63(F=-32, B=-32) 14=70(F=35, B=35) 15=-49(F=-25, B=-25)

This item has been digitally signed and sealed by ORegan, Philip, PE on the date indicated here. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.


Philip J. O'Regan PE No.58126  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

February 25,2024



Job	Truss	Truss Type	Qty	Ply	IC CONST. - CHILDERS RES.	T33025978
3884251	T01	Hip Girder	1	1	Job Reference (optional)	

Builders FirstSource (Lake City, FL), Lake City, FL - 32055,		8.730 s Jan 4 2024 MiTek Industries, Inc. Thu Feb 22 14:11:20 2024 Page 1				
		ID:BoWxe1HTNSW5Es2aMYFFUuyPvrZ-fDUxAksadJM0pqUi7zb5KYg8zQSJWxmJDgcAclziZML				
-2-0-0	3-11-2	7-0-0	10-8-6	15-8-0	20-7-11	24-4-0
2-0-0	3-11-2	3-0-14	3-8-6	4-11-11	4-11-11	3-8-6
						27-4-14
						31-4-0
						33-4-0
						2-0-0
Scale = 1:57.6						



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL	20.0	Plate Grip DOL	1.25	TC	0.81	Vert(LL)	0.31 14-16	I/defl	>999	MT20	244/190
TCDL	7.0	Lumber DOL	1.25	BC	0.26	Vert(CT)	-0.39 14-16	L/d	>943		
BCLL	0.0 *	Rep Stress Incr	NO	WB	0.78	Horz(CT)	0.07 11		n/a		
BCDL	10.0	Code	FBC2023/TP12014	Matrix-MS						Weight: 216 lb	FT = 20%

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 2-0-6 oc purlins.
BOT CHORD	2x8 SP 2400F 2.0E	BOT CHORD	Rigid ceiling directly applied or 6-11-8 oc bracing.
WEBS	2x4 SP No.3		

REACTIONS.	(size) 2=0-3-8, 11=0-3-8
	Max Horz 2=-130(LC 27)
	Max Uplift 2=-1264(LC 5), 11=-1297(LC 4)
	Max Grav 2=-2338(LC 1), 11=-2381(LC 1)

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-4064/2338, 3-4=-3918/2332, 4-5=-3411/2065, 5-6=-4828/2919, 6-8=-4846/2920, 8-9=-3481/2118, 9-10=-4000/2395, 10-11=-4146/2401
BOT CHORD	2-17=-2064/3464, 16-17=-2638/4352, 14-16=-2997/4962, 13-14=-2630/4395, 11-13=-2012/3535
WEBS	4-17=-1001/1655, 5-17=-1449/923, 5-16=-491/774, 6-16=-371/249, 6-14=-319/209, 8-14=-452/727, 8-13=-1400/882, 9-13=-969/1623

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-22; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
  - Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=1264, 11=1297.
  - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 126 lb down and 112 lb up at 7-0-0, 126 lb down and 109 lb up at 9-0-12, 126 lb down and 109 lb up at 11-0-12, 126 lb down and 109 lb up at 13-0-12, 126 lb down and 106 lb up at 15-0-12, 126 lb down and 106 lb up at 16-3-4, 126 lb down and 109 lb up at 18-3-4, 126 lb down and 109 lb up at 20-3-4, and 126 lb down and 109 lb up at 22-3-4, and 258 lb down and 217 lb up at 24-4-0 on top chord, and 321 lb down and 258 lb up at 7-0-0, 85 lb down and 67 lb up at 9-0-12, 85 lb down and 67 lb up at 11-0-12, 85 lb down and 67 lb up at 13-0-12, 85 lb down and 67 lb up at 15-0-12, 85 lb down and 67 lb up at 16-3-4, 85 lb down and 67 lb up at 18-3-4, 85 lb down and 67 lb up at 20-3-4, and 85 lb down and 67 lb up at 22-3-4, and 321 lb down and 258 lb up at 24-3-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
  - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

This item has been digitally signed and sealed by O'Regan, Philip, PE on the date indicated here. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

Philip J. O'Regan PE No.58126  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

February 25,2024

LOAD CASE(S) Standard	
Continued on page 2	
<p><b>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.</b></p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see <b>ANSI/TPI1 Quality Criteria and DSB-22</b> available from Truss Plate Institute (www.tpinst.org) and <b>BCSI Building Component Safety Information</b> available from the Structural Building Component Association (www.sbcsccomponents.com)</p>	
<p><b>MiTek®</b></p> <p>16023 Swingley Ridge Rd. Chesterfield, MO 63017 314.434.1200 / MiTek-US.com</p>	

Job	Truss	Truss Type	Qty	Ply	IC CONST. - CHILDERS RES.	T33025978
3884251	T01	Hip Girder	1	1	Job Reference (optional)	

**LOAD CASE(S)**
Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25
- Uniform Loads (plf)

Vert: 1-4=-54, 4-9=-54, 9-12=-54, 2-11=-20
- Concentrated Loads (lb)

Vert: 4=-106(F) 9=-180(F) 15=-61(F) 17=-284(F) 13=-284(F) 22=-106(F) 23=-106(F) 24=-106(F) 25=-106(F) 26=-106(F) 27=-106(F) 28=-106(F) 29=-106(F) 30=-61(F) 31=-61(F) 32=-61(F) 33=-61(F) 34=-61(F) 35=-61(F) 36=-61(F)


**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcsccomponents.com](http://www.sbcsccomponents.com))


**MiTek**®

16023 Swingley Ridge Rd.  
Chesterfield, MO 63017  
314.434.1200 / [MiTek-US.com](http://MiTek-US.com)



Job	Truss	Truss Type	Qty	Ply	IC CONST. - CHILDERS RES.	T33025979
3884251	T02	Hip	1	1	Job Reference (optional)	

Builders FirstSource (Lake City,FL), Lake City, FL - 32055, 8.730 s Jan 4 2024 MiTek Industries, Inc. Thu Feb 22 14:11:22 2024 Page 1  
ID:BoWxe1HTNSW5Es2aMYFfUuyPvrZ-bbcibPuq9wck28e5FOdZPzIZFE1s\_a2cg\_5HhBziZMJ  
-2-0-0 4-10-15 9-0-0 15-8-0 22-4-0 26-5-1 31-4-0 33-4-0  
2-0-0 4-10-15 4-1-1 6-8-0 6-8-0 4-1-1 4-10-15 2-0-0  
Scale = 1:57.6



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL	20.0	Plate Grip DOL	1.25	TC	0.50	Vert(LL)	0.18 14-17 >999 240	MT20		244/190	
TCDL	7.0	Lumber DOL	1.25	BC	0.76	Vert(CT)	-0.32 10-20 >999 180				
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.21	Horz(CT)	0.08 8 n/a n/a				
BCDL	10.0	Code	FBC2023/TPI2014	Matrix-MS							
								Weight: 166 lb		FT = 20%	

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 4-0-9 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 6-5-7 oc bracing.
WEBS	2x4 SP No.3	WEBS	1 Row at midpt 5-14, 5-10

REACTIONS.	
(size)	2=0-3-8, 8=0-3-8
Max Horz	2=159(LC 11)
Max Uplift	2=-491(LC 9), 8=-491(LC 8)
Max Grav	2=1267(LC 1), 8=1267(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD	2-3=-1911/853, 3-4=-1693/800, 4-5=-1423/726, 5-6=-1423/726, 6-7=-1693/800, 7-8=-1911/853
BOT CHORD	2-14=-769/1618, 12-14=-819/1742, 10-12=-819/1742, 8-10=-673/1618
WEBS	3-14=-264/177, 4-14=-309/563, 5-14=-493/308, 5-10=-493/308, 6-10=-309/563, 7-10=-265/177

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-22; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Zone3 -2-0-0 to 1-1-10, Zone1 1-1-10 to 9-0-0, Zone2 9-0-0 to 13-5-3, Zone1 13-5-3 to 22-4-0, Zone2 22-4-0 to 26-6-12, Zone1 26-6-12 to 33-4-0 zone; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=491, 8=491.

This item has been digitally signed and sealed by ORegan, Philip, PE on the date indicated here. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

Philip J. O'Regan PE No.58126  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:


February 25,2024

Job	Truss	Truss Type	Qty	Ply	IC CONST. - CHILDERS RES.	T33025980
3884251	T03	Hip	1	1	Job Reference (optional)	


Builders FirstSource (Lake City,FL), Lake City, FL - 32055,

8.730 s Jan 4 2024 MiTek Industries, Inc. Thu Feb 22 14:11:23 2024 Page 1

ID:BoWxe1HTNSW5Es2aMYFFUuyPvrZ-3o94olvSwEkgbHDHo58oyAlnCdkGj0fmverqDdzizMI



Scale = 1:57.6



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL	20.0	Plate Grip DOL	1.25	TC	0.30	Vert(LL)	-0.29 11-13 >999 240	MT20		244/190	
TCDL	7.0	Lumber DOL	1.25	BC	0.92	Vert(CT)	-0.50 11-13 >759 180				
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.32	Horz(CT)	0.08 8 n/a n/a				
BCDL	10.0	Code	FBC2023/TPI2014	Matrix-MS							
								Weight: 174 lb		FT = 20%	

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 3-10-3 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS	2x4 SP No.3		

REACTIONS.	
(size)	2=0-3-8, 8=0-3-8
Max Horz	2=188(LC 10)
Max Uplift	2=436(LC 9), 8=436(LC 8)
Max Grav	2=1352(LC 2), 8=1352(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD	2-3=-2094/869, 3-4=-1721/751, 4-5=-1443/686, 5-6=-1443/686, 6-7=-1721/751, 7-8=-2094/869
BOT CHORD	2-14=-706/1763, 13-14=-706/1763, 11-13=-572/1521, 10-11=-672/1763, 8-10=-672/1763
WEBS	3-13=-424/239, 4-13=-286/648, 5-13=-266/180, 5-11=-266/180, 6-11=-286/648, 7-11=-425/239

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-22; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Zone3 -2-0-0 to 1-1-10, Zone1 1-1-10 to 11-0-0, Zone2 11-0-0 to 15-8-0, Zone1 15-8-0 to 20-4-0, Zone2 20-4-0 to 24-9-3, Zone1 24-9-3 to 33-4-0 zone; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=436, 8=436.

This item has been digitally signed and sealed by O'Regan, Philip, PE on the date indicated here. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

Philip J. O'Regan PE No.58126  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

February 25,2024

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

**MiTek®**  
16023 Swingley Ridge Rd.  
Chesterfield, MO 63017  
314.434.1200 / MiTek-US.com



Job	Truss	Truss Type	Qty	Ply	IC CONST. - CHILDERS RES.	T33025982
3884251	T05	Hip	1	1	Job Reference (optional)	

Builders FirstSource (Lake City,FL), Lake City, FL - 32055,

8.730 s Jan 4 2024 MiTek Industries, Inc. Thu Feb 22 14:11:26 2024 Page 1

ID:BoWxe1HTNSW5Es2aMYFfUuyPvrZ-UNrCRnxLD979XlysUEiVZpwDNrPowLWCbc3VqyziZMF




Plate Offsets (X,Y)--		[2:0-3-3,0-1-8], [3:0-4-0,0-3-0], [4:0-5-8,0-2-0], [5:0-3-0,0-1-12], [6:0-4-0,0-3-0], [7:0-3-3,0-1-8], [11:0-2-4,0-1-8]	
<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>
TCLL 20.0	Plate Grip DOL	1.25	TC 0.62
TCDL 7.0	Lumber DOL	1.25	BC 0.70
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.38
BCDL 10.0	Code	FBC2023/TPI2014	Matrix-MS
			<b>DEFL.</b>
			in (loc) l/defl L/d
			Vert(LL) 0.16 13-16 >999 240
			Vert(CT) -0.24 9-19 >999 180
			Horz(CT) 0.07 7 n/a n/a
			<b>PLATES</b> <b>GRIP</b>
			MT20 244/190
			Weight: 183 lb FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 3-4-13 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 7-3-1 oc bracing.
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 3-12, 4-10, 6-10

**REACTIONS.** (size) 2=0-3-8, 7=0-3-8  
Max Horz 2=246(LC 11)  
Max Uplift 2=344(LC 12), 7=344(LC 13)  
Max Grav 2=1267(LC 1), 7=1267(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-1866/818, 3-4=-1298/635, 4-5=-1033/590, 5-6=-1301/636, 6-7=-1865/818  
BOT CHORD 2-13=-590/1534, 12-13=-590/1534, 10-12=-318/1030, 9-10=-611/1532, 7-9=-611/1533  
WEBS 3-13=-127/333, 3-12=-615/353, 4-12=-227/387, 5-10=-252/414, 6-10=-610/350, 6-9=-124/328

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-22; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Zone3 -2-0-0 to 1-1-10, Zone1 1-1-10 to 15-0-0, Zone3 15-0-0 to 16-4-0, Zone2 16-4-0 to 20-9-3, Zone1 20-9-3 to 33-4-0 zone; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=344, 7=344.

This item has been digitally signed and sealed by ORegan, Philip, PE on the date indicated here. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

Philip J. O'Regan PE No.58126  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

February 25,2024


**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

**MiTek®**  
16023 Swingley Ridge Rd.  
Chesterfield, MO 63017  
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	IC CONST. - CHILDERS RES.	T33025983
3884251	T06	Common	2	1	Job Reference (optional)	

Builders FirstSource (Lake City,FL), Lake City, FL - 32055, 8.730 s Jan 4 2024 MiTek Industries, Inc. Thu Feb 22 14:11:27 2024 Page 1  
ID:BoWxe1HTNSW5Es2aMYFfUuyPvrZ-yZPbe7yz\_TF09vW21xDk60TNfI1fifLqGp2MOziZME



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL	20.0	Plate Grip DOL	1.25	TC	0.67	Vert(LL)	0.15 10-13 >999 240	MT20		244/190	
TCDL	7.0	Lumber DOL	1.25	BC	0.70	Vert(CT)	-0.24 8-16 >999 180				
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.77	Horz(CT)	0.07 6 n/a n/a				
BCDL	10.0	Code	FBC2023/TPI2014	Matrix-MS							
								Weight: 160 lb		FT = 20%	

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 3-5-10 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 7-2-15 oc bracing.
WEBS	2x4 SP No.3	WEBS	1 Row at midpt 5-9, 3-9

**REACTIONS.** (size) 2=0-3-8, 6=0-3-8  
Max Horz 2=-255(LC 10)  
Max Uplift 2=-342(LC 12), 6=-342(LC 13)  
Max Grav 2=1267(LC 1), 6=1267(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-1868/825, 3-4=-1275/631, 4-5=-1275/631, 5-6=-1868/825  
BOT CHORD 2-10=-597/1537, 9-10=-597/1537, 8-9=-616/1537, 6-8=-616/1537  
WEBS 4-9=-474/802, 5-9=-642/369, 5-8=-125/332, 3-9=-642/369, 3-10=-125/332

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-22; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Zone3 -2-0-0 to 1-1-10, Zone1 1-1-10 to 15-8-0, Zone2 15-8-0 to 20-1-3, Zone1 20-1-3 to 33-4-0 zone; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=342, 6=342.

This item has been digitally signed and sealed by ORegan, Philip, PE on the date indicated here. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.


Philip J. O'Regan PE No.58126  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

February 25,2024



## Symbols

### PLATE LOCATION AND ORIENTATION



\* Plate location details available in MITek software or upon request.

### PLATE SIZE

**4 X 4**


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

### LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

### BEARING




Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number/letter where bearings occur. Min size shown is for crushing only.

### Industry Standards:

ANSI/TP1: National Design Specification for Metal Plate Connected Wood Truss Construction.  
DSB-22: Design Standard for Bracing.  
BCSI: Building Component Safety Information, Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses.

## Numbering System



**JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.**

**CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.**

## Product Code Approvals

ICC-ES Reports:

ESR-1988, ESR-2362, ESR-2685, ESR-3282  
ESR-4722, ESL-1388

## Design General Notes

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TP1 1 section 6.3. These truss designs rely on lumber values established by others.

© 2023 MITek® All Rights Reserved

# MITek®

MITek Engineering Reference Sheet: MII-7473 rev. 1/2/2023

## General Safety Notes

**Failure to Follow Could Cause Property Damage or Personal Injury**

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.