



**ROOF VENTILATION:**  
R205.2 Minimum vent area.  
The minimum net free ventilating area shall be 1/150 of the area of the vented space.  
Exception: The minimum net free ventilation area shall be 1/300 of the vented space provided one or more of the following conditions are met:  
1. In Climate Zones 6, 7 and 8, a Class I or II vapor retarder is installed on the warm-in-winter side of the ceiling.  
2. At least 40 percent and not more than 50 percent of the required ventilating area is provided by ventilators located in the upper portion of the attic or rafter space.  
Upper ventilators shall be located no more than 3 feet below the ridge or highest point of the space, measured vertically, with the balance of the required ventilation provided by eave or cornice vents. Where the location of wall or roof framing members conflicts with the installation of upper ventilators, installation more than 3 feet below the ridge or highest point of the space shall be permitted.



**FRONT ELEVATION**  
SCALE: 1/4" = 1'-0"



**LEFT ELEVATION**  
SCALE: 1/4" = 1'-0"



**RIGHT ELEVATION**  
SCALE: 1/4" = 1'-0"



**REAR ELEVATION**  
SCALE: 1/4" = 1'-0"

Edgley Construction

Brenda Nelson Res.

PROJECT ADDRESS:  
Pinehurst Road  
Lake City, FL

**DIMENSIONS:**  
Stated dimensions supersede scaled dimensions. Refer all questions to Mark Disosway P.E. for resolution. Do not proceed without clarification.

**COPYRIGHTS AND PROPERTY RIGHTS:**  
Mark Disosway P.E. hereby expressly reserves all common law copyrights and property right in these instruments of service. This document is not to be reproduced, altered or copied in any form or manner without first the express written permission and consent of Mark Disosway.

**CERTIFICATION:** I hereby certify that I have examined this plan, and that the applicable portions of the plan, relating to wind engineering comply with the 2017 Florida Building Code Residential (2017) to the best of my knowledge.

**LIMITATION:** This design is valid for one building, at specified location.


MARK DISOSWAY P.E. 53915



Mark Disosway P.E.  
163 SV Midtown Place  
Suite 103  
Lake City, Florida 32025  
316.754.5419  
disoswaydesign@gmail.com

JOE NUMBER:  
200430

1  
OF 6 SHEETS



AREA SCHEDULE	
NAME	AREA
Living	1315.3 sq. ft.
Carport	242.0 sq. ft.
Front Porch	110.8 sq. ft.
Rear Porch	101.0 sq. ft.
Total Under Roof	1769.1 sq. ft.

Edgley Construction

Brenda Nelson Res.

**PROJECT ADDRESS:**  
Pinemount Road  
Lake City, FL

**DIMENSIONS:**  
Stated dimensions supercode scaled dimensions. Refer all questions to Mark Disosway P.E. for resolution. Do not proceed without clarification.

**COPYRIGHTS AND PROPERTY RIGHTS:**  
Mark Disoway P.E. hereby expressly reserves its common law copyright and property right in the instruments of service. This document is not to be reproduced, altered or copied in any form or manner without first the express written permission and consent of Mark Disoway.

**CERTIFICATION:** I hereby certify that I have examined this plan, and that the applicable portions of the plan, relating to wind engineering comply with the 2017 Florida Building Code Residential (2017) to the best of my knowledge.

LIMITATION: Its design is valid for one building, at specified location.

MARK DISOSWAY P.E. 53915



Friday, May 1, 2020

**MarkDisosway P.E.**  
**163 SW Midtown Place**  
**Suite 103**  
**Lake Cty, Florida 32025**  
**316.754.5419**  
**disoswaydesign@gmail.com**


JOB NUMBER:  
200430

2  
Q<sup>2</sup> 6 SH

OF 6 SHEETS

ELECTRICAL PLAN NOTES:	
E - 1	WIRE ALL APPLIANCES, HVAC UNITS AND OTHER EQUIPMENT PER MANUF. SPECIFICATIONS.
E - 2	CONSULT THE OWNER FOR THE NUMBER OF SEPERATE TELEPHONE LINES TO BE INSTALLED.
E - 3	ALL INSTALLATIONS SHALL BE PER NAT'L. ELECTRIC CODE.
E - 4	ALL SMOKE DETECTORS SHALL BE 120V W/ BATTERY BACKUP OF THE PHOTOELECTRIC TYPE, AND SHALL BE INTERLOCKED TOGETHER. INSTALL INSIDE AND NEAR ALL BEDROOMS.
E - 5	TELEPHONE, TELEVISION AND OTHER LOW VOLTAGE DEVICES OR OUTLETS SHALL BE AS PER THE OWNER'S DIRECTIONS, & IN ACCORDANCE W/ APPLICABLE SECTIONS OF NEC-LATEST EDITION.
E - 6	ELECTRICAL CONTR SHALL BE RESPONSIBLE FOR THE DESIGN & SIZING OF ELECTRICAL SERVICE AND CIRCUITS.
E - 7	ENTRY OF SERVICE (UNDERGROUND OR OVERHEAD) TO BE DETERMINED BY POWER COMPANY.
E - 8	ALL 120-VOLT, SINGLE-PHASE, 15- AND 20-AMPERE BRANCH CIRCUITS SUPPLYING OUTLETS INSTALLED IN DWELLING UNIT FAMILY ROOMS, DINING ROOMS, LIVING ROOMS, PARLORS, LIBRARIES, DENS, BEDROOMS, SUN ROOMS, RECREATION ROOMS, CLOSETS, HALLWAYS, OR SIMILAR ROOMS OR AREAS SHALL BE PROTECTED BY A LISTED ARC-FAULT CIRCUIT INTERRUPTER, COMBINATION-TYPE INSTALLED TO PROVIDE PROTECTION OF THE BRANCH CIRCUIT.
E - 9	ALL OUTLETS TO BE LOCATED ABOVE BASE FLOOD ELEVATION.
E - 10	A SERVICE DISCONNECT WITH OVER CURRENT PROTECTION SHALL BE INSTALLED OUTSIDE OF THE BUILDING, ON THE LOAD SIDE OF THE METER, AT THE PLACE ELECTRIC CONDUCTORS ENTER THE BUILDING. SERVICE ENTRANCE CONDUCTORS MAY NOT BE LOCATED INSIDE OF THE OF THE BUILDING WITHOUT SPECIAL APPROVAL OF THE BUILDING OFFICIAL.
E - 11	CARBON MONOXIDE ALARMS SHALL BE REQUIRED WITHIN 10' OF ALL ROOMS FOR SLEEPING PURPOSES IN BUILDINGS HAVING A FOSSIL-FUEL-BURNING HEATER OR APPLIANCE, A FIREPLACE, OR ATTACHED GARAGE.
E - 12	ALL OUTLETS LOCATED IN RESIDENTIAL TO BE TAMPER-RESISTANT PER NEC.
E - 13	A MINIMUM OF 75% OF PERMANENTLY INSTALLED LAMPS OR LIGHTING FIXTURES SHALL BE HIGH EFFICACY 2014 FCC E.C. SEC. R404.1

ELECTRICAL LEGEND	
	CEILING FAN (PRE-WIRE FOR LIGHT KIT)
	DOUBLE SECURITY LIGHT
	2X4 FLUORESCENT LIGHT FIXTURE
	RECESSED CAN LIGHT
	BATH EXHAUST FAN WITH LIGHT
	BATH EXHAUST FAN
	LIGHT FIXTURE
	DUPLEX OUTLET
	220V OUTLET
	GFI DUPLEX OUTLET
	SMOKE DETECTOR
	WALL SWITCH
	3 WAY WALL SWITCH
	4 WAY WALL SWITCH
	WATER PROOF GFI OUTLET
	PHONE JACK
	TELEVISION JACK
	GARAGE DOOR OPENER
	CARBON MONOXIDE ALARM



ELECTRICAL PLAN  
SCALE: 1/4" = 1'-0"

Edgley Construction

Brenda Nelson Res.


PROJECT ADDRESS:  
Pinehurst Road  
Lake City, FL

DIMENSIONS:  
Stated dimensions supercede scaled dimensions. Refer all questions to Mark Disosway, P.E. for resolution. Do not proceed without clarification.

COPYRIGHTS AND PROPERTY RIGHTS:  
Mark Disosway P.E. hereby expressly reserves its common law copyrights and property right in these instruments of service. This document is not to be reproduced, altered or copied in any form or manner without first the express written permission and consent of Mark Disosway.

CERTIFICATION: I hereby certify that I have examined this plan, and that the applicable portions of the plan, relating to wind engineering comply with the 2017 Florida Building Code Residential (2017) to the best of my knowledge.

LIMITATION: This design is valid for one building, at specified location.




Friday, May 1, 2020


Mark Disosway P.E.  
163 SV Midtown Place  
Suite 103  
Lake City, Florida 32025  
386.754.5419  
disoswaydesign@gmail.com

JOB NUMBER:  
200430


3  
OF 6 SHEETS




**ONE STORY WALL SECTION**  
SCALE: 3/4" = 1'-0"



**ROOF SHEATHING FASTENING**



**SHEATHING FOR UPLIFT ATTACHMENT DETAILS**  
ONE STORY WOOD FRAME



**(TYP.) INTERIOR BEARING WALL**  
ONE STORY WOOD FRAME w/ STRAPS & ANCHORS

**CONNECTOR TABLE**

Uplift SP	Uplift SPF	Truss Connector	To Plate	To Truss/Rafter
615	485	SDWC15600		
415	290	H3	4-8d x 1 1/2"	4-8d x 1 1/2"
575	485	H2.5A	5-8d x 1 1/2"	5-8d x 1 1/2"
1340	1015	H10A	9-10d x 1 1/2"	9-10d x 1 1/2"
720	620	LTS12-20	6-10d x 1 1/2"	6-10d x 1 1/2"
1000	860	MTS12-30	7-10d x 1 1/2"	7-10d x 1 1/2"
1450	1245	HTS20-30	12-10d x 1 1/2"	12-10d x 1 1/2"
1235	1235	LSTA21	8-10d	8-10d
1640	1455	MSTA24	9-10d	9-10d
1030	1030	CS20	7-10d	7-10d
Uplift SP	Uplift SPF	Stud Plate Ties	To Stud	To Plate
585	535	SP1	6-10d	4-10d
1065	665	SP2	8-10d	6-10d
771	771	LSTA24	10-10d	wrap under or over plate
1235	1235	LSTA24	14-10d	wrap under or over plate
Uplift SP	Uplift SPF	Holdowns @ Stenwall	To Stud / Post	Anchor
1825	1800	DTT22	8-SDS 1/4"x1 1/2"	1/2"x12" Titen HD
4235	3640	HTT4	18-16d x 1/2"	1/2"x12" Titen HD
Uplift SP	Uplift SPF	Holdowns @ Mono	To Stud / Post	Anchor
1825	1800	DTT22	8-SDS 1/4"x1 1/2"	1/2"x12" Titen HD
4235	3640	HTT4	18-16d x 1/2"	1/2"x12" Titen HD
Uplift SP	Uplift SPF	Post Bases @ Stenwall	To Post	Anchor
2200	2000	ABU44	12-16d	5/8"x12" Drill & Epoxy
2300	2000	ABU66	12-16d	5/8"x12" Drill & Epoxy

**EXTERIOR WALL STUD TABLE FOR SPF #2 STUDS:**

THIS STUD HEIGHT TABLE IS PER 2012 WFCM, TABLE 3.2.0B5, EXTERIOR LOAD BEARING & NON LOAD BEARING STUD LENGTHS FOR WALLS WITH OSB EXTERIOR AND 1/2" GYP INTERIOR RESISTING INTERIOR ZONE WINDLOADS, 130 MPH, EXPOSURE C, STUD DEFLECTION LIMIT H/240 (NOT OK FOR BRITTLE FINISH). STUD SPACINGS SHALL BE MULTIPLIED BY 0.8 FOR FRAMING LOCATED WITHIN 4 FEET OF CORNERS FOR END ZONE LOADING. (END ZONE EXAMPLE 16" O.C. x 0.8 = 12.8" O.C.)

(1) 2x4 @ 16" OC	TO 10'-1" STUD HEIGHT
(1) 2x4 @ 12" OC	TO 11'-2" STUD HEIGHT
(1) 2x6 @ 16" OC	TO 15'-7" STUD HEIGHT
(1) 2x6 @ 12" OC	TO 17'-3" STUD HEIGHT

**GRADE & SPECIES TABLE**

	SP #2	Fb	E
2x8	SP #2	925	1.4
2x10	SP #2	800	1.4
2x12	SP #2	750	1.4
GLB	24F-V3 SP	2600	1.9
LSL	TIMBERSTRAND	1700	1.7
LVL	MICROLAM	2950	2.0
PSL	PARALAM	2900	2.0

**GENERAL NOTES:**

TRUSSES: TRUSSES SHALL BE DESIGNED BY A FLORIDA LICENSED ENGINEER IN ACCORDANCE WITH THE FBOR TRUSS ENGINEERING SHALL INCLUDE TRUSS DESIGN, PLACEMENT PLANS, TEMPORARY AND PERMANENT BRACING DETAILS, ALL BEARING LOCATIONS, TRUSS CONNECTIONS, AND UPLIFT AND REACTION LOADS FOR TRUSSES TO TRUSS CONNECTIONS. IT IS THE TRUSS ENGINEER'S RESPONSIBILITY TO VERIFY THE TRUSS DESIGNER'S FULLY SATISFIED ALL THE ABOVE REQUIREMENTS AND TO SELECT UPLIFT CONNECTIONS BASED ON TRUSS ENGINEERING UPLIFT AND PROVIDE FOOTINGS FOR INTERIOR BEARING WALLS. BUILDER IS TO FURNISH TRUSS ENGINEERING TO WIND LOAD ENGINEER FOR REVIEW OF TRUSS REACTIONS ON THE BUILDING STRUCTURE. STRAP 2x6 RAFTERS WITH MIN. UPLIFT CONNECTION 415 LB EACH END, 2x8 RAFTERS 700 LB EACH END.

SITE PREPARATION: SITE ANALYSIS AND PREPARATION IS NOT PART OF THIS PLAN. FOUNDATION: CONFIRM THAT THE FOUNDATION DESIGN & SITE CONDITIONS MEET GRAVITY LOAD REQUIREMENTS (ASSUME 1500 PSF BEARING CAPACITY UNLESS VISUAL OBSERVATION OR SOIL TEST PROVES OTHERWISE).

CONCRETE: MINIMUM COMPRESSIVE STRENGTH OF CONCRETE AT 28 DAYS,  $F_c = 2500$  PSI.

WELDED WIRE REINFORCED SLAB: 6" x 6" W1 x W1.4, FB = 85KSI, WELDED WIRE REINFORCEMENT FABRIC (W.W.M.) CONFORMING TO ASTM A185, LOCATED IN MIDDLE OF THE SLAB, SUPPORTED WITH APPROVED MATERIALS OR SUPPORTS AT SPACINGS NOT TO EXCEED 3'.

FIBER CONCRETE SLAB: CONCRETE SLABS ON GROUND CONTAINING SYNTHETIC FIBER REINFORCEMENT. FIBER LENGTH 1/2 INCH TO 2 INCHES. DOSAGE AMOUNTS FROM 0.75 TO 1.5 POUNDS PER CUBIC YARD PER THE MANUFACTURER'S RECOMMENDATIONS. FIBERS TO COMPLY WITH ASTM C 1116. SUPPLIER TO PROVIDE ASTM C 1116 CERTIFICATION OF COMPLIANCE WHEN REQUESTED BY BUILDING OFFICIAL.

CONTROL JOINTS: WHERE SPECIFIED, SAWN CONTROL JOINTS IN SLAB ON-GRADE SHALL BE CUT IN ACCORDANCE WITH ACI 302. JOINTS SHALL BE CUT WITHIN 12 HOURS OF SLAB PLACEMENT. THE LENGTH / WIDTH RATIOS OF SLAB AREAS SHALL NOT EXCEED 1.5 AND TYPICAL SPACING OF JOINTS TO NOT DO OUT WITH W.W.M. OR REINFORCING STEEL. CONTRACTOR'S APPROVAL. THE CONTROL JOINTS ARE NOT INTENDED TO PREVENT CRACKS BUT RATHER TO ENCOURAGE THE SLAB TO CRACK ON A GIVEN LINE.

REBAR: ASTM A615, GRADE 40, DEFORMED BARS,  $F_y = 40$  KSI. ALL LAP SPICES 48" DB (25" FOR #5 BARS); UNO. ALL REINFORCEMENT SHALL BE DETAILED AND PLACED IN ACCORDANCE WITH ACI 315-98, U.N.O.


ROOF SHEATHING: ALL ROOFS ARE HORIZONTAL DIAPHRAGMS; 7/16" OSB SHEATHING, UNLOCKED, APPLIED PERPENDICULAR TO FRAMING, OVER A MINIMUM OF 3 FRAMING MEMBERS, WITH PANEL EDGES STAGGERED.

STRUCTURAL CONNECTORS: MANUFACTURERS AND PRODUCT NUMBER FOR CONNECTORS, ANCHORS, AND REINFORCEMENT ARE LISTED FOR EXAMPLE NOT ENDORSEMENT. AN EQUIVALENT DEVICE OF THE SAME OR OTHER MANUFACTURER CAN BE SUBSTITUTED FOR ANY DEVICES LISTED IN THE EXAMPLE TABLES AS LONG AS IT MEETS THE REQUIRED LOAD CAPACITIES. MANUFACTURER'S INSTALLATION INSTRUCTIONS MUST BE FOLLOWED TO ACHIEVE RATED LOADS.


ANCHOR BOLTS: A-307 ANCHOR BOLTS WITH MINIMUM EMBEDMENT AS SPECIFIED IN DRAWINGS BUT NO LESS THAN 7" IN CONCRETE OR REINFORCED BOND BEAM OR 16" IN GROUTED CMU.

**BUILDER'S RESPONSIBILITY:**  
THE BUILDER AND OWNER ARE RESPONSIBLE FOR THE FOLLOWING, WHICH ARE SPECIFICALLY NOT PART OF THE WIND LOAD ENGINEER'S SCOPE OF WORK.  
CONFIRM SITE CONDITIONS, FOUNDATION BEARING CAPACITY, GRADE AND BACKFILL HEIGHT, WIND SPEED AND DEBRIS ZONE, AND FLOOD ZONE.  
PROVIDE MATERIALS AND CONSTRUCTION TECHNIQUES, WHICH COMPLY WITH FBOR REQUIREMENTS FOR THE STATED WIND VELOCITY AND DESIGN PRESSURES.  
PROVIDE A CONTINUOUS LOAD PATH FROM TRUSSES TO FOUNDATION; IF YOU BELIEVE THE PLAN OMTS A CONTINUOUS LOAD PATH CONNECTION, CALL THE WIND LOAD ENGINEER IMMEDIATELY.  
VERIFY THE TRUSS MANUFACTURER'S SEALED ENGINEERING INCLUDES TRUSS DESIGN, PLACEMENT PLANS, TEMPORARY AND PERMANENT BRACING DETAILS, TRUSS-TO-TRUSS CONNECTIONS, AND UPLIFT AND REACTION LOADS FOR ALL BEARING LOCATIONS.

**ROOF SYSTEM DESIGN:**  
THE SEAL ON THESE PLANS FOR COMPLIANCE WITH FBOR, IS BASED ON REACTIONS, UPLIFTS, AND BEARING LOCATIONS IN TRUSS ENGINEERING SUBMITTED TO THE WIND LOAD ENGINEER. IT IS THE RESPONSIBILITY OF THE BUILDER TO CHECK ALL DETAILS OF THE COMPLETE ROOF SYSTEM DESIGN SUBMITTED BY THE TRUSS MANUFACTURER AND HAVE IT SIGNED, AND SEALED BY A DESIGN PROFESSIONAL FOR CORRECT APPLICATION OF FBOR REQUIRED LOADS AND ANY SPECIAL LOADS. THE BUILDER IS RESPONSIBLE TO REVIEW EACH INDIVIDUAL TRUSS MEMBER AND THE TRUSS ROOF BRACING. THE BUILDER SHOULD USE CARE CHECKING THE ROOF DESIGN BECAUSE THE WIND LOAD ENGINEER IS SPECIFICALLY NOT RESPONSIBLE FOR THE TRUSS LAYOUT WHICH WAS CREATED BY THE TRUSS MANUFACTURER AND THE TRUSS DESIGNER ALSO DENIES RESPONSIBILITY FOR THE LAYOUT PER NOTES ON THEIR SEALED TRUSS SHEETS.



**(TYP.) INTERSECTING WALL FRAMING**  
WOOD FRAME




**(TYP.) CORNER FRAMING**  
WOOD FRAME

SPACE RAT RUN & DIAGONAL BRACE 6'-0" O.  
FOR GABLE HEIGHT UP TO 25'-0" 130 MPH, EX C, ENCLOSED

**(TYP.) GABLE BRACING DETAIL**  
WOOD FRAME

**(TYP.) GABLE WALL w/ VAULTED CEILING**  
WOOD FRAME



**TYPICAL HEADER STRAP DETAIL**  
ONE STORY WOOD FRAME w/ STRAPS & ANCHORS


**HEADER STRAP TABLE**

Uplift	Top Connection	Bottom Connection
< 1235	LSTA24, 14-10d wrap over plate	LSTA24, 14-10d wrap under plate
< 1455	MSTA24, 18-10d header to jacks	DTT22
< 1800	(2) MSTA24, 18-10d header to jacks	DTT22
< 2910	(2) MSTA24, 18-10d header to jacks	HTT4


**SILL PLATE SPANS FOR 10'-0" WALL HEIGHT**

DESIGN WIND SPEED	MAX. SPANS FOR SPF #2	BASED ON WFCM TABLE 3.2.0B
(1) 2x4	(2) 2x4	(1) 2x6
(2) 2x6	(1) 2x6	(2) 2x6
(3) 2x8	(1) 2x8	(2) 2x8
(4) 2x10	(1) 2x10	(2) 2x10

**(TYP.) PORCH POST**  
ONE STORY WOOD



**(TYP.) BEAM TO WALL**  
WOOD FRAME w/ STRAPS & ANCHORS



**(TYP.) WALL CONNECTIONS**  
ONE STORY WOOD FRAME

**DESIGN CRITERIA & LOADS:**

BUILDING CODE	6TH EDITION FLORIDA BUILDING CODE RESIDENTIAL (2017)
CODE FOR DESIGN LOADS	ASCE 7-10
WIND LOADS	
BASIC WIND SPEED (ASCE 7-10, 3S GUST)	130 MPH
WIND EXPOSURE (BUILDER MUST FIELD VERIFY)	C
TOPOGRAPHIC FACTOR (BUILDER MUST FIELD VERIFY)	1
RISK CATEGORY	II
ENCLOSURE CLASSIFICATION	ENCLOSED
INTERNAL PRESSURE COEFFICIENT	0.18
ROOF ANGLE	7-45 DEGREES
MEAN ROOF HEIGHT	30 FT
C & C DESIGN PRESSURES	SEE TABLE
FLOOR LOADING	
ROOMS OTHER THAN SLEEPING ROOM	40 PSF LIVE LOAD
SLEEPING ROOMS	30 PSF LIVE LOAD
ROOF LOADING	
FLAT OR < 4:12	20 PSF LIVE LOAD
4:12 TO < 12:12	16 PSF LIVE LOAD
12:12 & GREATER	12 PSF LIVE LOAD
SOIL BEARING CAPACITY	1500 PSF
FLOOD ZONE	THIS BUILDING IS NOT IN THE FLOOD ZONE

**COMPONENT & CLADDING DESIGN PRESSURES 130 MPH (EXP C)**

EFFECTIVE WIND AREA (Ft <sup>2</sup> )	ZONE 4 INTERIOR	ZONE 5 END 4' FROM ALL OUTSIDE CORNER
0-20	+25.6(Vsft)	-27.8(Vsft)
0-20	+42.6(Vsft)	-46.2(Vsft)

**GARAGE DOOR DESIGN PRESSURES 130 MPH (EXP C)**

9x7 GARAGE DOOR	+22.6(Vsft)	-25.5(Vsft)
16x7 GARAGE DOOR	+21.7(Vsft)	-24.1(Vsft)

Edgley Construction

Brenda Nelson Res.

PROJECT ADDRESS:  
Pinehurst Road  
Lake City, FL


DIMENSIONS:  
Stated dimensions supercede scaled dimension. Refer all questions to Mark Disoway, P.E. for resolution. Do not proceed without clarification.

COPYRIGHTS AND PROPERTY RIGHTS:  
Mark Disoway, P.E. hereby expressly reserves its control law copyrights and property right in these instruments of service. This document is not to be reproduced, altered or copied in any form or manner without first the express written permission and consent of Mark Disoway.

CERTIFICATION: I hereby certify that I have examined this plan, and that the applicable portions of the plan, relating to wind engineering comply with the 6th Edition Florida Building Code Residential (2017) to the best of my knowledge.

LIMITATION: This design is valid for one building, at specified location.


MRK DISOWAY, P.E. 53915




Friday, May 1, 2020

Mark Disoway P.E.  
163 3W Midtown Place  
Suite 103  
Lake City, Florida 32025  
386.754.5419  
disowaydesign@gmail.com


JCB NUMBER:  
200430  
S-1  
OF 6 SHEETS




**F1**  
S-2  
STEM WALL FOOTING  
SCALE: 1/2" = 1'-0"



**F2**  
S-2  
MONOLITHIC FOOTING  
SCALE: 1/2" = 1'-0"



**F3**  
S-2  
INTERIOR BEARING FOOTING  
SCALE: 1/2" = 1'-0"



**F4**  
S-2  
INTERIOR BEARING STEP FOOTING  
SCALE: 1/2" = 1'-0"


**TALL STEM WALL TABLE:**  
The table assumes 40 ksi for #5 rebar and 60 ksi for #7 & #8 rebar with 6" hook in the footing and bent 24" into the reinforced slab at the top. The vertical steel is to be placed toward the tension side of the CMU wall (away from the soil pressure, within 2" of the exterior side of the wall). If the wall is over 8' high, add Durawall ladder reinforcement at 16" OC vertically or a horizontal bond beam with #6 continuous at mid height. For higher parts of the wall 12" CMU may be used with reinforcement as shown in the table below.

STEM WALL HEIGHT (FEET)	UNBALANCED BACKFILL HEIGHT	VERTICAL REINFORCEMENT FOR 8" CMU STEM WALL (INCHES O.C.)			VERTICAL REINFORCEMENT FOR 12" CMU STEM WALL (INCHES O.C.)		
		#5	#7	#8	#5	#7	#8
3.3	3.0	96	96	96	96	96	96
4.0	3.7	96	96	96	96	96	96
4.7	4.3	88	96	96	96	96	96
5.3	5.0	56	96	96	96	96	96
6.0	5.7	40	80	96	80	96	96
6.7	6.3	32	56	80	56	96	96
7.3	7.0	24	40	56	40	80	96
8.0	7.7	16	32	48	32	64	80
8.7	8.3	8	24	32	24	48	64
9.3	9.0	8	16	24	16	40	48

**MASONRY NOTE:**  
MASONRY CONSTRUCTION AND MATERIALS FOR THIS PROJECT SHALL CONFORM TO ALL REQUIREMENTS OF "SPECIFICATION FOR MASONRY STRUCTURES" (ACI 530.1/ASCE 6/TMS 602). THE CONTRACTOR AND MASON MUST IMMEDIATELY, BEFORE PROCEEDING, NOTIFY THE ENGINEER OF ANY CONFLICTS BETWEEN ACI 530.1-02 AND THESE DESIGN DRAWINGS. ANY EXCEPTIONS TO ACI 530.1-02 MUST BE APPROVED BY THE ENGINEER IN WRITING.

ACI 530.1-02 Section	Specific Requirements
1.4A Compressive strength	8" block bearing walls $F_m = 1500$ psi
2.1 Mortar	ASTM C 270, Type N, UNO
2.2 Grout	ASTM C 476, admixtures require approval
2.3 CMU standard	ASTM C 90-02, Normal weight, Hollow, medium surface finish, 8"x8"x16" running bond and 12"x12" or 16"x16" column block
2.3 Clay brick standard	ASTM C 216-02, Grade SW, Type FBS, 5.7"x2.75"x11.2"
2.4 Reinforcing bars, #3 - #11	ASTM 615, Grade 40, $F_y = 40$ ksi, Lap splices min 40 bar dia. (25" for #6)
2.4F Coating for corrosion protection	Anchors, steel metal ties completely embedded in mortar or grout, ASTM A525, Class G80, 0.60 coat/2 or 304SS
2.4F Coating for corrosion protection	Joint reinforcement in walls exposed to moisture or wire ties, anchors, steel metal ties not completely embedded in mortar or grout, ASTM A153, Class B2, 1.50 coat/2 or 304SS
3.3.E.2 Pipes, conduits, and accessories	Any not shown on the project drawings require engineering approval.
3.3.E.7 Movement joints	Contractor assumes responsibility for type and location of movement joints if not detailed on project drawings.

BOTTOM OF EXTERIOR FOOTINGS SHALL BE A MINIMUM OF 12" BELOW UNDISTURBED SOIL OR ENGINEERED FILL PER FBC 2017-RES. SECTION R403.1.4



#### FOUNDATION PLAN

SCALE: 1/4" = 1'-0"

#### FOUNDATION NOTES

- FN-1 DIMENSIONS ON FOUNDATION & STRUCTURAL SHEETS ARE NOT EXACT. REFER TO ARCHITECTURAL PLANS FOR ACTUAL DIMENSIONS, RECESSES IN SLAB, STEP DOWNS, ETC. DISOWAY DESIGN GROUP OR MARK DISOWAY, P.E. IS NOT RESPONSIBLE FOR DIMENSION ERRORS ON THIS PLAN.
- CONTRACTOR SHALL VERIFY NEED FOR INTERIOR BEARING IN ALL AREAS BY REVIEWING THE ROOF TRUSS PLAN (BY THE SUPPLIER) BEFORE FINALIZING FOUNDATION PLAN.
- FN-2 THE SLAB SHALL BE: 4" CONCRETE SLAB REINFORCED W/ 8x8-14/14 WELDED WIRE MESH PLACED ON CHAIRS @ 12" DEPTH ON FIBER MESH CONCRETE, 5-MIL POLY VAPOR BARRIER W/ 6" LAPS SEALED W/ POLY TAPE OVER TERMITE-TREATED & COMPACTED FILL (ALSO, ANY OTHER CODE-APPROVED TERMITE-TREATMENT METHOD CAN BE USED INSTEAD).

Edgley Construction

Brenda Nelson Res.

PROJECT ADDRESS:  
Pharmacia Road  
Lake City, FL

**DIMENSIONS:**  
Stated dimensions supercede scaled dimensions. Refer all questions to Mark Disoway, P.E. for resolution. Do not proceed without clarification.

**COPYRIGHTS AND PROPERTY RIGHTS:**  
Mark Disoway, P.E. hereby expressly reserves its common law copyright and property right in these instruments of service. This document is not to be reproduced, altered or copied in any form or manner without first the express written permission and consent of Mark Disoway.

**CERTIFICATION:** I hereby certify that I have examined this plan, and that the applicable portions of the plan, relating to wind engineering comply with the 6th Edition Florida Building Code Residential (2017) to the best of my knowledge.

**LIMITATION:** This design is valid for one building, at specified location.

MARK DISOWAY P.E. 53915



Friday, May 1, 2020


MarkDisoway P.E.  
163 SW Midtown Place  
Suite 103  
Lake City, Florida 32025  
386.754.5419  
disowaydesign@gmail.com

JOB NUMBER:  
200430

S-2  
OF 6 SHEETS

# LUMBER SIZE & GRADE MINIMUM REQUIREMENTS

RISE BOARD	2X6 SYP #2
RAFTER SPANS 22'-0" OR LESS	2X4 SYP #2
PURLINS / LATERAL BRACING	2X4 SYP #2
SLEEPERS	2X WIDTH OF RAFTER BEAT CUT) SYP #3 OR 2 PARALLEL 2X4 SYP #3
CRIPPLES & BLOCKING	2X4 SYP #2 OR BETTER
TRUSS BELOW	SEE TRUSS DESIGN - SOUTHERN PINE MATERIAL



ROOF OVER FRAMING & BRACING DETAIL  
SCALE: 1/8" = 1'-0"

## VALLEY ROOF PLAN MEMBER LEGEND

—	TRUSS
—	TRUSS UNDER VALLEY FRAMING
—	VALLEY RAFTER OR RIDGE
—	CRIPPLE

CRIPPLES 4'-0" O.C. FOR 20 psf (T1) AND 10 psf (T2) (TYP. SINGLE ROOF) MAX

## CONNECTION REQUIREMENT NOTES


1	2X4 RAFTERS TO RIDGE	3-16d OR 8-131 x 3" TOE NAILS
2	CRIPPLE TO RIDGE	3-16d OR 8-131 x 3" FACE NAILS
3	CRIPPLE TO RAFTERS	3-16d OR 8-131 x 3" FACE NAILS
4	RAFTER TO SLEEPER OR BLOCKING	4-16d OR 12-131 x 3" TOE NAILS
5	SLEEPER TO TRUSS	4-16d OR 8-131 x 3" FACE NAILS EACH TRUSS
6	RIDGE BOARD TO ROOF BLOCK	3-16d OR 8-131 x 3" TOE NAILS
7	RIDGE BOARD TO TRUSS	3-16d OR 8-131 x 3" TOE NAILS
8	PURLIN TO TRUSS (TYP)	3-16d OR 8-131 x 3" NAILS
9	PURLIN TO TRUSS (IF CRIPPLE IS ATTACHED TO PURLIN)	4-16d OR 8-131 x 3" NAILS
10	TRUSS TO BLOCKING	3-16d OR 8-131 x 3" END NAILS
11	CRIPPLE TO TRUSS	3-16d OR 8-131 x 3" FACE NAILS
12	CRIPPLE TO PURLIN	3-16d OR 8-131 x 3" FACE NAILS

## GENERAL NOTES

MAXIMUM RAFTER SPANS: 6'-0" FOR 2X4 SYP FOR 20 PSF #2 OR SYP #2. MAXIMUM ROOF AREA PER SUPPORT: 180 sq. ft. IN ZONE 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121, 122, 123, 124, 125, 126, 127, 128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 250, 251, 252, 253, 254, 255, 256, 257, 258, 259, 260, 261, 262, 263, 264, 265, 266, 267, 268, 269, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 289, 290, 291, 292, 293, 294, 295, 296, 297, 298, 299, 300, 301, 302, 303, 304, 305, 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 350, 351, 352, 353, 354, 355, 356, 357, 358, 359, 360, 361, 362, 363, 364, 365, 366, 367, 368, 369, 370, 371, 372, 373, 374, 375, 376, 377, 378, 379, 380, 381, 382, 383, 384, 385, 386, 387, 388, 389, 390, 391, 392, 393, 394, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 431, 432, 433, 434, 435, 436, 437, 438, 439, 440, 441, 442, 443, 444, 445, 446, 447, 448, 449, 450, 451, 452, 453, 454, 455, 456, 457, 458, 459, 460, 461, 462, 463, 464, 465, 466, 467, 468, 469, 470, 471, 472, 473, 474, 475, 476, 477, 478, 479, 480, 481, 482, 483, 484, 485, 486, 487, 488, 489, 490, 491, 492, 493, 494, 495, 496, 497, 498, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 547, 548, 549, 550, 551, 552, 553, 554, 555, 556, 557, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 578, 579, 580, 581, 582, 583, 584, 585, 586, 587, 588, 589, 590, 591, 592, 593, 594, 595, 596, 597, 598, 599, 600, 601, 602, 603, 604, 605, 606, 607, 608, 609, 610, 611, 612, 613, 614, 615, 616, 617, 618, 619, 620, 621, 622, 623, 624, 625, 626, 627, 628, 629, 630, 631, 632, 633, 634, 635, 636, 637, 638, 639, 640, 641, 642, 643, 644, 645, 646, 647, 648, 649, 650, 651, 652, 653, 654, 655, 656, 657, 658, 659, 660, 661, 662, 663, 664, 665, 666, 667, 668, 669, 670, 671, 672, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 685, 686, 687, 688, 689, 690, 691, 692, 693, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 711, 712, 713, 714, 715, 716, 717, 718, 719, 720, 721, 722, 723, 724, 725, 726, 727, 728, 729, 730, 731, 732, 733, 734, 735, 736, 737, 738, 739, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 750, 751, 752, 753, 754, 755, 756, 757, 758, 759, 760, 761, 762, 763, 764, 765, 766, 767, 768, 769, 770, 771, 772, 773, 774, 775, 776, 777, 778, 779, 780, 781, 782, 783, 784, 785, 786, 787, 788, 789, 790, 791, 792, 793, 794, 795, 796, 797, 798, 799, 800, 801, 802, 803, 804, 805, 806, 807, 808, 809, 810, 811, 812, 813, 814, 815, 816, 817, 818, 819, 820, 821, 822, 823, 824, 825, 826, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 844, 845, 846, 847, 848, 849, 850, 851, 852, 853, 854, 855, 856, 857, 858, 859, 860, 861, 862, 863, 864, 865, 866, 867, 868, 869, 870, 871, 872, 873, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 898, 899, 900, 901, 902, 903, 904, 905, 906, 907, 908, 909, 910, 911, 912, 913, 914, 915, 916, 917, 918, 919, 920, 921, 922, 923, 924, 925, 926, 927, 928, 929, 930, 931, 932, 933, 934, 935, 936, 937, 938, 939, 940, 941, 942, 943, 944, 945, 946, 947, 948, 949, 950, 951, 952, 953, 954, 955, 956, 957, 958, 959, 960, 961, 962, 963, 964, 965, 966, 967, 968, 969, 970, 971, 972, 973, 974, 975, 976, 977, 978, 979, 980, 981, 982, 983, 984, 985, 986, 987, 988, 989, 990, 991, 992, 993, 994, 995, 996, 997, 998, 999, 1000.

## CRIPPLE, BRACING & BLOCKING NOTES

2X4 CONTINUOUS LATERAL BRACE (CLB) MIN. IS REQUIRED FOR CRIPPLES 8'-0" TO 10'-0" LONG NAIL TO 2-10d NAILS OR 2X4 11" OR 12" OR 14" OR 16" OR 18" OR 20" OR 22" OR 24" OR 26" OR 28" OR 30" OR 32" OR 34" OR 36" OR 38" OR 40" OR 42" OR 44" OR 46" OR 48" OR 50" OR 52" OR 54" OR 56" OR 58" OR 60" OR 62" OR 64" OR 66" OR 68" OR 70" OR 72" OR 74" OR 76" OR 78" OR 80" OR 82" OR 84" OR 86" OR 88" OR 90" OR 92" OR 94" OR 96" OR 98" OR 100" OR 102" OR 104" OR 106" OR 108" OR 110" OR 112" OR 114" OR 116" OR 118" OR 120" OR 122" OR 124" OR 126" OR 128" OR 130" OR 132" OR 134" OR 136" OR 138" OR 140" OR 142" OR 144" OR 146" OR 148" OR 150" OR 152" OR 154" OR 156" OR 158" OR 160" OR 162" OR 164" OR 166" OR 168" OR 170" OR 172" OR 174" OR 176" OR 178" OR 180" OR 182" OR 184" OR 186" OR 188" OR 190" OR 192" OR 194" OR 196" OR 198" OR 200" OR 202" OR 204" OR 206" OR 208" OR 210" OR 212" OR 214" OR 216" OR 218" OR 220" OR 222" OR 224" OR 226" OR 228" OR 230" OR 232" OR 234" OR 236" OR 238" OR 240" OR 242" OR 244" OR 246" OR 248" OR 250" OR 252" OR 254" OR 256" OR 258" OR 260" OR 262" OR 264" OR 266" OR 268" OR 270" OR 272" OR 274" OR 276" OR 278" OR 280" OR 282" OR 284" OR 286" OR 288" OR 290" OR 292" OR 294" OR 296" OR 298" OR 300" OR 302" OR 304" OR 306" OR 308" OR 310" OR 312" OR 314" OR 316" OR 318" OR 320" OR 322" OR 324" OR 326" OR 328" OR 330" OR 332" OR 334" OR 336" OR 338" OR 340" OR 342" OR 344" OR 346" OR 348" OR 350" OR 352" OR 354" OR 356" OR 358" OR 360" OR 362" OR 364" OR 366" OR 368" OR 370" OR 372" OR 374" OR 376" OR 378" OR 380" OR 382" OR 384" OR 386" OR 388" OR 390" OR 392" OR 394" OR 396" OR 398" OR 400" OR 402" OR 404" OR 406" OR 408" OR 410" OR 412" OR 414" OR 416" OR 418" OR 420" OR 422" OR 424" OR 426" OR 428" OR 430" OR 432" OR 434" OR 436" OR 438" OR 440" OR 442" OR 444" OR 446" OR 448" OR 450" OR 452" OR 454" OR 456" OR 458" OR 460" OR 462" OR 464" OR 466" OR 468" OR 470" OR 472" OR 474" OR 476" OR 478" OR 480" OR 482" OR 484" OR 486" OR 488" OR 490" OR 492" OR 494" OR 496" OR 498" OR 500" OR 502" OR 504" OR 506" OR 508" OR 510" OR 512" OR 514" OR 516" OR 518" OR 520" OR 522" OR 524" OR 526" OR 528" OR 530" OR 532" OR 534" OR 536" OR 538" OR 540" OR 542" OR 544" OR 546" OR 548" OR 550" OR 552" OR 554" OR 556" OR 558" OR 560" OR 562" OR 564" OR 566" OR 568" OR 570" OR 572" OR 574" OR 576" OR 578" OR 580" OR 582" OR 584" OR 586" OR 588" OR 590" OR 592" OR 594" OR 596" OR 598" OR 600" OR 602" OR 604" OR 606" OR 608" OR 610" OR 612" OR 614" OR 616" OR 618" OR 620" OR 622" OR 624" OR 626" OR 628" OR 630" OR 632" OR 634" OR 636" OR 638" OR 640" OR 642" OR 644" OR 646" OR 648" OR 650" OR 652" OR 654" OR 656" OR 658" OR 660" OR 662" OR 664" OR 666" OR 668" OR 670" OR 672" OR 674" OR 676" OR 678" OR 680" OR 682" OR 684" OR 686" OR 688" OR 690" OR 692" OR 694" OR 696" OR 698" OR 700" OR 702" OR 704" OR 706" OR 708" OR 710" OR 712" OR 714" OR 716" OR 718" OR 720" OR 722" OR 724" OR 726" OR 728" OR 730" OR 732" OR 734" OR 736" OR 738" OR 740" OR 742" OR 744" OR 746" OR 748" OR 750" OR 752" OR 754" OR 756" OR 758" OR 760" OR 762" OR 764" OR 766" OR 768" OR 770" OR 772" OR 774" OR 776" OR 778" OR 780" OR 782" OR 784" OR 786" OR 788" OR 790" OR 792" OR 794" OR 796" OR 798" OR 800" OR 802" OR 804" OR 806" OR 808" OR 810" OR 812" OR 814" OR 816" OR 818" OR 820" OR 822" OR 824" OR 826" OR 828" OR 830" OR 832" OR 834" OR 836" OR 838" OR 840" OR 842" OR 844" OR 846" OR 848" OR 850" OR 852" OR 854" OR 856" OR 858" OR 860" OR 862" OR 864" OR 866" OR 868" OR 870" OR 872" OR 874" OR 876" OR 878" OR 880" OR 882" OR 884" OR 886" OR 888" OR 890" OR 892" OR 894" OR 896" OR 898" OR 900" OR 902" OR 904" OR 906" OR 908" OR 910" OR 912" OR 914" OR 916" OR 918" OR 920" OR 922" OR 924" OR 926" OR 928" OR 930" OR 932" OR 934" OR 936" OR 938" OR 940" OR 942" OR 944" OR 946" OR 948" OR 950" OR 952" OR 954" OR 956" OR 958" OR 960" OR 962" OR 964" OR 966" OR 968" OR 970" OR 972" OR 974" OR 976" OR 978" OR 980" OR 982" OR 984" OR 986" OR 988" OR 990" OR 992" OR 994" OR 996" OR 998" OR 1000.




## STRUCTURAL PLAN

SCALE: 1/4" = 1'-0"

## STRUCTURAL PLAN NOTES

- SN-1 ALL LOAD BEARING FRAME WALL & PORCH HEADERS SHALL BE A MINIMUM OF (2) 2X10 SP #2 (U.N.O.)
- SN-2 ALL LOAD BEARING FRAME WALL HEADERS SHALL HAVE (1) JACK STUD & (1) KING STUD EACH SIDE (U.N.O.)
- SN-3 ALL HEADERS w/ UPLIFT TO BE STRAPPED DOWN @ EACH SIDE WITH (1) LSTA24, 14-104 @ TOP & BOTTOM OF WALL. WRAP UNDER BOTTOM PLATE & OVER TOP PLATE 1/2" X 10" ANCHOR BOLT w/ 3" X 3" X 1/4" WASHER MUST BE LOCATED WITHIN 6" OF KING STUD @ ALL DOOR LOCATIONS (U.N.O.)
- SN-4 USE ONE JACK STUD GIRDER SUPPORT PER 2500 LB LOAD
- SN-5 DIMENSIONS ON STRUCTURAL SHEETS ARE NOT EXACT. REFER TO ARCHITECTURAL FLOOR PLAN FOR ACTUAL DIMENSIONS
- SN-6 PERMANENT TRUSS BRACING IS TO BE INSTALLED AT LOCATIONS AS SHOWN ON THE SEALED TRUSS DRAWINGS. LATERAL BRACING IS TO BE RESTRAINED PER BCSI-03, BCSI-B1, BCSI-B2, & BCSI-B3. BCSI-B1, BCSI-B2, & BCSI-B3 ARE FURNISHED BY THE TRUSS SUPPLIER, WITH THE SEALED TRUSS PACKAGE

## HEADER LEGEND



## ACTUAL vs REQUIRED SHEARWALL

	TRANSVERSE	LONGITUDINAL
ACTUAL	27466 LBF	21294 LBF
REQUIRED	13125 LBF	7380 LBF

CONNECTIONS, WALL, & HEADER DESIGN IS BASED ON REACTIONS & UPLIFTS FROM TRUSS ENGINEERING FURNISHED BY BUILDER. BUILDERS FIRST SOURCE JOB #2352916

Edgley Construction

Brenda Nelson Res.

PROJECT ADDRESS:  
Pinehurst Road  
Lake City, FL

DIMENSIONS  
Stated dimensions supersede scaled dimensions. Refer all questions to Mark Disosway, P.E. for resolution. Do not proceed without clarification.

COPYRIGHT AND PROPERTY RIGHTS:  
Mark Disosway, P.E. hereby expressly reserves its common law copyrights and property right in these instruments of service. This document is not to be reproduced, altered or copied in any form or manner without first the express written permission an consent of Mark Disosway.

CERTIFICATION: I hereby certify that I have examined this plan, and that the applicable portions of the plan, relating to wind engineering comply with the 6th Edition Florida Building Code-Residential (2017) to the best of my knowledge.

LIMITATION: This design is valid for one building, at specified location.

MARI DISOSWAY P.E. 53915



Mark Disosway P.E.  
163 SW Midtown Place  
Suite 103  
Lake City, Florida 32025  
386.754.5419  
disoswaydesign@gmail.com

JOB NUMBER:  
200430

S-3

OF 6 SHEETS