

FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name: Lot 41 Jewel Lake II Street: City, State, Zip: Lake City, FL, 32025 Owner: Design Location: FL, Gainesville	Builder Name: Century CMP Florida Permit Office: Columbia County Permit Number: Jurisdiction: County: Columbia (Florida Climate Zone 2)
---	---

<table style="width:100%;"> <tr> <td style="width:30%;">1. New construction or existing</td> <td style="width:70%;">New (From Plans)</td> </tr> <tr> <td>2. Single family or multiple family</td> <td>Detached</td> </tr> <tr> <td>3. Number of units, if multiple family</td> <td>1</td> </tr> <tr> <td>4. Number of Bedrooms</td> <td>4</td> </tr> <tr> <td>5. Is this a worst case?</td> <td>No</td> </tr> <tr> <td>6. Conditioned floor area above grade (ft²)</td> <td>1607</td> </tr> <tr> <td>Conditioned floor area below grade (ft²)</td> <td>0</td> </tr> <tr> <td>7. Windows (153.3 sqft.)</td> <td> <table style="width:100%;"> <tr> <th style="width:40%;">Description</th> <th style="width:60%;">Area</th> </tr> <tr> <td>a. U-Factor: Dbl, U=0.36</td> <td>153.33 ft²</td> </tr> <tr> <td>SHGC: SHGC=0.25</td> <td></td> </tr> <tr> <td>b. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td>SHGC:</td> <td></td> </tr> <tr> <td>c. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td>SHGC:</td> <td></td> </tr> <tr> <td>Area Weighted Average Overhang Depth:</td> <td>3.141 ft.</td> </tr> <tr> <td>Area Weighted Average SHGC:</td> <td>0.250</td> </tr> </table> </td> </tr> <tr> <td>8. Skylights</td> <td>Area</td> </tr> <tr> <td>c. U-Factor (AVG): N/A</td> <td>ft²</td> </tr> <tr> <td>SHGC (AVG): N/A</td> <td></td> </tr> <tr> <td>9. Floor Types (1607.0 sqft.)</td> <td> <table style="width:100%;"> <tr> <th style="width:30%;">Insulation</th> <th style="width:70%;">Area</th> </tr> <tr> <td>a. Slab-On-Grade Edge Insulation</td> <td>R=0.0 1607.00 ft²</td> </tr> <tr> <td>b. N/A</td> <td>R= ft²</td> </tr> <tr> <td>c. N/A</td> <td>R= ft²</td> </tr> </table> </td> </tr> </table>	1. New construction or existing	New (From Plans)	2. Single family or multiple family	Detached	3. Number of units, if multiple family	1	4. Number of Bedrooms	4	5. Is this a worst case?	No	6. Conditioned floor area above grade (ft²)	1607	Conditioned floor area below grade (ft²)	0	7. Windows (153.3 sqft.)	<table style="width:100%;"> <tr> <th style="width:40%;">Description</th> <th style="width:60%;">Area</th> </tr> <tr> <td>a. U-Factor: Dbl, U=0.36</td> <td>153.33 ft²</td> </tr> <tr> <td>SHGC: SHGC=0.25</td> <td></td> </tr> <tr> <td>b. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td>SHGC:</td> <td></td> </tr> <tr> <td>c. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td>SHGC:</td> <td></td> </tr> <tr> <td>Area Weighted Average Overhang Depth:</td> <td>3.141 ft.</td> </tr> <tr> <td>Area Weighted Average SHGC:</td> <td>0.250</td> </tr> </table>	Description	Area	a. U-Factor: Dbl, U=0.36	153.33 ft²	SHGC: SHGC=0.25		b. U-Factor: N/A	ft²	SHGC:		c. U-Factor: N/A	ft²	SHGC:		Area Weighted Average Overhang Depth:	3.141 ft.	Area Weighted Average SHGC:	0.250	8. Skylights	Area	c. U-Factor (AVG): N/A	ft²	SHGC (AVG): N/A		9. Floor Types (1607.0 sqft.)	<table style="width:100%;"> <tr> <th style="width:30%;">Insulation</th> <th style="width:70%;">Area</th> </tr> <tr> <td>a. Slab-On-Grade Edge Insulation</td> <td>R=0.0 1607.00 ft²</td> </tr> <tr> <td>b. N/A</td> <td>R= ft²</td> </tr> <tr> <td>c. N/A</td> <td>R= ft²</td> </tr> </table>	Insulation	Area	a. Slab-On-Grade Edge Insulation	R=0.0 1607.00 ft²	b. N/A	R= ft²	c. N/A	R= ft²	<table style="width:100%;"> <tr> <td style="width:30%;">10. Wall Types (1464.0 sqft.)</td> <td style="width:40%;">Insulation</td> <td style="width:30%;">Area</td> </tr> <tr> <td>a. Frame - Wood, Exterior</td> <td>R=13.0</td> <td>1162.70 ft²</td> </tr> <tr> <td>b. Frame - Wood, Adjacent</td> <td>R=13.0</td> <td>301.33 ft²</td> </tr> <tr> <td>c. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>d. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>11. Ceiling Types (1687.0 sqft.)</td> <td>Insulation</td> <td>Area</td> </tr> <tr> <td>a. Under Attic (Vented)</td> <td>R=38.0</td> <td>1687.00 ft²</td> </tr> <tr> <td>b. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>c. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>12. Ducts</td> <td>R</td> <td>ft²</td> </tr> <tr> <td>a. Sup: Attic, Ret: Attic, AH: Main</td> <td>6</td> <td>401.75</td> </tr> <tr> <td>13. Cooling systems</td> <td>kBtu/hr</td> <td>Efficiency</td> </tr> <tr> <td>a. Central Unit</td> <td>19.3</td> <td>SEER: 15.00</td> </tr> <tr> <td>14. Heating systems</td> <td>kBtu/hr</td> <td>Efficiency</td> </tr> <tr> <td>a. Electric Heat Pump</td> <td>24.2</td> <td>HSPF: 8.20</td> </tr> <tr> <td>15. Hot water systems</td> <td></td> <td></td> </tr> <tr> <td>a. Electric</td> <td></td> <td>Cap: 50 gallons</td> </tr> <tr> <td></td> <td></td> <td>EF: 0.920</td> </tr> <tr> <td>b. Conservation features</td> <td></td> <td></td> </tr> <tr> <td>None</td> <td></td> <td></td> </tr> <tr> <td>16. Credits</td> <td></td> <td>CV, Pstat</td> </tr> </table>	10. Wall Types (1464.0 sqft.)	Insulation	Area	a. Frame - Wood, Exterior	R=13.0	1162.70 ft²	b. Frame - Wood, Adjacent	R=13.0	301.33 ft²	c. N/A	R=	ft²	d. N/A	R=	ft²	11. Ceiling Types (1687.0 sqft.)	Insulation	Area	a. Under Attic (Vented)	R=38.0	1687.00 ft²	b. N/A	R=	ft²	c. N/A	R=	ft²	12. Ducts	R	ft²	a. Sup: Attic, Ret: Attic, AH: Main	6	401.75	13. Cooling systems	kBtu/hr	Efficiency	a. Central Unit	19.3	SEER: 15.00	14. Heating systems	kBtu/hr	Efficiency	a. Electric Heat Pump	24.2	HSPF: 8.20	15. Hot water systems			a. Electric		Cap: 50 gallons			EF: 0.920	b. Conservation features			None			16. Credits		CV, Pstat
1. New construction or existing	New (From Plans)																																																																																																																	
2. Single family or multiple family	Detached																																																																																																																	
3. Number of units, if multiple family	1																																																																																																																	
4. Number of Bedrooms	4																																																																																																																	
5. Is this a worst case?	No																																																																																																																	
6. Conditioned floor area above grade (ft²)	1607																																																																																																																	
Conditioned floor area below grade (ft²)	0																																																																																																																	
7. Windows (153.3 sqft.)	<table style="width:100%;"> <tr> <th style="width:40%;">Description</th> <th style="width:60%;">Area</th> </tr> <tr> <td>a. U-Factor: Dbl, U=0.36</td> <td>153.33 ft²</td> </tr> <tr> <td>SHGC: SHGC=0.25</td> <td></td> </tr> <tr> <td>b. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td>SHGC:</td> <td></td> </tr> <tr> <td>c. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td>SHGC:</td> <td></td> </tr> <tr> <td>Area Weighted Average Overhang Depth:</td> <td>3.141 ft.</td> </tr> <tr> <td>Area Weighted Average SHGC:</td> <td>0.250</td> </tr> </table>	Description	Area	a. U-Factor: Dbl, U=0.36	153.33 ft²	SHGC: SHGC=0.25		b. U-Factor: N/A	ft²	SHGC:		c. U-Factor: N/A	ft²	SHGC:		Area Weighted Average Overhang Depth:	3.141 ft.	Area Weighted Average SHGC:	0.250																																																																																															
Description	Area																																																																																																																	
a. U-Factor: Dbl, U=0.36	153.33 ft²																																																																																																																	
SHGC: SHGC=0.25																																																																																																																		
b. U-Factor: N/A	ft²																																																																																																																	
SHGC:																																																																																																																		
c. U-Factor: N/A	ft²																																																																																																																	
SHGC:																																																																																																																		
Area Weighted Average Overhang Depth:	3.141 ft.																																																																																																																	
Area Weighted Average SHGC:	0.250																																																																																																																	
8. Skylights	Area																																																																																																																	
c. U-Factor (AVG): N/A	ft²																																																																																																																	
SHGC (AVG): N/A																																																																																																																		
9. Floor Types (1607.0 sqft.)	<table style="width:100%;"> <tr> <th style="width:30%;">Insulation</th> <th style="width:70%;">Area</th> </tr> <tr> <td>a. Slab-On-Grade Edge Insulation</td> <td>R=0.0 1607.00 ft²</td> </tr> <tr> <td>b. N/A</td> <td>R= ft²</td> </tr> <tr> <td>c. N/A</td> <td>R= ft²</td> </tr> </table>	Insulation	Area	a. Slab-On-Grade Edge Insulation	R=0.0 1607.00 ft²	b. N/A	R= ft²	c. N/A	R= ft²																																																																																																									
Insulation	Area																																																																																																																	
a. Slab-On-Grade Edge Insulation	R=0.0 1607.00 ft²																																																																																																																	
b. N/A	R= ft²																																																																																																																	
c. N/A	R= ft²																																																																																																																	
10. Wall Types (1464.0 sqft.)	Insulation	Area																																																																																																																
a. Frame - Wood, Exterior	R=13.0	1162.70 ft²																																																																																																																
b. Frame - Wood, Adjacent	R=13.0	301.33 ft²																																																																																																																
c. N/A	R=	ft²																																																																																																																
d. N/A	R=	ft²																																																																																																																
11. Ceiling Types (1687.0 sqft.)	Insulation	Area																																																																																																																
a. Under Attic (Vented)	R=38.0	1687.00 ft²																																																																																																																
b. N/A	R=	ft²																																																																																																																
c. N/A	R=	ft²																																																																																																																
12. Ducts	R	ft²																																																																																																																
a. Sup: Attic, Ret: Attic, AH: Main	6	401.75																																																																																																																
13. Cooling systems	kBtu/hr	Efficiency																																																																																																																
a. Central Unit	19.3	SEER: 15.00																																																																																																																
14. Heating systems	kBtu/hr	Efficiency																																																																																																																
a. Electric Heat Pump	24.2	HSPF: 8.20																																																																																																																
15. Hot water systems																																																																																																																		
a. Electric		Cap: 50 gallons																																																																																																																
		EF: 0.920																																																																																																																
b. Conservation features																																																																																																																		
None																																																																																																																		
16. Credits		CV, Pstat																																																																																																																

Glass/Floor Area: 0.095	Total Proposed Modified Loads: 40.57	PASS
	Total Baseline Loads: 41.36	

I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code. PREPARED BY: _____ DATE: 3 / 10 / 2022 I hereby certify that this building, as designed, is in compliance with the Florida Energy Code. OWNER/AGENT: _____ DATE: _____	Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes. BUILDING OFFICIAL: _____ DATE: _____
--	--

- Compliance requires certification by the air handler unit manufacturer that the air handler enclosure qualifies as certified factory-sealed in accordance with R403.3.2.1.
- Compliance requires an Air Barrier and Insulation Inspection Checklist in accordance with R402.4.1.1 and this project requires an envelope leakage test report with envelope leakage no greater than 5.00 ACH50 (R402.4.1.2).

INPUT SUMMARY CHECKLIST REPORT

PROJECT

Title:	Lot 41 Jewel Lake II	Bedrooms:	4	Address Type:	Lot Information
Building Type:	User	Conditioned Area:	1607	Lot #	41
Owner Name:		Total Stories:	1	Block/Subdivision:	Jewel Lake II
# of Units:	1	Worst Case:	No	PlatBook:	
Builder Name:	Century CMP Florida	Rotate Angle:	0	Street:	
Permit Office:	Columbia County	Cross Ventilation:	Yes	County:	Columbia
Jurisdiction:		Whole House Fan:	No	City, State, Zip:	Lake City , FL , 32025
Family Type:	Detached				
New/Existing:	New (From Plans)				
Comment:					

CLIMATE

✓	Design Location	TMY Site	Design Temp		Int Design Temp		Heating	Design	Daily Temp
			97.5 %	2.5 %	Winter	Summer	Degree Days	Moisture	Range
_____	FL, Gainesville	FL_GAINESVILLE_REGI	32	92	70	75	1305.5	51	Medium

BLOCKS

Number	Name	Area	Volume
1	Block1	1607	12856

SPACES

Number	Name	Area	Volume	Kitchen	Occupants	Bedrooms	Infil ID	Finished	Cooled	Heated
1	Main	1607	12856	Yes	8	4	1	Yes	Yes	Yes

FLOORS

✓	#	Floor Type	Space	Perimeter	R-Value	Area		Tile	Wood	Carpet
_____	1	Slab-On-Grade Edge Insulation	Main	183.33 ft	0	1607 ft²	----	0	0	1

ROOF

✓	#	Type	Materials	Roof Area	Gable Area	Roof Color	Rad Barr	Solar Absor.	SA Tested	Emitt	Emitt Tested	Deck Insul.	Pitch (deg)
_____	1	Hip	Composition shingles	1797 ft²	0 ft²	Medium	Y	0.96	No	0.9	No	0	26.57

ATTIC

✓	#	Type	Ventilation	Vent Ratio (1 in)	Area	RBS	IRCC
_____	1	Full attic	Vented	300	1607 ft²	Y	N

CEILING

✓	#	Ceiling Type	Space	R-Value	Ins Type	Area	Framing Frac	Truss Type
_____	1	Under Attic (Vented)	Main	38	Double Batt	1687 ft²	0.11	Wood

INPUT SUMMARY CHECKLIST REPORT

WALLS

✓ #	Ornt	Adjacent To	Wall Type	Space	Cavity R-Value	Width Ft	In	Height Ft	In	Area	Sheathing R-Value	Framing Fraction	Solar Absor.	Below Grade%
1	SW	Exterior	Frame - Wood	Main	13	17	8	8		141.3 ft²		0.23	0.75	0
2	SE	Garage	Frame - Wood	Main	13	18		8		144.0 ft²		0.23	0.75	0
3	SW	Garage	Frame - Wood	Main	13	19	8	8		157.3 ft²		0.23	0.75	0
4	SE	Exterior	Frame - Wood	Main	13	36		8		288.0 ft²		0.23	0.75	0
5	NE	Exterior	Frame - Wood	Main	13	28	8	8		229.3 ft²		0.23	0.75	0
6	NW	Exterior	Frame - Wood	Main	13	8		8		64.0 ft²		0.23	0.75	0
7	NE	Exterior	Frame - Wood	Main	13	9		8		72.0 ft²		0.23	0.75	0
8	NW	Exterior	Frame - Wood	Main	13	46		8		368.0 ft²		0.23	0.75	0

DOORS

✓ #	Ornt	Door Type	Space	Storms	U-Value	Width Ft	In	Height Ft	In	Area
1	E	Insulated	Main	None	.46	3		6	8	20 ft²
2	N	Insulated	Main	None	.46	2	8	6	8	17.8 ft²

WINDOWS

Orientation shown is the entered, Proposed orientation.

✓ #	Ornt	Wall ID	Frame	Panes	NFRC	U-Factor	SHGC	Imp	Area	Overhang Depth	Separation	Int Shade	Screening
1	SW	1	Vinyl	Low-E Double	Yes	0.36	0.25	N	30.0 ft²	1 ft 0 in	3 ft 0 in	None	None
2	SE	4	Vinyl	Low-E Double	Yes	0.36	0.25	N	15.0 ft²	1 ft 6 in	1 ft 0 in	None	None
3	NE	5	Vinyl	Low-E Double	Yes	0.36	0.25	N	60.0 ft²	1 ft 6 in	1 ft 0 in	None	None
4	NE	7	Metal	Low-E Double	Yes	0.36	0.25	N	33.3 ft²	9 ft 6 in	1 ft 0 in	None	None
5	NW	8	Vinyl	Low-E Double	Yes	0.36	0.25	N	15.0 ft²	1 ft 6 in	1 ft 0 in	None	None

GARAGE

✓ #	Floor Area	Ceiling Area	Exposed Wall Perimeter	Avg. Wall Height	Exposed Wall Insulation
1	396.435 ft²	396.435 ft²	42.2 ft	8 ft	1

INFILTRATION

#	Scope	Method	SLA	CFM 50	ELA	EqLA	ACH	ACH 50
1	Wholehouse	Proposed ACH(50)	.000254	1071.3	58.78	110.35	.098	5

HEATING SYSTEM

✓ #	System Type	Subtype	Speed	Efficiency	Capacity	Block	Ducts
1	Electric Heat Pump/	None	Single	HSPF:8.2	24.16 kBtu/hr	1	sys#1

INPUT SUMMARY CHECKLIST REPORT

COOLING SYSTEM																								
✓	#	System Type	Subtype	Subtype	Efficiency	Capacity	Air Flow	SHR	Block	Ducts														
_____	1	Central Unit/	None	Single	SEER: 15	19.3 kBtu/hr	570 cfm	0.7	1	sys#1														
HOT WATER SYSTEM																								
✓	#	System Type	SubType	Location	EF	Cap	Use	SetPnt	Conservation															
_____	1	Electric	None	Main	0.92	50 gal	40 gal	120 deg	None															
SOLAR HOT WATER SYSTEM																								
✓	FSEC Cert #	CompanyName	System Model#		Collector Model#		Collector Area	Storage Volume	FEF															
_____	None	None					ft²																	
DUCTS																								
✓	#	--- Supply ---		--- Return ---		LeakageType		Air Handler	CFM 25 TOT	CFM25 OUT	QN	RLF	HVAC # Heat Cool											
_____	1	Attic	6	401.75 f	Attic	80.35 ft²	Default Leakage	Main	(Default) c	(Default) c			1	1										
TEMPERATURES																								
ProgramableThermostat: Y					Ceiling Fans:																			
Cooling Heating Venting	☐ Jan ☒ Jan ☐ Jan	☐ Feb ☒ Feb ☐ Feb	☐ Mar ☒ Mar ☐ Mar	☐ Apr ☒ Apr ☐ Apr	☐ May ☐ May ☐ May	☒ Jun ☐ Jun ☐ Jun	☒ Jul ☐ Jul ☐ Jul	☒ Aug ☐ Aug ☐ Aug	☒ Sep ☐ Sep ☐ Sep	☐ Oct ☒ Oct ☐ Oct	☐ Nov ☒ Nov ☐ Nov	☐ Dec ☒ Dec ☐ Dec												
Thermostat Schedule: HERS 2006 Reference																								
Schedule Type	1		2		3		4		5		6		7		8		9		10		11		12	
Cooling (WD)	AM PM	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80	78 80
Cooling (WEH)	AM PM	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78
Heating (WD)	AM PM	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68
Heating (WEH)	AM PM	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68	66 68
MASS																								
Mass Type			Area			Thickness			Furniture Fraction			Space												
Default(8 lbs/sq.ft.)			0 ft²			0 ft			0.3			Main												

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE INDEX* = 98

The lower the EnergyPerformance Index, the more efficient the home.

, Lake City, FL, 32025

1. New construction or existing	New (From Plans)		10. Wall Type and Insulation	Insulation	Area
2. Single family or multiple family	Detached		a. Frame - Wood, Exterior	R=13.0	1162.70 ft ²
3. Number of units, if multiple family	1		b. Frame - Wood, Adjacent	R=13.0	301.33 ft ²
4. Number of Bedrooms	4		c. N/A	R=	ft ²
5. Is this a worst case?	No		d. N/A	R=	ft ²
6. Conditioned floor area (ft ²)	1607		11. Ceiling Type and insulation level	Insulation	Area
7. Windows**	Description	Area	a. Under Attic (Vented)	R=38.0	1687.00 ft ²
a. U-Factor:	Dbl, U=0.36	153.33 ft ²	b. N/A	R=	ft ²
SHGC:	SHGC=0.25		c. N/A	R=	ft ²
b. U-Factor:	N/A	ft ²	12. Ducts, location & insulation level	R	ft ²
SHGC:			a. Sup: Attic, Ret: Attic, AH: Main	6	401.75
c. U-Factor:	N/A	ft ²	13. Cooling systems	kBtu/hr	Efficiency
SHGC:			a. Central Unit	19.3	SEER:15.00
d. U-Factor:	N/A	ft ²	14. Heating systems	kBtu/hr	Efficiency
SHGC:			a. Electric Heat Pump	24.2	HSPF:8.20
Area Weighted Average Overhang Depth:	3.141 ft.		15. Hot water systems		
Area Weighted Average SHGC:	0.250		a. Electric	Cap: 50 gallons	
8. Skylights	Description	Area		EF: 0.92	
a. U-Factor(AVG):	N/A	ft ²	b. Conservation features		
SHGC(AVG):	N/A		None		
9. Floor Types	Insulation	Area	Credits (Performance method)		CV, Pstat
a. Slab-On-Grade Edge Insulation	R=0.0	1607.00 ft ²			
b. N/A	R=	ft ²			
c. N/A	R=	ft ²			

I certify that this home has complied with the Florida Energy Efficiency Code for Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature: Brittany Dunn Date: _____

Address of New Home: _____ City/FL Zip: _____



*Note: This is not a Building Energy Rating. If your Index is below 70, your home may qualify for energy efficient mortgage (EEM) incentives if you obtain a Florida Energy Rating. For information about the Florida Building Code, Energy Conservation, contact the Florida Building Commission's support staff.

**Label required by Section R303.1.3 of the Florida Building Code, Energy Conservation, if not DEFAULT.