

COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST

MINIMUM PLAN REQUIREMENTS: FLORIDA BUILDING CODE RESIDENTIAL 2014 EFFECTIVE 1 JULY 2015 AND THE NATIONAL ELECTRICAL CODE 2011 EFFECTIVE 1 JULY 2015

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE WITH THE CURRENT 2014 FLORIDA BUILDING CODES RESIDENTIAL, EFFECTIVE 1 JULY 2015. NATIONAL ELECTRICAL CODE 2011 EFFECTIVE 1 JULY 2015. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FLORIDA BUILDING CODE FIGURE 1609-A
THROUGH 1609-C ULTIMATE DESIGN WIND SPEEDS FOR RISK CATEGORY AND BUILDINGS AND OTHER STRUCTURES
Revised 12/2016

GENERAL REQUIREMENTS:

APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

		Select From the Dropbox		
1	Two (2) complete sets of plans containing the following:	- Ues		
2	All drawings must be clear, concise, drawn to scale, details that are not used shall be marked void	-1110		
3	Condition space (Sq. Ft.) 1407 Sq. Total (Sq. Ft.) under roof 1927 59	YES NO N/A		
_	ft. fL			
De	signers name and signature shall be on all documents and a licensed architect or engineer, signature an	nd official embossed seal shal		
	affixed to the plans and documents as per the FLORIDA BUILDING CODES RESIDENTIAL R101.	2.1		
Si	te Plan information including:			
4	Dimensions of lot or parcel of land	- 185		
	Dimensions of all building set backs	- ves		
6	Location of all other structures (include square footage of structures) on parcel, existing or proposed			
	well and septic tank and all utility easements.	- Yes		
7	Provide a full legal description of property.	-1100		
W	ind-load Engineering Summary, calculations and any details are required.			
	GENERAL REQUIREMENTS:	Items to Include-		
The party	APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each Box shall be		
N.		Marked as		
18.0		Applicable		
8	Plans or specifications must show compliance with FBCR Chapter 3	(YES) NO N/A		
		Select From the Dropbox		
9	Basic wind speed (3-second gust), miles per hour	Select From the Dropbox		
9	(Wind exposure – if more than one wind exposure	- UPS		
10	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated)			
	(Wind exposure – if more than one wind exposure	- UPS		
10 11	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated) Wind importance factor and nature of occupancy	- UPS		
10	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated) Wind importance factor and nature of occupancy The applicable internal pressure coefficient, Components and Cladding	- UPS		
10 11 12	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated) Wind importance factor and nature of occupancy The applicable internal pressure coefficient, Components and Cladding The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component,	- UPS		
10	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated) Wind importance factor and nature of occupancy The applicable internal pressure coefficient, Components and Cladding	- UPS		
10 11 12 13	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated) Wind importance factor and nature of occupancy The applicable internal pressure coefficient, Components and Cladding The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component,	- yes - yes - yes		
10 11 12 13	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated) Wind importance factor and nature of occupancy The applicable internal pressure coefficient, Components and Cladding The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component, cladding materials not specifally designed by the registered design professional.	- yes - yes - yes - yes		
10 11 12 13 Ele	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated) Wind importance factor and nature of occupancy The applicable internal pressure coefficient, Components and Cladding The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component, cladding materials not specifally designed by the registered design professional.	- yes - yes - yes - yes - yes		
10 11 12 13 Ele	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated) Wind importance factor and nature of occupancy The applicable internal pressure coefficient, Components and Cladding The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component, cladding materials not specifally designed by the registered design professional. vations Drawing including: All side views of the structure Roof pitch	- yes - yes - yes - yes - yes - yes		
10 11 12 13 Ele 14 15	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated) Wind importance factor and nature of occupancy The applicable internal pressure coefficient, Components and Cladding The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component, cladding materials not specifally designed by the registered design professional. vations Drawing including: All side views of the structure	- yes - yes - yes - yes - yes		
10 11 12 13 Ele 14 15 16	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated) Wind importance factor and nature of occupancy The applicable internal pressure coefficient, Components and Cladding The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component, cladding materials not specifally designed by the registered design professional. vations Drawing including: All side views of the structure Roof pitch Overhang dimensions and detail with attic ventilation Location, size and height above roof of chimneys	- 4PS - 4PS - 4PS - 4PS - 4PS - 4PS - 4PS - 4PS		
10 11 12 13 Ele 14 15 16 17	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated) Wind importance factor and nature of occupancy The applicable internal pressure coefficient, Components and Cladding The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component, cladding materials not specifally designed by the registered design professional. vations Drawing including: All side views of the structure Roof pitch Overhang dimensions and detail with attic ventilation	- yes		
10 11 12 13 Ele 14 15 16 17 18	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated) Wind importance factor and nature of occupancy The applicable internal pressure coefficient, Components and Cladding The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component, cladding materials not specifally designed by the registered design professional. vations Drawing including: All side views of the structure Roof pitch Overhang dimensions and detail with attic ventilation Location, size and height above roof of chimneys Location and size of skylights with Florida Product Approval	- 485 - 485 - 485 - 485 - 485 - 485 - 485 - 485		

Items to Include-Each Box shall be

Marked as

Applicable

Floor Plan including: Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, deck, Hec 20 21 Raised floor surfaces located more than 30 inches above the floor or grade 22 All exterior and interior shear walls indicated 23 Shear wall opening shown (Windows, Doors and Garage doors) Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each bedroom (net clear opening shown) and Show compliance with Section FBC 1405.13.2 where the opening of an operable window is located more than 72 inches above the finished grade or surface below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above the finished floor of the room in which the window is located. Glazing between the floor and 24 inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass. Safety glazing of glass where needed nla Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth 75 26 (see chapter 10 and chapter 24 of FBCR) 27 Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails Identify accessibility of bathroom (see FBCR SECTION 320) All materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida product approval number and mfg. installation information submitted with the plans (see Florida product approval form) GENERAL REQUIREMENTS: Items to Include-APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL Each Box shall be Marked as Applicable YES / NO / N/A FBCR 403: Foundation Plans Select From the Dropbox 29 Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size Lies and type of reinforcing. Ués 30 All posts and/or column footing including size and reinforcing 31 Any special support required by soil analysis such as piling. 32 Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Ma Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 FBCR 506: CONCRETE SLAB ON GRADE 34 Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) 35 Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports FBCR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered URS 36 termiticides FBCR 606: Masonry Walls and Stem walls (load bearing & shear Walls) 37 Show all materials making up walls, wall height, and Block size, mortar type 38 Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement Metal frame shear wall and roof systems shall be designed, signed and sealed by Florida Prof. Engineer or Architect Floor Framing System: First and/or second story Floor truss package shall including layout and details, signed and sealed by Florida Registered - UPS

Professional Engineer

	Show conventional floor joist type, size, span, spacing and attachment to load bearing walls,	- ues
40	stem walls and/or priers	
41 42	Girder type, size and spacing to load bearing walls, stem wall and/or priers Attachment of joist to girder	- 1162
13		1 - yes
4	Show required under-floor crawl space	- UP
5	Show required amount of ventilation opening for under-floor spaces	- hia
6	Show required covering of ventilation opening	- ma
7	Show the required access opening to access to under-floor spaces	- Ma
Ť	Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges &	
8	intermediate of the areas structural panel sheathing	- yes
9	Show Draftstopping, Fire caulking and Fire blocking	- U-es
0	Show fireproofing requirements for garages attached to living spaces, per FBCR section 302.6	- U-PO
1	Provide live and dead load rating of floor framing systems (psf).	- Liex
Τ		YES / NO / N/A
B	CR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION	
	CENEDAL DECUMPARENTS.	Items to Include-
	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each Box shall be
	THE LEGITATION OF THE ATTEICABLE BUXES BEFORE SUBMITTAL	Marked as
100		Applicable
2		elect From the Dropbo
3	Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls Fastener schedule for structural members per table IRC 602.3 are to be shown	- 4-5
1		- yes
1	Show Wood structural panel's sheathing attachment to study, joist, trusses, rafters and structural	11100
	members, showing fastener schedule attachment on the edges & intermediate of the areas structural panel sheathing	- yes
	Show all required connectors with a max uplift rating and required number of connectors and	
5	oc spacing for continuous connection of structural walls to foundation and roof trusses or rafter systems	-yes
5	Show sizes, type, span lengths and required number of support jack studs, king studs for shear wall opening and girder or header per IRC Table 502.5 (1)	- 4-85
7	Indicate where pressure treated wood will be placed	-11-65
1	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural	
8	panel sheathing edges & intermediate areas	- yes
)	A detail showing gable truss bracing, wall balloon framing details or/ and wall hinge bracing detail	- hes
В	CR :ROOF SYSTEMS:	
	Truss design drawing shall meet section FBCR 802.1.6.1 Wood trusses	- Ues
1	Include a layout and truss details, signed and sealed by Florida Professional Engineer	- 1128
	Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters	- 400
	Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details	- 118
	Provide dead load rating of trusses	- 425
B	CR 802:Conventional Roof Framing Layout	
	Rafter and ridge beams sizes, span, species and spacing	1.00
+	Connectors to wall assemblies' include assemblies' resistance to uplift rating	- 400
	Valley framing and support details	1100
-	Provide dead load rating of rafter system	- 25
		- 123
	CR 803 ROOF SHEATHING	
T	Include all materials which will make up the roof decking, identification of structural panel	1.00
	sheathing, grade, thickness	- UPS
	Show fastener Size and schedule for structural panel sheathing on the edges & intermediate areas	- URS
	OF ASSEMBLIES FRC Chapter 9	
	Include all materials which will make up the roof assembles covering	- 4-6
	Submit Florida Product Approval numbers for each component of the roof assembles covering	- 491
	TI TOTAL TOTAL OF THE TOTAL OF THE TOTAL BUTCHES OF THE TOTAL BUTCHES	

FBCR Chapter 11 Energy Efficiency Code for residential building

Residential construction shall comply with this code by using the following compliance methods in the FBCR chapter 11 Residential buildings compliance methods. Two of the required forms are to be submitted, N1100.1.1.1 As an alternative to the computerized Compliance Method A, the Alternate Residential Point System Method hand calculation, Alternate Form 600A, may be used. All requirements specific to this calculation are located in Sub appendix C to Appendix G. Buildings complying by this alternative shall meet all mandatory requirements of this chapter. Computerized versions of the Alternate Residential Point System Method shall not be acceptable for code compliance.

YES / NO / N/A

	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to Include- Each Box shall be Marked as Applicable
7 2		Select From the Dropbox
73	Show the insulation R value for the following areas of the structure	- 1163
74	Attic space	- UPS
75	Exterior wall cavity Crawl space	- Wes
	2011 2010 N	I - WI-Ze
	VAC information	
77		- UES
78	Exhaust fans shown in bathrooms Mechanical exhaust capacity of 50 cfm intermittent or 20 cfm continuous required	- 425
79	Show clothes dryer route and total run of exhaust duct	- 425
Pl ₁ 80 81	All fixtures waste water lines shall be shown on the foundation plan Show the location of water heater	- Cles
	ivate Potable Water Pump motor horse power	-
83	Reservoir pressure tank gallon capacity	E E
84	Rating of cycle stop valve if used	-
E16	Show Switches, receptacles outlets, lighting fixtures and Ceiling fans	I - Ues I
86	Show all 120-volt, single phase, 15- and 20-ampere branch circuits outlets required to be protected	
	by Ground-Fault Circuit Interrupter (GFCI) Article 210.8 A	- 4-6
87	Show the location of smoke detectors & Carbon monoxide detectors	- 447
88	Show service panel, sub-panel, location(s) and total ampere ratings	- 422
89	On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type.	- 4.65
	For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an Grounding electrode system. Per the National Electrical Code article 250.52.3	
90	Appliances and HVAC equipment and disconnects	- N+7
91	Show all 120-volt, single phase, 15- and 20-ampere branch circuits supplying outlets installed in dwelling unit family rooms, dining rooms, living rooms, parlors, libraries, dens, bedrooms, sunrooms, recreation rooms, closets, hallways, or similar rooms or areas shall be protected by a listed Combination arc-fault circuit interrupter , Protection device.	- 4-es

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

Items to Include-Each Box shall be Circled as Applicable

THE FOLLOWING ITEMS MUST BE SUBMITTED WITH BUILDING PLANS

		YES	NO	N/A
92	Building Permit Application A current Building Permit Application is to be completed, by following the Checklist all supporting documents must be submitted. There is a \$15.00 application fee. The completed application with attached documents and application fee can be mailed.	NO		
93	Parcel Number The parcel number (Tax ID number) from the Property Appraisers Office (386) 758-1083 is required. A copy of property deed is also required. www.columbiacountyfla.com	NO	ye.	3
94	Town of Fort White (386) 497-2321 If the parcel in the application for building permit is within the Corporate city limits of Fort White, an approval land use development letter issued by the Town of Fort is required to be submitted with the application for a building permit.	NO	1	
***	BELOW ITEMS ONLY NEEDED AFTER ZONING APPROVAL HAS GIVEN.	****	***	***
95	Environmental Health Permit or Sewer Tap Approval A copy of a approved Columbia County Environmental Health (386) 758-1058	NO	yes	?
96	City of Lake City A City Water and/or Sewer letter. Call 386-752-2031	NO		1
97	Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers shall require permitting through the Suwannee River Water Management District, before submitting a application to this office. Any project located within a flood zone where the base flood elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the Columbia County Land Development Regulations. Any project located within a flood zone where the base flood elevation has not been established (Zone A) shall meet the requirements of Section 8.5.3 of the Columbia County Land Development Regulations	NO		
98	CERTIFIED FINISHED FLOOR ELEVATIONS will be required on any project where the approved FIRM Flood Maps show the property is in a AE, Floodway, and AH flood zones. Additionally One Foot Rise letters are required for AE and AH zones. In the Floodway Flood zones a Zero Rise letter is required.			
99	A Flood development permit is also required for AE, Floodway & AH. Development permit cost is \$50.00			
100	Driveway Connection: If the property does not have an existing access to a public road, then an application for a culvert permit (\$25.00) must be made. County Public Works Dept. determines the size and length of every culvert before instillation and completes a final inspection before permanent power is granted. If the applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00) Separate Check when issued. If the project is to be located on an F.D.O.T. maintained road, then an F.D.O.T. access permit is required.	NO		
101	911 Address: An application for a 911address must be applied for and received through the Columbia County Emergency Management Office of 911 Addressing Department (386) 758-1125.	NO		

TOILET FACILITIES SHALL BE PROVIDED FOR ALL CONSTRUCTION SITES. NO

<u>Disclosure Statement for Owner Builders</u> If you as the applicant will be acting as an owner/builder under section 489.103(7) of the Florida Statutes, submit the required owner builder disclosure statement form.

Notice Of Commencement

A notice of commencement form **recorded** in the Columbia County Clerk Office is required to be filed with the building department Before Any Inspections can be preformed.

Section R101.2.1 of the Florida Building Code Residential:

The provisions of Chapter 1, Florida Building Code shall govern the administration and enforcement of the Florida Building Code, Residential.