



Lumber design values are in accordance with ANSI/TPI 1 section 6.3  
These truss designs rely on lumber values established by others.

RE: 2544205 - IC CONST. - MCNUTT RES.

MiTek USA, Inc.

6904 Parke East Blvd.  
Tampa, FL 33610-4115

**Site Information:**

Customer Info: IC CONST. Project Name: McNutt Res. Model: Custom  
Lot/Block: N/A Subdivision: N/A  
Address: 952 SW Mandiva, N/A  
City: Columbia Cty State: FL

**Name Address and License # of Structural Engineer of Record, If there is one, for the building.**

Name: License #:  
Address:  
City: State:

**General Truss Engineering Criteria & Design Loads (Individual Truss Design Drawings Show Special Loading Conditions):**

Design Code: FBC2017/TPI2014 Design Program: MiTek 20/20 8.2  
Wind Code: ASCE 7-10 Wind Speed: 130 mph  
Roof Load: 37.0 psf Floor Load: N/A psf

This package includes 49 individual, Truss Design Drawings and 0 Additional Drawings.

With my seal affixed to this sheet, I hereby certify that I am the Truss Design Engineer and this index sheet conforms to 61G15-31.003, section 5 of the Florida Board of Professional Engineers Rules.


No.	Seal#	Truss Name	Date	No.	Seal#	Truss Name	Date
1	T21943132	CJ01	11/19/20	23	T21943154	T07	11/19/20
2	T21943133	CJ02	11/19/20	24	T21943155	T08	11/19/20
3	T21943134	CJ03	11/19/20	25	T21943156	T09	11/19/20
4	T21943135	CJ03A	11/19/20	26	T21943157	T10	11/19/20
5	T21943136	CJ04	11/19/20	27	T21943158	T11	11/19/20
6	T21943137	CJ05	11/19/20	28	T21943159	T12	11/19/20
7	T21943138	CJ05A	11/19/20	29	T21943160	T13	11/19/20
8	T21943139	CJ06	11/19/20	30	T21943161	T13G	11/19/20
9	T21943140	EJ01	11/19/20	31	T21943162	T14	11/19/20
10	T21943141	EJ02	11/19/20	32	T21943163	T15	11/19/20
11	T21943142	EJ03	11/19/20	33	T21943164	T16	11/19/20
12	T21943143	HJ09	11/19/20	34	T21943165	T17	11/19/20
13	T21943144	HJ10	11/19/20	35	T21943166	T17G	11/19/20
14	T21943145	PB01	11/19/20	36	T21943167	T18	11/19/20
15	T21943146	PB01G	11/19/20	37	T21943168	T19	11/19/20
16	T21943147	T01	11/19/20	38	T21943169	T20	11/19/20
17	T21943148	T01G	11/19/20	39	T21943170	T21	11/19/20
18	T21943149	T02	11/19/20	40	T21943171	T22	11/19/20
19	T21943150	T03	11/19/20	41	T21943172	T23	11/19/20
20	T21943151	T04	11/19/20	42	T21943173	T24	11/19/20
21	T21943152	T05G	11/19/20	43	T21943174	T25	11/19/20
22	T21943153	T06G	11/19/20	44	T21943175	T26	11/19/20

The truss drawing(s) referenced above have been prepared by MiTek USA, Inc. under my direct supervision based on the parameters provided by Builders FirstSource-Jacksonville.

Truss Design Engineer's Name: Lee, Julius

My license renewal date for the state of Florida is February 28, 2021.

**IMPORTANT NOTE:** The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020



RE: 2544205 - IC CONST. - MCNUTT RES.

MiTek USA, Inc.  
6904 Parke East Blvd.  
Tampa, FL 33610-4115

**Site Information:**

Customer Info: IC CONST. Project Name: McNutt Res. Model: Custom  
Lot/Block: N/A Subdivision: N/A  
Address: 952 SW Mandiva, N/A  
City: Columbia Cty State: FL

No.	Seal#	Truss Name	Date
45	T21943176	T27	11/19/20
46	T21943177	T28	11/19/20
47	T21943178	T29	11/19/20
48	T21943179	T30	11/19/20
49	T21943180	T30G	11/19/20

Job 2544205	Truss CJ01	Truss Type JACK-OPEN	Qty 4	Ply 1	IC CONST. - MCNUTT RES. Job Reference (optional)	T21943132
----------------	---------------	-------------------------	----------	----------	---	-----------

Builders FirstSource (Jacksonville, FL),

Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:22 2020 Page 1  
ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-jaPd3hmhKxarCtMjF3e7xEQ82RbnYzyfwmRWlyHgJh



Scale = 1:5.9




Plate Offsets (X,Y)-- [2:0-3-2,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.14	Vert(LL)	0.00	5	>999	240	MT20
TCDL 7.0	Lumber DOL	1.25	BC 0.02	Vert(CT)	-0.00	5	>999	180	244/190
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	2	n/a	n/a	
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MP						
								Weight: 6 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 1-2-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS.

(size) 2=0-3-8, 4=Mechanical  
Max Horz 2=38(LC 8)  
Max Uplift 2=-173(LC 8), 4=-16(LC 1)  
Max Grav 2=176(LC 1), 4=25(LC 16)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

#### NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4 except (jt=lb) 2=173.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**


Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610

Job 2544205	Truss CJ02	Truss Type Jack-Open	Qty 1	Ply 1	IC CONST. - MCNUTT RES. T21943133
Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,					

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:23 2020 Page 1  
ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-Bmz?G1nK5Eiiq1xwpm9MUSyGmrwlHQCo9WV\_2kyHgJg



Scale = 1:17.0

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.34	Vert(LL)	-0.00 4-5	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.11	Vert(CT)	-0.00 4-5	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.01 3	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MR					Weight: 12 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-2-9 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


#### REACTIONS.

(size) 5=0-3-0, 3=Mechanical, 4=Mechanical  
Max Horz 5=111(LC 12)  
Max Uplift 5=-50(LC 12), 3=-60(LC 12), 4=-15(LC 12)  
Max Grav 5=204(LC 1), 3=43(LC 19), 4=35(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

#### NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 3, 4.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610




Job 2544205	Truss CJ03A	Truss Type Jack-Open	Qty 1	Ply 1	IC CONST. - MCNUTT RES. Job Reference (optional)	T21943135
----------------	----------------	-------------------------	----------	----------	---	-----------

Builders FirstSource (Jacksonville, FL),

Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:24 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-fzXNUNnysYqZSAW6NTgb1fVRrFEB0tSyOAFxbAyHgJf



Scale = 1:19.6

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	L/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.38	Vert(LL)	0.01 4-5	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.22	Vert(CT)	-0.01 4-5	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.03 3	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MR					Weight: 13 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-5-2 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


#### REACTIONS.

(size) 5=0-3-0, 3=Mechanical, 4=Mechanical  
Max Horz 5=98(LC 9)  
Max Uplift 5=-39(LC 12), 3=-69(LC 12), 4=-24(LC 12)  
Max Grav 5=208(LC 1), 3=54(LC 19), 4=44(LC 10)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

#### NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 3, 4.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610




Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUTT RES.	T21943136
2544205	CJ04	Jack-Open	1	1		
Job Reference (optional)						

Builders FirstSource (Jacksonville, FL),

Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:25 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-795lhoadsyQ3K5lxBBqZt2cvfZFIKi5cq\_57dyHgJe



Scale = 1:22.8

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.36	Vert(LL)	0.02	4-5	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.23	Vert(CT)	-0.02	4-5	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.03	3	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MR						Weight: 17 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2

BOT CHORD 2x4 SP No.2

WEBS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-9-3 oc purlins, except end verticals.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 5=0-3-0, 3=Mechanical, 4=Mechanical

Max Horz 5=167(LC 12)

Max Uplift 5=-46(LC 12), 3=-114(LC 12), 4=-17(LC 12)

Max Grav 5=244(LC 1), 3=99(LC 19), 4=66(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

#### NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 4 except (jt=lb) 3=114.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610

Job 2544205	Truss CJ05	Truss Type Jack-Open	Qty 4	Ply 1	IC CONST. - MCNUTT RES. Job Reference (optional)	T21943137
----------------	---------------	-------------------------	----------	----------	---	-----------

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:26 2020 Page 1  
ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-bLf8v3pCO94HhUgUUi364an13tqUnyFrUkef3yHgJd



Scale = 1:12.7




Plate Offsets (X,Y)--		[2:0-1-2,Edge]									
<b>LOADING</b> (psf)		<b>SPACING-</b>	2-0-0	<b>CSI.</b>		<b>DEFL.</b>	in (loc)	I/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0		Plate Grip DOL	1.25	TC 0.33		Vert(LL)	0.08 4-7	>751	240	MT20	244/190
TCDL 7.0		Lumber DOL	1.25	BC 0.34		Vert(CT)	0.07 4-7	>870	180		
BCLL 0.0 *		Rep Stress Incr	YES	WB 0.00		Horz(CT)	-0.00 3	n/a	n/a		
BCDL 10.0		Code FBC2017/TPI2014		Matrix-MP						Weight: 18 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS.

(size) 3=Mechanical, 2=0-3-8, 4=Mechanical  
Max Horz 2=84(LC 8)  
Max Uplift 3=88(LC 8), 2=232(LC 8), 4=49(LC 8)  
Max Grav 3=110(LC 1), 2=276(LC 1), 4=85(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

#### NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 4 except (jt=lb) 2=232.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610




Job 2544205	Truss CJ05A	Truss Type Jack-Open	Qty 1	Ply 1	IC CONST. - MCNUTT RES. Job Reference (optional)	T21943138
----------------	----------------	-------------------------	----------	----------	---	-----------

Builders FirstSource (Jacksonville, FL),

Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:27 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-3YDW6Oqq9TC8JeFh2cDle17spSBnDECO48TCBVyHgJc



Scale = 1:26.9

Plate Offsets (X,Y)-- [2:0-2-0,0-1-12]							
<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	L/defl	<b>L/d</b>
TCLL 20.0	Plate Grip DOL	1.25	TC 0.72	Vert(LL)	0.06 4-5	>956	240
TCDL 7.0	Lumber DOL	1.25	BC 0.48	Vert(CT)	-0.08 4-5	>765	180
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.14 3	n/a	n/a
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MR				
						Weight: 21 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 5'-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10'-0-0 oc bracing.

#### REACTIONS.

(size) 5=0-3-0, 3=Mechanical, 4=Mechanical  
Max Horz 5=150(LC 12)  
Max Uplift 5=57(LC 12), 3=141(LC 12), 4=23(LC 12)  
Max Grav 5=284(LC 1), 3=138(LC 19), 4=90(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

#### NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-6-0 tall by 2'-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 4 except (jt=lb) 3=141.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610

Job 2544205	Truss CJ06	Truss Type Jack-Open	Qty 1	Ply 1	IC CONST. - MCNUTT RES. Job Reference (optional)	T21943139
----------------	---------------	-------------------------	----------	----------	---	-----------

Builders FirstSource (Jacksonville, FL),


Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:28 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-YknuKkrSwNk?woqtCjKXBVg3JsYvyhRYJoDlkxyHgJb

-1-6-8  
1-6-8  
5-3-14  
5-3-14

Scale = 1:29.2



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.60	Vert(LL)	0.07	4-5	>865	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.43	Vert(CT)	-0.08	4-5	>729	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.08	3	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MR						Weight: 22 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2

BOT CHORD 2x4 SP No.2

WEBS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-3-14 oc purlins, except end verticals.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 5=0-3-0, 3=Mechanical, 4=Mechanical  
Max Horz 5=224(LC 12)  
Max Uplift 5=48(LC 12), 3=-162(LC 12), 4=-21(LC 12)  
Max Grav 5=295(LC 1), 3=148(LC 19), 4=95(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

#### NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 4 except (jt=lb) 3=162.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610

6904 Parke East Blvd.  
Tampa, FL 36610


Job 2544205	Truss EJ02	Truss Type Jack-Partial	Qty 2	Ply 1	IC CONST. - MCNUTT RES. Job Reference (optional)	T21943141
----------------	---------------	----------------------------	----------	----------	---	-----------

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:29 2020 Page 1  
ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-0wLGX4r4h4SsYyP3A1GmkjCCAGpbh8hhXSylGOyHgJa



Scale = 1:16.3



										7-0-0																			
Plate Offsets (X,Y)--										[2:0-1-8,Edge]										7-0-0									
<b>LOADING</b> (psf)		<b>SPACING-</b> 2-0-0				<b>CSI.</b>				<b>DEFL.</b> in (loc) l/defl L/d				<b>PLATES</b>				<b>GRIP</b>											
TCLL	20.0	Plate Grip DOL 1.25				TC 0.73				Vert(LL) 0.32 4-7 >262 240				MT20				244/190											
TCDL	7.0	Lumber DOL 1.25				BC 0.72				Vert(CT) 0.27 4-7 >305 180																			
BCLL	0.0 *	Rep Stress Incr YES				WB 0.00				Horz(CT) -0.01 3 n/a n/a																			
BCDL	10.0	Code FBC2017/TPI2014				Matrix-MS								Weight: 24 lb				FT = 20%											

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


#### REACTIONS.

(size) 3=Mechanical, 2=0-3-8, 4=Mechanical  
Max Horz 2=109(LC 8)  
Max Uplift 3=-129(LC 8), 2=-282(LC 8), 4=-71(LC 8)  
Max Grav 3=162(LC 1), 2=346(LC 1), 4=122(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

#### NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4 except (jt=lb) 3=129, 2=282.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




6904 Parke East Blvd.  
Tampa, FL 33610

Job 2544205	Truss EJ03	Truss Type Jack-Open	Qty 8	Ply 1	IC CONST. - MCNUTT RES. Job Reference (optional)	T21943142
----------------	---------------	-------------------------	----------	----------	---	-----------

Builders FirstSource (Jacksonville, FL),

Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:30 2020 Page 1  
ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-U7uekQsjSOajA5zGjkn?GwlWvgKWQbqhm6isoqyHgJZ



Scale = 1:8.5

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.15	Vert(LL)	-0.00	9	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.03	Vert(CT)	-0.00	9	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.02	Horz(CT)	0.00	2	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MP						Weight: 9 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS.

(size) 2=0-3-8, 5=Mechanical  
Max Horz 2=64(LC 8)  
Max Uplift 2=-144(LC 8), 5=-21(LC 12)  
Max Grav 2=184(LC 1), 5=46(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

#### NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5 except (jt=lb) 2=144.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610

Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUTT RES.	T21943143
2544205	HJ09	Diagonal Hip Girder	1	1		

Builders FirstSource (Jacksonville, FL),

Jacksonville, FL - 32244,


8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:31 2020 Page 1

ID:n6lIfAxwnDhbiCo\_iGpf14cyqw8Q-yJS1ymtLDianFYSHSIEp8laF4W89zq\_?mRPLGyHgJY

Job Reference (optional)



Scale = 1:34.5



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	L/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.62	Vert(LL)	0.10	6-7	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.58	Vert(CT)	-0.12	6-7	>939	180		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.34	Horz(CT)	-0.01	4	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS						Weight: 55 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** (size) 8=0-3-3, 4=Mechanical, 5=Mechanical  
Max Horz 8=225(LC 8)  
Max Uplift 8=320(LC 4), 4=237(LC 8), 5=300(LC 8)  
Max Grav 8=542(LC 32), 4=192(LC 1), 5=347(LC 29)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 2-8=-518/329, 2-3=-557/328  
BOT CHORD 6-7=-425/406  
WEBS 2-7=-297/510, 3-6=-518/541

#### NOTES-

- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone; end vertical left exposed; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 8=320, 4=237, 5=300.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 101 lb down and 55 lb up at 2-1-3, 124 lb down and 62 lb up at 3-2-2, 127 lb down and 117 lb up at 4-7-10, 162 lb down and 147 lb up at 6-5-4, and 156 lb down and 171 lb up at 7-2-0, and 79 lb down and 93 lb up at 9-7-5 on top chord, and 23 lb down and 19 lb up at 2-1-3, 34 lb down and 29 lb up at 3-2-2, 40 lb down and 27 lb up at 4-7-10, and 56 lb down and 37 lb up at 6-5-4, and 58 lb down and 36 lb up at 7-2-0 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

#### LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25  
Uniform Loads (plf)  
Vert: 1-2=-54, 2-4=-54, 5-8=-20  
Concentrated Loads (lb)  
Vert: 4=-50(B) 7=-8(B) 3=-8(B) 11=-23(F) 12=-51(B) 13=5(B) 14=3(F) 15=-17(F) 16=-30(B)



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610



Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUTT RES.	T21943144
2544205	HJ10	Diagonal Hip Girder	2	1		
Job Reference (optional)						

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:32 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-QV0P96uz\_?qRPP7er9pTLLqkrTpXuK\_7DQBytjyHgJX



Scale = 1:21.8




Plate Offsets (X,Y)-- [2:0-2-11,Edge], [6:0-0-4,0-1-14]							
<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d
TCLL 20.0	Plate Grip DOL	1.25	TC 0.63	Vert(LL)	0.20	6-7	>596
TCDL 7.0	Lumber DOL	1.25	BC 0.83	Vert(CT)	-0.19	6-7	>615
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.67	Horz(CT)	0.02	5	n/a
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS				
						<b>PLATES</b>	<b>GRIP</b>
						MT20	244/190
						Weight: 41 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-10-3 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 5-1-2 oc bracing.

#### REACTIONS.

(size) 4=Mechanical, 2=0-4-9, 5=Mechanical  
Max Horz 2=107(LC 4)  
Max Uplift 4=122(LC 8), 2=448(LC 4), 5=240(LC 4)  
Max Grav 4=158(LC 1), 2=531(LC 1), 5=294(LC 1)

#### FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1388/1042  
BOT CHORD 2-7=-1085/1357, 6-7=-1085/1357  
WEBS 3-7=-145/276, 3-6=-1378/1103

#### NOTES-

- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone; porch left and right exposed; Lumber DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 4=122, 2=448, 5=240.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 26 lb down and 47 lb up at 4-4-0, 26 lb down and 47 lb up at 4-4-0, and 48 lb down and 98 lb up at 7-1-15, and 48 lb down and 98 lb up at 7-1-15 on top chord, and 62 lb down and 22 lb up at 1-6-1, 62 lb down and 22 lb up at 1-6-1, 19 lb down and 36 lb up at 4-4-0, 19 lb down and 36 lb up at 4-4-0, and 40 lb down and 67 lb up at 7-1-15, and 40 lb down and 67 lb up at 7-1-15 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

#### LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25  
Uniform Loads (plf)  
Vert: 1-4=-54, 5-8=-20  
Concentrated Loads (lb)  
Vert: 3=0(F=0, B=0) 7=-13(F=-7, B=-7) 11=-68(F=-34, B=-34) 13=-63(F=-32, B=-32)



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




6904 Parke East Blvd.  
Tampa, FL 33610

Job 2544205	Truss PB01	Truss Type Piggyback	Qty 17	Ply 1	IC CONST. - MCNUTT RES. Job Reference (optional)	T21943145
----------------	---------------	-------------------------	-----------	----------	---	-----------

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:33 2020 Page 1  
ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-uhannSubJyl1ZirPsKiuZN1MtL?dxQHS4wWP9yHgJW



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.07	Vert(LL)	0.00	5	n/r	120	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.05	Vert(CT)	0.00	5	n/r	120		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.02	Horz(CT)	0.00	4	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-P						Weight: 18 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
OTHERS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS.

(size) 2=4-3-12, 4=4-3-12, 6=4-3-12  
Max Horz 2=-49(LC 10)  
Max Uplift 2=-63(LC 12), 4=-69(LC 13), 6=-29(LC 12)  
Max Grav 2=115(LC 1), 4=115(LC 20), 6=147(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4, 6.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610

Job 2544205	Truss PB01G	Truss Type PIGGYBACK	Qty 2	Ply 1	IC CONST. - MCNUTT RES. Job Reference (optional)	T21943146
----------------	----------------	-------------------------	----------	----------	---	-----------


Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:34 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-Mu89aovDVd58ejH1yarxQmwDeHhaMOMQhkg3xbyHgJV

2-5-2 2-5-2 4-10-3 2-5-1

Scale = 1:9.5



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL	20.0	Plate Grip DOL	1.25	TC	0.04	Vert(LL)	0.00	MT20		244/190	
TCDL	7.0	Lumber DOL	1.25	BC	0.03	Vert(CT)	0.00				
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.01	Horz(CT)	0.00				
BCDL	10.0	Code FBC2017/TPI2014		Matrix-P							
								Weight: 14 lb		FT = 20%	

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
OTHERS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-10-3 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


#### REACTIONS.

(size) 2=3-1-14, 4=3-1-14, 6=3-1-14  
Max Horz 2=-38(LC 10)  
Max Uplift 2=-53(LC 12), 4=-58(LC 13), 6=-18(LC 12)  
Max Grav 2=94(LC 1), 4=94(LC 20), 6=104(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4, 6.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610

Job 2544205	Truss T01	Truss Type Common	Qty 1	Ply 1	IC CONST. - MCNUTT RES.	T21943147
Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,						8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:35 2020 Page 1
Job Reference (optional)						ID:n6lfAxwnDhbiCo_iGpf14cyqw8Q-q4iXo7wrGwD?GtsDWHMAz_SEwhrF5fKZwOPdU2yHgJU




Plate Offsets (X,Y)-- [2:0-8-7,0-0-2], [8:0-8-7,0-0-2]							
<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d
TCLL 20.0	Plate Grip DOL	1.25	TC 0.64	Vert(LL)	-0.18 9-11	>999	240
TCDL 7.0	Lumber DOL	1.25	BC 0.83	Vert(CT)	-0.34 9-11	>709	180
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.82	Horz(CT)	0.04 8	n/a	n/a
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS				
				<b>PLATES</b>		<b>GRIP</b>	
				MT20		244/190	
				Weight: 136 lb		FT = 20%	

#### LUMBER-

TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x6 SP No.2  
 WEBS 2x4 SP No.3  
 SLIDER Left 2x6 SP No.2 1-11-8, Right 2x6 SP No.2 1-11-8

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-0-8 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS.

(size) 8=0-3-0, 2=0-3-0  
 Max Horz 2=256(LC 11)  
 Max Uplift 8=378(LC 13), 2=432(LC 12)  
 Max Grav 8=1023(LC 20), 2=1108(LC 19)

#### FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-4=-1362/578, 4-5=-1434/776, 5-6=-1431/781, 6-8=-1372/582  
 BOT CHORD 2-11=-436/1167, 9-11=-198/747, 8-9=-346/1046  
 WEBS 5-9=-503/889, 6-9=-297/324, 5-11=-493/871, 4-11=-298/322

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 8=378, 2=432.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

#### LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25  
 Uniform Loads (plf)  
 Vert: 1-5=-54, 5-8=-54, 11-16=-20, 9-11=-80(F=-60), 9-12=-20



Julius Lee PE No.34869  
 MiTek USA, Inc. FL Cert 6634  
 6904 Parke East Blvd. Tampa FL 33610  
 Date:

November 19,2020

#### WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




6904 Parke East Blvd.  
 Tampa, FL 33610

Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUTT RES.	T21943148
2544205	T01G	GABLE	1	1		

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:37 2020 Page 1  
ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-nTpiCpy6oYTjWA0ceiPe2PXguUcsZeysNiuYwyHgJS



4x6 ||

Scale = 1:48.7




Plate Offsets (X,Y)-- [2:0-3-4,0-1-5], [10:0-3-4,0-1-5], [15:0-4-0,0-4-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.29	Vert(LL)	-0.08 14-16	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.44	Vert(CT)	-0.15 14-16	>945	180		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.49	Horz(CT)	0.01 10	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS						
								Weight: 187 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x6 SP No.2  
WEBS 2x4 SP No.3  
OTHERS 2x4 SP No.3  
SLIDER Left 2x6 SP No.2 1-8-3, Right 2x6 SP No.2 1-8-3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS.

All bearings 3-11-0 except (jt=length) 17=0-3-8, 17=0-3-8, 13=0-3-8, 13=0-3-8.  
(lb) - Max Horz 2=-257(LC 6)  
Max Uplift All uplift 100 lb or less at joint(s) except 2=-276(LC 8), 10=-247(LC 9), 18=-219(LC 36), 12=-247(LC 33), 17=-182(LC 8), 13=-166(LC 9)  
Max Grav All reactions 250 lb or less at joint(s) 18, 12 except 2=799(LC 33), 10=777(LC 2), 17=294(LC 1), 17=294(LC 1), 13=294(LC 1), 13=294(LC 1)


#### FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-5=-851/335, 5-6=-818/488, 6-7=-839/505, 7-10=-838/320  
BOT CHORD 2-18=-215/717, 17-18=-234/713, 16-17=-234/713, 14-16=-111/480, 13-14=-161/634, 12-13=-161/634, 10-12=-152/650  
WEBS 6-14=-324/485, 7-14=-292/326, 6-16=-312/467, 5-16=-291/325

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCCL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 276 lb uplift at joint 2, 247 lb uplift at joint 10, 219 lb uplift at joint 18, 247 lb uplift at joint 12, 182 lb uplift at joint 17 and 166 lb uplift at joint 13.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 20 lb down and 31 lb up at 3-8-4, 20 lb down and 31 lb up at 5-8-4, 20 lb down and 31 lb up at 7-8-4, 20 lb down and 31 lb up at 9-8-4, 20 lb down and 31 lb up at 10-2-12, 20 lb down and 31 lb up at 12-2-12, and 20 lb down and 31 lb up at 14-2-12, and 20 lb down and 31 lb up at 16-2-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

Continued on page 2

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITTEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**  
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610

Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUTT RES.	T21943148
2544205	T01G	GABLE	1	1	Job Reference (optional)	

**LOAD CASE(S)** Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-6=-54, 6-11=-54, 2-10=-20

Concentrated Loads (lb)

Vert: 14=-13(B) 16=-13(B) 15=-13(B) 17=-13(B) 13=-13(B) 32=-13(B) 33=-13(B) 34=-13(B)





Job 2544205	Truss T02	Truss Type Roof Special	Qty 9	Ply 1	IC CONST. - MCNUTT RES. T21943149
Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,					

-1-6-8 1-6-8	5-5-6 5-5-6	9-11-8 4-6-2	14-5-10 4-6-2	18-5-7 3-11-13	21-11-0 3-5-9	23-5-8 1-6-8
-----------------	----------------	-----------------	------------------	-------------------	------------------	-----------------

4x6 ||

Scale = 1:53.6




Plate Offsets (X,Y)-- [2:0-8-7,0-0-2]							
<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	I/defl	L/d
TCLL 20.0	Plate Grip DOL	1.25	TC 0.68	Vert(LL)	-0.16 12-14	>999	240
TCDL 7.0	Lumber DOL	1.25	BC 0.82	Vert(CT)	-0.32 12-14	>814	180
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.78	Horz(CT)	-0.02 2	n/a	n/a
BCDL 10.0	Code FBC2017/TP12014		Matrix-MS				
				<b>PLATES</b>	<b>GRIP</b>		
				MT20	244/190		
				Weight: 155 lb		FT = 20%	

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x6 SP No.2  
WEBS 2x4 SP No.3  
SLIDER Left 2x6 SP No.2 1-11-8

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-9-5 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 8-9-0 oc bracing: 11-12.  
WEBS 1 Row at midpt 5-12

#### REACTIONS.

(size) 2=0-3-0, 10=0-3-0  
Max Horz 2=-266(LC 10)  
Max Uplift 2=-462(LC 12), 10=-466(LC 13)  
Max Grav 2=1208(LC 19), 10=1145(LC 1)

#### FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-4=-1489/677, 4-5=-1543/871, 5-6=-1807/996, 6-7=-1724/791, 7-8=-1558/744, 8-10=-1024/602  
BOT CHORD 2-14=-442/1285, 12-14=-212/886, 11-12=-674/1534  
WEBS 4-14=-296/321, 5-14=-478/826, 5-12=-644/1258, 6-12=-354/329, 7-12=-294/214, 7-11=-680/327, 8-11=-673/1464

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 462 lb uplift at joint 2 and 466 lb uplift at joint 10.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

#### LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25  
Uniform Loads (plf)  
Vert: 1-5=-54, 5-7=-54, 7-8=-54, 8-9=-54, 14-15=-20, 12-14=-80(F=-60), 10-12=-20



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

#### WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.


Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610

Job 2544205	Truss T03	Truss Type Common	Qty 7	Ply 1	IC CONST. - MCNUTT RES. T21943150
Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,					

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:40 2020 Page 1  
ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-B2VQrr\_5TrlNekBJryLg195hiYamwoJ3g7O9FyHgJP



4x6 ||

Scale = 1:52.5




Plate Offsets (X,Y)-- [2:0-8-7,0-0-2], [8:0-8-7,0-0-2]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.64	Vert(LL)	-0.17 10-12	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.82	Vert(CT)	-0.33 10-12	>716	180		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.81	Horz(CT)	0.04 8	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS					Weight: 139 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x6 SP No.2  
WEBS 2x4 SP No.3  
SLIDER Left 2x6 SP No.2 1-11-8, Right 2x6 SP No.2 1-11-8


**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 4-0-10 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 2=0-3-0, 8=0-3-0  
Max Horz 2=269(LC 11)  
Max Uplift 2=-431(LC 12), 8=-431(LC 13)  
Max Grav 2=1098(LC 19), 8=1099(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-4=-1344/574, 4-5=-1432/772, 5-6=-1432/772, 6-8=-1347/574  
BOT CHORD 2-12=-412/1172, 10-12=-174/756, 8-10=-298/1047  
WEBS 5-10=-494/866, 6-10=-298/322, 5-12=-494/862, 4-12=-298/322

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 431 lb uplift at joint 2 and 431 lb uplift at joint 8.
  - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard  
1) Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25  
Uniform Loads (plf)  
Vert: 1-5=-54, 5-9=-54, 12-13=-20, 10-12=-80(F=-60), 10-17=-20



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610



6904 Parke East Blvd.  
Tampa, FL 33610

Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUTT RES.	T21943151
2544205	T04	Common Girder	1	2	Job Reference (optional)	

**LOAD CASE(S)** Standard

Uniform Loads (plf)

Vert: 1-5=-54, 5-8=-54, 12-16=-20

Concentrated Loads (lb)

Vert: 9=-1024(F) 20=-2221(F) 21=-1024(F) 22=-1024(F) 23=-1024(F) 24=-1024(F) 25=-1080(F)




Job 2544205	Truss T05G	Truss Type Monopitch Supported Gable	Qty 2	Ply 1	IC CONST. - MCNUTT RES. Job Reference (optional)	T21943152
----------------	---------------	---	----------	----------	---	-----------

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:42 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-7QdBGX?Ed450cxuZQF\_plSFZTVQNE0RbX\_cUD8yHgJN



Scale = 1:12.6

Plate Offsets (X,Y)-- [2:0-5-0,0-2-0]							
<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d
TCLL 20.0	Plate Grip DOL	1.25	TC 0.18	Vert(LL)	0.01	5	n/r
TCDL 7.0	Lumber DOL	1.25	BC 0.03	Vert(CT)	0.00	5	n/r
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.03	Horz(CT)	-0.00	6	n/a
BCDL 10.0	Code FBC2017/TPI2014		Matrix-P				
				<b>PLATES</b>	<b>GRIP</b>		
				MT20	244/190		
				Weight: 17 lb	FT = 20%		

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS.

(size) 7=2-0-0, 6=2-0-0  
Max Horz 7=59(LC 9)  
Max Uplift 7=121(LC 8), 6=125(LC 9)  
Max Grav 7=159(LC 1), 6=146(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

#### NOTES-

- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed on one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 121 lb uplift at joint 7 and 125 lb uplift at joint 6.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




6904 Parke East Blvd.  
Tampa, FL 33610

Job 2544205	Truss T06G	Truss Type Common Supported Gable	Qty 1	Ply 1	IC CONST. - MCNUTT RES. Job Reference (optional)	T21943153
----------------	---------------	--------------------------------------	----------	----------	---	-----------

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:44 2020 Page 1  
ID:n6lfxwnDhbiCo\_iGpf14cyqw8Q-4plxgC1V9hLkrF2yYg1HqtKvpJ5oiwiu\_H5b10yHgJL



Scale = 1:28.9

Plate Offsets (X,Y)-- [2:0-5-4,0-2-8], [10:0-5-4,0-2-8]												
LOADING (psf)		SPACING- 2-0-0		CSI.		DEFL. in (loc) l/defl L/d				PLATES GRIP		
TCLL	20.0	Plate Grip DOL	1.25	TC	0.19	Vert(LL)	-0.01	11	n/r	120	MT20	244/190
TCDL	7.0	Lumber DOL	1.25	BC	0.03	Vert(CT)	-0.01	11	n/r	120		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.05	Horz(CT)	0.00	12	n/a	n/a		
BCDL	10.0	Code FBC2017/TPI2014		Matrix-S							Weight: 75 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3  
OTHERS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

#### REACTIONS.

All bearings 10-5-0.  
(lb) - Max Horz 18=-179(LC 10)  
Max Uplift All uplift 100 lb or less at joint(s) 12 except 18=-119(LC 8), 16=-108(LC 12), 17=-139(LC 9), 14=-108(LC 13), 13=-109(LC 13)  
Max Grav All reactions 250 lb or less at joint(s) 18, 12, 15, 16, 17, 14, 13

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCCL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 12 except (jt=lb) 18=119, 16=108, 17=139, 14=108, 13=109.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610



Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUTT RES.	T21943154
2544205	T07	HALF HIP GIRDER	1	2	Job Reference (optional)	

Builders FirstSource (Jacksonville, FL),
Jacksonville, FL - 32244,

8.240 s Mar 9 2020
MiTek Industries, Inc.
Thu Nov 19 08:41:47 2020
Page 1
ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-UOQ4JE3NScjlijnXDpa\_SWyLmW2Pv3aLgFJfVlyHgJl
21-6-12 6-10-8 28-7-0 7-0-4

-1-6-8 1-6-8
3-11-13 3-11-13
7-8-1 3-8-5
14-8-5 7-0-4

Scale = 1:50.3





Plate Offsets (X,Y)-- [4:0-5-8,0-2-0], [9:Edge,0-4-4]							
<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d
TCLL 20.0	Plate Grip DOL	1.25	TC 0.46	Vert(LL)	0.12 11-13	>999	240
TCDL 7.0	Lumber DOL	1.25	BC 0.36	Vert(CT)	-0.11 11-13	>999	180
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.93	Horz(CT)	-0.03 9	n/a	n/a
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS				
				<b>PLATES</b>	<b>GRIP</b>		
				MT20	244/190		
				Weight: 412 lb		FT = 20%	

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x6 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	

**REACTIONS.** (size) 9=Mechanical, 15=0-3-0  
Max Horz 15=230(LC 27)  
Max Uplift 9=1931(LC 5), 15=1521(LC 8)  
Max Grav 9=2338(LC 35), 15=2075(LC 33)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-2182/1652, 3-4=-2615/2103, 4-5=-2834/2353, 5-7=-2834/2353, 2-15=-1998/1498  
BOT CHORD 14-15=-280/153, 13-14=-1575/1884, 11-13=-1875/2250, 10-11=-1752/2152, 9-10=-1752/2152  
WEBS 3-14=-771/651, 3-13=-654/648, 4-13=-392/572, 4-11=-790/887, 5-11=-501/474, 7-11=-838/904, 7-10=-528/892, 7-9=-2819/2289, 2-14=-1397/1885

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.  
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TC DL=4.2psf; BC DL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone; end vertical left exposed; Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Refer to girder(s) for truss to truss connections.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 9=1931, 15=1521.
  - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 95 lb down and 87 lb up at 9-8-13, 95 lb down and 87 lb up at 11-8-13, 95 lb down and 87 lb up at 13-8-13, 95 lb down and 87 lb up at 15-8-13, 95 lb down and 87 lb up at 17-8-13, 95 lb down and 87 lb up at 19-8-13, 95 lb down and 87 lb up at 21-8-13, 95 lb down and 87 lb up at 23-8-13, and 95 lb down and 87 lb up at 25-8-13, and 89 lb down and 89 lb up at 27-8-13 on top chord, and 462 lb down and 500 lb up at 7-8-1, 164 lb down and 167 lb up at 9-8-13, 164 lb down and 167 lb up at 11-8-13, 164 lb down and 167 lb up at 13-8-13, 164 lb down and 167 lb up at 15-8-13, 164 lb down and 167 lb up at 17-8-13, 164 lb down and 167 lb up at 19-8-13, 164 lb down and 167 lb up at 21-8-13, 164 lb down and 167 lb up at 23-8-13, and 164 lb down and 167 lb up at 25-8-13, and 167 lb down and 167 lb up at 27-8-13 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUTT RES.	T21943154
2544205	T07	HALF HIP GIRDER	1	2	Job Reference (optional)	

**LOAD CASE(S)**
Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25
- Uniform Loads (plf)
- Vert: 1-2=-54, 2-4=-54, 4-8=-54, 9-15=-20
- Concentrated Loads (lb)
- Vert: 6=-29(B) 13=-391(B) 10=-136(B) 7=-29(B) 16=-29(B) 17=-29(B) 18=-29(B) 19=-29(B) 20=-29(B) 22=-29(B) 23=-29(B) 24=-37(B) 25=-136(B) 27=-136(B) 28=-136(B) 29=-136(B) 30=-136(B) 32=-136(B) 33=-136(B) 34=-136(B) 35=-139(B)



Job 2544205	Truss T09	Truss Type Hip	Qty 1	Ply 1	IC CONST. - MCNUTT RES. Job Reference (optional)	T21943156
----------------	--------------	-------------------	----------	----------	---	-----------

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:49 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-QmYqkw5dzEz0y0wvLEdSXx1fYKi0N6wd8ZoMzEyHgJG

-1-6-8 1-6-8	6-9-2 6-9-2	12-9-13 6-0-10	15-9-3 2-11-7	21-9-13 6-0-9	28-7-0 6-9-3
-----------------	----------------	-------------------	------------------	------------------	-----------------

Scale = 1:58.9




Plate Offsets (X,Y)--	[2:0-3-0,0-1-12], [3:0-3-0,0-3-0], [4:0-5-8,0-2-0], [7:0-1-4,0-1-12]
-----------------------	--

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.57	Vert(LL)	-0.05	8-9	>999	240	MT20
TCDL 7.0	Lumber DOL	1.25	BC 0.48	Vert(CT)	-0.11	8-9	>999	180	
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.37	Horz(CT)	0.03	8	n/a	n/a	
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS						
								Weight: 196 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-7-3 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 8-10-6 oc bracing.  
WEBS 1 Row at midpt 3-12, 4-10, 6-10

#### REACTIONS.

(size) 14=0-3-0, 8=Mechanical  
Max Horz 14=-297(LC 10)  
Max Uplift 14=-438(LC 12), 8=-382(LC 13)  
Max Grav 14=1141(LC 1), 8=1044(LC 1)

#### FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1249/569, 3-4=-1034/581, 4-5=-921/562, 5-6=-1039/582, 6-7=-1256/562, 2-14=-1079/573, 7-8=-982/469  
BOT CHORD 13-14=-299/335, 12-13=-443/1023, 10-12=-241/815, 9-10=-394/1016  
WEBS 3-12=-372/276, 4-12=-160/329, 5-10=-144/332, 6-10=-374/282, 2-13=-307/943, 7-9=-354/961

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCCL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 14=438, 8=382.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610

Job 2544205	Truss T10	Truss Type Common	Qty 3	Ply 1	IC CONST. - MCNUTT RES. T21943157
----------------	--------------	----------------------	----------	----------	--------------------------------------

Builders FirstSource (Jacksonville, FL),

Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:51 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-M9gb9c6uVrEkBK4iSefwdM7z28HTryjwbHT26yHgJE




Plate Offsets (X,Y)-- [2:0-2-0,0-1-12], [3:0-4-0,0-3-0], [5:0-4-0,0-3-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.70	Vert(LL)	-0.24 10-11	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.86	Vert(CT)	-0.49 10-11	>688	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.54	Horz(CT)	0.04 7	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS					Weight: 172 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 8-3-10 oc bracing.  
WEBS 1 Row at midpt 3-11, 5-7

#### REACTIONS.

(size) 11=0-3-0, 7=Mechanical  
Max Horz 11=-323(LC 10)  
Max Uplift 11=-432(LC 12), 7=-376(LC 13)  
Max Grav 11=1206(LC 19), 7=1118(LC 20)

#### FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-269/195, 3-4=-1255/638, 4-5=-1259/637, 2-11=-342/269  
BOT CHORD 10-11=-489/1234, 8-10=-208/896, 7-8=-415/1048  
WEBS 3-10=-259/332, 4-10=-235/543, 4-8=-239/554, 5-8=-262/337, 3-11=-1219/478, 5-7=-1220/514

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCCL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (it=lb) 11=432, 7=376.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610




Job 2544205	Truss T11	Truss Type Roof Special	Qty 1	Ply 1	IC CONST. - MCNUTT RES. T21943158
----------------	--------------	----------------------------	----------	----------	--------------------------------------

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:52 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-rLDzMX7WG9MbpUfU0MA99Zf8NXcmaOZ4qX10aYyHgJD

1-6-0 7-7-0 14-4-0 21-1-0 23-0-0 28-7-8  
1-6-0 7-7-0 6-9-0 6-9-0 1-11-0 5-7-8



Scale = 1:67.0

Plate Offsets (X,Y)--	[2:0-6-2,Edge], [4:0-3-0,0-3-0], [6:0-2-8,0-3-4]
-----------------------	--

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.66	Vert(LL)	-0.29 13-15	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.92	Vert(CT)	-0.47 13-15	>725	180	MT20HS	187/143
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.63	Horz(CT)	0.06 9	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS						
								Weight: 180 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2 "Except"  
7-10: 2x4 SP No.3  
WEBS 2x4 SP No.3  
SLIDER Left 2x6 SP No.2 1-11-8

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-4-5 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing. Except: 10-0-0 oc bracing: 10-12

#### REACTIONS.

(size) 2=0-3-8, 9=Mechanical  
Max Horz 2=278(LC 9)  
Max Uplift 2=431(LC 12), 9=368(LC 13)  
Max Grav 2=1209(LC 19), 9=1123(LC 20)

#### FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-4=-1591/661, 4-5=-1495/725, 5-6=-1478/708, 6-7=-1559/676, 7-8=-1620/621, 8-9=-1087/451  
BOT CHORD 2-15=-517/1480, 13-15=-216/985, 12-13=-428/1278, 10-12=0/253  
WEBS 4-15=-401/370, 5-15=-323/743, 5-13=-295/711, 6-13=-436/334, 8-12=-423/1277

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- All plates are MT20 plates unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=431, 9=368.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610



Job 2544205	Truss T12	Truss Type Common	Qty 3	Ply 1	IC CONST. - MCNUTT RES. Job Reference (optional)	T21943159
----------------	--------------	----------------------	----------	----------	---	-----------

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:53 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-JYnLZH881SUSQeEha3hOinCIGxzHJqYD3Bma6?yHgJC




Plate Offsets (X,Y)-- [1:0-5-14,0-0-3], [3:0-3-0,0-3-0], [5:0-3-0,0-3-0], [7:0-6-7,Edge]									
<b>LOADING</b> (psf)		<b>SPACING-</b> 2-0-0		<b>CSI.</b>		<b>DEFL.</b> in (loc) l/defl L/d		<b>PLATES</b>	<b>GRIP</b>
TCLL	20.0	Plate Grip DOL	1.25	TC	0.72	Vert(LL)	-0.32 9-11 >999 240	MT20	244/190
TCDL	7.0	Lumber DOL	1.25	BC	0.84	Vert(CT)	-0.47 9-11 >731 180	MT20HS	187/143
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.65	Horz(CT)	0.07 7 n/a n/a		
BCDL	10.0	Code FBC2017/TPI2014		Matrix-MS				Weight: 148 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3  
SLIDER Left 2x6 SP No.2 1-11-8, Right 2x6 SP No.2 1-11-8

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-1-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 8-0-10 oc bracing.

#### REACTIONS.

(size) 1=0-3-8, 7=0-3-0  
Max Horz 1=-279(LC 10)  
Max Uplift 1=-386(LC 12), 7=-438(LC 13)  
Max Grav 1=1126(LC 19), 7=1210(LC 20)

#### FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-3=-1598/677, 3-4=-1502/741, 4-5=-1488/735, 5-7=-1584/671  
BOT CHORD 1-11=-512/1502, 9-11=-206/1006, 7-9=-424/1281  
WEBS 3-11=-402/373, 4-11=-332/743, 4-9=-322/724, 5-9=-399/367

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCCL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- All plates are MT20 plates unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (it=lb) 1=386, 7=438.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020


**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITTEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610

Job 2544205	Truss T13	Truss Type Piggyback Base	Qty 1	Ply 1	IC CONST. - MCNUTT RES.	T21943160
Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,						8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:54 2020 Page 1
ID:n6lfAxwnDhbiCo_iGpf14cyqw8Q-nkLjnd9momcJ2npt7nCdE_IXVLMf2HwMHRW7fRyHgJB						Job Reference (optional)



Scale = 1:72.1

Plate Offsets (X,Y)--		[2:0-2-0,0-1-12], [6:0-3-0,0-1-12], [7:0-5-8,0-2-0]					
<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	<b>L/d</b>
TCLL 20.0	Plate Grip DOL	1.25	TC 0.49	Vert(LL)	-0.19 15-17	>999	240
TCDL 7.0	Lumber DOL	1.25	BC 0.70	Vert(CT)	-0.31 15-17	>999	180
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.70	Horz(CT)	0.04 11	n/a	n/a
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS				
				<b>PLATES</b>	<b>GRIP</b>		
				MT20	244/190		
				Weight: 253 lb		FT = 20%	

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3 \*Except\*  
7-15: 2x4 SP No.2, 9-11: 2x6 SP No.2

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-8-15 oc purlins, except end verticals, and 2-0-0 oc purlins (5-4-3 max.): 6-7.  
BOT CHORD Rigid ceiling directly applied or 7-2-9 oc bracing.  
WEBS 1 Row at midpt 5-15, 7-13, 3-18

#### REACTIONS.

(size) 18=0-3-0, 11=0-3-0  
Max Horz 18=462(LC 11)  
Max Uplift 18=520(LC 12), 11=478(LC 13)  
Max Grav 18=1301(LC 19), 11=1305(LC 2)

#### FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 3-5=-1444/725, 5-6=-1129/679, 6-7=-993/645, 7-8=-991/620, 8-9=-788/468, 2-18=-325/271, 9-11=-1276/664  
BOT CHORD 17-18=-666/1382, 15-17=-565/1296, 13-15=-319/831, 12-13=-300/666  
WEBS 5-17=-95/269, 5-15=-506/357, 6-15=-122/354, 7-15=-208/386, 8-13=-192/314, 8-12=-590/333, 3-18=-1443/568, 9-12=-390/971

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 18=520, 11=478.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

#### WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610


Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUTT RES.	T21943161
2544205	T13G	GABLE II	1	1		

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:41:59 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-7i9cqlDvdlEb8ZhqwKoox2SQ7MATjU\_6R7DuKeyHgJ6

Job Reference (optional)



Job 2544205	Truss T14	Truss Type Piggyback Base	Qty 2	Ply 1	IC CONST. - MCNUTT RES.	T21943162
Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,						8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:01 2020 Page 1
Job Reference (optional)						ID:n6lfAxwnDhbiCo_iGpf14cyqw8Q-44GMF0E99wUJOsrD2lqG1TXhCAkFBSLOuRi?OxyHgJ4




Plate Offsets (X,Y)-- [5:0-3-0,0-1-12], [6:0-5-8,0-2-0]							
<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	L/defl	<b>PLATES</b>
TCLL 20.0	Plate Grip DOL	1.25	TC 0.65	Vert(LL)	-0.19 13-15	>999	MT20
TCDL 7.0	Lumber DOL	1.25	BC 0.71	Vert(CT)	-0.31 13-15	>999	GRIP
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.66	Horz(CT)	0.05 9	n/a	244/190
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS				Weight: 254 lb FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 WEBS 2x4 SP No.3 \*Except\*  
 6-13: 2x4 SP No.2, 8-9: 2x6 SP No.2  
 OTHERS 2x6 SP No.2

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-8-10 oc purlins, except end verticals, and 2-0-0 oc purlins (5-3-8 max.): 5-6.  
 BOT CHORD Rigid ceiling directly applied or 6-9-8 oc bracing.  
 WEBS 1 Row at midpt 4-13, 6-11, 2-16

#### REACTIONS.


(size) 16=0-3-0, 9=0-3-0  
 Max Horz 16=435(LC 9)  
 Max Uplift 16=-464(LC 12), 9=-392(LC 13)  
 Max Grav 16=1223(LC 19), 9=1203(LC 2)

#### FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-4=-1472/728, 4-5=-1149/677, 5-6=-1001/644, 6-7=-1016/618, 7-8=-821/464, 8-9=-1178/548  
 BOT CHORD 15-16=-751/1394, 13-15=-645/1300, 11-13=-396/839, 10-11=-366/680  
 WEBS 4-15=-98/277, 4-13=-506/357, 5-13=-121/363, 6-13=-208/375, 7-11=-196/286, 7-10=-554/357, 2-16=-1471/623, 8-10=-400/876

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 16=464, 9=392.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



Julius Lee PE No.34869  
 MiTek USA, Inc. FL Cert 6634  
 6904 Parke East Blvd. Tampa FL 33610  
 Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
 Tampa, FL 33610

Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUTT RES.	T21943163
2544205	T15	Piggyback Base	3	1		

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:02 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-YHqISMFvDcA?0QPbSLVZg4vQZ7UwuyY75SYzyHgJ3

2-3-0	7-0-0	11-11-8	16-5-14	22-5-15	28-2-4	32-11-0	34-5-8
2-3-0	4-9-0	4-11-8	4-6-6	6-0-1	5-8-5	4-8-12	1-6-8




Plate Offsets (X,Y)-- [6:0-3-0,0-1-12], [7:0-5-8,0-2-0]																			
<b>LOADING</b> (psf)		<b>SPACING-</b>		2-0-0		<b>CSI.</b>		<b>DEFL.</b>		in (loc)		l/defl		L/d		<b>PLATES</b>		<b>GRIP</b>	
TCLL 20.0		Plate Grip DOL		1.25		TC 0.50		Vert(LL)		0.11 5		>999		240		MT20		244/190	
TCDL 7.0		Lumber DOL		1.25		BC 0.51		Vert(CT)		-0.17 17-18		>999		180					
BCLL 0.0 *		Rep Stress Incr		YES		WB 0.71		Horz(CT)		0.14 11		n/a		n/a					
BCDL 10.0		Code FBC2017/TPI2014				Matrix-MS										Weight: 272 lb		FT = 20%	

#### LUMBER-

TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2 "Except"  
 2-20: 2x4 SP M 31, 5-16: 2x4 SP No.3  
 WEBS 2x4 SP No.3 "Except"  
 7-15: 2x4 SP No.2, 9-11: 2x6 SP No.2

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-3-13 oc purlins, except end verticals, and 2-0-0 oc purlins (5-4-1 max.): 6-7.  
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing. Except:  
 1 Row at midpt 5-17  
 1 Row at midpt 6-17, 6-15, 7-13

#### REACTIONS.

(size) 21=0-3-0, 11=0-3-0  
 Max Horz 21=423(LC 11)  
 Max Uplift 21=-464(LC 12), 11=-477(LC 13)  
 Max Grav 21=1201(LC 1), 11=1302(LC 1)

#### FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-1009/450, 2-3=-1729/806, 3-5=-1465/751, 5-6=-1501/895, 6-7=-990/646,  
 7-8=-980/620, 8-9=-777/469, 1-21=-1277/576, 9-11=-1264/663  
 BOT CHORD 20-21=-414/353, 19-20=-552/269, 2-19=-530/288, 18-19=-828/1571, 17-18=-776/1605,  
 5-17=-323/278, 13-15=-318/794, 12-13=-300/665  
 WEBS 2-18=-165/308, 3-17=-434/272, 15-17=-357/910, 6-17=-519/945, 6-15=-349/272,  
 7-15=-208/332, 8-13=-191/306, 8-12=-594/331, 1-20=-455/1038, 9-12=-389/932

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCCL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- All plates are 3x6 MT20 unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 21=464, 11=477.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



Julius Lee PE No.34869  
 MiTek USA, Inc. FL Cert 6634  
 6904 Parke East Blvd. Tampa FL 33610  
 Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
 Tampa, FL 33610




Job 2544205	Truss T16	Truss Type Piggyback Base	Qty 1	Ply 1	IC CONST. - MCNUTT RES. T21943164
Job Reference (optional)					

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:04 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-UfyVt2G1RrsuFKaojtOze59CpNouOp2raPxf?syHgJ1



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL	20.0	Plate Grip DOL	1.25	TC	0.63	Vert(LL)	0.12 5 >999	240	MT20	244/190	
TCDL	7.0	Lumber DOL	1.25	BC	0.52	Vert(CT)	-0.17 16-17 >999	180			
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.66	Horz(CT)	0.14 10 n/a	n/a			
BCDL	10.0	Code FBC2017/TPI2014		Matrix-MS							
										Weight: 276 lb	FT = 20%

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 4-3-9 oc purlins, except end verticals, and 2-0-0 oc purlins (5-3-8 max.): 6-7.
BOT CHORD	2x4 SP No.2 "Except"	BOT CHORD	Rigid ceiling directly applied or 5-11-5 oc bracing. Except:
WEBS	2x4 SP No.3 "Except"	WEBS	1 Row at midpt 5-16
OTHERS	2x6 SP No.2		1 Row at midpt 6-16, 6-14, 7-12

REACTIONS.	
(size)	20=0-3-0, 10=0-3-0
Max Horz	20=416(LC 11)
Max Uplift	20=-464(LC 12), 10=-391(LC 13)
Max Grav	20=1212(LC 1), 10=1176(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD	1-2=-1018/452, 2-4=-1747/818, 4-5=-1485/753, 5-6=-1515/898, 6-7=-997/644, 7-8=-991/618, 8-9=-795/465, 1-20=-1289/581, 9-10=-1143/547
BOT CHORD	19-20=-407/331, 18-19=-557/263, 2-18=-535/283, 17-18=-955/1557, 16-17=-876/1597, 5-16=-323/278, 12-14=-394/796, 11-12=-366/678
WEBS	2-17=-158/310, 4-16=-431/275, 14-16=-435/905, 6-16=-540/943, 6-14=-345/277, 7-14=-208/325, 8-12=-195/288, 8-11=-556/355, 1-19=-455/1047, 9-11=-399/835

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - All plates are 3x6 MT20 unless otherwise indicated.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 20=464, 10=391.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




6904 Parke East Blvd.  
Tampa, FL 33610



T21943165

Job Reference (optional)



**NOTES-**

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDF=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=472, 11=478.
- 7) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.




November 19, 2020

8.240 s Mar. 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:07 2020 Page 1

Job Reference (optional)

ID:n6lfAxwnDhbiCo\_iGpf14cygw8Q-uEdeV4.lwkmET6pINQ?xqGkpkWan2hAiHhM9.lcByHq.l



**NOTES-**

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDFL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCp=-0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) Provide adequate drainage to prevent water ponding.
- 5) All plates are 2x4 MT20 unless otherwise indicated.
- 6) Gable studs spaced at 2'-0" oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-6" tall by 2'-0" wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 14 except (jt=lb) 1=401, 15=529, 13=207.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



November 19, 2020

**WARNING** - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601.

Job 2544205	Truss T18	Truss Type Piggyback Base	Qty 1	Ply 1	IC CONST. - MCNUTT RES. T21943167
Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,					

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:09 2020 Page 1  
ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-rdlOwmKAGNVBL5SIWQz8L9s15OQB37takgeQf3yHgLy  
5-6-0 11-0-0 16-6-6 20-11-8 22-6-7 28-2-4 30-8-8 32-11-8 34-6-0  
5-6-0 5-6-0 5-6-6 4-5-2 1-6-15 5-7-13 2-6-4 2-3-0 1-6-8

Scale = 1:74.0




Plate Offsets (X,Y)--		[1:0-5-14,0-0-3], [6:0-3-0,0-1-12], [8:0-5-8,0-2-0], [20:0-5-0,0-2-4]							
<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>2-0-0</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>in (loc)</b>	<b>l/defl</b>	<b>L/d</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.25	TC 0.72	Vert(LL)	-0.22 20-22	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.89	Vert(CT)	-0.39 20-22	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.43	Horz(CT)	0.12 13	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS					Weight: 270 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2 \*Except\*  
7-19,10-14: 2x4 SP No.3  
WEBS 2x4 SP No.3 \*Except\*  
11-13: 2x6 SP No.2  
SLIDER Left 2x6 SP No.2 1-11-8

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-10-9 oc purlins, except end verticals, and 2-0-0 oc purlins (5-8-0 max.): 6-8.  
BOT CHORD Rigid ceiling directly applied or 4-0-8 oc bracing. Except:  
1 Row at midpt 7-18  
WEBS 1 Row at midpt 5-20, 7-20, 8-17

#### REACTIONS.

(size) 1=0-3-8, 13=0-3-0  
Max Horz 1=390(LC 11)  
Max Uplift 1=472(LC 12), 13=478(LC 13)  
Max Grav 1=1208(LC 1), 13=1309(LC 1)

#### FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-3=-1794/824, 3-5=-1651/822, 5-6=-1221/707, 6-7=-1065/667, 7-8=-1038/655,  
8-9=-1164/655, 9-10=-957/524, 10-11=-578/356, 11-13=-1362/692  
BOT CHORD 1-22=-776/1631, 20-22=-612/1371, 17-18=-358/932, 16-17=-376/860, 15-16=-215/509,  
14-15=-791/328, 10-15=-828/353  
WEBS 5-22=-133/396, 5-20=-601/393, 6-20=-169/394, 18-20=-382/964, 8-18=-261/413,  
9-16=-474/269, 10-16=-307/732, 11-14=-390/965

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=472, 13=478.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**


Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610

Job 2544205	Truss T19	Truss Type Piggyback Base	Qty 2	Ply 1	IC CONST. - MCNUTT RES. T21943168
Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,					

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:11 2020 Page 1  
ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-n?i8LRMqo\_lubPc8dr0cQayQrC56XwxtB\_7XkyyHglw



<div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div>&lt;/</div></div>									
---	--	--	--	--	--	--	--	--	--

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2 "Except"  
3-22,10-14,23-24: 2x4 SP No.3  
WEBS 2x4 SP No.3 "Except"  
11-13: 2x6 SP No.2  
SLIDER Left 2x6 SP No.2 1-10-11

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-4-1 oc purlins, except end verticals, and 2-0-0 oc purlins (4-9-4 max.): 7-8.  
BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.  
WEBS 1 Row at midpt 6-19, 8-17

#### REACTIONS.


(size) 1=0-3-8, 13=0-3-0  
Max Horz 1=390(LC 11)  
Max Uplift 1=472(LC 12), 13=478(LC 13)  
Max Grav 1=1208(LC 1), 13=1309(LC 1)

#### FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-455/205, 2-3=-2809/1298, 3-4=-2918/1382, 4-6=-2061/983, 6-7=-1339/728, 7-8=-1136/689, 8-9=-1163/655, 9-10=-955/525, 10-11=-578/356, 11-13=-1362/692  
BOT CHORD 1-22=-696/1423, 21-22=-562/1168, 20-21=-1055/2274, 19-20=-715/1639, 17-19=-359/934, 16-17=-375/860, 15-16=-215/509, 14-15=-793/329, 10-15=-831/354  
WEBS 2-22=-1619/804, 2-21=-1174/2483, 4-21=-354/736, 4-20=-535/357, 6-20=-231/651, 6-19=-721/443, 7-19=-146/420, 8-19=-215/404, 9-16=-467/266, 10-16=-305/728, 11-14=-391/967

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCCL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=472, 13=478.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610



Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUTT RES.	T21943169
2544205	T20	Piggyback Base	1	1		
Job Reference (optional)						

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:13 2020 Page 1  
ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-jO?vm7NhKc?cqimXIG24W?1lg?nR?ql9fcdpryHglu

1-6-0	3-3-8	5-6-0	11-0-0	16-6-6	22-6-7	28-2-4	30-8-8	32-11-8
1-6-0	1-9-8	2-2-8	5-6-0	5-6-6	6-0-1	5-7-13	2-6-4	2-3-0

Scale = 1:67.7




Plate Offsets (X,Y)--	[1:0-3-4,0-0-7], [2:0-1-5,0-2-4], [7:0-3-0,0-1-12], [8:0-5-8,0-2-0]
-----------------------	---

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.62	Vert(LL)	-0.18 18-19	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.94	Vert(CT)	-0.36 18-19	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.85	Horz(CT)	0.19 12	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS					Weight: 253 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2 "Except"  
3-21,22-23: 2x4 SP No.3  
WEBS 2x4 SP No.3 "Except"  
11-12: 2x6 SP No.2  
OTHERS 2x6 SP No.2  
SLIDER Left 2x6 SP No.2 1-10-11

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-3-14 oc purlins, except end verticals, and 2-0-0 oc purlins (4-8-11 max.): 7-8.  
BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.  
WEBS 1 Row at midpt 6-18, 8-16

#### REACTIONS.

(size) 1=0-3-8, 12=0-3-0  
Max Horz 1=384(LC 11)  
Max Uplift 1=473(LC 12), 12=391(LC 13)  
Max Grav 1=1219(LC 1), 12=1183(LC 1)

#### FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-458/205, 2-3=-2822/1353, 3-4=-2931/1444, 4-6=-2084/997, 6-7=-1361/734,  
7-8=-1151/694, 8-9=-1193/661, 9-10=-1016/535, 10-11=-646/373, 11-12=-1256/588  
BOT CHORD 1-21=-780/1418, 20-21=-632/1164, 19-20=-1170/2272, 18-19=-813/1639, 16-18=-449/960,  
15-16=-461/881, 14-15=-291/540, 13-14=-674/330, 10-14=-719/363  
WEBS 2-21=-1612/903, 2-20=-1305/2478, 4-20=-399/731, 4-19=-533/363, 6-19=-237/649,  
6-18=-720/445, 7-18=-149/429, 8-18=-215/392, 9-15=-432/273, 10-15=-324/696,  
11-13=-395/828

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=473, 12=391.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610

Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUTT RES.	T21943170
2544205	T21	Piggyback Base	2	1		

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,


8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:14 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-BaZHzTOJ5v7TSsLjL\_ZJ2CawYP7VkhHaJuyMBLHyHgt

Job Reference (optional)

1-6-0	3-3-8	5-6-0	11-0-0	16-6-6	17-0-8	22-6-7	28-2-4	32-11-8
1-6-0	1-9-8	2-2-8	5-6-0	5-6-6	0-6-2	5-5-15	5-7-13	4-9-4

Scale = 1:65.9



3-3-8	8-3-0	17-0-8	22-6-7	28-2-4	32-11-8
3-3-8	4-11-8	8-9-8	5-5-15	5-7-13	4-9-4

Plate Offsets (X,Y)-- [1:0-3-4,0-0-7], [2:0-1-5,0-2-4], [7:0-3-0,0-1-12], [9:0-5-8,0-2-0], [16:0-4-8,0-2-12]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.61	Vert(LL)	-0.21 16-17	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.95	Vert(CT)	-0.46 16-17	>868	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.85	Horz(CT)	0.13 12	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS					Weight: 259 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2 "Except"  
3-19,8-15: 2x4 SP No.3  
WEBS 2x4 SP No.3 "Except"  
11-12: 2x6 SP No.2  
OTHERS 2x6 SP No.2  
SLIDER Left 2x6 SP No.2 1-10-11

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 3-3-15 oc purlins, except end verticals, and 2-0-0 oc purlins (5-1-8 max.): 7-9.  
BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing. Except:  
1 Row at midpt 8-16  
WEBS 1 Row at midpt 6-16, 9-14

**REACTIONS.** (size) 1=0-3-8, 12=0-3-0  
Max Horz 1=384(LC 11)  
Max Uplift 1=473(LC 12), 12=391(LC 13)  
Max Grav 1=1219(LC 1), 12=1183(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-2=-458/205, 2-3=-2776/1354, 3-4=-2877/1445, 4-6=-2091/996, 6-7=-1325/719,  
7-8=-1139/694, 8-9=-1138/696, 9-10=-1085/639, 10-11=-912/495, 11-12=-1145/541  
BOT CHORD 1-19=-780/1400, 18-19=-633/1143, 17-18=-1169/2245, 16-17=-813/1605, 13-14=-394/751  
WEBS 2-19=-1583/904, 2-18=-1306/2434, 4-18=-402/717, 4-17=-531/364, 6-17=-233/679,  
6-16=-739/447, 7-16=-235/469, 14-16=-384/896, 9-16=-266/542, 10-14=-177/253,  
10-13=-503/318, 11-13=-386/834

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=473, 12=391.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610



Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUIT RES.	T21943171
2544205	T22	Piggyback Base	2	1		
Job Reference (optional)						


Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:16 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-8zg109QZcXNBhAU5QOcn7dfG4DphCEWclGrHP9yHglr

1-6-0	3-3-8	5-6-0	11-0-0	16-6-6	17-0-8	22-6-7	28-2-4	32-11-8
1-6-0	1-9-8	2-2-8	5-6-0	5-6-6	0-6-2	5-5-15	5-7-13	4-9-4

Scale = 1:65.9



3-3-8	8-3-0	17-0-8	22-6-7	28-2-4	28-4-0	32-11-8
3-3-8	4-11-8	8-9-8	5-5-15	5-7-13	0-1-12	4-7-8

Plate Offsets (X,Y)-- [1:0-3-4,0-0-3], [2:0-1-9,0-2-4], [7:0-3-0,0-1-12], [9:0-5-8,0-2-0], [13:0-3-8,0-3-0], [16:0-4-8,0-2-12], [18:0-2-12,0-2-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.61	Vert(LL)	0.39 16-17	>863	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.84	Vert(CT)	-0.41 16-17	>828	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.69	Horz(CT)	-0.10 13	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS					Weight: 259 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2 "Except"  
3-19,8-15: 2x4 SP No.3  
WEBS 2x4 SP No.3 "Except"  
11-12: 2x6 SP No.2  
OTHERS 2x6 SP No.2  
SLIDER Left 2x6 SP No.2 1-10-11

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 3-8-6 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 7-9.  
BOT CHORD Rigid ceiling directly applied or 3-6-12 oc bracing. Except:  
1 Row at midpt 8-16  
WEBS 1 Row at midpt 6-16, 9-16, 9-14, 10-14, 10-13

**REACTIONS.** (size) 1=0-3-8, 13=0-3-8  
Max Horz 1=476(LC 11)  
Max Uplift 1=468(LC 9), 13=528(LC 9)  
Max Grav 1=1019(LC 1), 13=1383(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-2=-391/451, 2-3=-2346/2661, 3-4=-2428/2806, 4-6=-1673/1905, 6-7=-909/1059,  
7-8=-732/1000, 8-9=-732/997, 9-10=-576/718  
BOT CHORD 1-19=-1543/1214, 18-19=-1246/989, 17-18=-2184/1897, 16-17=-1475/1283,  
8-16=-251/245  
WEBS 4-18=-837/614, 4-17=-477/524, 6-17=-805/658, 6-16=-727/767, 7-16=-389/311,  
14-16=-611/508, 9-16=-702/664, 9-14=-565/479, 10-14=-783/773, 10-13=-1189/1202,  
2-19=-1369/1697, 2-18=-2528/2079

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever right exposed; end vertical right exposed; porch right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=468, 13=528.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601





6904 Parke East Blvd.  
Tampa, FL 33610

Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUTT RES.	T21943172
2544205	T23	Piggyback Base	1	1		
Job Reference (optional)						

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:18 2020 Page 1

ID:n6lffAxwnDhbiCo\_iGpf14cyqw8Q-4MoopqRp88dvwUeUXpeFD2kdE0YZg9MvoaKOU2yHglp



Scale = 1:65.9




Plate Offsets (X,Y)-- [1:0-6-2,Edge], [6:0-3-0,0-1-12], [7:0-5-8,0-2-0], [11:0-3-8,0-3-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.57	Vert(LL)	0.24 14-16	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.69	Vert(CT)	-0.33 14-16	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.61	Horz(CT)	0.03 11	n/a	n/a		
BCDL 10.0	Code FBC2017/TPI2014		Matrix-MS					Weight: 230 lb	FT = 20%


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 3-9-12 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 6-7.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 4-7-8 oc bracing.
WEBS 2x4 SP No.3 *Except*	WEBS 1 Row at midpt 5-14, 7-14, 7-12, 8-12, 8-11
7-14: 2x4 SP No.2, 9-10: 2x6 SP No.2	
OTHERS 2x6 SP No.2	
SLIDER Left 2x6 SP No.2 1-11-8	

**REACTIONS.** (size) 1=0-3-8, 11=0-3-8  
Max Horz 1=384(LC 11)  
Max Uplift 1=470(LC 9), 11=526(LC 9)  
Max Grav 1=1036(LC 19), 11=1392(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-3=-1496/1518, 3-5=-1381/1517, 5-6=-869/1032, 6-7=-700/952, 7-8=-589/717  
BOT CHORD 1-16=-1463/1438, 14-16=-1148/1160, 12-14=-474/482  
WEBS 3-16=-251/237, 5-16=-526/415, 5-14=-608/620, 6-14=-302/213, 7-14=-574/593,  
7-12=-492/383, 8-12=-774/787, 8-11=-1184/1188

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever right exposed; end vertical right exposed; porch right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=470, 11=526.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610

Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUTT RES.	T21943173
2544205	T24	Monopitch	7	1		

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:18 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-4MoopqRp88dwUeUXpeFD2kcU0amgFTvoaKOU2yHglp



Scale = 1:26.7




Plate Offsets (X,Y)-- [2:0-0-14,0-0-5]											
LOADING (psf)		SPACING- 2-0-0		CSI.		DEFL. in (loc) l/defl L/d				PLATES GRIP	
TCLL	20.0	Plate Grip DOL	1.25	TC	0.62	Vert(LL)	0.22	6-9	>441	240	MT20 244/190
TCDL	7.0	Lumber DOL	1.25	BC	0.54	Vert(CT)	0.19	6-9	>510	180	
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.22	Horz(CT)	-0.01	6	n/a	n/a	
BCDL	10.0	Code FBC2017/TPI2014		Matrix-MS						Weight: 42 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 5-4-9 oc bracing.

#### REACTIONS.

(size) 5=Mechanical, 2=0-3-8, 6=0-3-8  
Max Horz 2=176(LC 8)  
Max Uplift 5=-73(LC 8), 2=-290(LC 8), 6=-362(LC 8)  
Max Grav 5=91(LC 1), 2=377(LC 1), 6=448(LC 1)

#### FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-486/578  
BOT CHORD 2-6=-753/467  
WEBS 3-6=-471/724

#### NOTES-

- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5 except (jt=lb) 2=290, 6=362.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 36610

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:19 2020 Page 1  
ID:n6lfAxwnDhbiCo iGpf14cvaw8Q-YYMA1ASSvSlmYdPg5X9UIGHmAQw Pid21E3v0UvHqlo

-1-6-0	4-7-0	8-3-8	11-0-12
1-6-0	4-7-0	3-8-8	2-9-2

Scale: 1/2"=1'




Plate Offsets (X,Y)-- [2:0-0-14,0-0-5]												
LOADING (psf)		SPACING- 2:0-0		CSI.		DEFL. in (loc) l/defl L/d					PLATES GRIP	
TCLL	20.0	Plate Grip DOL	1.25	TC	0.62	Vert(LL)	0.22	6-9	>444	240	MT20	244/190
TCDL	7.0	Lumber DOL	1.25	BC	0.55	Vert(CT)	0.19	6-9	>513	180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.22	Horz(CT)	-0.01	6	n/a	n/a		
BCDL	10.0	Code FBC2017/TPI2014		Matrix-MS							Weight: 40 lb	FT = 20%

<b>LUMBER-</b>		<b>BRACING-</b>	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2		
WEBS	2x4 SP No.3	BOT CHORD	Rigid ceiling directly applied or 5-3-3 oc bracing.


**REACTIONS.** (size) 5=Mechanical, 2=0-3-8, 6=0-3-8  
 Max Horz 2=158(LC 8)  
 Max Uplift 5=-45(LC 8), 2=-299(LC 8), 6=-323(LC 8)  
 Max Grav 5=56(LC 1), 2=382(LC 1), 6=400(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD	2-3=-513/636
BOT CHORD	2-6=-785/494
WEBS	3-6=-487/743

**NOTES-**

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5 except (jt=lb) 2=299, 6=323.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19, 2020

 **WARNING** - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCS1 Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 36610

Job	Truss	Truss Type	Qty	Ply	IC CONST. - MCNUTT RES.	T21943175
2544205	T26	Monopitch	1	1		
Job Reference (optional)						

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:20 2020 Page 1  
ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-0kwYEWt4gldAnotfEgjlTpxzqGR89nBGupVYxyHgln




Plate Offsets (X,Y)--	[2:0-0-14,0-0-5]								
<b>LOADING</b> (psf)		<b>SPACING-</b>	2-0-0	<b>CSI.</b>		<b>DEFL.</b>	in (loc)	l/defl	L/d
TCLL 20.0		Plate Grip DOL	1.25	TC 0.62		Vert(LL)	0.21 5-9	>460	240
TCDL 7.0		Lumber DOL	1.25	BC 0.53		Vert(CT)	0.18 5-9	>531	180
BCLL 0.0 *		Rep Stress Incr	YES	WB 0.23		Horz(CT)	-0.03 6	n/a	n/a
BCDL 10.0		Code FBC2017/TPI2014		Matrix-MS					
						<b>PLATES</b>		<b>GRIP</b>	
						MT20		244/190	
						Weight: 37 lb		FT = 20%	

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 5-2-12 oc bracing.

#### REACTIONS.

(size) 2=0-3-8, 6=0-3-8  
Max Horz 2=123(LC 8)  
Max Uplift 2=-314(LC 8), 6=-239(LC 8)  
Max Grav 2=390(LC 1), 6=294(LC 1)

#### FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-552/717, 5-6=-294/485  
BOT CHORD 2-5=-816/532  
WEBS 3-5=-513/760

#### NOTES-

- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 6 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=314, 6=239.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

#### WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610



8.240 s Mar. 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:21 2020 Page 1

ID:n6lfAxwnDhpiCo\_jGpf14cvqw8Q-UwUwRsUjR30UnxN3DvBvghMCNEgatdbLVYY25NyHgIm






Plate Offsets (X,Y)--	[2:0-3-2,Edge]
-----------------------	----------------



November 19, 2020





6904 Parke East Blvd.  
Tampa, FL 36610

Job 2544205	Truss T29	Truss Type Half Hip Girder	Qty 1	Ply 1	IC CONST. - MCNUTT RES.	T21943178
----------------	--------------	-------------------------------	----------	----------	-------------------------	-----------

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:23 2020 Page 1

ID:n6lfAxwnDhbiCo\_iGpf14cyqw8Q-QJbhsYVyzgGB1FXSKNEQw6RYs1L2LW2eys199FyHglk



Scale = 1:18.4




Plate Offsets (X,Y)--		[2:0-3-2,Edge]									
<b>LOADING</b> (psf)		<b>SPACING-</b> 2-0-0		<b>CSI.</b>		<b>DEFL.</b> in (loc) l/defl L/d		<b>PLATES</b>		<b>GRIP</b>	
TCLL	20.0	Plate Grip DOL	1.25	TC	0.19	Vert(LL)	0.03 8-11 >999 240	MT20		244/190	
TCDL	7.0	Lumber DOL	1.25	BC	0.28	Vert(CT)	-0.04 8-11 >999 180				
BCLL	0.0 *	Rep Stress Incr	NO	WB	0.19	Horz(CT)	-0.01 6 n/a n/a				
BCDL	10.0	Code FBC2017/TPI2014		Matrix-MS				Weight: 40 lb		FT = 20%	

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 7-4-9 oc bracing.

#### REACTIONS.

(size) 2=0-3-8, 6=0-3-8  
Max Horz 2=110(LC 4)  
Max Uplift 2=-364(LC 4), 6=-559(LC 4)  
Max Grav 2=446(LC 1), 6=680(LC 1)

#### FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-816/598, 3-4=-394/297  
BOT CHORD 2-8=-632/777, 7-8=-632/777, 6-7=-333/403  
WEBS 3-7=-447/366, 4-7=-422/508, 4-6=-726/600

#### NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=364, 6=559.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 127 lb down and 127 lb up at 7-0-0 on top chord, and 335 lb down and 365 lb up at 7-0-0 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

#### LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25  
Uniform Loads (plf)  
Vert: 1-4=-54, 4-5=-54, 6-9=-20  
Concentrated Loads (lb)  
Vert: 7=-335(B) 4=-108(B)



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

#### WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.  
Tampa, FL 33610

Job 2544205	Truss T30	Truss Type MONO TRUSS	Qty 16	Ply 1	IC CONST. - MCNUTT RES. Job Reference (optional)	T21943179
----------------	--------------	--------------------------	-----------	----------	---	-----------

Builders FirstSource (Jacksonville, FL), Jacksonville, FL - 32244,

8.240 s Mar 9 2020 MiTek Industries, Inc. Thu Nov 19 08:42:24 2020 Page 1  
ID:n6lIfAxwnDhbiCo\_iGpf14cyqw8Q-vV934uWak\_O2eP6eu4lfSJ\_fxRh84x5nBWnjhiyHglj



Scale = 1:14.5




Plate Offsets (X,Y)--		[2:0-1-10,Edge], [4:Edge,0-1-8]		6-0-0 6-0-0	
<b>LOADING</b> (psf)		<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>
TCLL 20.0		Plate Grip DOL	1.25	TC 0.49	in (loc) l/defl L/d
TCDL 7.0		Lumber DOL	1.25	BC 0.29	Vert(LL) 0.06 4-8 >999 240
BCLL 0.0 *		Rep Stress Incr	YES	WB 0.33	Vert(CT) 0.05 4-8 >999 180
BCDL 10.0		Code FBC2017/TPI2014		Matrix-MR	Horz(CT) -0.00 2 n/a n/a
				<b>PLATES</b>	<b>GRIP</b>
				MT20	244/190
				Weight: 23 lb	FT = 20%

#### LUMBER-

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3  
OTHERS 2x4 SP No.3

#### BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 9-2-7 oc bracing.

#### REACTIONS.

(size) 2=0-3-8, 9=0-2-0  
Max Horz 2=92(LC 8)  
Max Uplift 2=-257(LC 8), 9=-147(LC 8)  
Max Grav 2=309(LC 1), 9=183(LC 1)

#### FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-223/317  
BOT CHORD 2-4=-359/201

#### NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=18ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Bearing at joint(s) 9 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 5) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 9.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (it=lb) 2=257, 9=147.



Julius Lee PE No.34869  
MiTek USA, Inc. FL Cert 6634  
6904 Parke East Blvd. Tampa FL 33610  
Date:

November 19,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601





6904 Parke East Blvd.  
Tampa, FL 33610



# Symbols

## PLATE LOCATION AND ORIENTATION



For 4 x 2 orientation, locate plates 0- 1/16" from outside edge of truss.

This symbol indicates the required direction of slots in connector plates.

## PLATE SIZE


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

## LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.


## BEARING



Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number where bearings occur. Min size shown is for crushing only.

**Industry Standards:**  
ANSI/TPI 1: National Design Specification for Metal Plate Connected Wood Truss Construction.  
DSB-89: Design Standard for Bracing.  
BCSI: Building Component Safety Information, Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses.

# Numbering System



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

## PRODUCT CODE APPROVALS

ICC-ES Reports:  
ESR-1311, ESR-1352, ESR1988  
ER-3907, ESR-2362, ESR-1397, ESR-3282

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TPI 1 section 6.3 These truss designs rely on lumber values established by others.

© 2012 MITek® All Rights Reserved



Mitek Engineering Reference Sheet: MII-7473 rev. 5/19/2020

# General Safety Notes

## Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TPI 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TPI 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TPI 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.