
Roof Replacement or Repair Application #73755





Checklist:					
AddressDrive/ROWSepticSite Use ApprovedDocs Reviewed/Accepted	ApplicationZoning ReviePlans RevievRequired Ins	ew	Flood Zo		
APPLICANT: Tanesha Bouthner			PHONE : (81	3) 464-9965	
ADDRESS: 1130 1st Street South Winte	er Haven FL 33880				
OWNER: VAUGHN PEGGY E,			PHONE : (30	PHONE : (305) 301-1904	
ADDRESS: 483 SW LONG LEAF DR L	AKE CITY, FL 32024				
PARCEL ID: 16-4S-16-03048-004	S	UBDIVISION: FORE	EST COUNTRY P	HASE 1	
LOT: 4 BLOCK:	PHASE:		UNIT:	ACRES: 0.77	
CONTRACTOR	TYPE	LIC#	BUSINESS NA	AME	
Tanesha Bouthner	General	CCC1335469	Solar Roofing	& Construction Specialist Corp	
ROOFING JOB DETAILS	·				
Type Roofing Job			Re	placement - Tear off Existing and Replace	
Further Job Details (Explain if decking is b	peing replaced and or Repa	irs are being done.)	Remove exist	ing shingle roof and replace with Titan XT shingles	
Type of structure				House	
Further Structure Details (if needed)				Single family residence	
Total Estimated Cost				26308	
Commercial or Residential				Residential	
Roof Area (for this job) Sq Ft				3946	
No. of Stories				1	
Ventilation:				Ridge Vent	
Flashing:				Replace All	
Drip Edge:				Replace All	
Valley Treatment:				New Mineral Surface	
Roof Pitch				4:12 or Greater	
Second Roof Pitch (if applicable)					
Any cable and/or race-way wiring located	on or within the roof assem	bly?		No	
Is the existing roof being removed?				Yes	
Explain if not removing the existing roofing	g material?				
Type of New Roofing Product				Asphalt Shingles	
Florida Product Approval Number				18355.1	
Product Manufacturer				TAMKO Building Products LLC	
Product Description				Titan XT Shingles	
Other Roofing Product Type Not Listed					

Sealed roof decking options: (Must select an option.)	a minimum 4-inch wide strip of selfadhering polymer- modified bitumen complying with ASTM D1970 or a minimum 3 ¾ - inch wide strip of selfadhering flexible flashing tape complying with AAMA 711, applied over all joints in the roof decking. A felt underlayment complying with ASTM D226 Type II, ASTM D4869 Type III or IV, or ASTM D6757, or a synthetic underlayment meeting the performance requirements specified, is required to be applied over the strips/tape over the entire roof.
Sealed roof decking explanation for other option.	
Review Notes:	