

DATE 08/14/2007

Columbia County Building Permit

PERMIT

This Permit Expires One Year From the Date of Issue

000026123

APPLICANT WADE WILLIS PHONE 961-9962

ADDRESS P.O. BOX 1546 LAKE CITY FL 32056

OWNER WADE WILLIS PHONE 961-9962

ADDRESS 686 SW CHESTERFIELD DR LAKE CITY FL 32024

CONTRACTOR WADE WILLIS PHONE 961-9962

LOCATION OF PROPERTY 47S, TR ON 242, TR ON ARROWHEAD RD, TL ON CANNON CREEK,
TL CROSSWINDS, TR ON CHESTERFIELD CIRCLE, 6TH LOT ON LEFT

TYPE DEVELOPMENT SFD,UTILITY ESTIMATED COST OF CONSTRUCTION 73900.00

HEATED FLOOR AREA 1478.00 TOTAL AREA 1936.00 HEIGHT STORIES 1

FOUNDATION CONC WALLS FRAMED ROOF PITCH 6/12 FLOOR SLAB

LAND USE & ZONING RSF-2 MAX. HEIGHT 16

Minimum Set Back Requirments: STREET-FRONT 25.00 REAR 15.00 SIDE 10.00

NO. EX.D.U. 0 FLOOD ZONE X PP DEVELOPMENT PERMIT NO.

PARCEL ID 24-4S-16-03117-139 SUBDIVISION CROSSWINDS

LOT 39 BLOCK PHASE UNIT TOTAL ACRES 0.57

000001433 CBC1252441

Culvert Permit No. Culvert Waiver Contractor's License Number Applicant/Owner/Contractor

CULVERT 07-231 BK JH Y

Driveway Connection Septic Tank Number LU & Zoning checked by Approved for Issuance New Resident

COMMENTS: ONE FOOT ABOVE THE ROAD, NOC ON FILE

COMPACTION TEST RECEIVED

Check # or Cash 1637

FOR BUILDING & ZONING DEPARTMENT ONLY

(footer/Slab)

Temporary Power date/app. by Foundation date/app. by Monolithic date/app. by

Under slab rough-in plumbing date/app. by Slab date/app. by Sheathing/Nailing date/app. by

Framing date/app. by Rough-in plumbing above slab and below wood floor date/app. by

Electrical rough-in date/app. by Heat & Air Duct date/app. by Peri. beam (Lintel) date/app. by

Permanent power date/app. by C.O. Final date/app. by Culvert date/app. by

M/H tie downs, blocking, electricity and plumbing date/app. by Pool date/app. by

Reconnection date/app. by Pump pole date/app. by Utility Pole date/app. by

M/H Pole date/app. by Travel Trailer date/app. by Re-roof date/app. by

BUILDING PERMIT FEE \$ 370.00 CERTIFICATION FEE \$ 9.68 SURCHARGE FEE \$ 9.68

MISC. FEES \$ 0.00 ZONING CERT. FEE \$ 50.00 FIRE FEE \$ 0.00 WASTE FEE \$

FLOOD DEVELOPMENT FEE \$ FLOOD ZONE FEE \$ 25.00 CULVERT FEE \$ 25.00 TOTAL FEE 489.36

INSPECTORS OFFICE CLERKS OFFICE

NOTICE: IN ADDITION TO THE REQUIREMENTS OF THIS PERMIT, THERE MAY BE ADDITIONAL RESTRICTIONS APPLICABLE TO THIS PROPERTY THAT MAY BE FOUND IN THE PUBLIC RECORDS OF THIS COUNTY. AND THERE MAY BE ADDITIONAL PERMITS REQUIRED FROM OTHER GOVERNMENTAL ENTITIES SUCH AS WATER MANAGEMENT DISTRICTS, STATE AGENCIES, OR FEDERAL AGENCIES.

"WARNING TO OWNER: YOUR FAILURE TO RECORD A NOTICE OF COMMENCEMENT MAY RESULT IN YOUR PAYING TWICE FOR IMPROVEMENTS TO YOUR PROPERTY. IF YOU INTEND TO OBTAIN FINANCING, CONSULT WITH YOUR LENDER OR AN ATTORNEY BEFORE RECORDING YOUR NOTICE OF COMMENCEMENT."

This Permit Must Be Prominently Posted on Premises During Construction

PLEASE NOTIFY THE COLUMBIA COUNTY BUILDING DEPARTMENT AT LEAST 24 HOURS IN ADVANCE OF EACH INSPECTION, IN ORDER THAT IT MAY BE MADE WITHOUT DELAY OR INCONVENIENCE, PHONE 758-1008. THIS PERMIT IS NOT VALID UNLESS THE WORK AUTHORIZED BY IT IS COMMENCED WITHIN 6 MONTHS AFTER ISSUANCE.

The Issuance of this Permit Does Not Waive Compliance by Permittee with Deed Restrictions.

1st message 8/8/07

Columbia County Building Permit Application

For Office Use Only Application # 0708-01 Date Received 8/1 By JW Permit # 1433, 26123
Application Approved by - Zoning Official BLK Date 08.08.07 Plans Examiner OKJTH Date 8-2-07
Flood Zone APR plot Development Permit N/A Zoning RSF-2 Land Use Plan Map Category RES. Low Dev.
Comments Finished floor 1st. above Rd.
☐ NOC ☒ EH ☐ Deed or PA ☐ Site Plan ☐ State Road Info ☐ Parent Parcel # ☐ Development Permit

Name Authorized Person Signing Permit Wade Willis Fax _____ Phone _____

Address _____

Owners Name Wade Willis Construction Phone 961 9962

911 Address 686 SW Chesterfield, LAKE CITY, FL 32024

Contractors Name Wade Willis Construction Phone 961 9962

Address PO Box 1546 LC 32056

Fee Simple Owner Name & Address _____

Bonding Co. Name & Address _____

Architect/Engineer Name & Address Mark Disabney

Mortgage Lenders Name & Address CASH

Circle the correct power company - FL Power & Light - Clay Elec. - Suwannee Valley Elec. - Progressive Energy

Property ID Number 24-45-16-03117-139 Estimated Cost of Construction 150,000

Subdivision Name Crosswinds Lot 39 Block _____ Unit _____ Phase _____

Driving Directions SR 47 south, Turn Rt 242, turn Rt Arrowhead R,
TL on cannon creek, TL into crosswinds, TR Chesterfield Circle
it's the 1st lot on the left

Type of Construction New construction single Number of Existing Dwellings on Property NA

Total Acreage .57 Lot Size _____ Do you need a - Culvert Permit or Culvert Waiver or Have an Existing Drive

Actual Distance of Structure from Property Lines - Front 50 Side 10 Side 35 Rear 125

Total Building Height 16' 10" Number of Stories 1 Heated Floor Area 1478 Roof Pitch 6/12
TOTAL 1936

Application is hereby made to obtain a permit to do work and installations as indicated. I certify that no work or installation has commenced prior to the issuance of a permit and that all work be performed to meet the standards of all laws regulating construction in this jurisdiction.

OWNERS AFFIDAVIT: I hereby certify that all the foregoing information is accurate and all work will be done in compliance with all applicable laws and regulating construction and zoning.

WARNING TO OWNER: YOUR FAILURE TO RECORD A NOTICE OF COMMENCEMENT MAY RESULT IN YOU PAYING TWICE FOR IMPROVEMENTS TO YOUR PROPERTY. IF YOU INTEND TO OBTAIN FINANCING, CONSULT WITH YOUR LENDER OR ATTORNEY BEFORE RECORDING YOUR NOTICE OF COMMENCEMENT.

Wade Scott Willis

Owner Builder or Authorized Person by Notarized Letter

STATE OF FLORIDA
COUNTY OF COLUMBIA

Sworn to (or affirmed) and subscribed before me

this 1st day of August 20 07

Personally known _____ or Produced Identification ☒

Contractor Signature
Contractors License Number BC 1252491
Competency Card Number _____

NOTARY STAMP/SEAL S. EPPERSON
Notary Public - State of Florida
My Commission Expires Aug 29, 2009
Commission # DD466928
Bonded by National Notary Assn.

Notary Signature

(Revised Sept. 2006)

UNIVERSAL

ENGINEERING SCIENCES

**Consultants In: Geotechnical Engineering •
Environmental Sciences • Construction Materials Testing**

REPORT ON IN-PLACE DENSITY TESTS

4475 S.W. 35th Terrace • Gainesville, Florida 32608 • (352) 372-3392

CLIENT: Wade W. S. Conner

PROJECT: 686 SW Chesterfield Rd Lot 39

AREA TESTED: B/F to prop bldg pool

COURSE: 516

DEPTH OF TEST: 0' - 1'

TYPE OF TEST: ASTM D-2922

DATE TESTED: 8-7-67

NOTE: The below tests ~~DO/DO NOT~~ meet the minimum 95 % compaction requirements of maximum density.

REMARKS:

[illegible]

TECH.

FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Community Affairs Residential Whole Building Performance Method A

Project Name:	702263WadeWillisConstruction	Builder:	<i>Wade Willis</i>
Address:	Lot: 39, Sub: Crosswinds, Plat:	Permitting Office:	<i>DAWNB</i>
City, State:	, FL	Permit Number:	<i>26123</i>
Owner:	Spec House Lot 39 Crosswinds S/D	Jurisdiction Number:	<i>221000</i>
Climate Zone:	North		

1. New construction or existing	New	12. Cooling systems	
2. Single family or multi-family	Single family	a. Central Unit	Cap: 32.0 kBtu/hr
3. Number of units, if multi-family	1		SEER: 13.00
4. Number of Bedrooms	3	b. N/A	
5. Is this a worst case?	Yes	c. N/A	
6. Conditioned floor area (ft²)	1478 ft²	13. Heating systems	
7. Glass type ¹ and area: (Label reqd. by 13-104.4.5 if not default)		a. Electric Heat Pump	Cap: 32.0 kBtu/hr
a. U-factor:	Description Area		HSPF: 7.90
(or Single or Double DEFAULT)	7a. (Dble Default) 160.0 ft²	b. N/A	
b. SHGC:		c. N/A	
(or Clear or Tint DEFAULT)	7b. (Clear) 160.0 ft²	14. Hot water systems	
8. Floor types		a. Electric Resistance	Cap: 40.0 gallons
a. Slab-On-Grade Edge Insulation	R=0.0, 180.0(p) ft		EF: 0.93
b. N/A		b. N/A	
c. N/A		c. Conservation credits	
9. Wall types		(HR-Heat recovery, Solar	
a. Frame, Wood, Exterior	R=13.0, 1040.0 ft²	DHP-Dedicated heat pump)	
b. Frame, Wood, Adjacent	R=13.0, 180.0 ft²	15. HVAC credits	
c. N/A		(CF-Ceiling fan, CV-Cross ventilation,	
d. N/A		HF-Whole house fan,	
e. N/A		PT-Programmable Thermostat,	
10. Ceiling types		MZ-C-Multizone cooling,	
a. Under Attic	R=30.0, 1558.0 ft²	MZ-H-Multizone heating)	
b. N/A			
c. N/A			
11. Ducts			
a. Sup: Unc. Ret: Unc. AH: Interior	Sup. R=6.0, 150.0 ft		
b. N/A			

Glass/Floor Area: 0.11

Total as-built points: 19908

Total base points: 23376

PASS

I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.

PREPARED BY: *[Signature]*
DATE: *3-19-07*

I hereby certify that this building, as designed, is in compliance with the Florida Energy Code.

OWNER/AGENT: _____
DATE: _____

Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.

BUILDING OFFICIAL: _____
DATE: _____



¹ Predominant glass type. For actual glass type and areas, see Summer & Winter Glass output on pages 2&4.

SUMMER CALCULATIONS

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 39, Sub: Crosswinds, Plat: , , FL,

PERMIT #:

BASE				AS-BUILT							
GLASS TYPES .18 X Conditioned X BSPM = Points Floor Area				Type/SC Overhang Ornt Len Hgt Area X SPM X SOF = Points							
.18	1478.0	20.04	5331.4	Double, Clear	NW	1.5	5.5	30.0	25.97	0.91	710.4
				Double, Clear	NW	1.5	5.5	20.0	25.97	0.91	473.6
				Double, Clear	NW	1.5	5.5	30.0	25.97	0.91	710.4
				Double, Clear	NE	1.5	5.5	20.0	29.56	0.91	535.3
				Double, Clear	SE	1.5	0.0	30.0	42.75	0.38	486.7
				Double, Clear	SE	1.5	5.5	30.0	42.75	0.86	1104.3
				As-Built Total:							
WALL TYPES Area X BSPM = Points				Type R-Value Area X SPM = Points							
Adjacent	180.0	0.70	126.0	Frame, Wood, Exterior			13.0	1040.0	1.50	1560.0	
Exterior	1040.0	1.70	1768.0	Frame, Wood, Adjacent			13.0	180.0	0.60	108.0	
Base Total:		1220.0	1894.0	As-Built Total:				1220.0	1668.0		
DOOR TYPES Area X BSPM = Points				Type Area X SPM = Points							
Adjacent	20.0	1.60	32.0	Exterior Insulated			20.0	4.10	82.0		
Exterior	40.0	4.10	164.0	Exterior Insulated			20.0	4.10	82.0		
				Adjacent Insulated			20.0	1.60	32.0		
Base Total:		60.0	196.0	As-Built Total:				60.0	196.0		
CEILING TYPES Area X BSPM = Points				Type R-Value Area X SPM X SCM = Points							
Under Attic	1478.0	1.73	2556.9	Under Attic			30.0	1558.0	1.73 X 1.00	2695.3	
Base Total:		1478.0	2556.9	As-Built Total:				1558.0	2695.3		
FLOOR TYPES Area X BSPM = Points				Type R-Value Area X SPM = Points							
Slab	180.0(p)	-37.0	-6660.0	Slab-On-Grade Edge Insulation			0.0	180.0(p)	-41.20	-7416.0	
Raised	0.0	0.00	0.0								
Base Total:		-6660.0		As-Built Total:				180.0	-7416.0		
INFILTRATION Area X BSPM = Points				Area X SPM = Points							
		1478.0	10.21	15090.4					1478.0	10.21	15090.4

SUMMER CALCULATIONS**Residential Whole Building Performance Method A - Details**

ADDRESS: Lot: 39, Sub: Crosswinds, Plat: , , FL,

PERMIT #:

BASE				AS-BUILT						
Summer Base Points: 18408.8				Summer As-Built Points: 16254.2						
Total Summer Points	X System Multiplier	=	Cooling Points	Total Component (System - Points)	X Cap Ratio (DM x DSM x AHU)	X Duct Multiplier	X System Multiplier	X Credit Multiplier	=	Cooling Points
18408.8	0.4266		7853.2	(sys 1: Central Unit 32000 btuh ,SEER/EFF(13.0) Ducts:Unc(S),Unc(R),Int(AH),R6.0(INS) 16254 1.00 (1.09 x 1.147 x 0.91) 0.263 1.000 4855.0 16254.2 1.00 1.138 0.263 1.000 4855.0						

WINTER CALCULATIONS

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 39, Sub: Crosswinds, Plat: , , FL,

PERMIT #:

BASE				AS-BUILT							
GLASS TYPES .18 X Conditioned X BWPM = Points Floor Area				Type/SC	Overhang Ornt Len Hgt		Area X WPM X WOF = Points				
.18	1478.0	12.74	3389.3	Double, Clear	NW	1.5	5.5	30.0	24.30	1.00	731.9
				Double, Clear	NW	1.5	5.5	20.0	24.30	1.00	487.9
				Double, Clear	NW	1.5	5.5	30.0	24.30	1.00	731.9
				Double, Clear	NE	1.5	5.5	20.0	23.57	1.01	475.1
				Double, Clear	SE	1.5	0.0	30.0	14.71	2.65	1169.1
				Double, Clear	SE	1.5	5.5	30.0	14.71	1.11	491.5
				As-Built Total:				160.0			
WALL TYPES Area X BWPM = Points				Type	R-Value		Area X WPM = Points				
Adjacent	180.0	3.60	648.0	Frame, Wood, Exterior	13.0		1040.0	3.40		3536.0	
Exterior	1040.0	3.70	3848.0	Frame, Wood, Adjacent	13.0		180.0	3.30		594.0	
Base Total:		1220.0	4496.0	As-Built Total:		1220.0		4130.0			
DOOR TYPES Area X BWPM = Points				Type			Area X WPM = Points				
Adjacent	20.0	8.00	160.0	Exterior Insulated			20.0	8.40		168.0	
Exterior	40.0	8.40	336.0	Exterior Insulated			20.0	8.40		168.0	
				Adjacent Insulated			20.0	8.00		160.0	
Base Total:		60.0	496.0	As-Built Total:		60.0		496.0			
CEILING TYPESArea X BWPM = Points				Type	R-Value		Area X WPM X WCM = Points				
Under Attic	1478.0	2.05	3029.9	Under Attic	30.0		1558.0	2.05 X 1.00		3193.9	
Base Total:		1478.0	3029.9	As-Built Total:		1558.0		3193.9			
FLOOR TYPES Area X BWPM = Points				Type	R-Value		Area X WPM = Points				
Slab	180.0(p)	8.9	1602.0	Slab-On-Grade Edge Insulation	0.0		180.0(p)	18.80		3384.0	
Raised	0.0	0.00	0.0								
Base Total:		1602.0	As-Built Total:	180.0		3384.0					
INFILTRATION Area X BWPM = Points				Area X WPM = Points							
1478.0		-0.59	-872.0	1478.0		-0.59		-872.0			

WINTER CALCULATIONS

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 39, Sub: Crosswinds, Plat: , , FL,

PERMIT #:

BASE				AS-BUILT									
Winter Base Points: 12141.2				Winter As-Built Points: 14419.3									
Total Winter Points	X	System Multiplier	= Heating Points	Total Component (System - Points)	X	Cap Ratio	X	Duct Multiplier (DM x DSM x AHU)	X	System Multiplier	X	Credit Multiplier	= Heating Points
12141.2		0.6274	7617.4	(sys 1: Electric Heat Pump 32000 btuh ,EFF(7.9) Ducts:Unc(S),Unc(R),Int(AH),R6.0 14419.3 1.000 (1.069 x 1.169 x 0.93) 0.432 1.000 7233.5 14419.3 1.00 1.162 0.432 1.000 7233.5									

WATER HEATING & CODE COMPLIANCE STATUS

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 39, Sub: Crosswinds, Plat: , , FL,

PERMIT #:

BASE				AS-BUILT					
WATER HEATING									
Number of Bedrooms	X	Multiplier	= Total	Tank Volume	EF	Number of Bedrooms	X Tank X Ratio	Multiplier X Credit	= Total Multiplier
3		2635.00	7905.0	40.0	0.93	3	1.00	2606.67	7820.0
				As-Built Total:					7820.0

CODE COMPLIANCE STATUS

BASE				AS-BUILT			
Cooling Points	+	Heating Points	= Total Points	Cooling Points	+	Heating Points	= Total Points
7853		7617	7905	4855		7233	7820
			23376				19908

PASS

Code Compliance Checklist

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 39, Sub: Crosswinds, Plat: , , FL,

PERMIT #:

6A-21 INFILTRATION REDUCTION COMPLIANCE CHECKLIST

COMPONENTS	SECTION	REQUIREMENTS FOR EACH PRACTICE	CHECK
Exterior Windows & Doors	606.1.ABC.1.1	Maximum: .3 cfm/sq.ft. window area; .5 cfm/sq.ft. door area.	
Exterior & Adjacent Walls	606.1.ABC.1.2.1	Caulk, gasket, weatherstrip or seal between: windows/doors & frames, surrounding wall; foundation & wall sole or sill plate; joints between exterior wall panels at corners; utility penetrations; between wall panels & top/bottom plates; between walls and floor. EXCEPTION: Frame walls where a continuous infiltration barrier is installed that extends from, and is sealed to, the foundation to the top plate.	
Floors	606.1.ABC.1.2.2	Penetrations/openings >1/8" sealed unless backed by truss or joint members. EXCEPTION: Frame floors where a continuous infiltration barrier is installed that is sealed to the perimeter, penetrations and seams.	
Ceilings	606.1.ABC.1.2.3	Between walls & ceilings; penetrations of ceiling plane of top floor; around shafts, chases, soffits, chimneys, cabinets sealed to continuous air barrier; gaps in gyp board & top plate; attic access. EXCEPTION: Frame ceilings where a continuous infiltration barrier is installed that is sealed at the perimeter, at penetrations and seams.	
Recessed Lighting Fixtures	606.1.ABC.1.2.4	Type IC rated with no penetrations, sealed; or Type IC or non-IC rated, installed inside a sealed box with 1/2" clearance & 3" from insulation; or Type IC rated with < 2.0 cfm from conditioned space, tested.	
Multi-story Houses	606.1.ABC.1.2.5	Air barrier on perimeter of floor cavity between floors.	
Additional Infiltration reqts	606.1.ABC.1.3	Exhaust fans vented to outdoors, dampers; combustion space heaters comply with NFPA, have combustion air.	

6A-22 OTHER PRESCRIPTIVE MEASURES (must be met or exceeded by all residences.)

COMPONENTS	SECTION	REQUIREMENTS	CHECK
Water Heaters	612.1	Comply with efficiency requirements in Table 612.1.ABC.3.2. Switch or clearly marked circuit breaker (electric) or cutoff (gas) must be provided. External or built-in heat trap required.	
Swimming Pools & Spas	612.1	Spas & heated pools must have covers (except solar heated). Non-commercial pools must have a pump timer. Gas spa & pool heaters must have a minimum thermal efficiency of 78%.	
Shower heads	612.1	Water flow must be restricted to no more than 2.5 gallons per minute at 80 PSIG.	
Air Distribution Systems	610.1	All ducts, fittings, mechanical equipment and plenum chambers shall be mechanically attached, sealed, insulated, and installed in accordance with the criteria of Section 610. Ducts in unconditioned attics: R-6 min. insulation.	
HVAC Controls	607.1	Separate readily accessible manual or automatic thermostat for each system.	
Insulation	604.1, 602.1	Ceilings-Min. R-19. Common walls-Frame R-11 or CBS R-3 both sides. Common ceiling & floors R-11.	

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE SCORE* = 86.1

The higher the score, the more efficient the home.

Spec House Lot 39 Crosswinds S/D, Lot: 39, Sub: Crosswinds, Plat: , FL,

1. New construction or existing	New	___	12. Cooling systems	
2. Single family or multi-family	Single family	___	a. Central Unit	Cap: 32.0 kBtu/hr
3. Number of units, if multi-family	1	___		SEER: 13.00
4. Number of Bedrooms	3	___	b. N/A	___
5. Is this a worst case?	Yes	___	c. N/A	___
6. Conditioned floor area (ft²)	1478 ft²	___		___
7. Glass type ¹ and area: (Label reqd. by 13-104.4.5 if not default)		___	13. Heating systems	
a. U-factor:	Description Area	___	a. Electric Heat Pump	Cap: 32.0 kBtu/hr
(or Single or Double DEFAULT)	7a. (Dble Default) 160.0 ft²	___		HSPF: 7.90
b. SHGC:		___	b. N/A	___
(or Clear or Tint DEFAULT)	7b. (Clear) 160.0 ft²	___	c. N/A	___
8. Floor types		___	14. Hot water systems	
a. Slab-On-Grade Edge Insulation	R=0.0, 180.0(p) ft	___	a. Electric Resistance	Cap: 40.0 gallons
b. N/A	___	___		EF: 0.93
c. N/A	___	___	b. N/A	___
9. Wall types		___	c. Conservation credits	___
a. Frame, Wood, Exterior	R=13.0, 1040.0 ft²	___	(HR-Heat recovery, Solar	___
b. Frame, Wood, Adjacent	R=13.0, 180.0 ft²	___	DHP-Dedicated heat pump)	___
c. N/A	___	___	15. HVAC credits	___
d. N/A	___	___	(CF-Ceiling fan, CV-Cross ventilation,	___
e. N/A	___	___	HF-Whole house fan,	___
10. Ceiling types		___	PT-Programmable Thermostat,	___
a. Under Attic	R=30.0, 1558.0 ft²	___	MZ-C-Multizone cooling,	___
b. N/A	___	___	MZ-H-Multizone heating)	___
c. N/A	___	___		___
11. Ducts		___		___
a. Sup: Unc. Ret: Unc. AH: Interior	Sup. R=6.0, 150.0 ft	___		___
b. N/A	___	___		___

I certify that this home has complied with the Florida Energy Efficiency Code For Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature: _____ Date: _____

Address of New Home: _____ City/FL Zip: _____




**NOTE: The home's estimated energy performance score is only available through the FLA/RES computer program. This is not a Building Energy Rating. If your score is 80 or greater (or 86 for a US EPA/DOE EnergyStarTM designation), your home may qualify for energy efficiency mortgage (EEM) incentives if you obtain a Florida Energy Gauge Rating. Contact the Energy Gauge Hotline at 321/638-1492 or see the Energy Gauge web site at www.fsec.ucf.edu for information and a list of certified Raters. For information about Florida's Energy Efficiency Code For Building Construction, contact the Department of Community Affairs at 850/487-1824.*

**Application for Onsite Sewage Disposal System
Construction Permit. Part II Site Plan**
Permit Application Number: _____

ALL CHANGES MUST BE APPROVED BY THE COUNTY HEALTH UNIT

WILLIS/CR 06-3918

Crosswinds Phase 1, Lot 39




Site Plan Submitted By _____ Date _____
 Plan Approved _____ Not Approved _____ Date _____

By _____ CPHU

Notes: _____

23 May 2006

Scale: 1 inch = 300 feet



THIS INSTRUMENT WAS PREPARED BY:

TERRY McDAVID 06-593
POST OFFICE BOX 1328
LAKE CITY, FL 32056-1328

RETURN TO:

TERRY McDAVID
POST OFFICE BOX 1328
LAKE CITY, FL 32056-1328

Inst:2006026346 Date:11/06/2006 Time:12:58

Doc Stamp-Deed : 700.00

4.2 DC, P. Dewitt Cason, Columbia County B:1101 P:749

Property Appraiser's
Parcel Identification No. Part of R03117-000 & R03117-001

WARRANTY DEED

THIS INDENTURE, made this 2nd day of November, 2006, between DELTA OMEGA PROPERTIES, INC., a corporation existing under the laws of the State of Florida, whose post office address is: 3454 SW CR 242, Lake City, FL 32024 and having its principal place of business in the County of Columbia, State of Florida, party of the first part, and WADE WILLIS CONSTRUCTION, LLC, A Florida Limited Liability, whose Document No. is L04000040779 and FEI No. is 20124-550, whose post office address is: Post Office Box 1546, Lake City, FL 32056, of the State of Florida, party of the second part,

WITNESSETH: that the said party of the first part, for and in consideration of the sum of Ten Dollars (\$10.00), to it in hand paid, the receipt whereof is hereby acknowledged, has granted, bargained, sold, aliened, remised, released, conveyed and confirmed, and by these presents doth grant, bargain, sell, alien, remise, release, convey and confirm unto the said party of the second part, their heirs and assigns forever, all that certain parcel of land lying and being in the County of Columbia and State of Florida, more particularly described as follows:

Lots 39 and 59, CROSSWINDS, Phase One, a subdivision according to the plat thereof as recorded in Plat Book 8, Pages 79-82 of the public records of Columbia County, Florida.

SUBJECT TO: Restrictions, easements and outstanding mineral rights of record, if any, and taxes for the current year.

TOGETHER with all the tenements, hereditaments and appurtenances, with every privilege, right, title, interest and estate, reversion, remainder and easement thereto belong or in anyway appertaining:

TO HAVE AND TO HOLD the same in fee simple forever.

And the said party of the first part doth covenant with said

party of the second part that it is lawfully seized of said premises; that they are free of all encumbrances, and that it has good right and lawful authority to sell the same; and the said party of the first part does hereby fully warrant the title to said land, and will defend the same against the lawful claims of all persons whomsoever.


IN WITNESS WHEREOF, the party of the first part has caused these presents to be signed in its name by its President, the day and year above written.

Signed, sealed and delivered
in our presence:

DELTA OMEGA PROPERTIES, INC.


Witness: Terry McDavid


By: JAMES R. SMITHEY, President


Witness: Crystal L. Brunner


STATE OF FLORIDA
COUNTY OF COLUMBIA

The foregoing instrument was acknowledged before me this 2nd day of November, 2006, by JAMES R. SMITHEY, as President of DELTA OMEGA PROPERTIES, INC., a State of Florida corporation, on behalf of the corporation. He is personally known to me and did not take an oath.

(Seal)


Notary Public

My Commission Expires: _____



Inst:2006026346 Date:11/06/2006 Time:12:58
Doc Stamp-Deed : 700.00
DC,P.Dewitt Cason,Columbia County B:1101 P:750

HALL'S PUMP & WELL SERVICE, INC.

SPECIALIZING IN 4"-8" WELLS



DONALD AND MARY HALL
OWNERS

PHONE (904) 762-1864
FAX (904) 765-7022
XXXXXXXXXXXXXXXXXXXXX
LAKE CITY, FLORIDA 32055
904 NW Main Blvd.


June 12, 2002

NOTICE TO ALL CONTRACTORS

Please be advised that due to the new building codes we will use a large capacity diaphragm tank on all new wells. This will insure a minimum of one (1) minute draw down or one (1) minute refill. If a smaller diaphragm tank is used then we will install a cycle stop valve which will produce the same results.

If you have any questions please feel free to call our office anytime.

Thank you,



Donald D. Hall
DDH/jk

**Application for Onsite Sewage Disposal System
Construction Permit. Part II Site Plan**
Permit Application Number: 07-231

ALL CHANGES MUST BE APPROVED BY THE COUNTY HEALTH UNIT

WILLIS/CR 06-3918

Crosswinds Phase 1, Lot 39



Site Plan Submitted By Paul Lep Date 3/25/07
Plan Approved ☒ Not Approved ☐ Date 3/23/07
By Wade Willis Columbin CPHU

Notes: _____

Columbia County Building Department Culvert Permit

Culvert Permit No.
000001433

DATE 08/14/2007 PARCEL ID # 24-4S-16-03117-139

APPLICANT WADE WILLIS PHONE 961-9962

ADDRESS P.O. BOX 1546 LAKE CITY FL 32056

OWNER WADE WILLIS PHONE 961-9962

ADDRESS 686 SW CHESTERFIELD DR LAKE CITY FL 32024

CONTRACTOR WADE WILLIS PHONE 961-9962

LOCATION OF PROPERTY 47S, TR ON 242, TR ON ARROWHEAD RD, TL ON CANNON CREEK,
TL CROSSWINDS, TR ON CHESTERFIELD CIRCLE, 6TH LOT ON LEFT

SUBDIVISION/LOT/BLOCK/PHASE/UNIT CROSSWINDS 39

SIGNATURE

INSTALLATION REQUIREMENTS



Culvert size will be 18 inches in diameter with a total length of 32 feet, leaving 24 feet of driving surface. Both ends will be mitered 4 foot with a 4 : 1 slope and poured with a 4 inch thick reinforced concrete slab.

INSTALLATION NOTE: Turnouts will be required as follows:

- a) a majority of the current and existing driveway turnouts are paved, or;
 - b) the driveway to be served will be paved or formed with concrete.
- Turnouts shall be concrete or paved a minimum of 12 feet wide or the width of the concrete or paved driveway, whichever is greater. The width shall conform to the current and existing paved or concreted turnouts.



Culvert installation shall conform to the approved site plan standards.



Department of Transportation Permit installation approved standards.



Other _____

ALL PROPER SAFETY REQUIREMENTS SHOULD BE FOLLOWED
DURING THE INSTALLATION OF THE CULVERT.

135 NE Hernando Ave., Suite B-21
Lake City, FL 32055

Phone: 386-758-1008 Fax: 386-758-2160

Amount Paid 25.00



NOTICE OF COMMENCEMENT FORM
COLUMBIA COUNTY, FLORIDA

THIS DOCUMENT MUST BE RECORDED AT THE COUNTY
CLERKS OFFICE BEFORE YOUR FIRST INSPECTION

THE UNDERSIGNED hereby gives notice that improvement will be made to certain real property, and
in accordance with Chapter 713, Florida Statutes, the following information is provided in this Notice of
Commencement.

IF YOU INTEND TO OBTAIN FINANCING, CONSULT WITH YOUR LENDER OR AN ATTORNEY BEFORE
RECORDING YOUR NOTICE OF COMMENCEMENT.

Tax Parcel ID Number 24-45-16-03117-134 Permit Number _____

1. Description of property: (legal description of the property and street address or 911 address)

683 SW Chesterfield Circle, Lake City, FL 32025

2. General description of improvement: new construction single res

3. Owner Name & Address Wade Willis Construction

PO Box 1546 LC FL 32056 Interest in Property owner

4. Name & Address of Fee Simple Owner (if other than owner): _____

5. Contractor Name Wade Willis

Phone Number 386-961-9967

Address PO Box 1546 Lake City 32056

6. Surety Holders Name _____

Phone Number _____

Address _____

Amount of Bond _____

7. Lender Name _____

Inst: 200712018401 Date: 8/14/2007 Time: 11:03 AM

DC, P. DeWitt Cason, Columbia County Page 1 of 1

one Number _____

Address _____

8. Persons within the State of Florida designated by the Owner upon whom notices or other documents may be
served as provided by section 718.13 (1)(a) 7; Florida Statutes:

Name _____

Phone Number _____

Address _____

9. In addition to himself/herself the owner designates _____ of

_____ to receive a copy of the Lien Notice as provided in Section 713.13 (1) -

(a) 7. Phone Number of the designee _____

10. Expiration date of the Notice of Commencement (the expiration date is 1 (one) year from the date of
recording, (Unless a different date is specified) _____

THE OWNER MUST SIGN THE NOTICE OF COMMENCEMENT AND NO ONE ELSE MAY BE PERMITTED TO SIGN
IN HIS/HER STEAD.


[Signature]
Signature of Owner

Sworn to (or affirmed) and subscribed before day of August 14


, 20 07

[Signature]
Signature of Notary

NOTARY STAMP/SEAL




Door Model	Gauge	Decimal
2250/2251	25	.0155
4250/4251	25	.0155
2240/2241	24	.0225
4240/4241	24	.0225
5240/5241	24	.0225



door height	section quantity	strut quantity	Dr. lite quantity
6'-6" to 7'-0"	4	7	3
7'-6" to 8'-0"	5	8	4
8'-3" to 8'-9"	5	9	4
8'-1" to 10'-6"	6	11	5
10'-9" to 12'-3"	7	12	6
12'-6" to 14'-0"	8	15	7

Refer to Supplemental Instructions for
strut placement on door over 7'-0" high



Track Bracket Chart	door height											
	6'-6"	6'-9"	7'-0"	7'-6"	7'-9"	8'-0"	8'-3"	8'-6"	8'-9"	9'-0"	9'-3"	9'-6"
D	n/a	n/a	n/a	n/a	68"	72"	81"	84"	87"	90"	93"	96"
C	60"	57"	55"	58"	55"	58"	60"	63"	66"	69"	72"	75"
B	35"	35"	38"	34"	31"	34"	32"	35"	38"	41"	44"	47"
A	10"	7"	10"	10"	7"	10"	4"	7"	10"	13"	16"	19"

Track bracket locations shown above are for doors up to five sections high. Additional door sections may be added for a maximum door height of 14'-0". One track bracket (per track) must be added for each section and spaced at a distance not greater than the corresponding section height.

John E. Scales, P.E.
1411 LeMay Street #205
Carrollton, Texas 75007
Florida P.E. #51737

Professional Engineer's seal provided
only for verification of windload
construction details

This door has been tested in accordance with ANSI/ASHRAE 100-2002

Design Pressure (DP): 18.5 psf / 20.7 neg

Test Pressure (TP): 27.5 psf / 31.1 neg

Per 2004 FBC Table 1609.6E, DP meets or exceeds test wind speed of:

V = 110 MPH for Exposure B and mean roof height of 33' or less

V = 93 MPH for Exposure C and mean roof height of 39' or less

Maximum door size: 16'-0" wide by 14'-0" tall

Glazing and door have not been tested for windborne debris.

Wood back and supporting structural elements shall be designed by a registered professional engineer for wind loads shown on this drawing.

If door is not electrically operated, a lock must be installed.

Model 2250S1 (16'-0" wide)
C.H.I. Drawing: Z3-1607-01100

FL 5519

LOT 39

ITW Building Components Group, Inc.

1950 Marley Drive Haines City, FL 33844
Florida Engineering Certificate of Authorization Number: 567
Florida Certificate of Product Approval # FL1999
Page 1 of 1 Document ID: 1T5E8228Z0306084918

Truss Fabricator: Anderson Truss Company
Job Identification: 7-075--WADE WILLIS CONSTRUCTION SPEC LOT 39 CROSSWINDS -- , **
Truss Count: 34
Model Code: Florida Building Code 2004 and 2006 Supplement
Truss Criteria: ANSI/TPI-2002(STD)/FBC
Engineering Software: Alpine Software, Version 7.24.
Structural Engineer of Record: The identity of the structural EOR did not exist as of
Address: the seal date per section 61G15-31.003(5a) of the FAC
Minimum Design Loads: Roof - 40.0 PSF @ 1.25 Duration
Floor - N/A
Wind - 110 MPH ASCE 7-02 -Closed

Notes:

1. Determination as to the suitability of these truss components for the structure is the responsibility of the building designer/engineer of record, as defined in ANSI/TPI 1
2. The drawing date shown on this index sheet must match the date shown on the individual truss component drawing.
3. As shown on attached drawings; the drawing number is preceded by: HCUSR8228

Details: BRCLBSUB-TCFILLER-BCFILLER-REPBCFIL-A11015EE-GBLLETIN-

Seal Date: 03/06/2007

-Truss Design Engineer-

Arthur R. Fisher


Florida License Number: 59687

1950 Marley Drive

Haines City, FL 33844

#	Ref	Description	Drawing#	Date
1	23104--H7 A		07065017	03/06/07
2	23105--H7 AA		07065018	03/06/07
3	23106--H9 AA		07065001	03/06/07
4	23107--H11 AA		07065002	03/06/07
5	23108--H15 AA		07065003	03/06/07
6	23109--H17 AA		07065004	03/06/07
7	23110--A7		07065005	03/06/07
8	23111--A6		07065019	03/06/07
9	23112--A5		07065020	03/06/07
10	23113--A4		07065021	03/06/07
11	23114--A3		07065022	03/06/07
12	23115--A2		07065006	03/06/07
13	23116--A1		07065023	03/06/07
14	23117--H11 A		07065024	03/06/07
15	23118--H9 A		07065025	03/06/07
16	23119--B1		07065007	03/06/07
17	23120--B2		07065008	03/06/07
18	23121--B GE		07065026	03/06/07
19	23122--C5 G		07065027	03/06/07
20	23123--C GE		07065028	03/06/07
21	23124--C1		07065003	03/06/07
22	23125--C2		07065029	03/06/07
23	23126--C3		07065010	03/06/07
24	23127--C4		07065011	03/06/07
25	23128--EJ7		07065012	03/06/07
26	23129--CJ5		07065013	03/06/07
27	23130--HJ7		07065030	03/06/07
28	23131--CJ3		07065004	03/06/07
29	23132--CJ1		07065031	03/06/07
30	23133--EJ7 S		07065032	03/06/07
31	23134--CJ5 S		07065015	03/06/07
32	23135--CJ3 S		07065016	03/06/07
33	23136--HJ7 S		07065033	03/06/07
34	23137--M1		07065034	03/06/07





PAGE NO:
1 OF 1

1800

Top Chord: 1 Row @12.00" o.c.

Bol. Chord: 1 Row @12.00" o.c.
 Webs : 1 Row @ 4" o.c.
 Use equal spacing between rows and stagger nails
 in each row to avoid spilling.
 (**) 2 Plate(s) require special positioning. Refer to scaled plate plot
 details for special positioning requirements.
 110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located
 within 4.50 ft from roof edge, CAT 1I, EXP B, Wind TC DL=5.0 psf, Wind
 BC DL=5.0 psf, IW=1.00 GCPI(+/-)=0.18
 Wind reactions based on MMFRS pressures.
 Calculated horizontal deflection is 0.19" due to live load and 0.29"
 due to dead load.

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.



Scale = .3125"/Ft.

ARTHUR R. FISHER
LICENSE
No. 59687
STATE OF

****IMPORTANT****FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITM BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH

BC LL	0.0 PSF	HC-ENG	CB/AF
TOT.LD.	40.0 PSF	SEQN-	156156
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8228Z03

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf Iw=1.00 gcpi(+/-)=0.18


Wind reactions based on MWFRS pressures.

----- (LUMBER DUR.FAC.=1.25 / PLATE DUR.FAC.=1.25)
TC - From 62 PLF at -1.50 to 62 PLF at 7.00

Case	From	to	Case	From	to
1C	62 PLF	at 7.00	to 62 PLF	at 23.29	
BC	4 PLF	at -1.50	to 4 PLF	at 0.00	
BC	20 PLF	at 0.00	to 20 PLF	at 23.29	

TC - 187 LB Conc. Load at 9.06, 11.06, 13.06, 15.06, 17.06
19.06, 21.06, 22.73

BC - 82 LB Conc. Load at 9.06, 11.06, 13.06, 15.06, 17.06
19.06, 21.06, 22.73



Design Crit: $TPI-2002(STD)/FBC$
 $Cq/RT=1.00(1.25)$

 $Cq/RT=1.00(1.25)/10(0)$

FL/-/4/-/-/R/-

Scale = .3125"/Ft.

*****WARNING*** TRUSS REQUIRE EXTERIOR CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING, AND BRACING.**
 REFER TO BC51 (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY IP (TRUSS PLATE INSTITUTE), 218
 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314 AND WICA (WOOD TRUSS COUNCIL OF AMERICA), 6300
 ENTERPRISE LANE, MIDLOTHIAN, VA, 53119 FOR SAFETY PRACTICES AND MISC. TO PREVENTING THE EFFECTS. UNLESS
 OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE
 PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT**

TP1: OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.



CONNECTION PLATES ARE MADE OF 20/18/16GA (W.H/55/K) ASIM A653 GRADE 40/60 (W. K/H.55) GALV. STEEL. APPLY PLATES TO EACH FACE OF TRUSS AND UNLESS OTHERWISE LOCATED ON THIS DESIGN POSITION PER DRAWINGS 160A-7

DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT

BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



ITW Building Components Group, Inc.
Haines City, FL 33844



TC LL	20.0 PSF	REF	R8228- 23105
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCU8R8228 07065018
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN-	155312
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8228Z03

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Wind reactions based on MMFRS pressures.


(A) 1x4 SP #3 or better "T" brace. 80% length of web member.
Attach with 8d Box or Gun (0.113"x2.5".min.)nails @ 6" OC.

Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. IW=1.00 GCP(+/-)=0.18

Right end vertical not exposed to wind pressure.

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.



9-0-0
23-3.8 Over 2 Supports
14-3.8
R=1069 U=180 W=3.5*
R=949 U=180 W=3.5*

PLT TYP. Wave


Design Crt: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)/10(0)

TY:1 FL/-/4/-/-/R/-


Scale = .3125"/ft.

WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCST (BUILDING COMPONENT SAFETY INFORMATION) PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND NCTA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI, OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. DESIGN CORRECTIONS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY AF&PA) AND TPI. CONNECTOR PLATES ARE MADE OF 2018/1604 (40/50/55) ASTM A553 GRADE 40/50 (4. K7H/55 GALV. STEEL. ITW BCG PLATES EACH SIDE OF TRUSS AND, UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 160A.2. DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



ITW Building Components Group, Inc.
Haines City, FL 33844
Telephone: 800-451-0721




TC LL	20.0 PSF	REF	R8228-23106
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCU8R8228 07065001
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN-	155305
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8228203

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Wind reactions based on MMFRS pressures.

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. IW=1.00 Gcpl(+/-)=0.18
Right end vertical not exposed to wind pressure.
Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.



11'-0-0
11'-4-0
0'-11-8
5'-4-7
8'-0-0
23'-3-8 Over 2 Supports
R=1069 U=180 W=3.5"
R=949 U=180 W=3.5"


PLT TYP. Wave
Design Crit: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)/10(0)
7.24.1
Scale = .3125"/ft.

WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCSI (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE), 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314 AND WICA (WOOD TRUSS COUNCIL OF AMERICA), 6300 ENTERPRISE LANE, MADISON, WI 53719 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN; ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI; OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. BY A/R/P/A AND TPI. ITW BCG DESIGN COMPONENTS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY A/R/P/A AND TPI. ITW BCG CONNECTOR PLATES ARE MADE OF 20/18/16GA (W/H/S/S/R) ASTM A653 GRADE 40/50 (N, K/R, S) GALV. STEEL. APPLY LATEREACH OF THE TRUSSES OR UNLESS OTHERWISE SPECIFIED ON THIS DESIGN, POSITION PER DRAWINGS. 16GA.2. DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENTS BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



ITW Building Components Group, Inc.
Haines City, FL 33844
www.alpinebuilding.com



TC LL	20.0 PSF	REF	R8228-23107
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228 07065002
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT. LD.	40.0 PSF	SEQN-	155317
DUR. FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8228203

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3


Wind reactions based on MMFRS pressures.

In lieu of structural panels or rigid ceiling use purlins to
brace TC @ 24" OC, BC @ 24" OC.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not
located within 4.50 ft from roof edge, CAT II, EXP B, wind TC
DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ $G_{cp}(+/-)=0.18$

Right end vertical not exposed to wind pressure.

Deflection meets $L/240$ live and $L/180$ total load. Creep increase
factor for dead load is 1.50.



R=1069 U=180 W=3.5*

R=949 U=180 W=3.5*

PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)/10(0)


TY:1

FL/-/4/-/R/-


Scale = .3125"/ft.

****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BC31 (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE), 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314 AND WCA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN; ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI; OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. BY ACPA AND TPI. DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY ACPA AND TPI. ITW BCG CONNECTOR PLATES ARE MADE OF 20/18/16GA (W/H/S/R) ASTM A653 GRADE 40/60 (W. K/R, SSI GALV. STEEL. APPLY PLATES EACH SIDE OF TRUSS AND, UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 160A, 2, 160B, 3, 160C, 4, 160D, 5, 160E, 6, 160F, 7, 160G, 8, 160H, 9, 160I, 160J, 160K, 160L, 160M, 160N, 160O, 160P, 160Q, 160R, 160S, 160T, 160U, 160V, 160W, 160X, 160Y, 160Z, 160AA, 160AB, 160AC, 160AD, 160AE, 160AF, 160AG, 160AH, 160AI, 160AJ, 160AK, 160AL, 160AM, 160AN, 160AO, 160AP, 160AQ, 160AR, 160AS, 160AT, 160AU, 160AV, 160AW, 160AX, 160AY, 160AZ, 160BA, 160BB, 160BC, 160BD, 160BE, 160BF, 160BG, 160BH, 160BI, 160BJ, 160BK, 160BL, 160BM, 160BN, 160BO, 160BP, 160BQ, 160BR, 160BS, 160BT, 160BU, 160BV, 160BW, 160BX, 160BY, 160BZ, 160CA, 160CB, 160CC, 160CD, 160CE, 160CF, 160CG, 160CH, 160CI, 160CJ, 160CK, 160CL, 160CM, 160CN, 160CO, 160CP, 160CQ, 160CR, 160CS, 160CT, 160CU, 160CV, 160CW, 160CX, 160CY, 160CZ, 160DA, 160DB, 160DC, 160DD, 160DE, 160DF, 160DG, 160DH, 160DI, 160DJ, 160DK, 160DL, 160DM, 160DN, 160DO, 160DP, 160DQ, 160DR, 160DS, 160DT, 160DU, 160DV, 160DW, 160DX, 160DY, 160DZ, 160EA, 160EB, 160EC, 160ED, 160EE, 160EF, 160EG, 160EH, 160EI, 160EJ, 160EK, 160EL, 160EM, 160EN, 160EO, 160EP, 160EQ, 160ER, 160ES, 160ET, 160EU, 160EV, 160EW, 160EX, 160EY, 160EZ, 160FA, 160FB, 160FC, 160FD, 160FE, 160FF, 160FG, 160FH, 160FI, 160FJ, 160FK, 160FL, 160FM, 160FN, 160FO, 160FP, 160FQ, 160FR, 160FS, 160FT, 160FU, 160FV, 160FW, 160FX, 160FY, 160FZ, 160GA, 160GB, 160GC, 160GD, 160GE, 160GF, 160GG, 160GH, 160GI, 160GJ, 160GK, 160GL, 160GM, 160GN, 160GO, 160GP, 160GQ, 160GR, 160GS, 160GT, 160GU, 160GV, 160GW, 160GX, 160GY, 160GZ, 160HA, 160HB, 160HC, 160HD, 160HE, 160HF, 160HG, 160HH, 160HI, 160HJ, 160HK, 160HL, 160HM, 160HN, 160HO, 160HP, 160HQ, 160HR, 160HS, 160HT, 160HU, 160HV, 160HW, 160HX, 160HY, 160HZ, 160IA, 160IB, 160IC, 160ID, 160IE, 160IF, 160IG, 160IH, 160II, 160IJ, 160IK, 160IL, 160IM, 160IN, 160IO, 160IP, 160IQ, 160IR, 160IS, 160IT, 160IU, 160IV, 160IW, 160IX, 160IY, 160IZ, 160JA, 160JB, 160JC, 160JD, 160JE, 160JF, 160JG, 160JH, 160JI, 160JJ, 160JK, 160JL, 160JM, 160JN, 160JO, 160JP, 160JQ, 160JR, 160JS, 160JT, 160JU, 160JV, 160JW, 160JX, 160JY, 160JZ, 160KA, 160KB, 160KC, 160KD, 160KE, 160KF, 160KG, 160KH, 160KI, 160KJ, 160KK, 160KL, 160KM, 160KN, 160KO, 160KP, 160KQ, 160KR, 160KS, 160KT, 160KU, 160KV, 160KW, 160KX, 160KY, 160KZ, 160LA, 160LB, 160LC, 160LD, 160LE, 160LF, 160LG, 160LH, 160LI, 160LJ, 160LK, 160LL, 160LM, 160LN, 160LO, 160LP, 160LQ, 160LR, 160LS, 160LT, 160LU, 160LV, 160LW, 160LX, 160LY, 160LZ, 160MA, 160MB, 160MC, 160MD, 160ME, 160MF, 160MG, 160MH, 160MI, 160MJ, 160MK, 160ML, 160MN, 160MO, 160MP, 160MQ, 160MR, 160MS, 160MT, 160MU, 160MV, 160MW, 160MX, 160MY, 160MZ, 160NA, 160NB, 160NC, 160ND, 160NE, 160NF, 160NG, 160NH, 160NI, 160NJ, 160NK, 160NL, 160NM, 160NO, 160NP, 160NQ, 160NR, 160NS, 160NT, 160NU, 160NV, 160NW, 160NX, 160NY, 160NZ, 160OA, 160OB, 160OC, 160OD, 160OE, 160OF, 160OG, 160OH, 160OI, 160OJ, 160OK, 160OL, 160OM, 160ON, 160OO, 160OP, 160OQ, 160OR, 160OS, 160OT, 160OU, 160OV, 160OW, 160OX, 160OY, 160OZ, 160PA, 160PB, 160PC, 160PD, 160PE, 160PF, 160PG, 160PH, 160PI, 160PJ, 160PK, 160PL, 160PM, 160PN, 160PO, 160PP, 160PQ, 160PR, 160PS, 160PT, 160PU, 160PV, 160PW, 160PX, 160PY, 160PZ, 160QA, 160QB, 160QC, 160QD, 160QE, 160QF, 160QG, 160QH, 160QI, 160QJ, 160QK, 160QL, 160QM, 160QN, 160QO, 160QP, 160QQ, 160QR, 160QS, 160QT, 160QU, 160QV, 160QW, 160QX, 160QY, 160QZ, 160RA, 160RB, 160RC, 160RD, 160RE, 160RF, 160RG, 160RH, 160RI, 160RJ, 160RK, 160RL, 160RM, 160RN, 160RO, 160RP, 160RQ, 160RR, 160RS, 160RT, 160RU, 160RV, 160RW, 160RX, 160RY, 160RZ, 160SA, 160SB, 160SC, 160SD, 160SE, 160SF, 160SG, 160SH, 160SI, 160SJ, 160SK, 160SL, 160SM, 160SN, 160SO, 160SP, 160SQ, 160SR, 160SS, 160ST, 160SU, 160SV, 160SW, 160SX, 160SY, 160SZ, 160TA, 160TB, 160TC, 160TD, 160TE, 160TF, 160TG, 160TH, 160TI, 160TJ, 160TK, 160TL, 160TM, 160TN, 160TO, 160TP, 160TQ, 160TR, 160TS, 160TT, 160TU, 160TV, 160TW, 160TX, 160TY, 160TZ, 160UA, 160UB, 160UC, 160UD, 160UE, 160UF, 160UG, 160UH, 160UI, 160UJ, 160UK, 160UL, 160UM, 160UN, 160UO, 160UP, 160UQ, 160UR, 160US, 160UT, 160UU, 160UV, 160UW, 160UX, 160UY, 160UZ, 160VA, 160VB, 160VC, 160VD, 160VE, 160VF, 160VG, 160VH, 160VI, 160VJ, 160VK, 160VL, 160VM, 160VN, 160VO, 160VP, 160VQ, 160VR, 160VS, 160VT, 160VU, 160VV, 160VW, 160VX, 160VY, 160VZ, 160WA, 160WB, 160WC, 160WD, 160WE, 160WF, 160WG, 160WH, 160WI, 160WJ, 160WK, 160WL, 160WM, 160WN, 160WO, 160WP, 160WQ, 160WR, 160WS, 160WT, 160WU, 160WV, 160WW, 160WX, 160WY, 160WZ, 160XA, 160XB, 160XC, 160XD, 160XE, 160XF, 160XG, 160XH, 160XI, 160XJ, 160XK, 160XL, 160XM, 160XN, 160XO, 160XP, 160XQ, 160XR, 160XS, 160XT, 160XU, 160XV, 160XW, 160XX, 160XY, 160XZ, 160YA, 160YB, 160YC, 160YD, 160YE, 160YF, 160YG, 160YH, 160YI, 160YJ, 160YK, 160YL, 160YM, 160YN, 160YO, 160YP, 160YQ, 160YR, 160YS, 160YT, 160YU, 160YV, 160YW, 160YX, 160YY, 160YZ, 160ZA, 160ZB, 160ZC, 160ZD, 160ZE, 160ZF, 160ZG, 160ZH, 160ZI, 160ZJ, 160ZK, 160ZL, 160ZM, 160ZN, 160ZO, 160ZP, 160ZQ, 160ZR, 160ZS, 160ZT, 160ZU, 160ZV, 160ZW, 160ZX, 160ZY, 160ZZ



ITW Building Components Group, Inc.
Gaines City, FL 33844



TC LL	20.0 PSF	REF	R8228-23108
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCU8R228-07065003
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT. LD.	40.0 PSF	SEQN-	155322
DUR. FAC.	1.25	FROM	JFB
SPACING	24.0"	UREF-	1T5E8228203


Top chord	2x4	SP	#2	Dense
Bot chord	2x4	SP	#2	Dense
Webs	2x4	SP	#3	

(A) Continuous lateral bracing equally spaced on member.

Deflection meets $L/240$ live and $L/180$ total load. Creep increase factor for dead load is 1.50.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located within 4.50 ft from roof edge, CAT 11, EXP 8, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 Gcpi(+/-)=0.18

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.



1'-6"

15'-0"

23'-3" Over 2 Supports

3'-4"

4'-11"

R=1069 U=180 W=3.5"

R=949 U=180 W=3.5"

PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)

7.24.12

FL/-/4/-/-/R/-/

Scale = .25"/Ft.

*****WARNING***** TRUSS REQUIRE EXISTING CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BC51 (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PRACTICE INSTITUTE), 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314 AND WICA (WOOD TRUSS COUNCIL OF AMERICA), 63000 ENTERPRISE LANE, MIDLOTHIAN, NJ 07045 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITM BCG, INC. SHALL NOT**

TP1: OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

CONNECTOR PLATES ARE MADE OF 20/18/16GA (W.H/SS/K) ASTM A653 GRADE 40/60 (W. K/H.SS) GALV. STEEL. APPLY PLATES TO EACH FACE OF TRUSS AND WELDES OUTRIBS LOCATED ON THIS DESIGN POSITION PER DRAWINGS VEA-7

ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A3 OF VP11-2002 SEC.3. A SEAL ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT


DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.

ITW Building Components Group, Inc.
Haines City, FL 33844
E1 Certificate of Authorization # 557

ARTHUR R. FISHER
 PROFESSIONAL ENGINEER
 STATE OF FLORIDA
 No. 59687
 March 1907

TC LL	20.0 PSF	REF	R8228- 23109
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228 07065004
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN-	155327
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8228203

Deflection meets $L/240$ live and $L/180$ total load. Creep increase factor for dead load is 1.50.



Scale = .25"/ft.

Haines City, FL 33844

Scale = .25"/ft.


TC LL	20.0 PSF	REF	R8228- 23110
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228 07065005
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN-	156076
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8228Z03

(A) Continuous lateral bracing equally spaced on member.

Deflection meets $L/240$ live and $L/180$ total load. Creep increase factor for dead load is 1.50.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located within 4.50 ft from roof edge, CAT 11, EXP B, wind TC DL-5.0 psf, wind BC DL-5.0 psf. 1w-1.00 Gcpi(+/-)=0.18

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.



PLT TYP. Wave

Design Cr1t: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)

7.24.1

FL/-/4/-/-/R/-/

Scale = .25" / Ft.

WARNING TRUSSES REQUIRE EXTENSIVE CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING, AND BRACING. REFER TO GC-1 (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATING INSTITUTE), 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314 AND WPCA (WOOD TRUSS COUNCIL OF AMERICA, 65000 MIDWAY ENTERPRISE LANE, MOUNTAIN VIEW, MI 48139) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT**

TP1; OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

CONNECTOR PLATES ARE MADE OF 20/18/16GA (M, H/SS/K) ASTM A653 GRADE 40/60 (M, K/H,SS) GALV. STEEL. APPLY PLATES TO EACH FACE OF TRUSS AND SURFACE ORIENTED AS SHOWN IN THE DETAIL POSITION FOR CLEARANCE 160.3

ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A3 OF TP11-2002 SEC.3. A SEAL ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT

DESIGN SHOWN. THE SUSTAINABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2

100

ITW Building Components Group, Inc.
Haines City, FL 33844
F1 Certificate # A-00107012

□ □ □


Professional Engineer Seal for the State of Florida, No. 59887, signed by R. Fishback, dated Mar. 06 '07.

TC LL	20.0 PSF	REF	R8228- 23111
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228 0706019
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN-	156087
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E828Z03

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, closed bldg, not located within 4.50 ft from roof edge, Cat II, Exp B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 Gcpi(+/-)-0.18

Deflection meets $L/240$ live and $L/180$ total load. Creep increase factor for dead load is 1.50.



PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC

 $Cq/RT=1.00(1.25)/10(0)$

7.24.123616

FL/-/4/-/-/R/-

Scale = .25" / Ft.

*MAINING** TREES, REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO GC51 (BUILDING COMPONENT SAFETY INFORMATION). PUBLISHED BY TPI (TRESS PASTE INSTITUTE), 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314 AND WICA (WOOD TRESS COUNCIL OF AMERICA, 65000 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO UNLOADING THESE PRODUCTS. UNLESS OTHERWISE INDICATED, TPO CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED TIDEL CCELLING.

****IMPORTANT****FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITM BCG, INC. SHALL NOT

TP1: OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.



CONNECTOR PLATES ARE MADE OF 20/18/16GA (W.H/SS/K) ASTM A653 GRADE 40/60 (W. K/H.SS) GALV. STEEL. APPLY PLATES TO EACH FACE OF TRIUSS AND UNLESS OTHERWISE LOCATED ON THIS DESIGN POSITION PER DRAWINGS 160A-2

ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A3 OF IP112002 SEC.3. A SEAL ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT

BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.

1. The first step is to identify the problem or question that needs to be answered. This involves understanding the context and the specific requirements of the task.

TTW Building Components Group, Inc.
Haines City, FL 33844
ET Certificate of Authorization # 567





TC LL	20.0 PSF	REF	R8228- 23112
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCSUR8228 07065020
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN-	156093
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF -	1T5E8228Z03

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Wind reactions based on MMFRS pressures.

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $1w=1.00 GCP(+-)=0.18$
Right end vertical not exposed to wind pressure.
Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.



PLT TYP. Wave

Design Crit: TPI-2002 (STD) / FBC
Cq/RT=1.00(1.25)/10(0)



QTY: 1 FL/-/4/-/-R/-

Scale = .3125"/ft.

****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCSI (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 210 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND NCA (WOOD TRUSS COUNCIL OF AMERICA, 6200 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

DESIGN COMMENTS WITH APPLICABLE PROVISIONS OF BCS (NATIONAL DESIGN SPEC. BY AREA) AND TPI. ITW BCG CONNECTION PLATES ARE MADE OF 20/10/160A (W/55%) ASTM A653 GRADE 40/60 (W/ KIN-55) GALV. STEEL. APPLY THE FOLLOWING CONNECTION PER DRAWING PER SECTION 1. ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEAL AS OF TPI 2002 SEC.3. DESIGNER SHALL SIGN ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY. SOCIETY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.





TC LL	20.0 PSF	REF	R8228-23113
TC DL	10.0 PSF	DATE	03/04/07
BC DL	10.0 PSF	DRW	HCSR8228 07065021
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN	156099
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF	1T5E8228Z03

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Wind reactions based on MFRS pressures.
Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. IW=1.00 GCPI(+/-)=0.18
In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.



PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)/10(0)

7.24.1

FL/-/4/-/R/-

Scale = .3125"/ft.

****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCSI (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 718 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22304) AND WICA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.



****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. JTW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE OF THE TRUSS IN CONFORMANCE WITH TPI OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF AISC (NATIONAL DESIGN SPEC. BY AISC) AND TPI. JTW BCG

CONNECTOR PLATES ARE MADE OF 2018/16GA (W/H/S/S) ASTM A653 GRADE 40/60 (4, K/H/S5) GALV. STEEL. APPLY

ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEK AS OF TPI 11-2002 SEC.3. A SEAL ON THIS

DESIGN SHOWS THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.




TC LL	20.0 PSF	REF	R8228-23114
TC DL	10.0 PSF	DATE	03/04/07
BC DL	10.0 PSF	DRW	HCSR8228 07065022
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT. LD.	40.0 PSF	SEQN-	156103
DUR. FAC.	1.25	FROM	JFB
SPACING	24.0"	JRFF-	1T5E828Z03

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Wind reactions based on MWFRS pressures.
Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. 1w=1.00 GCPI(+/-)=0.18
In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.



PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)/10(0)



FL/-/4/-/R/-

Scale = .25"/ft.

ALPINE		ITW Building Components Group, Inc. Haines City, FL 33844	
HARING TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BEST PRACTICES FOR TRUSS CONSTRUCTION. NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA 22304 AND WICA (WOOD TRUSS COUNCIL OF AMERICA), 5300 ENTERPRISE LANE, MADISON, WI 53719 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.		**IMPORTANT** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI, OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY AFPA) AND TPI. ITW BCG CONNECTION PLATES ARE MADE OF 2018/16GA (W/SS/YS) ASTM A653 GRADE 40/60 (K/HS) GALV. STEEL. APPLY PLATES TO EACH FACE OF TRUSS AND, UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 160A, 2. ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PERFORMED AS OF TPI-2002 SEC.3. A SEAL ON THIS DESIGN SHOWS THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.	
TC LL	20.0 PSF	REF	R8228- 23115
TC DL	10.0 PSF	DATE	03/04/07
BC DL	10.0 PSF	DRW	HCSR8228 07065006
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN-	156107
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E828Z03


Top chord 2x4 SP #2 Dense :T2 2x6 SP #2:
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Wind reactions based on MMFRS pressures.

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.

RS1

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $W=1.00 GCP1(+/-)=0.18$
Calculated horizontal deflection is 0.18" due to live load and 0.28" due to dead load.
Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.
(1) 2x6x7-4-7 SP #2 Top chord scab centered 20-5-0 from left end. Attach to one face of chord with (3) rows of 12d Common (0.148"x3.25", min.) nails @ 6" O.C., staggered 3".



9-11-8 12-0-0 24-0-0 Over 2 Supports 13-8-8 11-8-0
R=1086 U=180 W=3.5"
R=991 U=180 W=3.5"

PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)/10(0)


7.24

FL/-/4/-/R/-


Scale = .3125"/ft.

WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BC51 (BUILDING COMPONENT SAFETY INFORMATION) PUBLISHED BY TPI (TRUSS PLATE INSTITUTE), 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22304 AND WICA (WOOD TRUSS COUNCIL OF AMERICA), 6300 ENTERPRISE LANE, MADISON, WI 53719 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN: ANY FAILURE OF THE TRUSS IN CONFORMANCE WITH TPI; OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. BY ATAPA AND TPI. ITW BCG DESIGN CORP. HAS MADE OF 20/18/1604 (W/H/S/R) (ASTM A553 GRADE 40/60 (A, K/H, S) GALV. STEEL. APPLY CONNECTOR PLATES ARE MADE OF 20/18/1604 (W/H/S/R) (ASTM A553 GRADE 40/60 (A, K/H, S) GALV. STEEL. APPLY THIS SPECIFICATION OF 6.0/18/1604 (W/H/S/R) (ASTM A553 GRADE 40/60 (A, K/H, S) GALV. STEEL. APPLY ANY DEVIATION FROM THIS DESIGN: ANY FAILURE OF THE TRUSS IN CONFORMANCE WITH TPI; OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.



ITW Building Components Group, Inc.
Haines City, FL 33844
P.O. Box 1000, Haines City, FL 33844



TC LL	20.0 PSF	REF	R8228- 23116
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228 07065023
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT. LD.	40.0 PSF	SEON-	156115
DUR. FAC.	1.25	FROM	JFB
SPACING	24.0"	UREF-	1T5E8228203


Top chord 2x4 SP #2 Dense :T3 2x6 SP #2:
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Wind reactions based on MWFRS pressures.

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. 1w=1.00 GCPI(+/-)-0.18
Calculated horizontal deflection is 0.19" due to live load and 0.29" due to dead load.
Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.


RS1
(1) 2x6X7-5-15 SP #2 Top chord scab centered 20-3-11 from left end. Attach to one face of chord with (3) rows of 12d Common (0.148"x3.25", min.) nails @ 6" O.C., staggered 3".




PLT TYP. Wave
Design Crit: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)/10(0) 7.24

WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BC31 (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE), 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22304, AND WCA (WOOD TRUSS COUNCIL OF AMERICA), 6900 ENTERPRISE LANE, MADISON, WI 53719, FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI: OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. ITW BCG DESIGN COMPANIES WITH APPLICABLE PROVISIONS OF MD5 (NATIONAL DESIGN SPEC. FOR AERPA) AND TPI. ITW BCG CONNECTION PLATES ARE MADE OF 20/16/1604 (W/H/55/7) ASH 1653 GRADE 40/60 (W, R/H/55) GALV. STEEL. APPLY PERMANENT IDENTIFICATION MARKS TO ALL TRUSS COMPONENTS PER DRAWING 3180A-2. ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEE A3 OF TPI-2002 SEC. 2. DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOCIETY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUSTAINABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



ITW Building Components Group, Inc.
Haines City, FL 33844
Tel: 888.444.4444



TC LL	20.0 PSF	REF	R8228-23117
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228 07065024
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN-	156120
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8228Z03

Top chord 2x4 SP #2 Dense :T3 2x6 SP #2:
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Wind reactions based on MMFRS pressures.

Calculated horizontal deflection is 0.17" due to live load and 0.26" due to dead load.

Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.


See detail BCFILLER1106, TCFILLER1106 and REPBFCFIL for filler details. Laterally brace chord above/below filler @ 24" O.C. (or as designed) including a brace on chord directly above/below both ends of filler (if no rigid diaphragm exists at that point)

(**) 1 plate(s) require special positioning. Refer to scaled plate plot details for special positioning requirements.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. 1W=1.00 GCPI(+/-)=0.18

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.

(1) 2x6x6-4-8 SP #2 Top chord scab centered 20'-10"-4 from left end. Attach to one face of chord with (3) rows of 12d Common (0.148"x3.25", min.) nails @ 6" O.C., staggered 3".




PLT TYP. Wave Design Crit: TPI-2002(STD)/FBC Cq/RT=1.00(1.25)/10(0) 7.24.1

HARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCSI (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI TRUSS PLATING INSTITUTE, 6300 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22304 AND WICA (WOOD TRUSS COUNCIL OF AMERICA, 100 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT FINISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE OF THE TRUSS IN CONFORMANCE WITH TPI OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. ITW BCG DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY ASEP) AND TPI. ITW BCG CONNECTOR PLATES ARE MADE OF 20/18/16GA (W/H/55/S) ASTM A653 GRADE 40/60 (W, K/H/55) GALV. STEEL. APPLY PLATES TO EACH FACE OF TRUSS AND UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 160A Z.

ITW Building Components Group, Inc. Haines City, FL 33844
Certificate of Authorization # 5627



TC LL	20.0 PSF	REF	R8228-23118
TC DL	10.0 PSF	DATE	03/04/07
BC DL	10.0 PSF	DRW	HCSR8228 07065025
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN-	156126
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8228203

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 GCPI(+/-)=0.18

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.

brace TC @ 24" OC, BC @ 24" OC.



R=951 U=180 W=3.5

Scale = .3125"/Ft.

NG.
218
6300
LESS
HAVE

STATE OF
JOHNSA
ENGINEER

TC LL	20.0 PSF	REF	R8228 - 23119
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228 Q7065007
BC LL	0.0 PSF	HC-ENG JB/AF	*
TOT.LD.	40.0 PSF	SEQN-	155266
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF -	1T5E8228203

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 Gcp(1+/-)=0.18



ITW Building Components Group, Inc.
Haines City, FL 33844
E1 Certificate of Authorization # 547

March 16, 2007

Professional Engineer Seal for Arthur R. Fisher, No. 59887, State of Florida.

TC LL	20.0 PSF	REF	R8228 - 23120
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228 07065008
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN-	155270
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF -	1T5E8228203

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3


Wind reactions based on MFRS pressures.

See DWGS A11015EE1106 & GBLLET1106 for more requirements.

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.

THE BUILDING DESIGNER IS RESPONSIBLE FOR THE DESIGN OF THE ROOF AND CEILING DIAPHRAGMS, GABLE END SHEAR WALLS, AND SUPPORTING SHEAR WALLS. SHEAR WALLS MUST PROVIDE CONTINUOUS LATERAL RESTRAINT TO THE GABLE END. ALL CONNECTIONS TO BE DESIGNED BY THE BUILDING DESIGNER.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ $GCP1(+/-)=0.18$
Truss spaced at 24.0" OC designed to support 1-0-0 top chord outlookers. Cladding load shall not exceed 10.00 PSF. Top chord must not be cut or notched.
Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.



R=105 PLF U=28 PLF W=20-4-8

R=276 U=236 W=3.5*

Note: All Plates Are 1.5X4 Except As Shown.
PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)/10(0)



7.24.11

Scale = .3125"/ft.

WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCST (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE), 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22304 AND WICA (WOOD TRUSS COUNCIL OF AMERICA), 6300 ENTERPRISE LANE, MADISON, WI 53719 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY AIAA) AND TPI. ITW BCG CONNECTOR PLATES ARE MADE OF 2018/16GA (W/H/5/5) ASTM A653 GRADE 40/60 (W, K/H/55) GALV. STEEL. APPLY PLATES TO EACH FACE OF TRUSS AND UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 160A-2.

DRIVING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



TC LL	20.0 PSF	REF	R8228-23121
TC DL	10.0 PSF	DATE	03/04/07
BC DL	10.0 PSF	DRW	HCUSR8228 07065026
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT. LD.	40.0 PSF	SEQN-	155276
DUR. FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8248203


2 COMPLETE TRUSSES REQUIRED

2 COMPLETE TRUSSES REQUIRED
Nailing Schedule: (12d_Common_ (0.148"x3.25"

Nailing Schedule: (12d Common(0.148"x3.25",min.)_nails)
 Top Chord: 1 Row @12.00" o.c.
 Bot Chord: 1 Row @ 3.50" o.c.
 Webs : 1 Row @ 4" o.c.
 Use equal spacing between rows and stagger nails
 in each row to avoid splitting.

Right end vertical not exposed to wind pressure.

Deflection meets $L/240$ live and $L/180$ total load. Creep increase factor for dead load is 1.50.



Design Crit: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)

 $Cq/RT=1.00(1.25)/10(0)$

7.24

QTY:1

FL/-/4/-/-/R/-/


Scale = .375" / Ft.

WARNING - FRAMES BEHIND EXTERIOR CEILING, IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING REFER TO BC51 (BUILDING COMPONENT SAFETY INFORMATION). PUBLISHED BY IP1 (TRUSS PLATE INSTITUTE), 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314 AND WICA (WOOD TRUSS COUNCIL OF AMERICA, 65000 ROCK ENTERPRISE LANE, MADISON, WI, 53719) FOR SAFETY PRACTICES PERTAINING TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED GRID CEILING.

ALPINE

ITW Building Components Group, Inc.
Haines City, FL 33844

IMPORTANT FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. THE IBC, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH THIS SPECIFICATION SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS, APPROVALS, AND INSURANCE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY MATERIALS, EQUIPMENT, AND LABOR. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY TRANSPORTATION AND LOGISTICS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY UTILITIES AND SERVICES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY INSURANCE AND BONDING. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS, APPROVALS, AND INSURANCE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY MATERIALS, EQUIPMENT, AND LABOR. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY TRANSPORTATION AND LOGISTICS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY UTILITIES AND SERVICES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY INSURANCE AND BONDING.



TC LL	20.0 PSF	REF	R8228 - 23122
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228 07065027
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN-	156192
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8228T03


See DWGS A11015EEL106 & GBLETTM1106 for more requirements.

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.

THE BUILDING DESIGNER IS RESPONSIBLE FOR THE DESIGN OF THE ROOF AND CEILING DIAPHRAGMS, GABLE END SHEAR WALLS, AND SUPPORTING SHEAR WALLS. SHEAR WALLS MUST PROVIDE CONTINUOUS LATERAL RESTRAINT TO THE GABLE END. ALL CONNECTIONS TO BE DESIGNED BY THE BUILDING DESIGNER.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 GCPI(+/-)=0.18

Deflection meets $L/240$ live and $L/180$ total load. Creep increase factor for dead load is 1.50.



R=221 U=180 W=3.5"
R=98 PLF U=15 PLF W=12'-0"-8'

PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC

 $Cq/RT=1.00(1.25)/10(0)$

7.24.13


FL/-/4/-/-/R/-

Scale = .5"/Ft.

*****WARNING***** FRUES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO GC#1 (BUILDING COMPONENT SAFETY INFORMATION). PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND WICA (WOOD TRUSS COUNCIL OF AMERICA, 65000 MIDWAY ENTERPRISE LANE, MOJOSUM, MI, 48139) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED RIGID CEILING.

ALPINE

ITW Building Components Group, Inc.
Haines City, FL 33844





TC LL	20.0 PSF	REF	R8228 - 23123
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUS8228 07065028
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN -	156161
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF -	1T5E8228203

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Wind reactions based on MMFRS pressures.

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, located anywhere in roof, CAT II, Exp B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ $GCP(+/ -)=0.18$
Calculated horizontal deflection is 0.12" due to live load and 0.19" due to dead load.
Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.



PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)/10(0)

TY:1 FL/-4/-/-R/-


Scale = .5"/ft.

****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLATION AND BRACING. REFERENCE TO THE DRAWING FOR THE LOCATION OF ALL MEMBERS AND BRACING. THE TRUSS IS TO BE INSTALLED IN THE NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA 22304 AND WICHITON TRUSS COMPANY OF AMERICA, UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.


****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE OF THE TRUSS IN PERFORMANCE WITH TPI, OR FABRICATING, HANDLING, SHIPPING, INSTALLING, A BRACING OF TRUSSES.

DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF AISC (NATIONAL DESIGN SPEC. BY AISC) AND TPI. ITW BCG CONNECTOR PLATES ARE MADE OF 2018/16GA (W/55/5) ASTM A653 GRADE 40/60 (W/ K/H/55) GALV. STEEL. APPLY PLATES TO EACH FACE OF TRUSS AND, UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 160A-Z.

ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A3 OF TPI-2002 SEC.3. A SEAL ON THIS DRAWING INDICATES THE ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOCIETY FOR THE TRUSS COMPONENT DESIGN. THE ACCEPTANCE OF THE SOCIETY OF PROFESSIONAL ENGINEERS FOR THE TRUSS COMPONENT DESIGN IS THE RESPONSIBILITY OF THE BOTTOMING DESIGNER PER ANSI/TPI 1 SEC. 2.



ITW Building Components Group, Inc.
Haines City, FL 33844
Haines City, FL 33844
Haines City, FL 33844




TC LL	20.0 PSF	REF	R8228-23124
TC DL	10.0 PSF	DATE	03/04/07
BC DL	10.0 PSF	DRW	HCSR8228 07065003
BC LL	0.0 PSF	HC-ENG	JB/AP
TOT. LD.	40.0 PSF	SEQN-	156164
DUR. FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E828203

Deflection meets $L/240$ live and $L/180$ total load. Creep increase factor for dead load is 1.50.

See detail1 BCFILLER1106, TCFILLER1106 and REPGFIL for filler details. Laterally brace chord above/below filler @ 24" O.C. (or as designed) including a brace on chord directly above/below both ends of filler (if no rigid diaphragm exists at that point)

(**) 6 plate(s) require special positioning. Refer to scaled plate plot details for special positioning requirements.




PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC

$$Cq/RT=1.00(1.25)/10(0)$$
[illegible]

QTY:1 FL/-/4/-/-/R/-/-

Scale = .375" / Ft.




ITW Building Components Group, Inc.
Haines City, FL 33844
Tel 888-444-4444

WARNING - RATES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING REFER TO GC51 (BUILDING COMPONENT SAFETY INFORMATION). PUBLISHED BY IP1 (FRUSS PASTL INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND WICA (WOOD TRUSS COUNCIL OF AMERICA, 65000 MIDWAY ENTERPRISE LANE, MIDWAY, MI 48139) FOR THE PURPOSE OF INFORMING THESE FUNCTIONS. USELESSNESS OF THE INFORMATION INDICATED THAT CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED RIGID CELLING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR, ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN: ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TCI OR FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING OF TRUSSES.

DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



TC LL	20.0 PSF	REF	R8228- 23125
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228 07065029
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN -	156180
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF -	1T5E8228Z03

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3


Wind reactions based on MWFRS pressures.

In lieu of structural panels or rigid ceiling use purlins to
brace TC @ 24" OC, BC @ 24" OC.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not
located within 4.50 ft from roof edge, CAT II, EXP B, wind TC
DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ $G_{CPI}(+/-)=0.18$

Right end vertical not exposed to wind pressure.

Deflection meets L/240 live and L/180 total load. Creep increase
factor for dead load is 1.50.



6-0-0
12-7-8
18-7-8 Over 2 Supports
R=878 U=180 W=3.5"
R=756 U=180 W=3.5"

PLT TYP. Wave


Design Crit: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)/10(0)

7.24.12


Scale = .375" / ft.

****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCST (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND WCA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI, OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY AIAA) AND TPI. CONNECTOR PLATES ARE MADE OF 2018/1604 (W/H/S/F) ASTM A553 GRADE 40/50 (W. K/P/S) GALV. STEEL. ITW BCG SHALL BE RESPONSIBLE FOR THE DESIGN OF THE TRUSS. ITW BCG SHALL BE RESPONSIBLE FOR THE DESIGN OF THE TRUSS. ANY INSPECTION OF PLATE FOLLOWED BY ITW BCG SHALL BE PERFORMED AS OF 12/02/00. SECTION PER DRAWING 1604.2. DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



ITW Building Components Group, Inc.
Haines City, FL 33844
Tel: 888-444-4444



TC LL	20.0 PSF	REF	R8228- 23126
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCU8R8228 07065010
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT. LD.	40.0 PSF	SEQN-	156184
DUR. FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8228Z03

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3


Wind reactions based on MMFRS pressures.

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ $GCP(+/-)=0.18$

Right end vertical not exposed to wind pressure.

Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.




8-0-0
18-7-8 Over 2 Supports
10-7-8
R=773 U=180 W=3.5"
R=761 U=180 W=3.5"


PLT TYP. Wave Design Crit: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)/10(0)

****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BC31 (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND WICA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. DESIGN COMPLIES WITH APPLICABLE PROVISIONS OF BCS (NATIONAL DESIGN SPEC. BY AREA) AND TPI. DESIGNER PLATES ARE MADE OF 2016/1604 (W/HS/FS) AS PER AREA SPEC. 40/60 (W/HS/FS) GALV. STEEL. APPLY TO ALL TRUSSES. ALL TRUSSES SHALL BE DESIGNED TO MEET THE REQUIREMENTS OF TPI-2002 (STD) AND TPI-2002 (FBC). ANY INSPECTION OF PLATES FOLLOWED BY PROFESSIONAL ENGINEERING RESPONSIBILITY SOCIETY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.




ITW Building Components Group, Inc.
Haines City, FL 33844
Tel: 888-444-4444



FL/-/4/-/-/R/-		Scale = .375"/ft.	
TC LL	20.0 PSF	REF	R8228-23127
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228 07065011
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT. LD.	40.0 PSF	SEQN-	156188
DUR. FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8228Z03

Deflection meets $L/240$ live and $L/180$ total load. Creep increase factor for dead load is 1.50.

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC



1.60

7-0-0 Over 3 Supports
R=408 U=180 W=3.5"

PLT TYP. Wave

Design Critt: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)

7.24.

TY:1 FL/-/4/-/-/R/-

Scale = .5"/Ft.

***WARNING:** ALL FRAMES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO GC-1 (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TROSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND NICK 4000 TROSS CONTROL OF AMERICA, 65000 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO TRANSFERRING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, THE CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED RIGID CEILING.

ALPINE

ITW Building Components Group, Inc.
Haines City, FL 33844
E1 Certificate of Authorization # 567


IMPORTANT FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. THE BCG, IN SMALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TUSSELS IN COMPLIANCE WITH THE: ON FABRICATING, HANDLING, SHIPPING, INSTALLING & BACKING OF TUSSELS.

CONNECTIONS WITH APPLICABLE PROVISIONS OF MOD (NATIONAL DESIGN SPEC. BY AREA) AND TPI. THE BCG SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TUSSELS IN COMPLIANCE WITH THE: ON FABRICATING, HANDLING, SHIPPING, INSTALLING & BACKING OF TUSSELS.

CONNECTION PLATES ARE MADE OF 201/8" (6.35mm) X 1/8" (3.18mm) X 1/8" (3.18mm) GALV. STEEL. APPLY THE FOLLOWING TOLERANCES UNLESS OTHERWISE SPECIFIED ON THIS DESIGN. POSITION PER TUSSELS 160.4. ANY DEVIATION FROM THIS DESIGN SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.

DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TUSSELS. THE BCG SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TUSSELS IN COMPLIANCE WITH THE: ON FABRICATING, HANDLING, SHIPPING, INSTALLING & BACKING OF TUSSELS.

DESIGN SHOWN. THE SUSTAINABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.




TC LL	20.0 PSF	REF	R8228 - 23128
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228 Q7065012
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT. LD.	40.0 PSF	SEQN -	155279
DUR. FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF -	1T5E8228203

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense

Wind reactions based on MFRS pressures.

Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ GCPI(+/-)-0.18
In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.



←1-6-0→

←5-0-0 Over 3 Supports →

R=331 U=180 W=3.5"

PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC

Cq/RT=1.00(1.25)/10(0)

7.24.12


TY:1

FL/-/4/-/-/R/-


Scale =.5"/Ft.

****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCSI (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE), 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND WCA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI: OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY ASEP) AND TPI. ITW BCG CONNECTOR PLATES ARE MADE OF 2018/1604 (A1) (W/55/51) ASH 1603 GRADE 40/60 (W, R/H/55) GALV. STEEL. APPLY TO ALL TRUSSES. ALL TRUSSES SHALL BE DESIGNED AND MANUFACTURED IN ACCORDANCE WITH THE DESIGN DRAWING. ANY INSPECTION OF PLATES FOLLOWED BY PROFESSIONAL ENGINEERING RESPONSIBILITY SOCIETY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



ITW Building Components Group, Inc.
Haines City, FL 33844




TC LL	20.0 PSF	REF	R8228-23129
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228 47065013
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN-	155284
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8228Z03

Hipjack supports 7-0-0 setback jacks with no webs.

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.

Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.


$$\overleftrightarrow{2-1-7}$$

R-461 U-180 W-4.95" 9-10-13 Over 3 Supports

PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)

$$Cq/RT=1.00(1.25)/10(0)$$

7.24.3

TY:1 FL/-/4/-/-/R/-

Scale = .5"/Ft.

WARNING—PROCES BUILDING EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, AND BRACING REFER TO GC#1 (BUILDING COMPONENT SAFETY INFORMATION). PUBLISHED BY IP1 (IRISS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND WICA (WOOD PRESERVATION COUNCIL OF AMERICA, 65000 ROCKY HILL DRIVE, SUITE 312, FARMINGTON, CT, 06031) FOR THE PURPOSES OF THE FOLLOWING: UNLESS OTHERWISE INDICATED, FOR CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED RIGID CEILING.

* * IMPORTANT * * FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITM BCG, INC. SHALL NOT

TPI; OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

CONNECTOR PLATES ARE MADE OF 20/18/16GA (W./H./SS/K) ASIM A653 GRADE 40/60 (W. K/H.SS) GALV. STEEL. APPLY PLATES TO EACH FACE OF TRUSS AND UNLESS OTHERWISE LOCATED ON THIS DESIGN POSITION PER DRAWINGS 160A-2

DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT

BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.

100

TTW Building Components Group, Inc.
Haines City, FL 33844
E1 Certificate of Authorization # 667

ALPINE

Mar 06 '07


TC LL	20.0 PSF	REF	R8228-23130
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228-07065030
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN-	155301
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8248Z03

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense

Wind reactions based on MMFRS pressures.

Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf, lw=1.00 GCPI(+/-)=0.18
In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.



←1-6-0→

3-0-0 Over 3 Supports

R=262 U=180 W=3.5"

PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC

Cq/RT=1.00(1.25)/10.0

7.24.1


FL/-/4/-/R/-

Scale =.5"/ft.

WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCST (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI TRUSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314 AND WICA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN; ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI: OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY AF&PA) AND TPI. ITW BCG CONNECTION PLATES ARE MADE OF 2018/1604 (A1) 4060 (N, K/H/SS) GALV. STEEL. APPLY PLATES TO EACH END OF TRUSS AND UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 1604.2.

ITW Building Components Group, Inc.
Haines City, FL 33844
The suitability and use of this component for any building is the responsibility of the building designer per ANSI/TPI 1 SEC. 2.



TC LL	20.0 PSF	REF	R8228-23131
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCSR8228 07065004
BC LL	0.0 PSF	HC-ENG	JB/AP
TOT.LD.	40.0 PSF	SEQN-	155288
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8228203


110 mph wind, 15.00 ft mean hgt., ASCE 7-02, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 Gcpl(+/-)=0.18

In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.

Scale = .5" / Ft.



R=254 U=180 W=3.5"


[illegible]

TC LL	20.0 PSF	REF	R8228-23132
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCSA8228 07065031
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEON-	155291
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8258Z03

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Wind reactions based on MWFRS pressures.
Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf, IW=1.00 Gcp1(+/-)=0.18 In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.



1-6-0

2-3-8
7-0-0 Over 3 Supports
R=408 U=180 W=3.5"

PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC

Cq/RT=1.00(1.25)/10(0)

7.24.1


FL/-/4/-/R/-

Scale = .5"/ft.

WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCSI BUILDING COMPONENT SAFETY INFORMATION PUBLISHED BY TPI TRUSS PLATE INSTITUTE, 210 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA 22314 AND WCA (WOOD TRUSS COUNCIL OF AMERICA, ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITM BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI OR FABRICATING, HANDLING, SHIPPING, INSTALLING A BRACING OF TRUSSES.

DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY AFAPA) AND TPI. ITM BCG CONNECTION PLATES ARE MADE OF 20/18/16GA (W/1/32IN) ASTM A653 GRADE 40/60 (K, K/1/32) GALV. STEEL. APPLY PLATES TO EACH FACE OF TRUSS AND, UNLESS OTHERWISE INDICATED ON THIS DESIGN, POSITION PER DRAWINGS 160A, 2, 160B, 2, 160C, 2, 160D, 2, 160E, 2, 160F, 2, 160G, 2, 160H, 2, 160I, 2, 160J, 2, 160K, 2, 160L, 2, 160M, 2, 160N, 2, 160O, 2, 160P, 2, 160Q, 2, 160R, 2, 160S, 2, 160T, 2, 160U, 2, 160V, 2, 160W, 2, 160X, 2, 160Y, 2, 160Z, 2. DRAWING INDICATES THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



ITM Building Components Group, Inc.
Haines City, FL 33844
Tel: 888-847-4447



FL/-/4/-/R/-

Scale = .5"/ft.

TC LL 20.0 PSF REF R8228-23133

TC DL 10.0 PSF DATE 03/06/07

BC DL 10.0 PSF DRW HCUSR8228 07065032

BC LL 0.0 PSF HC-ENG JB/AF

TOT.LD. 40.0 PSF SEON-156129

DUR.FAC. 1.25 FROM JFB


SPACING 24.0" JREF-175E8228203

(7-075-MADE MILLIS CONSTRUCTION SPEC LOT 39 CROSSWINDS - ** C/J3 S)
 Top chord 2x4 SP #2 Dense
 Bot chord 2x4 SP #2 Dense
 Webs 2x4 SP #3

Wind reactions based on MMFRS pressures.

Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. lw=1.00 GCPI (+/-)=0.18
 In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.



←1-6-0→

2-3-8
 3-0-0 Over 3 Supports
 R=262 U=180 W=3.5

PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC
 Cq/RI=1.00(1.25)/10(0)

7.24.1

TY:1


FL/-/4/-/R/-

Scale = .5"/ft.


WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCST (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND WCA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. TTM BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN; ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI; OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

DESIGN COMPLIES WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY AIA/PAI) AND TPI. DESIGN LOADS ARE: DEAD (20/10/10/0), LIVE (30/15/15/0), WIND (ASCE 7-02, 15.00 PSF), AND SEISMIC (ASCE 7-02, 0.05). ALL DIMENSIONS ARE IN FEET AND INCHES. ALL MATERIALS SHALL BE GRADE 40/60 (K, K<70.5) GALV. STEEL. APPLY ALL DIMENSIONS TO EXTERIOR SURFACES. ALL DIMENSIONS SHALL BE PERMITTED PER DIMENSIONS SHOWN. ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PERMITTED AS OF TPI-2002 SECTION PER DIMENSIONS SHOWN. DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENTS DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



TC LL	20.0 PSF	REF	R8228-23135
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228 07065016
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEON-	156135
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8228203




TTM Building Components Group, Inc.
 Gaines City, FL 33844
 813-333-1111

Top chord 2x6 SP #2
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Wind reactions based on MWFRS pressures.

Hipjack supports 7'-0" setback jacks with no webs.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ $G_{CPI}(+/-)=-0.18$
In lieu of structural panels or rigid ceiling use purlins to brace TC @ 24" OC, BC @ 24" OC.
Deflection meets L/240 live and L/180 total load. Creep increase factor for dead load is 1.50.



9'-10-13 Over 3 Supports
R=336 U=180 W=4.95

PLT TYP. Wave

Design Crit: TPI-2002(STD)/FBC

Cq/RT=1.00(1.25)/10(0)



FL/-/4/-/R/-

Scale = .5"/ft.

T/W Building Components Group, Inc. Haines City, FL 33844 Certificate of Approval No. 457		ALPINE		No. 59687 ARTHUR P. FISHER Professional Engineer STATE OF FLORIDA 06/07		REF R8228-23136 DATE 03/06/07 DRW HCUR8228 07065033 HC-ENG JB/AF SEON-156151 FROM JFB JREF-1T5E8228203	
WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BEST BUILDING COMPONENT SAFETY INFORMATION PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND TICA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.		**IMPORTANT** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. T/W BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES, BY ACPA AND TPI. T/W BCG DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY AF&PA) AND TPI. T/W BCG CONNECTION PLATES ARE MADE OF 20/18/16GA (U, W, S, K) ASTM A653 GRADE 40/60 (K, R, H, S) GALV. STEEL. APPLY PLATES TO EACH FACE OF TRUSS AND, UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 160A, 2, AND INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER AMES 03 OF TPI 2002 SEC. 3.3. A SEAL ON THIS DESIGN SHOWS THAT THE DESIGNER HAS REVIEWED THE DESIGN AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.		TC LL 20.0 PSF TC DL 10.0 PSF BC DL 10.0 PSF BC LL 0.0 PSF TOT. LD. 40.0 PSF DUR. FAC. 1.25 SPACING 24.0"			

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3


Wind reactions based on MWFRS pressures.

In lieu of structural panels or rigid ceiling use purlins to
brace TC @ 24" OC, BC @ 24" OC.

110 mph wind, 15.00 ft mean hgt, ASCE 7-02, CLOSED bldg, located
anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC
DL=5.0 psf, lw=1.00 GCPI(+/-)=0.18

Right end vertical not exposed to wind pressure.

Deflection meets L/240 live and L/180 total load. Creep increase
factor for dead load is 1.50.



←1-6-0→

0'-0'-8

←4-0-0 Over 2 Supports →
R-295 U-180 W-3.5" R-135 U-180 W-3.5"

PLT TYP. Wave


Design Cr1t: TPI-2002(STD)/FBC
Cq/RT=1.00(1.25)/10(0)

7.24.1


Scale = .5"/ft.

****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCST (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND WCA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITM BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN; ANY FAILURE OF THE TRUSS IN CONFORMANCE WITH TPI: OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. THE BCG DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY AF&PA) AND TPI. THE BCG CONNECTION PLATES ARE MADE OF 20/18/16GA (W/1/32IN) ASTM A653 GRADE 40/60 (W/ K/1/32IN) GALV. STEEL. APPLY TO ALL TRUSS PLATES AND ALL TRUSS MEMBERS. THE TRUSS SHALL BE PERMANENTLY MARKED WITH THE BCG DESIGN NUMBER AND DATE OF DESIGN. ANY INSPECTION OF PLATES FOLLOWED BY TPI SHALL BE PERMANENT AND SEALS ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



ITW Building Components Group, Inc.
Haines City, FL 33844
Certificate of Authorization # 647



FL / - / 4 / - / - / R / -		Scale = .5"/ft.	
TC LL	20.0 PSF	REF	R8228-23137
TC DL	10.0 PSF	DATE	03/06/07
BC DL	10.0 PSF	DRW	HCUSR8228 07065034
BC LL	0.0 PSF	HC-ENG	JB/AF
TOT.LD.	40.0 PSF	SEQN-	156167
DUR.FAC.	1.25	FROM	JFB
SPACING	24.0"	JREF-	1T5E8228203

THIS DETAIL IS TO BE USED WHEN CONTINUOUS LATERAL BRACING (CLB) IS SPECIFIED ON AN ALPINE TRUSS DESIGN BUT AN ALTERNATIVE WEB BRACING METHOD IS DESIRED.

THIS DETAIL IS ONLY APPLICABLE FOR CHANGING THE SPECIFIED CLB SHOWN ON SINGLE PLY SEALED DESIGNS TO T-BRACING OR SCAB BRACING.

ALTERNATIVE BRACING SPECIFIED IN CHART BELOW MAY BE CONSERVATIVE.
FOR MINIMUM ALTERNATIVE BRACING, RE-RUN DESIGN WITH APPROPRIATE
BRACING.

WEB MEMBER SIZE	SPECIFIED CLB BRACING	T OR L-BRACE	ALTERNATIVE BRACING SCAB BRACE
2X3 OR 2X4	1 ROW	2X4	1-2X4
2X3 OR 2X4	2 ROWS	2X6	2-2X4
2X6	1 ROW	2X4	1-2X6
2X6	2 ROWS	2X6	2-2X6(*)
2X8	1 ROW	2X6	1-2X8
2X8	2 ROWS	2X6	2-2X6(*)

T-BRACE, L-BRACE AND SCAB BRACE TO BE SAME SPECIES AND GRADE OR BETTER THAN WEB MEMBER UNLESS SPECIFIED OTHERWISE ON ENGINEER'S SEALED DESIGN.

(*) CENTER SCAB ON WIDE FACE OF WEB. APPLY (1) SCAB TO EACH FACE OF WEB.




ALPINE ENGINEERED PRODUCTS, INC.
POMPANO BEACH, FLORIDA

*****WARNING*****
 THESE PROCESSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND
 BRACING. REFER TO BEST BUILDING COMPONENT SAFETY INFORMATION, PUBLISHED BY THE TRUSS PLATE
 INSTITUTE, 218 NORTH LEE STR., SUITE 314, ALEXANDRIA, VA 22314 AND VITA GOOD TRUSS COUNCIL OF
 AMERICA, 6300 ENTERPRISE LANE, MADISON, VI 53719 FOR SAFETY PRACTICES PRIOR TO REPAIRING THESE
 PANELS. UNLESS OTHERWISE INDICATED, THE CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL
 PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.


FURNISH COPY OF THIS DESIGN TO INSTALLATION CONTRACTOR. ALPINE ENGINEERED QUALITY NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO

BUILD THE TRUSS IN CONFORMANCE WITH THE DR FABRICATION, HANDLING AND SHIPPING INSTALLATION SPECIFICATIONS. BRACING OF TRUSSES DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF NDS CANADIAN DESIGN SPEC, BY A876-90 AND TPI. ALPINE CONNECTOR PLATES ARE MADE OF 20/18/16/64 C/V/H/55/XO ASTM A653 GRADE 40/60 C/V/H/55/33 GALV STEEL. APPLY PLATES TO EACH FACE OF TRUSS AND UNLESS OTHERWISE INDICATED, LOCATE THIS DESIGN POSITION PER DRAWINGS 160A-Z AND INSPECTION CHECKLIST FOLLOWED BY CHAIRMAN'S SIGNATURE. THE DESIGN POSITION FOR THE TRUSS COMPONENT DESIGN SHOWS THE PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUSTAINABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER. PER ANSI/TPI 1 SEC. 2.

ATTACH TO EITHER SIDE OF WEB
NARROW FACE
ATTACH WITH 10D BOX OR GUN
(0.128" x 3".MIN) NAILS.
AT 6" O.C. BRACE IS A
MINIMUM 80% OF WEB
MEMBER LENGTH




APPLY SCAB(S) TO WIDE FACE OF WEB
NO MORE THAN (1) SCAB PER FACE.
ATTACH WITH 10d BOX OR GUN
(0.128"x 3",MIN) NAILS.
AT 6" O.C. BRACE IS A MINIMUM
80% OF WEB MEMBER LENGTH



TC LL	PSF	REF	CLB	SUBST.
-------	-----	-----	-----	--------


TC LL	PSF	REF	CLB	SUBST.
TC DL	PSF	DATE	11/1/06	
BC DL	PSF	DRWG	BRCCLBSUB1106	
BC LL	PSF	-ENG	MLH/KAR	
TOT. LD.	PSF			
DUR. FAC.				
SPACING				




TOP CHORD FILLER DETAIL

- + 2X4 CONTINUOUS LATERAL BRACING AT 24" O.C.
 MAXIMUM SPACING. ATTACH TO EACH TOP CHORD WITH
 (2) 16d COMMON (0.162"x 3.5", MIN) NAILS.
 BRACING MATERIAL TO BE SUPPLIED AND ATTACHED
 AT BOTH ENDS TO A SUITABLE SUPPORT BY ERECTION CONTRACTOR.
 ++ 2X4 SO. PINE #2 N OR SPF #1/#2 FILLER TOP CHORD.
 +++ 2X4 SO. PINE #3 OR SPF #1/#2 VERTICAL WEBS SPACED
 48" OC MAXIMUM.
 * 8/12 MAXIMUM PITCH.
 ** 2X8.25 PIGGYBACK SPECIAL PLATE. SEE DRAWING PIGBACKB0699
 FOR PIGGYBACK SPECIAL PLATE INFORMATION.
 *** 6'0" MAXIMUM HEIGHT.
 † W2X4 OR 3X6 TRUFOX.
 ‡ REFER TO ENGINEER'S SEALED DESIGN REFERENCING THIS
 DETAIL FOR LUMBER, PLATES, AND OTHER INFORMATION NOT
 SHOWN.
 0.120"x 1.375" NAILS REQUIRED
 FOR TRUFOX PLATE ATTACHMENT. NAILS SPECIFIED
 IN CIRCLES MUST BE APPLIED TO EACH FACE OF EACH TRUSS PLV.
 SEE DWG. 160TL FOR NAILING AND TRUFOX PLATE REQUIREMENTS.


EXTENDED TOP CHORD FILLER DETAIL



OFFSET FILLER DETAIL



TOP CHORD FILLER DETAIL




THIS DRAWING REPLACES DRAWING 884,080

TC LL	MAX 30 PSF	REF	TC-FILLER
TC DL	MAX 15 PSF	DATE	11/1/06
BC DL	MAX 10 PSF	DRWG	TCFILLER1106
BC LL	0 PSF	-ENG	SJP/KAR
TOT. LD. MAX	55 PSF		
DUR. FAC. 1.15 OR 1.33			
SPACING	24.0"		

TESTS REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND MAINTAINING. REFER TO BEST BUILDING COMPONENT SAFETY INFORMATION, PUBLISHED BY THE STEEL INSTITUTE, 218 NORTH LEE STR., SUITE 312, ALEXANDRIA, VA 22304, AND WELD WOOD TRUSS COUNCIL, BOX AMERICA, 6300 ENTERPRISE IN WADSWORTH, AL 35379, FOR SAFETY PRACTICES PRIOR TO TRUSSING THESE PANELS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PLYWOOD ATTACHED RIGID CEILING.

א

ALPINE ENGINEERED PRODUCTS, INC.
POMPANO BEACH, FLORIDA



BOTTOM CHORD FILLER DETAIL.


- * OPTIONAL INTERIOR OR CANTILEVER BEARING. MINIMUM PLATE SIZES (1X3 WAVE) MAY BE USED IF BEARING IS OMITTED. WEDGE OR VERTICAL MEMBER MUST COINCIDE WITH BEARING LOCATION.

0.120" X 1.375", NAILS, REQUIRED FOR TRULOX PLATE ATTACHMENT. NAILS SPECIFIED IN CIRCLES MUST BE APPLIED TO EACH FACE OF THE TRUSS. SEE DWG. 160TL FOR NAILING AND TRULOX PLATE REQUIREMENTS.

REFER TO ENGINEER'S SEALED DESIGN REFERENCING THIS
DETAIL FOR LUMBER, PLATES, AND OTHER INFORMATION NOT
SHOWN.

ALL TRULOX PLATES SHOWN ARE MINIMUMS. LARGER PLATES MAY BE REQUIRED TO ACCOMMODATE REQUIRED NAILS (**)

FILLER BOTTOM CHORD OR WEDGE SPECIES	MAXIMUM REACTION		MINIMUM BEARING AREA	** REQUIRED NAILS PER FACE WITH TRULOX PLATES					
	DOWNWARD	UPLIFT		1.00 D.O.L.	1.15 D.O.L.	1.25 D.O.L.	1.33 D.O.L.	1.60 D.O.L.	
DOUGLAS FIR-LARCH	3281#	1656#	1.5" X 3.5"	12	11	10	9	8	
HEM-FIR	2126#	1095#	1.5" X 3.5"	9	8	7	7	6	
SPRUCE-PINE-FIR	2231#	1192#	1.5" X 3.5"	10	9	8	8	6	
SOUTHERN PINE DENSE	3465#	1791#	1.5" X 3.5"	12	11	10	9	8	
SOUTHERN PINE	2966#	1492#	1.5" X 3.5"	10	9	8	8	7	
SOUTHERN PINE NON-DENSE	2520#	1343#	1.5" X 3.5"	9	8	7	7	6	




DRAWING REPLACES DRAWINGS A115 A115/R & 884,132

ALPINE

ALPINE ENGINEERED PRODUCTS, INC.
POMPANO BEACH, FLORIDA

WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BEST BUILDING COMPONENT SAFETY INFORMATION, PUBLISHED BY THE TRUSS PLATE INSTITUTE, 218 NORTH LEE STR., SUITE 314, ALEXANDRIA, VA 22314 AND VICA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LN, WADSWORTH, VI 5319) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT FURNISH COPY OF THIS DESIGN TO INSTALLATION CONTRACTOR. ALPINE ENGINEERED PRODUCTS, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES DESIGN CONDITIONS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. FOR AREA) AND TPI. ALPINE CONNECTOR PLATES ARE MADE OF 2018/16164 (A/H/SS2) ASTM A653 GRADE 60 UNFINISHED STEEL. UNLESS OTHERWISE INDICATED, ALL TRUSS MEMBERS SHALL BE MINIMUM 2" THICK. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL BE MINIMUM 2" THICK. UNLESS OTHERWISE INDICATED, BOTTOM CHORD SHALL BE MINIMUM 2" THICK. UNLESS OTHERWISE INDICATED, ALL TRUSS MEMBERS SHALL BE PER ANNEK A3 OF TPI 1-2002 SEC. 3. A SEAL ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS CONSTRUCTION DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER. PER ANSI/TPI 1 SEC. 2.



TC LL	—	PSF	REF	BC FILLER
TC DL	—	PSF	DATE	11/1/06
BC DL	10.0	PSF	DRWG	BCFILLER1106
BC LL	—	PSF	-ENG	DLJ/KAR
TOT. LD.	—	PSF		
DUR. FAC.10/1.15/1.25/1.33				
SPACING 24.0"				

BOTTOM CHORD FILLER REPAIR

RECOMMENDED REPAIR PROCEDURE

1. MEASURE DISTANCE FOR NEW LENGTH OF FILLER.
2. APPLY NEW 2X4 STUD GRADE OR BETTER VERTICAL SCAB TO BOTTOM CHORD AND FILLER WITH (3) NAILS 0.131" DIA. x 3.0" OR LARGER, (I.E. 10d OR 16d COMMON, SINKER, GUN, OR 16d BOX NAILS) TO EACH END OF VERTICAL.
3. CAREFULLY REMOVE EFFECTED CONNECTOR PLATES. USE CARE NOT TO DAMAGE THE REMAINING CONNECTOR PLATES OR LUMBER IN ANY WAY.
4. TRIM FILLER TO LENGTH, AT EDGE OF NEW VERTICAL SCAB.


MAXIMUM BOTTOM CHORD LOAD IS 10 PSF.

+ BOTTOM CHORD FILLER TO BE REMOVED. SEE NOTE #3.

++ FIELD APPLIED FILLER.

* 2X4 STUD GRADE OR BETTER VERTICAL SCAB. ATTACH TO BOTTOM CHORD AND FILLER WITH (3) NAILS WITH A MIN. 0.131" DIA. X 3.0" LENGTH.

REFER TO ENGINEER'S SEALED DESIGN REFERENCE THIS DETAIL FOR ALLOWABLE FILLER DIMENSIONS, PLACEMENT, AND WEBBING.



FIELD APPLIED FILLER MUST BE SPF #3 OR BETTER.


THIS DRAWING REPLACES DRAWING 962.767

ALPINE

ALPINE ENGINEERED PRODUCTS, INC.
POMPANO BEACH, FLORIDA

WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BEST BUILDING CODES (IN OR OUT OF STATE), AND SPEED BUILD TRUSS MANUFACTURING INSTITUTE, 6300 ENTERPRISE LN., MADISON, WI 53719 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT FURNISH COPY OF THIS DESIGN TO INSTALLATION CONTRACTOR. ALPINE ENGINEERED PRODUCTS, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN, ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. DESIGN CONDITIONS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. FOR WOOD CONSTRUCTION) SHALL BE USED. ALL TRUSSES SHALL BE DESIGNED TO MEET THE FOLLOWING: 40/60 (K/INCH) TENSILE STRENGTH FOR PLATES TO EACH FACE OF TRUSS AND UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 1604-2. ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A3 OF TPI 1-2002 SEC. 3. A SEAL ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER, PER ANSI/TPI 1 SEC. 2.




REF	BC FILLER REP.
DATE	11/1/06
DRWG	REPBCE11106
-ENG	MLH/KAR

GABLE VERTICAL SPACING	2X4 BRACE SPECIES	GRADE	NO BRACES	BRACE											
				(1) 1X4 "L" BRACE •	(1) 2X4 "L" BRACE •	(2) 2X4 "L" BRACE •	(1) 2X6 "L" BRACE •	(2) 2X6 "L" BRACE •	(1) 2X6 "L" BRACE •	(2) 2X6 "L" BRACE •	(1) 2X6 "L" BRACE •	(2) 2X6 "L" BRACE •	(1) 2X6 "L" BRACE •	(2) 2X6 "L" BRACE •	(1) 2X6 "L" BRACE •
12" O.C.	SPF	#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 5"	9' 8"	12' 5"	12' 9"	14' 0"	14' 0"	14' 0"	14' 0"
		#3	3' 9"	6' 0"	6' 0"	7' 11"	8' 1"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	14' 0"	14' 0"
		STUD	3' 9"	6' 0"	6' 0"	7' 11"	8' 1"	9' 5"	9' 5"	12' 3"	12' 3"	14' 0"	14' 0"	14' 0"	14' 0"
	HF	#1	3' 9"	5' 2"	5' 2"	6' 9"	6' 9"	9' 1"	10' 7"	10' 7"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
		#2	4' 3"	6' 8"	7' 2"	7' 11"	8' 6"	9' 5"	10' 2"	12' 5"	13' 5"	14' 0"	14' 0"	14' 0"	14' 0"
		STUD	4' 3"	6' 8"	7' 2"	7' 11"	8' 6"	9' 5"	10' 2"	12' 5"	13' 5"	14' 0"	14' 0"	14' 0"	14' 0"
16" O.C.	SPF	#1	4' 0"	6' 2"	6' 2"	7' 11"	8' 1"	9' 5"	10' 2"	12' 5"	13' 5"	14' 0"	14' 0"	14' 0"	14' 0"
		#2	4' 0"	6' 2"	6' 2"	7' 11"	8' 1"	9' 5"	10' 2"	12' 5"	13' 5"	14' 0"	14' 0"	14' 0"	14' 0"
		STUD	4' 0"	6' 2"	6' 2"	7' 11"	8' 1"	9' 5"	10' 2"	12' 5"	13' 5"	14' 0"	14' 0"	14' 0"	14' 0"
	HF	#1	4' 0"	6' 1"	6' 1"	7' 11"	8' 0"	9' 5"	9' 11"	12' 5"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"
		#2	4' 0"	6' 1"	6' 1"	7' 11"	8' 0"	9' 5"	9' 11"	12' 5"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"
		STUD	4' 0"	6' 1"	6' 1"	7' 11"	8' 0"	9' 5"	9' 11"	12' 5"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"
24" O.C.	SPF	#1	3' 10"	5' 3"	5' 3"	6' 11"	6' 11"	9' 4"	9' 4"	10' 10"	10' 10"	14' 0"	14' 0"	14' 0"	14' 0"
		#2	4' 5"	7' 8"	7' 8"	9' 1"	9' 4"	10' 10"	11' 1"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
		STUD	4' 5"	7' 8"	7' 8"	9' 1"	9' 4"	10' 10"	11' 1"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	HF	#1	4' 4"	7' 4"	7' 4"	9' 1"	9' 1"	10' 10"	10' 10"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
		#2	4' 4"	7' 4"	7' 4"	9' 1"	9' 1"	10' 10"	10' 10"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
		STUD	4' 4"	7' 4"	7' 4"	9' 1"	9' 1"	10' 10"	10' 10"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"

BRACING GROUP SPECIES AND GRADES:					
GROUP A:			GROUP B:		
SPRUCED-PINE-FIR			HEM-FIR		
#1 / #2	STUD	STUD	#2	STUD	STUD
#3	STUD	STUD	#3	STUD	STUD
DOUGLAS FIR-LARCH			SOUTHERN PINE		
#3	STUD	STUD	#3	STUD	STUD
STANDARD	STUD	STUD	STANDARD	STUD	STUD

GABLE TRUSS DETAIL NOTES:

LIVE LOAD DEFLECTION CRITERIA IS L/240
 PROVIDE UPLIFT CONNECTIONS FOR 80 PSF OVER
 CONTINUOUS BEARING (5 PSF TC DEAD LOAD).
 GABLE END SUPPORTS LOAD FROM 4' 0"
 OUTLOOKERS WITH 2' 0" OVERHANG, OR 12"
 PLYWOOD OVERHANG.
 ATTACH EACH "L" BRACE WITH 10d NAILS.
 * FOR (1) "L" BRACE: SPACE NAILS AT 2' 0" O.C.
 IN 18" END ZONES AND 4' 0" O.C. BETWEEN ZONES.
 ** FOR (2) "L" BRACES: SPACE NAILS AT 3' 0" O.C.
 IN 18" END ZONES AND 6' 0" O.C. BETWEEN ZONES.
 "L" BRACING MUST BE A MINIMUM OF 80% OF WEB
 MEMBER LENGTH.



GABLE VERTICAL PLATE SIZES			
VERTICAL LENGTH	NO SPLICE	1X4 OR 2X3	2X4
LESS THAN 4' 0"			
GREATER THAN 4' 0", BUT LESS THAN 11' 6"			
GREATER THAN 11' 6"			2.5X4

+ REFER TO COMMON TRUSS DESIGN FOR PEAK, SPLICE, AND HEEL PLATES.

ALPINE

ALPINE ENGINEERED PRODUCTS, INC.
POMPAHO BEACH, FLORIDA

MAX. TOT. LD. 60 PSF

MAX. SPACING 24.0"

REF ASC7-02-GAB11015

DATE 11/1/06

DRWG A11015EE1106

-ENG


Mar 06

PROFESSIONAL ENGINEER

STATE OF FLORIDA

No. 59867

GABLE DETAIL FOR LET-IN VERTICALS




CABLE VERTICAL PLATE SIZES

VERTICAL LENGTH BETWEEN CHORDS	PLATE SIZE	IF PLATES OVERLAP*
LESS THAN 4' 0"	1X4 OR 2X3	2X8
GREATER THAN 4' 0", BUT LESS THAN 11' 6"	2X4	2X8
GREATER THAN 11' 6"	2.5X4	2.5X8

* REFER TO ENGINEERED TRUSS DESIGN FOR PEAK, SPLICE, WEB AND HEEL PLATES.

* IF GABLE VERTICAL PLATES OVERLAP, USE A SINGLE PLATE TO SPAN THE WEB.



PROVIDE CONNECTIONS FOR UPLIFT SPECIFIED ON THE ENGINEERED TRUSS DESIGN. ATTACH EACH "T" REINFORCING MEMBER WITH HAND DRIVEN NAILS:
(4) 10d COMMON (0.148" X 3.3" MIN) TOENAILS AT 4" O.C. PLUS
(4) 16d COMMON (0.162" X 3.5" MIN) TOENAILS IN TOP AND BOTTOM CHORD.
(4) GUN DRIVEN NAILS:
8d COMMON (0.131" X 2.5" MIN) TOENAILS AT 4" O.C. PLUS
(4) TOENAILS IN TOP AND BOTTOM CHORD.


THIS DETAIL TO BE USED WITH THE APPROPRIATE ALPINE CABLE DETAIL FOR ASCE OR SBCCI WIND LOAD.
ASCE 7-93 GABLE DETAIL DRAWINGS
A11015EN1103, A10015EN1103, A09015EN1103, A08015EN1103, A11030EN1103, A10030EN1103, A09030EN1103, A08030EN1103, A07030EN1103
ASCE 7-98 GABLE DETAIL DRAWINGS
A13015EC1103, A12015EC1103, A11015EC1103, A10015EC1103, A08515EC1103
A13030EC1103, A12030EC1103, A11030EC1103, A10030EC1103, A08530EC1103
ASCE 7-02 GABLE DETAIL DRAWINGS
A13015EB0405, A12015EB0405, A11015EB0405, A10015EB0405, A08515EB0405, A13030EB0405, A12030EB0405, A11030EB0405, A10030EB0405, A08530EB0405

SEE APPROPRIATE ALPINE GABLE DETAIL (ASCE OR SBCCI WIND LOAD) FOR MAXIMUM UNREINFORCED GABLE VERTICAL LENGTH.

WARNING: TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO THE TRUSS MANUFACTURER'S SPECIFICATIONS FOR THE TRUSS MANUFACTURER'S INSTRUCTIONS. 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA 22314, AND VITA (WOOD) TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LN, MADISON, WI 53719, FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.



TO CONVERT FROM "L" TO "T" REINFORCING MEMBERS, MULTIPLY "T" FACTOR BY LENGTH (BASED ON CABLE VERTICAL SPECIES, GRADE AND SPACING) FOR (1) 2X4 "L" BRACE, GROUP A, OBTAINED FROM THE APPROPRIATE ALPINE GABLE DETAIL FOR ASCE OR SBCCI WIND LOAD.




WEB LENGTH INCREASE W/ "T" BRACE

WIND SPEED AND MRR	"T" REINFORCING MEMBER SIZE	SBCCI	ASCE
110 MPH	2x4	10 %	10 %
15 FT	2x4	40 %	50 %
110 MPH	2x4	10 %	10 %
30 FT	2x6	50 %	50 %
100 MPH	2x4	10 %	10 %
15 FT	2x6	30 %	50 %
100 MPH	2x4	10 %	10 %
30 FT	2x6	40 %	40 %
90 MPH	2x4	20 %	10 %
15 FT	2x6	20 %	40 %
90 MPH	2x4	10 %	10 %
30 FT	2x6	30 %	50 %
80 MPH	2x4	10 %	20 %
15 FT	2x6	10 %	30 %
80 MPH	2x4	20 %	10 %
30 FT	2x6	20 %	40 %
70 MPH	2x4	0 %	20 %
15 FT	2x6	0 %	20 %
70 MPH	2x4	10 %	20 %
30 FT	2x6	10 %	30 %

EXAMPLE:
ASCE WIND SPEED = 100 MPH
MEAN ROOF HEIGHT = 30 FT
CABLE VERTICAL = 24" O.C. SP #3
"T" REINFORCING MEMBER SIZE = 2X4
"T" BRACE INCREASE (FROM ABOVE) = 10% = 1.10
(1) 2X4 "L" BRACE LENGTH = 6' 7"
MAXIMUM "T" REINFORCED GABLE VERTICAL LENGTH
1.10 x 6' 7" = 7' 3"

REPLACES DRAWINGS GAB98117 876,719 & HC28294035

MAX TOT. LD. 60 PSF	REF	LET-IN	VERT
DUR. FAC. ANY	DATE	11/1/06	
MAX SPACING 24.0"	DRWG	GBLETTIN1106	
	-ENG	DJL/KAR	



Residential System Sizing Calculation

Summary

Spec House Lot 39 Crosswinds S/D
FL

Project Title:
702263WadeWillisConstruction

Class 3 Rating
Registration No. 0
Climate: North


3/19/2007

Location for weather data: Gainesville - Defaults: Latitude(29) Altitude(152 ft.) Temp Range(M)			
Humidity data: Interior RH (50%) Outdoor wet bulb (77F) Humidity difference(54gr.)			
Winter design temperature	33 F	Summer design temperature	92 F
Winter setpoint	70 F	Summer setpoint	75 F
Winter temperature difference	37 F	Summer temperature difference	17 F
Total heating load calculation	27132 Btuh	Total cooling load calculation	21856 Btuh
Submitted heating capacity	% of calc Btuh	Submitted cooling capacity	% of calc Btuh
Total (Electric Heat Pump)	117.9 32000	Sensible (SHR = 0.75)	140.1 24000
Heat Pump + Auxiliary(0.0kW)	117.9 32000	Latent	169.2 8000
		Total (Electric Heat Pump)	146.4 32000

WINTER CALCULATIONS

Winter Heating Load (for 1478 sqft)


Load component	Load
Window total 160 sqft	5150 Btuh
Wall total 1220 sqft	4007 Btuh
Door total 60 sqft	777 Btuh
Ceiling total 1558 sqft	1836 Btuh
Floor total 180 sqft	7859 Btuh
Infiltration 185 cfm	7504 Btuh
Duct loss	0 Btuh
Subtotal	27132 Btuh
Ventilation 0 cfm	0 Btuh
TOTAL HEAT LOSS	27132 Btuh



SUMMER CALCULATIONS

Summer Cooling Load (for 1478 sqft)

Load component	Load
Window total 160 sqft	8341 Btuh
Wall total 1220 sqft	2441 Btuh
Door total 60 sqft	588 Btuh
Ceiling total 1558 sqft	2580 Btuh
Floor total	0 Btuh
Infiltration 97 cfm	1797 Btuh
Internal gain	1380 Btuh
Duct gain	0 Btuh
Sens. Ventilation 0 cfm	0 Btuh
Total sensible gain	17127 Btuh
Latent gain(ducts)	0 Btuh
Latent gain(infiltration)	3529 Btuh
Latent gain(ventilation)	0 Btuh
Latent gain(internal/occupants/other)	1200 Btuh
Total latent gain	4729 Btuh
TOTAL HEAT GAIN	21856 Btuh



For Florida residences only

EnergyGauge® System Sizing

PREPARED BY: *[Signature]*

DATE: 3-19-07

System Sizing Calculations - Winter

Residential Load - Whole House Component Details

Spec House Lot 39 Crosswinds S/D

Project Title:
702263WadeWillisConstruction

Class 3 Rating
Registration No. 0
Climate: North

, FL

Reference City: Gainesville (Defaults) Winter Temperature Difference: 37.0 F

3/19/2007

This calculation is for Worst Case. The house has been rotated 315 degrees.

Component Loads for Whole House

Window	Panes/SHGC/Frame/U	Orientation	Area(sqft)	X	HTM=	Load
1	2, Clear, Metal, 0.87	NW	30.0		32.2	966 Btuh
2	2, Clear, Metal, 0.87	NW	20.0		32.2	644 Btuh
3	2, Clear, Metal, 0.87	NW	30.0		32.2	966 Btuh
4	2, Clear, Metal, 0.87	NE	20.0		32.2	644 Btuh
5	2, Clear, Metal, 0.87	SE	30.0		32.2	966 Btuh
6	2, Clear, Metal, 0.87	SE	30.0		32.2	966 Btuh
Window Total			160(sqft)			5150 Btuh
Walls	Type	R-Value	Area	X	HTM=	Load
1	Frame - Wood - Ext(0.09)	13.0	1040		3.3	3415 Btuh
2	Frame - Wood - Adj(0.09)	13.0	180		3.3	591 Btuh
Wall Total			1220			4007 Btuh
Doors	Type		Area	X	HTM=	Load
1	Insulated - Adjacent		20		12.9	259 Btuh
2	Insulated - Exterior		20		12.9	259 Btuh
3	Insulated - Exterior		20		12.9	259 Btuh
Door Total			60			777Btuh
Ceilings	Type/Color/Surface	R-Value	Area	X	HTM=	Load
1	Vented Attic/D/Shin)	30.0	1558		1.2	1836 Btuh
Ceiling Total			1558			1836Btuh
Floors	Type	R-Value	Size	X	HTM=	Load
1	Slab On Grade	0	180.0 ft(p)		43.7	7859 Btuh
Floor Total			180			7859 Btuh
Zone Envelope Subtotal:						19629 Btuh
Infiltration	Type	ACH X	Zone Volume	CFM=		
	Natural	0.94	11824	185.2		7504 Btuh
Ductload	Average sealed, R6.0, Supply(Attic), Return(Attic) (DLM of 0.00)					0 Btuh
Zone #1	Sensible Zone Subtotal					27132 Btuh

WHOLE HOUSE TOTALS

	Subtotal Sensible	27132 Btuh
	Ventilation Sensible	0 Btuh
	Total Btuh Loss	27132 Btuh

Manual J Winter Calculations

Residential Load - Component Details (continued)

Spec House Lot 39 Crosswinds S/D

Project Title:

Class 3 Rating

Registration No. 0

Climate: North

, FL

702263WadeWillisConstruction

2/10/2007

Key: Window types (SHGC - Shading coefficient of glass as SHGC numerical value or as clear


(Frame types - metal, wood or insulated metal)

(U - Window U-Factor or 'DEF' for default)

(HTM - ManualJ Heat Transfer Multiplier)

Key: Floor size (perimeter(p) for slab-on-grade or area for all other floor types)

For Florida residences only



System Sizing Calculations - Winter

Residential Load - Room by Room Component Details

Spec House Lot 39 Crosswinds S/D
, FL

Project Title:
702263WadeWillisConstruction

Class 3 Rating
Registration No. 0
Climate: North

Reference City: Gainesville (Defaults) Winter Temperature Difference: 37.0 F
This calculation is for Worst Case. The house has been rotated 315 degrees.

3/19/2007

Component Loads for Zone #1: Main

Window	Panes/SHGC/Frame/U	Orientation	Area(sqft)	X	HTM=	Load
1	2, Clear, Metal, 0.87	NW	30.0		32.2	966 Btuh
2	2, Clear, Metal, 0.87	NW	20.0		32.2	644 Btuh
3	2, Clear, Metal, 0.87	NW	30.0		32.2	966 Btuh
4	2, Clear, Metal, 0.87	NE	20.0		32.2	644 Btuh
5	2, Clear, Metal, 0.87	SE	30.0		32.2	966 Btuh
6	2, Clear, Metal, 0.87	SE	30.0		32.2	966 Btuh
Window Total			160(sqft)			5150 Btuh
Walls	Type	R-Value	Area	X	HTM=	Load
1	Frame - Wood - Ext(0.09)	13.0	1040		3.3	3415 Btuh
2	Frame - Wood - Adj(0.09)	13.0	180		3.3	591 Btuh
Wall Total			1220			4007 Btuh
Doors	Type		Area	X	HTM=	Load
1	Insulated - Adjacent		20		12.9	259 Btuh
2	Insulated - Exterior		20		12.9	259 Btuh
3	Insulated - Exterior		20		12.9	259 Btuh
Door Total			60			777Btuh
Ceilings	Type/Color/Surface	R-Value	Area	X	HTM=	Load
1	Vented Attic/D/Shin)	30.0	1558		1.2	1836 Btuh
Ceiling Total			1558			1836Btuh
Floors	Type	R-Value	Size	X	HTM=	Load
1	Slab On Grade	0	180.0	ft(p)	43.7	7859 Btuh
Floor Total			180			7859 Btuh
Zone Envelope Subtotal:						19629 Btuh
Infiltration	Type	ACH X	Zone Volume	CFM=		
	Natural	0.94	11824	185.2		7504 Btuh
Ductload	Average sealed, R6.0, Supply(Attic), Return(Attic) (DLM of 0.00)					0 Btuh
Zone #1	Sensible Zone Subtotal					27132 Btuh

WHOLE HOUSE TOTALS

	Subtotal Sensible	27132 Btuh
	Ventilation Sensible	0 Btuh
	Total Btuh Loss	27132 Btuh

Manual J Winter Calculations

Residential Load - Component Details (continued)

Spec House Lot 39 Crosswinds S/D

Project Title:

Class 3 Rating

Registration No. 0

Climate: North

, FL

702263WadeWillisConstruction

01/10/2007



Key: Window types (SHGC - Shading coefficient of glass as SHGC numerical value or as clear

(Frame types - metal, wood or insulated metal)

(U - Window U-Factor or 'DEF' for default)

(HTM - ManualJ Heat Transfer Multiplier)

Key: Floor size (perimeter(p) for slab-on-grade or area for all other floor types)

For Florida residences only

System Sizing Calculations - Summer

Residential Load - Whole House Component Details

Spec House Lot 39 Crosswinds S/D

Project Title:

702263WadeWillisConstruction

Class 3 Rating

Registration No. 0

Climate: North

, FL

Reference City: Gainesville (Defaults)

Summer Temperature Difference: 17.0 F

3/19/2007

This calculation is for Worst Case. The house has been rotated 315 degrees.

Component Loads for Whole House

Window	Type*	Ornt	Overhang		Window Area(sqft)			HTM		Load	
	Pn/SHGC/U/InSh/ExSh/IS		Len	Hgt	Gross	Shaded	Unshaded	Shaded	Unshaded		
1	2, Clear, 0.87, None,N,N	NW	1.5ft.	5.5ft.	30.0	0.0	30.0	29	60	1801	Btuh
2	2, Clear, 0.87, None,N,N	NW	1.5ft.	5.5ft.	20.0	0.0	20.0	29	60	1201	Btuh
3	2, Clear, 0.87, None,N,N	NW	1.5ft.	5.5ft.	30.0	0.0	30.0	29	60	1801	Btuh
4	2, Clear, 0.87, None,N,N	NE	1.5ft.	5.5ft.	20.0	0.0	20.0	29	60	1201	Btuh
5	2, Clear, 0.87, None,N,N	SE	1.5ft.	0ft.	30.0	30.0	0.0	29	63	869	Btuh
6	2, Clear, 0.87, None,N,N	SE	1.5ft.	5.5ft.	30.0	12.1	17.9	29	63	1468	Btuh
Window Total					160 (sqft)					8341 Btuh	
Walls	Type	R-Value/U-Value			Area(sqft)		HTM		Load		
1	Frame - Wood - Ext	13.0/0.09			1040.0		2.1		2169 Btuh		
2	Frame - Wood - Adj	13.0/0.09			180.0		1.5		272 Btuh		
Wall Total						1220 (sqft)				2441 Btuh	
Doors	Type				Area (sqft)		HTM		Load		
1	Insulated - Adjacent				20.0		9.8		196 Btuh		
2	Insulated - Exterior				20.0		9.8		196 Btuh		
3	Insulated - Exterior				20.0		9.8		196 Btuh		
Door Total						60 (sqft)				588 Btuh	
Ceilings	Type/Color/Surface	R-Value			Area(sqft)		HTM		Load		
1	Vented Attic/DarkShingle	30.0			1558.0		1.7		2580 Btuh		
Ceiling Total						1558 (sqft)				2580 Btuh	
Floors	Type	R-Value			Size		HTM		Load		
1	Slab On Grade	0.0			180 (ft(p))		0.0		0 Btuh		
Floor Total						180.0 (sqft)				0 Btuh	
Zone Envelope Subtotal:										13950 Btuh	
Infiltration	Type	ACH			Volume(cuft)		CFM=		Load		
	SensibleNatural	0.49			11824		96.6		1797 Btuh		
Internal gain	Occupants			Btuh/occupant			Appliance		Load		
	6			X 230 +			0		1380 Btuh		
Duct load	Average sealed, R6.0, Supply(Attic), Return(Attic)							DGM = 0.00		0.0 Btuh	
Sensible Zone Load										17127 Btuh	

Manual J Summer Calculations

Residential Load - Component Details (continued)

Spec House Lot 39 Crosswinds S/D

Project Title:

702263WadeWillisConstruction

Class 3 Rating

Registration No. 0

Climate: North

, FL

3/19/2007

WHOLE HOUSE TOTALS

Whole House Totals for Cooling	Sensible Envelope Load All Zones	17127 Btuh
	Sensible Duct Load	0 Btuh
	Total Sensible Zone Loads	17127 Btuh
	Sensible ventilation	0 Btuh
	Blower	0 Btuh
	Total sensible gain	17127 Btuh
	Latent infiltration gain (for 54 gr. humidity difference)	3529 Btuh
	Latent ventilation gain	0 Btuh
	Latent duct gain	0 Btuh
	Latent occupant gain (6 people @ 200 Btuh per person)	1200 Btuh
	Latent other gain	0 Btuh
	Latent total gain	4729 Btuh
	TOTAL GAIN	21856 Btuh

*Key: Window types (Pn - Number of panes of glass)

(SHGC - Shading coefficient of glass as SHGC numerical value or as clear or tint)

(U - Window U-Factor or 'DEF' for default)

(InSh - Interior shading device: none(N), Blinds(B), Draperies(D) or Roller Shades(R))

(ExSh - Exterior shading device: none(N) or numerical value)

(BS - Insect screen: none(N), Full(F) or Half(H))

(Ornt - compass orientation)



For Florida residences only

System Sizing Calculations - Summer

Residential Load - Room by Room Component Details

Spec House Lot 39 Crosswinds S/D

Project Title:

702263WadeWillisConstruction

Class 3 Rating

Registration No. 0

Climate: North

, FL

Reference City: Gainesville (Defaults) Summer Temperature Difference: 17.0 F

3/19/2007

This calculation is for Worst Case. The house has been rotated 315 degrees.

Component Loads for Zone #1: Main

Window	Type*	Ornt	Overhang		Window Area(sqft)			HTM		Load		
	Pn/SHGC/U/InSh/ExSh/IS		Len	Hgt	Gross	Shaded	Unshaded	Shaded	Unshaded			
1	2, Clear, 0.87, None,N,N	NW	1.5ft.	5.5ft.	30.0	0.0	30.0	29	60	1801	Btuh	
2	2, Clear, 0.87, None,N,N	NW	1.5ft.	5.5ft.	20.0	0.0	20.0	29	60	1201	Btuh	
3	2, Clear, 0.87, None,N,N	NW	1.5ft.	5.5ft.	30.0	0.0	30.0	29	60	1801	Btuh	
4	2, Clear, 0.87, None,N,N	NE	1.5ft.	5.5ft.	20.0	0.0	20.0	29	60	1201	Btuh	
5	2, Clear, 0.87, None,N,N	SE	1.5ft.	0ft.	30.0	30.0	0.0	29	63	869	Btuh	
6	2, Clear, 0.87, None,N,N	SE	1.5ft.	5.5ft.	30.0	12.1	17.9	29	63	1468	Btuh	
Window Total					160 (sqft)					8341 Btuh		
Walls	Type	R-Value/U-Value			Area(sqft)			HTM		Load		
1	Frame - Wood - Ext	13.0/0.09			1040.0			2.1		2169 Btuh		
2	Frame - Wood - Adj	13.0/0.09			180.0			1.5		272 Btuh		
Wall Total						1220 (sqft)					2441 Btuh	
Doors	Type				Area (sqft)			HTM		Load		
1	Insulated - Adjacent				20.0			9.8		196 Btuh		
2	Insulated - Exterior				20.0			9.8		196 Btuh		
3	Insulated - Exterior				20.0			9.8		196 Btuh		
Door Total						60 (sqft)					588 Btuh	
Ceilings	Type/Color/Surface	R-Value			Area(sqft)			HTM		Load		
1	Vented Attic/DarkShingle	30.0			1558.0			1.7		2580 Btuh		
Ceiling Total						1558 (sqft)					2580 Btuh	
Floors	Type	R-Value			Size			HTM		Load		
1	Slab On Grade	0.0			180 (ft(p))			0.0		0 Btuh		
Floor Total						180.0 (sqft)					0 Btuh	
	Zone Envelope Subtotal:									13950 Btuh		
Infiltration	Type	ACH			Volume(cuft)			CFM=		Load		
	SensibleNatural	0.49			11824			96.6		1797 Btuh		
Internal gain	Occupants			Btuh/occupant			Appliance		Load			
	6			X 230 +			0		1380 Btuh			
Duct load	Average sealed, R6.0, Supply(Attic), Return(Attic)							DGM = 0.00		0.0 Btuh		
	Sensible Zone Load									17127 Btuh		

Manual J Summer Calculations

Residential Load - Component Details (continued)

Spec House Lot 39 Crosswinds S/D

Project Title:

702263WadeWillisConstruction

Class 3 Rating

Registration No. 0

Climate: North

, FL

3/19/2007

WHOLE HOUSE TOTALS

Whole House Totals for Cooling	Sensible Envelope Load All Zones	17127 Btuh
	Sensible Duct Load	0 Btuh
	Total Sensible Zone Loads	17127 Btuh
	Sensible ventilation	0 Btuh
	Blower	0 Btuh
	Total sensible gain	17127 Btuh
	Latent infiltration gain (for 54 gr. humidity difference)	3529 Btuh
	Latent ventilation gain	0 Btuh
	Latent duct gain	0 Btuh
	Latent occupant gain (6 people @ 200 Btuh per person)	1200 Btuh
	Latent other gain	0 Btuh
	Latent total gain	4729 Btuh
	TOTAL GAIN	21856 Btuh

*Key: Window types (Pn - Number of panes of glass)

(SHGC - Shading coefficient of glass as SHGC numerical value or as clear or tint)

(U - Window U-Factor or 'DEF' for default)

(InSh - Interior shading device: none(N), Blinds(B), Draperies(D) or Roller Shades(R))

(ExSh - Exterior shading device: none(N) or numerical value)

(BS - Insect screen: none(N), Full(F) or Half(H))

(Ornt - compass orientation)



For Florida residences only

Residential Window Diversity

MidSummer

Spec House Lot 39 Crosswinds S/D
, FL

Project Title:
702263WadeWillisConstruction


Class 3 Rating
Registration No. 0
Climate: North

3/19/2007

Weather data for: Gainesville - Defaults

Summer design temperature	92 F	Average window load for July	6527 Btuh
Summer setpoint	75 F	Peak window load for July	9362 Btuh
Summer temperature difference	17 F	Excursion limit(130% of Ave.)	8486 Btuh
Latitude	29 North	Window excursion (July)	877 Btuh

WINDOW Average and Peak Loads



Warning: This application has glass areas that produce relatively large heat gains for part of the day. Variable air volume devices may be required to overcome spikes in solar gain for one or more rooms. A zoned system may be required or some rooms may require zone control.

EnergyGauge® System Sizing for Florida residences only

PREPARED BY: *[Signature]*

DATE: 3-19-07

EnergyGauge® FLR2PB v4.1



PRODUCT APPROVAL SPECIFICATION SHEET

Location: _____

Project Name: _____

As required by Florida Statute 553.842 and Florida Administrative Code 9B-72, please provide the information and the product approval number(s) on the building components listed below if they will be utilized on the construction project for which you are applying for a building permit on or after April 1, 2004. We recommend you contact your local product supplier should you not know the product approval number for any of the applicable listed products. More information about statewide product approval can be obtained at www.floridabuilding.org

Category/Subcategory	Manufacturer	Product Description	Approval Number(s)
A. EXTERIOR DOORS			
1. Swinging	Thermax	6'8" STEEL/WOOD up to 6 FT OPEN	01-0828, 08
2. Sliding		INCLUDES SIDELITES	
3. Sectional			
4. Roll up			
5. Automatic			
6. Other			
B. WINDOWS			
1. Single hung	CAPITAL + BETTER BUILT. MI Products	SINGLE HUNG 740, 165, 3240, 4250 Series	AAMA CERT BB-101/13.2.-97
2. Horizontal Slider			CTLA-744W-B
3. Casement			
4. Double Hung			
5. Fixed		740 165 3240 4250 Series	01-35673.05
6. Awning			
7. Pass-through			
8. Projected			
9. Mullion	MI Products	740, 165, 3240, 4250 Series	01-35673.05
10. Wind Breaker			
11. Dual Action			
12. Other			
C. PANEL WALL			
1. Siding (Sleeper Wall)	NORBOARD	8'-9'x10' OSB WALL SHEETING	NER 108
2. Soffits		WIND STORM	
3. EIFS			
4. Storefronts			
5. Curtain walls			
6. Wall louver			
7. Glass block			
8. Membrane	BARRICADE	BUILDING WRAP FED SPEC.	44 B790A
9. Greenhouse			
10. Other			
D. ROOFING PRODUCTS			
1. Asphalt Shingles			
2. Underlayments	WOODLAND	15#, 30# FELT	ASTM D-4869
3. Roofing Fasteners			
4. Non-structural Metal Rf			
5. Built-Up Roofing			
6. Modified Bitumen			
7. Single Ply Roofing Sys			
8. Roofing Tiles			
9. Roofing Insulation			
10. Waterproofing			
11. Wood shingles /shakes			
12. Roofing State			

Category/Subcategory (cont.)	Manufacturer	Product Description	Approval Number(s)
13. Liquid Applied Roof Sys			
14. Cements-Adhesives - Coatings			
15. Roof Tile Adhesive			
16. Spray Applied Polyurethane Roof			
17. Other			
E. SHUTTERS			
1. Accordion			
2. Bahama			
3. Storm Panels			
4. Colonial			
5. Roll-up			
6. Equipment			
7. Others			
F. SKYLIGHTS			
1. Skylight			
2. Other			
G. STRUCTURAL COMPONENTS			
1. Wood connector/anchor	SIMPSON STRONG TIE	H-16; SP4, H2.5A, H-10, L3TA, FL 2822	
2. Truss plates			
3. Engineered lumber	ANTHONY	3 1/2" - 5 1/2" to 24' GLU-LAM	ASTM 7182.80
4. Railing			
5. Coolers-freezers			
6. Concrete Admixtures			
7. Material			
8. Insulation Forms			
9. Plastics			
10. Deck-Roof	NORBOARD	7/16" - 1/2" OSB	NER 108
11. Wall			
12. Sheds			
13. Other			
H. NEW EXTERIOR ENVELOPE PRODUCTS			
1.			
2.			

The products listed below did not demonstrate product approval at plan review. I understand that at the time of inspection of these products, the following information must be available to the inspector on the jobsite; 1) copy of the product approval, 2) the performance characteristics which the product was tested and certified to comply with, 3) copy of the applicable manufacturers installation requirements.

I understand these products may have to be removed if approval cannot be demonstrated during inspect on.

Contractor or Contractor's Authorized Agent Signature

Print Name

Date

Location

Permit # (FOR STAFF USE ONLY)

COLUMBIA COUNTY FLORIDA DEPARTMENT OF BUILDING AND ZONING

OCCUPANCY

COLUMBIA COUNTY, FLORIDA

Department of Building and Zoning Inspection

This Certificate of Occupancy is issued to the below named permit holder for the building and premises at the below named location, and certifies that the work has been completed in accordance with the Columbia County Building Code.

Parcel Number 24-4S-16-03117-139

Building permit No. 000026123

Use Classification SFD, UTILITY

Fire: 44.94

Permit Holder WADE WILLIS


Waste: 117.25

Owner of Building WADE WILLIS

Total: 162.19

Location: 686 SW CHESTER FIELD DR, LAKE CITY, FL

Date: 03/19/2008


Building Inspector



POST IN A CONSPICUOUS PLACE
(Business Places Only)

Notice of Prevention for Subterranean Termites

(As required by Florida Building Code (FBC) 104.2.6)



A locally owned
company serving
you since 1973

17856 U.S. 129 • McALPIN, FLORIDA 32062
(386) 362-3887 • 1-800-771-3887 • Fax: (386) 364-3529

2/12/23

CROSSWINDS SUBDIVISION LOT 39 LAKE CITY FL.

8/16/07

Date

9:00 A.M.

Time

PREVAL

Product Used

CYPERMETHRIN

Chemical used (active ingredient)

KEVIN KELLY

Applicator

237

Number of gallons applied

.25%

Percent Concentration

1936

Area treated (square feet)

234

Linear feet treated

HORIZONTAL / VERTICAL / INITIAL TREATMENT.
Stage of treatment (Horizontal, Vertical, Adjoining Slab, retreat of disturbed area)

As per 104.2.6 - If soil chemical barrier method for Subterranean termite prevention is used, final exterior treatment shall be completed prior to final building approval.

If this notice is for the final exterior treatment, initial and date this line.