



**ROOF VENTILATION:**  
R806.2 Minimum vent area.  
The minimum net free ventilating area shall be 1/150 of the area of the vented space.  
Exception: The minimum net free ventilation area shall be 1/300 of the vented space provided one or more of the following conditions are met:  
1. In Climate Zones 6, 7 and 8, a Class I or II vapor retarder is installed on the warm-in-winter side of the ceiling.  
2. At least 40 percent and not more than 50 percent of the required ventilating area is provided by ventilators located in the upper portion of the attic or rafter space.  
Upper ventilators shall be located no more than 3 feet below the ridge or highest point of the space, measured vertically, with the balance of the required ventilation provided by eaves or cornice vents. Where the location of wall or roof framing members conflicts with the installation of upper ventilators, installation more than 3 feet below the ridge or highest point of the space shall be permitted.



**FRONT ELEVATION**  
SCALE: 1/4" = 1'-0"




**REAR ELEVATION**  
SCALE: 1/4" = 1'-0"

**1995 MODEL  
ELEVATION B  
9' CEILING**



**RIGHT ELEVATION**  
SCALE: 1/4" = 1'-0"



**LEFT ELEVATION**  
SCALE: 1/4" = 1'-0"

Aaron Simque Homes

1995 Model (Elevation B)  
Lot 33 Tine F. reserves

PROJECT ADDRESS:  
Lot 33 Tine F. reserves  
Lake City, FL

**DIMENSIONS:**  
Stated dimensions supersede scaled dimensions. Refer all questions to Mark Disoway P.E. for resolution. Do not proceed without clarification.

**COPYRIGHTS AND PROPERTY RIGHTS:**  
Mark Disoway P.E. hereby expressly reserves its common law copyrights and property right in these instruments of service. This document is not to be reproduced, altered or copied in any form or manner without the express written permission and consent of Mark Disoway.

**CERTIFICATION:** I hereby certify that I have examined this plan, and sat the applicable portions of the plan, relating to wind engineering comply with the 7th Edition Florida Building Code Residenc (2020) to the best of my knowledge.

**LIMITATION:** This designs valid for one building, at specified location.

MARK DISOWAY P.E. 53815




Mark Disoway P.E.  
163 SW Midtown Place  
Suite 103  
Lake City, Florida 32025  
386.751.5419  
disowaydesign@gmail.com

**JOB NUMBER:**  
210455


1  
OF 6 SHEETS





**TYPICAL DESIGN WALL SECTION  
NON - STRUCTURAL DATA**

SCALE: 1" = 1'-0"



**FLOOR PLAN**  
SCALE: 1/4" = 1'-0"  
ALL CEILING HEIGHTS TO BE 9'-0" UNLESS NOTED OTHERWISE

**R302.5.1 Opening protection:**  
Openings from a private garage directly into a room used for sleeping purposes shall not be permitted. Other openings between the garage and residence shall be equipped with solid wood doors not less than 1 3/8 inches in thickness, solid or honeycomb-core steel doors not less than 1 3/8 inches thick, or 20-minute fire-rated doors, equipped with a self-closing device.

**TABLE R302.6 DWELLING/GARAGE SEPARATION:**

SEPARATION	MATERIAL
From the residence and attics	Not less than 1/2-inch gypsum board or equivalent applied to the garage side
From all habitable rooms above the garage	Not less than 5/8-inch Type X gypsum board or equivalent
Structure(s) supporting floor/ceiling assemblies used for separation required by this section	Not less than 1/2-inch gypsum board or equivalent
Garages located less than 3 feet from a dwelling unit on the same lot	Not less than 1/2-inch gypsum board or equivalent applied to the interior side of exterior walls that are within this area

Aaron Simque Homes

1995 Model (Elevation B)  
Lot 53 The Preserves

PROJECT ADDRESS:  
Lot 53 The Preserves  
Lake City, FL


**DIMENSIONS:**  
Stalled dimensions surround scaled dimensions. Refer all usations to Mark Disoway, P.E. for resolution. Do not proceed without clarification.

**COPYRIGHTS AND PROPERTY RIGHTS:**  
Mark Disoway, P.E. hereby expressly reserves its common law copyrights and property right in these instruments of service. This document is not to be reproduced, altered or copied in any form or manner without the express written permission and consent of Mark Disoway.

**CERTIFICATION:** I hereby certify that I have examined this plan, and that the applicable portions of the plan, relating to wind engineering comply with the 7th Edition Florida Building Code Residential (2020) to the best of my knowledge.

**LIMITATION:** This design is valid for one building, at specified location.

MARK DISOWAY P.E. 53915




Mark Disoway P.E.  
163 SW Midtown Place  
Suite 103  
Lake City, Florida 32025  
386.754.5419  
disowaydesign@gmail.com

JOB NUMBER:  
211555



ELECTRICAL PLAN NOTES:	
E - 1	WIRE ALL APPLIANCES, HVAC UNITS AND OTHER EQUIPMENT PER MANUF. SPECIFICATIONS
E - 2	CONSULT THE OWNER FOR THE NUMBER OF SEPERATE TELEPHONE LINES TO BE INSTALLED.
E - 3	ALL INSTALLATIONS SHALL BE PER NAT'L. ELECTRIC CODE.
E - 4	ALL SMOKE DETECTORS SHALL BE 120V W/ BATTERY BACKUP OF THE PHOTOELECTRIC TYPE AND SHALL BE INTERLOCKED TOGETHER. INSTALL INSIDE AND NEAR ALL BEDROOMS.
E - 5	TELEPHONE, TELEVISION AND OTHER LOW VOLTAGE DEVICES OR OUTLETS SHALL BE AS PER THE OWNER'S DIRECTIONS, & IN ACCORDANCE W/ APPLICABLE SECTIONS OF NEC-LATEST EDITION.
E - 6	ELECTRICAL CONTR SHALL BE RESPONSIBLE FOR THE DESIGN & SIZING OF ELECTRICAL SERVICE AND CIRCUITS.
E - 7	ENTRY OF SERVICE ( UNDERGROUND OR OVERHEAD ) TO BE DETERMINED BY POWER COMPANY.
E - 8	ALL 120-VOLT, SINGLE-PHASE, 15- AND 20-AMPERE BRANCH CIRCUITS SUPPLYING OUTLETS INSTALLED IN DWELLING UNIT FAMILY ROOMS, DINING ROOMS, LIVING ROOMS, PARLORS, LIBRARIES, DEN'S, BEDROOMS, SUN ROOMS, RECREATION ROOMS, CLOSETS, HALLWAYS, OR SIMILAR ROOMS OR AREAS SHALL BE PROTECTED BY A LISTED ARC-FAULT CIRCUIT INTERRUPTER, COMBINATION-TYPE INSTALLED TO PROVIDE PROTECTION OF THE BRANCH CIRCUIT.
E - 9	ALL OUTLETS TO BE LOCATED ABOVE BASE FLOOD ELEVATION.
E - 10	A SERVICE DISCONNECT WITH OVER CURRENT PROTECTION SHALL BE INSTALLED OUTSIDE OF THE BUILDING, ON THE LOAD SIDE OF THE METER, AT THE PLACE ELECTRIC CONDUCTORS ENTER THE BUILDING. SERVICE ENTRANCE CONDUCTORS MAY NOT BE LOCATED INSIDE OF THE OF THE BUILDING WITHOUT SPECIAL APPROVAL OF THE BUILDING OFFICIAL.
E - 11	CARBON MONOXIDE ALARMS SHALL BE REQUIRED WITHIN 10' OF ALL ROOMS FOR SLEEPING PURPOSES IN BUILDINGS HAVING A FOSSIL-FUEL-BURNING HEATER OR APPLIANCE, A FIREPLACE, OR ATTACHED GARAGE.
E - 12	ALL OUTLETS LOCATED IN RESIDENTIAL TO BE TAMPER-RESISTANT PER NEC.
E - 13	A MINIMUM OF 75% OF PERMANENTLY INSTALLED LAMPS OR LIGHTING FIXTURES SHALL BE HIGH EFFICACY 2014 FBQ EC SEC. R404.1

ELECTRICAL LEGEND	
	CEILING FAN (PRE-WIRE FOR LIGHT KIT)
	DOUBLE SECURITY LIGHT
	2x4 FLUORESCENT LIGHT FIXTURE
	RECESSED CAN LIGHT
	BATH EXHAUST FAN WITH LIGHT
	BATH EXHAUST FAN
	LIGHT FIXTURE
	DUPLEX OUTLET
	220v OUTLET
	GFI DUPLEX OUTLET
	SMOKE DETECTOR
	WALL SWITCH
	3 WAY WALL SWITCH
	4 WAY WALL SWITCH
	WATER PROOF GFI OUTLET
	PHONE JACK
	TELEVISION JACK
	GARAGE DOOR OPENER
	CARBON MONOXIDE ALARM



ELECTRICAL PLAN  
SCALE: 1/4" = 1'-0"

Aaron Sinique Homes

1995 Model (Elevation B)  
Lot 53 The Preserves

PROJECT ADDRESS:  
Lot 53 The Preserves  
Lake City, FL


DIMENSIONS:  
Stated dimensions suprcode scaled  
dimensions. Refer all questions to  
Mark Disoway, P.E. for resolution.  
Do not proceed without verification.

COPYRIGHTS AND PROPERTY RIGHTS:  
Mark Disoway, P.E. hereby expressly reserves  
its common law copyrights and property right in  
these instruments of service. This document is  
not to be reproduced, aered or copied in any  
form or manner without the express written  
permission and consent of Mark Disoway.

CERTIFICATION: I hereby certify that I have  
examined this plan, and that the applicable  
portions of the plan, relating to wind engineering  
comply with the 7th Edition Florida  
Building Code Residential (2020)  
to the best of my knowledge.

LIMITATION: This design is valid for one  
building, at specified location.

MARK DISOWAY P.E. 63915




Mark Disoway P.E.  
163 SW Miltown Place  
Suite 103  
Lake City, Florida 32025  
386.744.5419  
disowaydesign@gmail.com

JOB NUMBER:  
210555

3  
OF 6 SHEETS







**ONE STORY WALL SECTION**  
SCALE: 3/4\" = 1'-0"

Wind Speed Exp. B Exp. C Exp. D	Sheathing Thickness Plywood Or OSB	Required Nail	Nail spacing along panel edges	Nail spacing along intermediate supps in the panel
120 mph	7/16"	ASTM F1667 RRSR-01 (2 3/8" x 0.131")	6" oc	12" oc
120 mph	7/16"	ASTM F1667 RRSR-01 (2 3/8" x 0.131")	6" oc	6" oc
120 mph	19/32"	ASTM F1667 RRSR-03 (2 1/2" x 0.131") or ASTM F1667 RRSR-04 (3" x 0.120")	6" oc	6" oc
130 mph	7/16"	ASTM F1667 RRSR-01 (2 3/8" x 0.131")	6" oc	6" oc
130 mph	15/32"	ASTM F1667 RRSR-01 (2 3/8" x 0.131")	6" oc	6" oc
130 mph	19/32"	ASTM F1667 RRSR-03 (2 1/2" x 0.131") or ASTM F1667 RRSR-04 (3" x 0.120")	6" oc	6" oc
140 mph	7/16"	ASTM F1667 RRSR-01 (2 3/8" x 0.131")	6" oc	6" oc
140 mph	19/32"	ASTM F1667 RRSR-03 (2 1/2" x 0.131") or ASTM F1667 RRSR-04 (3" x 0.120")	6" oc	6" oc
140 mph	19/32"	ASTM F1667 RRSR-03 (2 1/2" x 0.131") or ASTM F1667 RRSR-04 (3" x 0.120")	6" oc	6" oc
150 mph	19/32"	ASTM F1667 RRSR-03 (2 1/2" x 0.131") or ASTM F1667 RRSR-04 (3" x 0.120")	4" oc	4" oc

Note: For sheathing located a minimum of 4 feet from the perimeter edge of the raftering 4 feet on each side of ridge and hips, nail spacing is permitted to be 6 inches on centering panel edges and 8 inches on center along intermediate supports in the panel field. Note: This specifies the code minimum thickness of roof sheathing. The thickness of the sheathing may not be increased based in the type of roofing material being used. See manufacturer Florida product approval.



**SHEATHING FOR UPLIFT ATTACHMENT DETAILS**  
ONE STORY WOOD FRAME



**(TYP.) INTERIOR BEARING WALL ATTACHMENT DETAILS**  
ONE STORY WOOD FRAME w/ STRAPS & ANCHORS

Uplift SP	Uplift SPF	Truss Connector	To Plate	To Truss/Rafter
615	485	SDWC15600	4-8d x 1 1/2"	4-8d x 1 1/2"
415	260	H3	4-8d x 1 1/2"	4-8d x 1 1/2"
575	485	H2.5A	5-8d x 1 1/2"	5-8d x 1 1/2"
1340	1015	H10A	9-10d 1 1/2"	9-10d 1 1/2"
720	820	LTS12-20	6-10d 1 1/2"	6-10d 1 1/2"
1000	860	MTS12-30	7-10d 1 1/2"	7-10d 1 1/2"
1460	1245	MTS35-30	12-10d 1 1/2"	12-10d 1 1/2"
Uplift SP	Uplift SPF	Strap Ties	To One Member	To Other Member
1235	1235	LSTA21	8-10d	8-10d
1640	1455	MSTA24	9-10d	9-10d
1030	1030	CS20	7-10d	7-10d
Uplift SP	Uplift SPF	Stud Plate Ties	To Stud	To Plate
585	535	SP1	6-10d	4-10d
1065	605	SP2	6-10d	6-10d
771	771	LSTA24	10-10d	wrap under or over plate
1235	1235	LSTA24	10-10d	wrap under or over plate
Uplift SP	Uplift SPF	Holdowns @ Stewall	To Stud / Post	Anchor
1825	1800	DT12Z	8-SDS 1/4"x1 1/2"	1/2"x12" Titen HD
4235	3640	HT14	18-16d x 1/2"	1/2"x12" Titen HD
Uplift SP	Uplift SPF	Holdowns @ Mono	To Stud / Post	Anchor
1825	1800	DT12Z	8-SDS 1/4"x1 1/2"	1/2"x6" Titen HD
4235	3640	HT14	18-16d x 1/2"	1/2"x12" Titen HD
Uplift SP	Uplift SPF	Post Bases @ Stewall	To Post	Anchor
2200	ABU44	ABU44	12-16d	5/8"x12" Drill & Epoxy
2300	ABU66	ABU66	12-16d	5/8"x12" Drill & Epoxy
Uplift SP	Uplift SPF	Post Bases @ Mono	To Post	Anchor
2200	ABU44	ABU44	12-16d	5/8"x7" Drill & Epoxy
2300	ABU66	ABU66	12-16d	5/8"x7" Drill & Epoxy

**EXTERIOR WALL STUD TABLE FOR SPF #2 STUDS:**

THIS STUD HEIGHT TABLE IS PER 2012 WFCM, TABLE 3.20B5, EXTERIOR LOAD BEARING & NON LOAD BEARING STUD LENGTHS FOR WALLS WITH OSB EXTERIOR AND 1/2" GYP INTERIOR. RESISTING INTERIOR ZONE WIND LOADS, 130 MPH, EXPOSURE C, STUD DEFLECTION LIMIT H/240 (NOT OK FOR BRITTLE FINISH). STUD SPACINGS SHALL BE MULTIPLIED BY 0.8 FOR FRAMING LOCATED WITHIN 4 FEET OF CORNERS FOR END ZONE LOADING. (END ZONE EXAMPLE 16" O.C. x 0.8 = 12.8" O.C.)

(1) 2x4 @ 16" OC	TO 10'-1" STUD HEIGHT
(1) 2x4 @ 12" OC	TO 11'-2" STUD HEIGHT
(1) 2x6 @ 16" OC	TO 15'-7" STUD HEIGHT
(1) 2x6 @ 12" OC	TO 17'-3" STUD HEIGHT

	SP #2	Qts	F	E
2x8		925	1.4	
2x10		800	1.4	
2x12		750	1.4	
GLB	24F-V3 SP	2600	1.9	
LSL	TIMBERSTRAND	1700	1.7	
LVL	MICROLAM	2950	2.0	
PSL	PARALAM	2900	2.0	

## GENERAL NOTES:

TRUSSES: TRUSSES SHALL BE DESIGNED BY A FLORIDA LICENSED ENGINEER IN ACCORDANCE WITH THE FBCL. TRUSS ENGINEERING SHALL INCLUDE TRUSS DESIGN, PLACEMENT PLANS, TEMPORARY AND PERMANENT BRACING DETAILS, TRUSS-TO-TRUSS CONNECTIONS, AND UPLIFT AND REACTION LOADS FOR ALL BEARING LOCATIONS. TRUSS ENGINEERING IS THE RESPONSIBILITY OF THE TRUSS MANUFACTURER AND SHALL BE SIGNED & SEALED BY THE MANUFACTURER'S DESIGN ENGINEER. IT IS THE BUILDER'S RESPONSIBILITY TO VERIFY THE TRUSS DESIGNER FULLY SATISFIED ALL THE ABOVE REQUIREMENTS AND TO SELECT UPLIFT CONNECTIONS BASED ON TRUSS ENGINEERING UPLIFT AND PROVIDE FOOTINGS FOR INTERIOR BEARING WALLS. BUILDER IS TO FURNISH TRUSS DESIGNER'S REVIEW OF TRUSS REACTIONS ON THE BUILDING STRUCTURE. STRAP 2X6 RAFTERS WITH MIN. UPLIFT CONNECTION 415LB EACH END, 2X6 RAFTERS 700 LB EACH END.

SITE PREPARATION: SITE ANALYSIS AND PREPARATION IS NOT PART OF THIS PLAN. FOUNDATION: CONFIRM THAT THE FOUNDATION DESIGN & SITE CONDITIONS MEET GRANTY LOAD REQUIREMENTS (ASSUME 1500 PSF BEARING CAPACITY UNLESS VISUAL OBSERVATION OR SOILS TEST PROVES OTHERWISE).

CONCRETE: MINIMUM COMPRESSIVE STRENGTH OF CONCRETE AT 28 DAYS,  $F_c = 2500$  PSI.

WELDED WIRE REINFORCED SLAB: 6" x 6" W1.4 x W1.4,  $F_y = 60$  KSI, WELDED WIRE REINFORCEMENT FABRIC (W.W.M.) CONFORMING TO ASTM A185, LOCATED IN MIDDLE OF THE SLAB, SUPPORTED WITH APPROVED MATERIALS OR SUPPORTS AT SPACINGS NOT TO EXCEED 3'.

FIBER CONCRETE SLAB: CONCRETE SLABS ON GROUND CONTAINING SYNTHETIC FIBER REINFORCEMENT, FIBER LENGTH 1/2 INCH TO 2 INCHES. DOSAGE AMOUNTS FROM 0.75 TO 1.5 POUNDS PER CUBIC YARD PER THE MANUFACTURER'S RECOMMENDATIONS. FIBERS TO COMPLY WITH ASTM C 1116. SUPPLIER TO PROVIDE ASTM C 1116 CERTIFICATION OF COMPLIANCE WHEN REQUESTED BY BUILDING OFFICIAL.

CONTROL JOINTS: WHERE SPECIFIED, SAWN CONTROL JOINTS IN SLAB-ON-GRADE SHALL BE CUT IN ACCORDANCE WITH ACI 302. JOINTS SHALL BE CUT WITHIN 12 HOURS OF SLAB PLACEMENT. THE LENGTH / WIDTH RATIOS OF SLAB AREAS SHALL NOT EXCEED 1.5 AND TYPICAL SPACING OF CUTS TO BE 12FT. DO NOT CUT W/M OR REINFORCING STEEL. RECOMMENDED LOCATION OF CONTROL JOINTS IS SUBJECT TO OWNER AND CONTRACTOR'S APPROVAL. THE CONTROL JOINTS ARE NOT INTENDED TO PREVENT CRACKS BUT RATHER TO ENCOURAGE THE SLAB TO CRACK ON A GIVEN LINE.

REBAR: ASTM A615, GRADE 40, DEFORMED BARS,  $F_y = 60$  KSI, ALL LAP SPICES 40" DB (25" FOR #5 BARS), UNO. ALL REINFORCEMENT SHALL BE WELDED AND PLACED IN ACCORDANCE WITH ACI 315-68, U.N.O.


ROOF SHEATHING: ALL ROOFS ARE HORIZONTAL DIAPHRAGMS; ROOF SHEATHING, UNBLOCKED, APPLIED PERPENDICULAR TO FRAMING, OVER A MINIMUM OF 3 FRAMING MEMBERS, WITH PANEL EDGES STAGGERED.

STRUCTURAL CONNECTORS: MANUFACTURERS AND PRODUCT NUMBER FOR CONNECTORS, ANCHORS, AND REINFORCEMENT ARE LISTED FOR EXAMPLE NOT ENDORSEMENT. AN EQUIVALENT DEVICE OF THE SAME OR OTHER MANUFACTURER CAN BE SUBSTITUTED FOR ANY DEVICES LISTED IN THE EXAMPLE TABLES AS LONG AS IT MEETS THE REQUIRED LOAD CAPACITIES. MANUFACTURER'S INSTALLATION INSTRUCTIONS MUST BE FOLLOWED TO ACHIEVE RATED LOADS.


ANCHOR BOLTS: A-307 ANCHOR BOLTS WITH MINIMUM EMBEDMENT AS SPECIFIED IN DRAWINGS BUT NO LESS THAN 7" IN CONCRETE OR REINFORCED BOND BEAM OR 15" IN GROUTED CMU.

**BUILDER'S RESPONSIBILITY:**  
THE BUILDER AND OWNER ARE RESPONSIBLE FOR THE FOLLOWING, WHICH ARE SPECIFICALLY NOT PART OF THE WIND LOAD ENGINEER'S SCOPE OF WORK. CONFIRM SITE CONDITIONS: FOUNDATION BEARING CAPACITY, GRADE AND BACKFILL HEIGHT, WIND SPEED AND DEBRIS ZONE, AND FLOOD ZONE. PROVIDE MATERIALS AND CONSTRUCTION TECHNIQUES, WHICH COMPLY WITH FBCL REQUIREMENTS FOR THE STATED WIND VELOCITY AND DESIGN PRESSURES. PROVIDE A CONTINUOUS LOAD PATH FROM TRUSSES TO FOUNDATION. IF YOU BELIEVE THE PLAN OMMITS A CONTINUOUS LOAD PATH CONNECTION, CALL THE WIND LOAD ENGINEER IMMEDIATELY. VERIFY THE TRUSS MANUFACTURER'S SEALED ENGINEERING INCLUDES TRUSS DESIGN, PLACEMENT PLANS, TEMPORARY AND PERMANENT BRACING DETAILS, TRUSS-TO-TRUSS CONNECTIONS, AND UPLIFT AND REACTION LOADS FOR ALL BEARING LOCATIONS.


**ROOF SYSTEM DESIGN:**  
THE SEAL ON THESE PLANS FOR COMPLIANCE WITH FBCL. IS BASED ON REACTIONS, UPLIFTS, AND BEARING LOCATIONS IN TRUSS ENGINEERING SUBMITTED TO THE WIND LOAD ENGINEER. IT IS THE RESPONSIBILITY OF THE BUILDER TO CHECK ALL DETAILS OF THE COMPLETE ROOF SYSTEM DESIGN SUBMITTED BY THE TRUSS MANUFACTURER AND HAVE IT SIGNED, AND SEALED BY A DESIGN PROFESSIONAL FOR CORRECT APPLICATION OF FROM REQUIRED LOADS AND ANY SPECIAL LOADS. THE BUILDER IS RESPONSIBLE TO REVIEW EACH INDIVIDUAL TRUSS MEMBER AND THE TRUSS ROOF SYSTEM AS A WHOLE AND TO PROVIDE RESTRAINT FOR ANY LATERAL BRACING. THE BUILDER SHOULD USE CARE CHECKING THE ROOF DESIGN BECAUSE THE WIND LOAD ENGINEER IS SPECIFICALLY NOT RESPONSIBLE FOR THE TRUSS LAYOUT WHICH WAS CREATED BY THE TRUSS MANUFACTURER AND THE TRUSS DESIGNER ALSO DENIES RESPONSIBILITY FOR THE LAYOUT PER NOTES ON THEIR SEALED TRUSS SHEETS.




**(TYP.) INTERSECTING WALL FRAMING**  
WOOD FRAME




**(TYP.) CORNER FRAMING**  
WOOD FRAME




**(TYP.) GABLE BRACING DETAIL**  
WOOD FRAME



**TYPICAL HEADER STRAPPING DETAIL**  
ONE STORY WOOD FRAME w/ STRAPS & ANCHORS



**(TYP.) BEAM TO WALL**  
WOOD FRAME w/ STRAPS & ANCHORS



**(TYP.) GARAGE DOOR BUCK ATTACHMENT**  
ONE STORY WOOD FRAME w/ STRAPS & AB

BUILDING CODE	7TH EDITION FLORIDA BUILDING CODE RESIDENTIAL (2020)
CODE FOR DESIGN LOADS	ASCE 7-16
<b>WINDLOADS</b>	
BASIC WIND SPEED	130 MPH (ASCE 7-10, 3S GUST)
WIND EXPOSURE (BUILDER MUST FIELD VERIFY)	C
TOPOGRAPHIC FACTOR (BUILDER MUST FIELD VERIFY)	I
RISK CATEGORY	II
ENCLOSURE CLASSIFICATION	ENCLOSED
INTERNAL PRESSURE COEFFICIENT	0.18
ROOF ANGLE	7-45 DEGREES
MEAN ROOF HEIGHT	30 FT
<b>C&amp;C DESIGN PRESSURES</b>	SEE TABLE
<b>FLOOR LOADING</b>	
ROOMS OTHER THAN SLEEPING ROOM	40 PSF LIVE LOAD
SLEEPING ROOMS	30 PSF LIVE LOAD
<b>ROOF LOADING</b>	
FLAT OR < 4:12	20 PSF LIVE LOAD
4:12 TO < 12:12	16 PSF LIVE LOAD
12:12 & GREATER	12 PSF LIVE LOAD
<b>SOIL BEARING CAPACITY</b>	1500 PSF
<b>FLOOD ZONE</b>	THIS BUILDING IS NOT IN THE FLOOD ZONE

EFFECTIVE WIND AREA (F <sub>T2</sub> )	ZONE 4 INTERIOR	ZONE 5 END 4' FROM ALL OUTSIDE CORNER
0 - 20	+25.8(Vsdt) -27.8(Vsdt)	+25.8(Vsdt) -34.2(Vsdt)
0 - 20	+42.6(VuIt) -46.2(VuIt)	+42.6(VuIt) -57.7(VuIt)
20 - 30	+22.8(Vsdt) -25.8(Vsdt)	+22.8(Vsdt) -34.2(Vsdt)
30 - 40	+21.7(Vsdt) -24.7(Vsdt)	+21.7(Vsdt) -34.2(Vsdt)

GARAGE DOOR	130 MPH (EXP C)
9x7 GARAGE DOOR	+22.8(Vsdt) -25.8(Vsdt)
16x7 GARAGE DOOR	+21.7(Vsdt) -24.7(Vsdt)

Aaron Simque Homes

1995 Model (Elevation B)  
Lot 53 The Preserves

PROJECT ADDRESS:  
Lot 53 The Preserves  
Lake City, FL

DIMENSIONS:  
Scaled dimensions, supercede scaled dimensions. Refer all questions to Mark Disoway, P.E. for resolution. Do not proceed without clarification.

COPYRIGHTS AND PROPERTY RIGHTS:

Mark Disoway, P.E. hereby expressly reserves its common law copyright and property right in these instruments of service. This document is not to be reproduced, altered or copied in any form or manner without the express written permission and consent of Mark Disoway.

CERTIFICATION: I hereby certify that I have examined this plan, and that the applicable portions of the plan, relate to wind engineering comply with the 7th Edition Florida Building Code Residential (2020) to the best of my knowledge.


LIMITATION: This design is valid for one building, at specified location.

MARK DISOWAY P.E. 53915


Mark Disoway P.E.  
163 SW Midtown Place  
Suite 103  
Lake City, Florida 32025  
386.75x5419  
disowaydesign@gmail.com

JOB NUMBER:  
210555  
S-I  
OF 6 SHEETS







**F1 S-2** OPTIONAL STEM WALL FOOTING  
SCALE: 1/2" = 1'-0"




**F1 S-2** MONOLITHIC FOOTING  
SCALE: 1/2" = 1'-0"




**F2 S-2** INTERIOR BEARING FOOTING  
SCALE: 1/2" = 1'-0"



**F3 S-2** INTERIOR BEARING STEP FOOTING  
SCALE: 1/2" = 1'-0"



**F4 S-2** MONOLITHIC CURB FOOTING  
SCALE: 1/2" = 1'-0"



**F5 S-2** GARAGE DOOR POCKET FOOTING  
SCALE: 1/2" = 1'-0"


**TALL STEM WALL TABLE:**  
The table assumes 40 ksi for #5 rebar and 60 ksi for #7 & #8 rebar with 6" hook in the footing and bent 24" into the reinforced slab at the top. The vertical steel is to be placed toward the tension side of the CMU wall (away from the soil pressure, within 2" of the exterior side of the wall). If the wall is over 8' high, add Duowall ladder reinforcement at 18" OC vertically or a horizontal bond beam with 1#5 continuous at mid height. For higher parts of the wall 12" CMU may be used with reinforcement as shown in the table below.

STEM WALL HEIGHT (FEET)	UNBALANCED BACKFILL HEIGHT	VERTICAL REINFORCEMENT FOR 8" CMU STEM WALL (INCHES O.C.)			VERTICAL REINFORCEMENT FOR 12" CMU STEM WALL (INCHES O.C.)		
		#6	#7	#8	#6	#7	#8
3.3	3.0	96	96	96	96	96	96
4.0	3.7	96	96	96	96	96	96
4.7	4.3	88	96	96	96	96	96
5.3	5.0	56	96	96	96	96	96
6.0	5.7	40	80	96	80	96	96
6.7	6.3	32	56	80	56	96	96
7.3	7.0	24	40	56	40	80	96
8.0	7.7	16	32	48	32	64	80
8.7	8.3	8	24	32	24	48	64
9.3	9.0	8	16	24	16	40	48

**MASONRY NOTE:**  
MASONRY CONSTRUCTION AND MATERIALS FOR THIS PROJECT SHALL CONFORM TO ALL REQUIREMENTS OF "SPECIFICATION FOR MASONRY STRUCTURES" (ACI 530.1/ASCE 6/TMS 602). THE CONTRACTOR AND MASON MUST IMMEDIATELY, BEFORE PROCEEDING, NOTIFY THE ENGINEER OF ANY CONFLICTS BETWEEN ACI 530.1-02 AND THESE DESIGN DRAWINGS. ANY EXCEPTIONS TO ACI 530.1-02 MUST BE APPROVED BY THE ENGINEER IN WRITING.

ACI 530.1-02 Section	Specific Requirements
1.4A Compressive strength	8" block bearing walls F'm = 1500 psi
2.1 Mortar	ASTM C 270, Type N, UNO
2.2 Grout	ASTM C 476, admixtures require approval
2.3 CMU standard	ASTM C 90-02, Normal weight, Hollow, medium surface finish, 8"x8"x16" running bond and 12"x12" or 15"x15" column block
2.3 Clay brick standard	ASTM C 216-02, Grade SW, Type FBS, S-2-S2, 7 1/2"x11 1/2"
2.4 Reinforcing bars, #3 - #11	ASTM 615, Grade 40, Fy = 40 ksi, Lap splices min 40 bar dia. (25" for #6)
2.4F Coating for corrosion protection	Anchors, steel metal ties completely embedded in mortar or grout, ASTM A525, Class G60, 0.60 co/rt2 or 304SS
2.4F Coating for corrosion protection	Joint reinforcement in walls exposed to moisture or wire ties, anchors, steel metal ties not completely embedded in mortar or grout, ASTM A153, Class B2, 1.50 co/rt2 or 304SS
3.3.E.2 Pipes, conduits, and accessories	Any not shown on the project drawings require engineering approval
3.3.E.7 Movement joints	Contractor assumes responsibility for type and location of movement joints if not detailed on project drawings.

BOTTOM OF EXTERIOR FOOTINGS SHALL BE A MINIMUM OF 12" BELOW UNDISTURBED SOIL OR ENGINEERED FILL




**F4 S-2** OPTIONAL STEM WALL CURB FOOTING  
SCALE: 1/2" = 1'-0"

#### FOUNDATION PLAN

SCALE: 1/4" = 1'-0"

**FOUNDATION NOTES**

- DIMENSIONS ON FOUNDATION & STRUCTURAL SHEETS ARE NOT EXACT. REFER TO ARCHITECTURAL PLANS FOR ACTUAL DIMENSIONS, RECESSES IN SLAB, STEP DOWNS, ETC. DISCOWAY DESIGN GROUP OR MARK DISCOWAY, P.E. IS NOT RESPONSIBLE FOR DIMENSION ERRORS ON THIS PLAN.
- CONTRACTOR SHALL VERIFY NEED FOR INTERIOR BEARING (BY THE SUPPLIER) BEFORE FINALIZING FOUNDATION PLAN.
- THE SLAB SHALL BE 4" CONCRETE SLAB REINFORCED w/ 1" 1/2" DEPTH OR FIBER MESH CONCRETE, 5-MIL POLY VAPOR BARRIER w/ #1 LAPS SEALED w/ POLY TAPE OVER TERMITE-TREATED & COMPACTED FILL. (ALSO, ANY OTHER CODE APPROVED TERMITE-TREATMENT METHOD CAN BE USED INSTEAD)



Aaron Simque Homes

1995 Model (Elevation B)  
Lot 53 The Preserves

PROJECT ADDRESS:  
Lot 53 The Preserves  
Lake City, FL


DIMENSIONS:  
Stated dimensions approximate scaled dimensions. Refer all questions to Mark Discoway, P.E. for resolution. Do not proceed without clarification.

COPYRIGHTS AND PROPERTY RIGHTS:  
Mark Discoway, P.E. hereby expressly reserves its common law copyright and property right in these instruments of service. This document is not to be reproduced, altered or copied in any form or manner without the express written permission and consent of Mark Discoway.

CERTIFICATION: I hereby certify that I have examined this plan, and that the applicable portions of the plan, relating to wind engineering comply with the 7th Edition Florida Building Code Residential (2020) to the best of my knowledge.

LIMITATION: This design is valid for one building, at specified location.

MARK DISCOWAY P.E. 53915




Mark Discoway P.E.  
163 SW Miltown Place  
Suite 103  
Lake City, Florida 32025  
386.74.5419  
disowaydesign@gmail.com

JOB NUMBER:  
210555


**S-2**  
OF 6 SHEETS





FRONT VIEW

SCALE: N.T.S



FRONT VIEW

**PRE-ENGINEERED ROOF TRUSSES  
(DESIGNED BY OTHERS)  
ATTACH TRUSSES  
TO WALL / BEAM  
w/ (1) SIMPSON SDWC15600  
FOR UP TO 485 LB UPLIFT  
OR  
(2) SIMPSON SDWC15600  
FOR UP TO 850 LB UPLIFT**

**NO SCREWS  
REQUIRED  
THIS HEADER**

**NO SCREWS  
REQUIRED  
THIS HEADER**

-1236 #  
HTS20 TOP  
HTT4 BOTTOM

-3496 #  
(3) HTS20 T  
HTT4 BOTT

		-
	(	H

SIMPSON SDWC15600 TOP  
(4) (2 IN EACH KING)  
SIMPSON SDWC15450 BOTTOM  
(4) (2 IN EACH KING)  
ANCHOR BOLT WITHIN 4"

(2) 2X8X4', 2J 2K  
T13 (3)  
S = 5.0'

USE OPENING FORCE TRANSFER  
DETAIL THIS OPENING SEE DETAIL  
ON SHEET S-1

SEE PORCH  
POST DETAIL (TYPICAL)

STRUCTURAL PLAN  
SCALE: 1/4" = 1'-0"

NUMBER OF PLIES IN HEADBOARD

ACTUAL vs REQUIRED SHEARWALL		
	TRANSVERSE	LONGITUDINAL
ACTUAL	18616 LBF	25154 LBF
REQUIRED	17773 LBF	8900 LBF

995 Model (Elevation B)  
Lot 53 The Preserves

**PROJECT ADDRESS:**  
Lot 53 The Preserves  
Lake City, FL

S-3

CONNECTIONS, WALL, & HEADER DESIGN IS BASED  
ON REACTIONS & UPLIFTS FROM TRUSS ENGINEERING  
FURNISHED BY BUILDER. BUILDERS FIRST SOURCE  
JOB #2329508